



## When Microseconds Matter

Performance-critical cloud and data center workloads demand consistently fast throughput and near real-time access to data. The Micron® 9300 series of NVM Express® (NVMe™) SSDs delivers industry-leading sequential write performance and the lowest average write latency in the market to accelerate your growing data center demands.\*

### Rely on a Trusted, Proven Architecture

Micron has proven the value of flash technologies like 3D TLC NAND and NVMe in building next-level data center and cloud infrastructures. Our flagship high-performance storage product, the Micron 9200 SSD, was the industry's highest 4K random read IOPS SSD and the first to deliver over 10TB of storage capacity to the marketplace. The Micron 9300 SSDs leverage this rich history while improving speed and performance and lowering power (28% versus the 9200 SSD). The familiar architecture of the 9300 accelerates OEM qual.

### Larger and More in Charge

With our highest-capacity data center SSDs, the Micron 9300 series challenges HDDs head-on with drives from 3.2TB to 15.36TB. The 9300 SSDs also offer simplified firmware management, expansion into multiple namespaces to accommodate multitenancy, and more parallel sessions for single storage devices. And the Micron 9300 SSDs are our most power-efficient and cost-efficient data center NVMe SSDs to date.

## Key Benefits

### No Read or Write Compromises

Consistently read *and* write up to 3.5 GB/s of sequential data.\*\* The Micron 9300 SSDs ingest and read at industry-leading speeds, enabling faster data analysis.

### Add IOPs to Your Balance Sheet

Maximize your data center investment with improved power efficiency (more than 28%) and performance.\*\*\* The Micron 9300 series saves rack/floor space and lowers license/power costs by using fewer drives to achieve more.

### Performance Pays

Take advantage of solutions optimized for low latency and performance-critical workloads like caching, database acceleration, online transaction processing (OLTP), high-frequency trading (HFT), block and object stores, and training/caching for artificial intelligence (AI), machine learning (ML) and deep learning (DL).

### HDD-Caliber Capacity, NVMe Results

Experience flexible, efficient storage utilization and multitenancy with up to 15.36TB capacity and 32 NVMe namespaces.

### One Size Fits All

Get more from a single part number with Micron's Flex Capacity feature, which lets you adjust SSD capacity, performance and endurance to meet your needs.

## Target Workloads and Applications

|                                                  |                                              |                                       |                                        |             |
|--------------------------------------------------|----------------------------------------------|---------------------------------------|----------------------------------------|-------------|
| <b>CACHING AND<br/>DATABASE<br/>ACCELERATION</b> | <b>AI/ML/DL<br/>TRAINING AND<br/>CACHING</b> | <b>HIGH<br/>FREQUENCY<br/>TRADING</b> | <b>BLOCK AND<br/>OBJECT<br/>STORES</b> | <b>OLTP</b> |
|--------------------------------------------------|----------------------------------------------|---------------------------------------|----------------------------------------|-------------|

\* Based on the best SKU in each NVMe high-performance product family's U.2 (15mm) form factor and information in public competitor data sheets accessed 1 February 2019. Actual performance may vary.

\*\*4KB transfers with a queue depth of 1 are used to measure READ/WRITE latency values.

\*\*\*Watt (average root mean square) of Micron 9200 SSD compared to the 9300.

## Best-Fit Workloads for the 9300

### AI/ML/DL Training and Caching

Accelerate data ingest and trim test and training cycle times for AI, ML and DL.

### OLTP

Increase performance and consistency for better platform transaction rates.

### NoSQL Databases

Build faster, smaller and more economical clusters at a lower cost.

### Large Object

Manage and store more blocks, streams and objects in less space.

### Small Random Block

Find significantly better performance than a hard disk drive, with fewer nodes.

### Big Data

Bring performance to all four corners of your high-performance stacks. Even the top tier of tiered storage becomes cost-efficient.



### Key Specifications

|                                     |                                  | 9300 PRO<br>(Read-Intensive, 1 Drive Write Per Day)                                                                                                                                                                                                               |         |          | 9300 MAX<br>(Mixed-Use, 3 Drive Writes Per Day) |        |         |
|-------------------------------------|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------|----------|-------------------------------------------------|--------|---------|
| Capacity <sup>1</sup>               |                                  | 3.84 TB                                                                                                                                                                                                                                                           | 7.68 TB | 15.36 TB | 3.2 TB                                          | 6.4 TB | 12.8 TB |
| Performance                         | Seq Read (MB/s) <sup>2</sup>     | 3500                                                                                                                                                                                                                                                              | 3500    | 3500     | 3500                                            | 3500   | 3500    |
|                                     | Seq Write (MB/s) <sup>2</sup>    | 3100                                                                                                                                                                                                                                                              | 3500    | 3500     | 3100                                            | 3500   | 3500    |
|                                     | Rand Read (K IOPS) <sup>3</sup>  | 835                                                                                                                                                                                                                                                               | 850     | 850      | 835                                             | 850    | 850     |
|                                     | Rand Write (K IOPS) <sup>3</sup> | 105                                                                                                                                                                                                                                                               | 145     | 150      | 210                                             | 310    | 310     |
| Endurance (Terabytes Written in PB) |                                  | 8.4                                                                                                                                                                                                                                                               | 16.8    | 33.6     | 18.6                                            | 37.3   | 74.7    |
| Basic Attributes                    | Interface                        | PCIe® Gen3 x4 NVMe                                                                                                                                                                                                                                                |         |          |                                                 |        |         |
|                                     | Form Factor                      | U.2 (2.5-inch, 15mm)                                                                                                                                                                                                                                              |         |          |                                                 |        |         |
|                                     | NAND                             | Micron 64-layer 3D TLC NAND                                                                                                                                                                                                                                       |         |          |                                                 |        |         |
|                                     | Average Latency                  | Random read: 86µs<br>Random write: 11µs                                                                                                                                                                                                                           |         |          |                                                 |        |         |
| Reliability                         | Mean Time to Failure             | 2 million device hours                                                                                                                                                                                                                                            |         |          |                                                 |        |         |
|                                     | UBER                             | <1 sector per 10 <sup>17</sup> bits read                                                                                                                                                                                                                          |         |          |                                                 |        |         |
|                                     | Warranty                         | Up to 5 years                                                                                                                                                                                                                                                     |         |          |                                                 |        |         |
| Environmental Characteristics       | Power                            | Sequential read: 14W MAX<br>Sequential write: 21W MAX                                                                                                                                                                                                             |         |          |                                                 |        |         |
|                                     | Operating Temp                   | 0–70°C                                                                                                                                                                                                                                                            |         |          |                                                 |        |         |
| Physical Characteristics            | Size (L x W x H)                 | 100.45mm x 70.10mm x 15.00mm                                                                                                                                                                                                                                      |         |          |                                                 |        |         |
|                                     | Weight                           | <235g                                                                                                                                                                                                                                                             |         |          |                                                 |        |         |
| Advanced Features <sup>4</sup>      |                                  | Up to 32 NVMe namespaces, crypto erase, Flex Capacity feature, power-loss protection (for data in flight and at rest), data center data path protection (user and metadata), Storage Executive SSD management tool, secure signed firmware, up to 5 year warranty |         |          |                                                 |        |         |

1.Unformatted. 1GB = 1 billion bytes. Formatted capacity is less.

2. 128KB transfer size, QD = 32, steady state.

3. 4KB transfer size, QD = 512, steady state.

4.No hardware, software or system can provide absolute security under all conditions. Micron assumes no liability for lost, stolen or corrupted data arising from the use of any Micron products, including those products that incorporate any of the mentioned security features.

### 9300 Base Part Numbers

| SSD Family | Standard Part            | Capacity | Form Factor |
|------------|--------------------------|----------|-------------|
| PRO        | MTFDHAL3T8TDP-1AT1ZABYY  | 3.84TB   | U.2         |
|            | MTFDHAL7T6TDP-1AT1ZABYY  | 7.68TB   | U.2         |
|            | MTFDHAL15T3TDP-1AT1ZABYY | 15.36TB  | U.2         |
| MAX        | MTFDHAL3T2TDR-1AT1ZABYY  | 3.2TB    | U.2         |
|            | MTFDHAL6T4TDR-1AT1ZABYY  | 6.4TB    | U.2         |
|            | MTFDHAL12T8TDR-1AT1ZABYY | 12.8TB   | U.2         |

[micron.com/9300](https://micron.com/9300)

©2020 Micron Technology, Inc. All rights reserved. All information herein is provided on as "AS IS" basis without warranties of any kind, including any implied warranties, warranties of merchantability or warranties of fitness for a particular purpose. Micron, the Micron logo, and all other Micron trademarks are the property of Micron Technology, Inc. All other trademarks are the property of their respective owners. Products are warranted only to meet Micron's production data sheet specifications. Products, programs and specifications are subject to change without notice.

Rev. B 06/2020 CCM004-676576390-11285



# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Micron Technology:](#)

[MTFDHAL3T2TDR-1AT1ZABYY](#) [MTFDHAL12T8TDR-1AT1ZABYY](#) [MTFDHAL15T3TDP-1AT1ZABYY](#)  
[MTFDHAL3T8TDP-1AT1ZABYY](#) [MTFDHAL6T4TDR-1AT1ZABYY](#) [MTFDHAL7T6TDP-1AT1ZABYY](#)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)