






6
N = Number of poles
Dim A = $N \times 8.25 + 2.0$
Dim B = $(N - 1) \times 8.25$

Poles	Tol.	Dim A & B
2-5p		± 0.20
6-10p		± 0.25
11-16p		± 0.35
17-24p		± 0.40
25-30p		± 0.50

SIGN	DATE	DESCRIPTION	APPROVER
6	20/10'06	added cULus approval	Steady
6	03/17'09	Add stipulation	Seamus
6	03/17'09	Dimension is changed	Seamus
6	06/04'11	Critical dimension is changed.	Tason
6	06/04'11	The Wire Range is changed from 20-12AWG to 22-12AWG	Tason
6	06/04'11	The tolerance table is changed.	Tason
6	11/27'12	Change the screw plating specification	Jacky
6	12/07'13	Change the withstand voltage and current	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL
RATED VOLTAGE & CURRENT: 300 V, 20 A/300 V, 32 A **6**
WITHSTAND VOLTAGE: AC 2500 V/Min **6**
INSULATION RESISTANCE: 1000 M Ω OR MORE AT DC 500 V
OPERATING TEMPERATURE RANG: -40 °C ~ +115 °C
SCREW TORQUE VALUE: 8.8 Lb-In..
WIRE RANGE: 22 - 12 AWG. **6**
1) MOLDED PARTS: POLYIMIDE 66, UL 94 V-0 BLACK
2) TERMINAL: BRASS, 0.8t, Tin PLATED
3) TERMINAL SCREWS: STEEL, M3

6 3) TERMINAL SCREWS: **6**
6 Critical dimension: **6**
6 APPROVAL: **6** **6** **6**

YK 334 xx 0 x x 00G G:RoHS compliant (lead<4%) in copper alloy
NO. OF POLES MARK
02: 2 POLES
03: 3 POLES
04: 4 POLES
:
30: 30 POLES
TERMINAL & SCREW PLATED
6 0: TERMINAL & SCREW: G/F
6 1: TERMINAL: G/F, SCREW: Zinc
6 2: TERMINAL: Sn, SCREW: G/F
6 3: TERMINAL: Sn, SCREW: Zinc

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK-334 Series						
PART NO.		YK334xx0xx00G			DWG NO.	8YK0001-334		
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.			Tolerance	
		Jacky 2013.12.07	Jacky 2013.12.07		UNIT: mm	X.	±0.50	
					SCALE: NONE	X.X	±0.30	
					REV.: F	X.XX	±0.10	
SHEET: 01/01						X°	±1°	

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru