



FireFly Mini Green

FireFly Mini Green

The FireFly Mini Green sets a new standard for small industrial grade, green laser diode modules. A radically new design provides TE stabilised performance without TE size cost and power consumption.

The self-contained laser offers the user impressive power stability over a wide operating temperature with a quick warm up time.



The new unit is ideal for space constricted applications whilst still offering the high performance linear and TTL/PWM Modulation capabilities that have come to be expected from Global Laser.

High accuracy bore sight aligned spot with low divergence and achieved by the integrated optics allows focusing over a wide operating range.





Power Stability

The profiles below show the typical power stability vs. time and power stability vs. temperature.





Focussing Characteristics

The following charts show the typical focusing of the FireFly laser. The focus charts indicate the minimum spot size (at $1/e^2$) achievable for a specific projection distance.



Depth of Field Characteristics

The following charts show the typical depth-of-field performance of the FireFly laser. The depth-of-field is defined as the distance between two points either side of the pre-set focus at which the spot size increases by a factor of $\sqrt{2}$.



Standard Driver Types

Pulse Width Modulation TTL Digital Control (PWM)

The FireFly Mini is also available with a TTL driver board that allows the unit to be gated on and off, or pulse-width modulated at TTL voltage levels via the yellow control lead. The standard version offers non inverting TTL where an input signal of $< 0.4 \text{ V}$ = off and $> 2 \text{ V}$ = on and vice versa for the inverted model. Frequency bandwidth is typically 50 kHz.

Rise Time: $< 10 \mu\text{s}$ (typical)


Fall Time: $< 10 \mu\text{s}$ (typical)

Specifications

Mechanical Information	
Mass (grams)	30
Dimensions (mm)	15 x 75
Housing	Green Anodised Aluminium
Isolated Body	Yes
Input Leads	CW Version - 250mm Cable 2 wires, Red (+ve) Black (0V)
	Modulated Version - 500mm Cable 3 wires, Red (+ve) Black (0V) Yellow (Modulation)
Optical Information	
Diode Power (mW)	1
Wavelength (nm)	532
Intensity Distribution	TEM ₀₀
Focus Range (mm)	115 to infinity
Warm Up Time to 75% of Full Power	< 30 seconds
Power Stability Over Operating Range	<10%
Power Stability Over Constant Temperature	< 1%
Beam Size At Aperture (mm)	1
Minimum Beam Divergence (mrad)	0.1
Pointing Stability (mrad)	0.5
M ²	<1.2
Focus	User Adjustable
Bore Sighting (mrad)	<2
Environmental Information	
Operating Case Temperature (°C)	+5 to +35
Storage Temperature (°C)	-10 to +85
Operating Humidity (%RH)	90 (non condensing)
MTTF @ 25°C (hrs)	>10,000
Electrical Specifications	
Input Voltage	3.3Vdc to 5Vdc
Operating Current (mA)	350 max (Diode Dependant)
Connector Type	CW Version - Flying Leads
Cable Length (mm)	250
Reverse Polarity Protection	Yes
Over Temperature Protection	Yes
Modulation	
Typical Rise & Fall Time	<10
Frequency	DC to 10 kHz
Modulation Input Voltage	<4V = Off >2V = On
NOTES All specifications are typical @ 25°C	

Laser Safety

Our lasers are compliant to IEC 60825-1 2007 standards. The lasers fall within one of the following classifications depending on power and wavelength.




Class 2 Label

Quality & Warranty

The FireFly range is supplied with a 12 month parts and labour warranty. Our manufacturing operations are certified to ISO9001.

Mechanical Drawings

FireFly Mini



Drawings not to scale

Please Note: Imatronic reserve the right to change descriptions and specifications without notice



ISO9001 Certified

IMATRONIC
A Global Laser Brand

For further information about any of our products please contact your local distributor or you can contact Global Laser in the UK. Your Local Distributor is:

T: +44 (0)1495 212213
F: +44 (0)1495 214004
E: sales@globallasertech.com
www.globallasertech.com

Global Laser Ltd, Cwmtillery Industrial Estate
Abertillery, Gwent NP13 1LZ UK

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru