POWER MATE TECHNOLOGY CO.,LTD.

# FEC30W-SERIES




## FEATURES

- 30 WATTS MAXIMUM OUTPUT POWER
- OUTPUT CURRENT UP TO 8A
- STANDARD 2.0 X 1.6 X 0.4 INCH PACKAGE
- HIGH EFFICIENCY UP TO 88%
- 4:1 WIDE INPUT VOLTAGE RANGE
- SIX-SIDED CONTINUOUS SHIELD
- FIXED SWITCHING FREQUENCY
- OFFER SINGLE AND DUAL OUTPUT
- CE MARK MEETS 2006/95/EC, 93/68/EEC AND 2004/108/EC
- UL60950-1, EN60950-1 AND IEC60950-1 LICENSED
- ISO9001 CERTIFIED MANUFACTURING FACILITIES
- COMPLIANT TO RoHS EU DIRECTIVE 2002/95/EC

## APPLICATIONS

Wireless Network
Telecom/Datacom
Industry Control System
Measurement Equipment
Semiconductor Equipment

## OPTIONS

Negative logic Remote On/Off

## DESCRIPTION

The FEC30W series offer 30 watts of output power from a 2 x 1.6 x 0.4 inch package .The FEC30W series with 4:1 wide input voltage of 10-40VDC and 18-75VDC and features 1600VDC of isolation, short-circuit and over-voltage protection.

## TECHNICAL SPECIFICATION

All specifications are typical at nominal input, full load and 25ºC otherwise noted

### OUTPUT SPECIFICATIONS

| | | | |
|---|---|---|---|
| Output power | | | 30 Watts, max. |
| Voltage accuracy | Full load and nominal Vin | | ± 1% |
| Minimum load | | | See Table |
| Voltage adjustability | | | ± 10% |
| Line regulation | LL to HL at Full Load | | ± 0.5% |
| Load regulation | No Load to Full Load | Single<br>Dual | ± 0.5%<br>± 1% |
| Cross regulation (Dual) | Asymmetrical load 25% / 100% FL | | ± 5% |
| Ripple and noise | 20MHz bandwidth (Measured with a 0.1µF/50V MLCC) | | See table |
| Temperature coefficient | | | ± 0.02% / ºC, max. |
| Transient response recovery time | 25% load step change | | 250µS |
| Over voltage protection Zener diode clamp | 1.5V output<br>1.8V output<br>2.5V output<br>3.3V output<br>5V output<br>12V output<br>15V output | | 3.9VDC<br>3.9VDC<br>3.9VDC<br>3.9VDC<br>6.2VDC<br>15VDC<br>18VDC |
| Over load protection | % of FL at nominal input | | 150%, max. |
| Short circuit protection | | | Hiccup, automatics recovery |

### GENERAL SPECIFICATIONS

| | | |
|---|---|---|
| Efficiency | | See table |
| Isolation voltage | Input to Output<br>Input (Output) to Case | 1600VDC, min.<br>1600VDC, min. |
| Isolation resistance | | $10^9$ ohms, min. |
| Isolation capacitance | | 1000pF, max. |
| Switching frequency | | 300KHz, typ. |
| Approvals and standard | | IEC60950-1, UL60950-1, EN60950-1 |
| Case material | | Nickel-coated copper |
| Base material | | FR4 PCB |
| Potting material | | Epoxy (UL94-V0) |
| Dimensions | | 2.00 X 1.60 X 0.40 Inch (50.8 X 40.6 X 10.2 mm) |
| Weight | | 48g (1.69oz) |
| MTBF (Note 1) | BELLCORE TR-NWT-000332<br>MIL-HDBK-217F | 1.315 x $10^6$ hrs<br>3.456 x $10^5$ hrs |

### INPUT SPECIFICATIONS

| | | | |
|---|---|---|---|
| Input voltage range | 24V nominal input<br>48V nominal input | | 10 – 40VDC<br>18 – 75VDC |
| Input filter | | | L-C type |
| Input surge voltage 100mS max | 24V input<br>48V input | | 50VDC<br>100VDC |
| Input reflected ripple current | Nominal Vin and full load | | 20mAp-p |
| Start up time | Nominal Vin and constant resistive load | Power up<br>Remote ON/OFF | 10mS, typ.<br>10mS, typ. |
| Start-up voltage | 24V input<br>48V input | | 10VDC<br>18VDC |
| Shutdown voltage | 24V input<br>48V input | | 8VDC<br>16VDC |
| Remote ON/OFF (Note 6) (Positive logic)(Standard) | DC-DC ON<br>DC-DC OFF | | Open or 3V < Vr < 12V<br>Short or 0V < Vr < 1.2V |
| (Negative logic)(Option) | DC-DC ON<br>DC-DC OFF | | Short or 0V < Vr < 1.2V<br>Open or 3V < Vr < 12V |
| Input current of remote control pin | Nominal Vin | | -0.5mA ~ +0.5mA |
| Remote off state input current | Nominal Vin | | 3mA |

### ENVIRONMENTAL SPECIFICATIONS

| | | |
|---|---|---|
| Operating ambient temperature | | -40ºC ~ +85ºC (with derating) |
| Maximum case temperature | | 100ºC |
| Over temperature protection | | 115ºC, typ. |
| Storage temperature range | | -55ºC ~ +105ºC |
| Thermal impedance (Note 7) | Nature convection<br>Nature convection with heat-sink | 10ºC/Watt<br>8.24ºC/Watt |
| Thermal shock | | MIL-STD-810F |
| Vibration | | MIL-STD-810F |
| Relative humidity | | 5% to 95% RH |

### EMC CHARACTERISTICS


| | | | |
|---|---|---|---|
| EMI (Note 8) | EN55022 | | Class A |
| ESD | EN61000-4-2 | Air ± 8KV<br>Contact ± 6KV | Perf. Criteria B |
| Radiated immunity | EN61000-4-3 | 10 V/m | Perf. Criteria A |
| Fast transient (Note 9) | EN61000-4-4 | ± 2KV | Perf. Criteria A |
| Surge (Note 9) | EN61000-4-5 | ± 1KV | Perf. Criteria B |
| Conducted immunity | EN61000-4-6 | 10 Vr.m.s | Perf. Criteria A |


WWW.PDUKE.COM


| Model Number | Input Range | Output Voltage | Output Current | | Output (4) Ripple & Noise | Input Current | | Eff (4) (%) | Capacitor (5) Load max |
|---|---|---|---|---|---|---|---|---|---|
| | | | Min. load | Full load | | No load (3) | Full load (2) | | |
| FEC30-24S1P5W | 10 – 40 VDC | 1.5 VDC | 0mA | 8000mA | 60mVp-p | 35mA | 658mA | 80 | 65000μF |
| FEC30-24S1P8W | 10 – 40 VDC | 1.8 VDC | 0mA | 8000mA | 60mVp-p | 35mA | 759mA | 83 | 65000μF |
| FEC30-24S2P5W | 10 – 40 VDC | 2.5 VDC | 0mA | 8000mA | 60mVp-p | 40mA | 1029mA | 85 | 33000μF |
| FEC30-24S3P3W | 10 – 40 VDC | 3.3 VDC | 0mA | 6000mA | 60mVp-p | 50mA | 994mA | 87 | 19500μF |
| FEC30-24S05W | 10 – 40 VDC | 5 VDC | 0mA | 6000mA | 75mVp-p | 65mA | 1506mA | 87 | 10200μF |
| FEC30-24S12W | 10 – 40 VDC | 12 VDC | 0mA | 2500mA | 100mVp-p | 65mA | 1506mA | 87 | 3300μF |
| FEC30-24S15W | 10 – 40 VDC | 15 VDC | 0mA | 2000mA | 100mVp-p | 70mA | 1488mA | 88 | 1100μF |
| FEC30-24D12W | 10 – 40 VDC | ±12VDC | 0mA | ±1250mA | 100mVp-p | 30mA | 1563mA | 84 | ±1000μF |
| FEC30-24D15W | 10 – 40 VDC | ±15VDC | 0mA | ±1000mA | 100mVp-p | 35mA | 1543mA | 85 | ±680μF |
| FEC30-48S1P5W | 18 – 75 VDC | 1.5 VDC | 0mA | 8000mA | 60mVp-p | 20mA | 329mA | 80 | 65000μF |
| FEC30-48S1P8W | 18 – 75 VDC | 1.8 VDC | 0mA | 8000mA | 60mVp-p | 20mA | 380mA | 83 | 65000μF |
| FEC30-48S2P5W | 18 – 75 VDC | 2.5 VDC | 0mA | 8000mA | 60mVp-p | 25mA | 508mA | 86 | 33000μF |
| FEC30-48S3P3W | 18 – 75 VDC | 3.3 VDC | 0mA | 6000mA | 60mVp-p | 30mA | 497mA | 87 | 19500μF |
| FEC30-48S05W | 18 – 75 VDC | 5 VDC | 0mA | 6000mA | 75mVp-p | 30mA | 744mA | 88 | 10200μF |
| FEC30-48S12W | 18 – 75 VDC | 12 VDC | 0mA | 2500mA | 100mVp-p | 35mA | 753mA | 87 | 3300μF |
| FEC30-48S15W | 18 – 75 VDC | 15 VDC | 0mA | 2000mA | 100mVp-p | 45mA | 744mA | 88 | 1100μF |
| FEC30-48D12W | 18 – 75 VDC | ±12VDC | 0mA | ±1250mA | 100mVp-p | 25mA | 772mA | 85 | ±1000μF |
| FEC30-48D15W | 18 – 75 VDC | ±15VDC | 0mA | ±1000mA | 100mVp-p | 25mA | 762mA | 86 | ±680μF |


Note


1. BELLCORE TR-NWT-000332. Case 1: 50% Stress, Temperature at 40ºC.
   MIL-HDBK-217F Notice2 @Ta=25 ºC, Full load(Ground, Benign, controlled environment).
2. Maximum value at nominal input voltage and full load.
3. Typical value at nominal input voltage and no load.
4. Typical value at nominal input voltage and full load.
5. Test by minimum Vin and constant resistive load.
6. The ON/OFF control pin voltage is referenced to -Vin.
   To order negative logic ON-OFF control add the suffix-N (Ex: FEC30-24S05W-N).
7. Heat sink is optional and P/N: 7G-0011C-F.
8. The FEC30W series can meet EN55022 Class A with parallel an external capacitor to the input pins.
   Recommend: 24Vin : 6.8μF/50V 1812 MLCC .
   48Vin : 2.2μF/100V*2 PCS 1812 MLCC.
9. An external input filter capacitor is required if the module has to meet EN61000-4-4, EN61000-4-5.
   The filter capacitor Power Mate suggest: Nippon chemi-con KY series, 220μF/100V, ESR 48mΩ.








1. All dimensions in Inches (mm)
   Tolerance: X.XX±0.02 (X.X±0.5)
   X.XXX±0.01 (X.XX±0.25)
2. Pin pitch tolerance ±0.01(0.25)
3. Pin dimension tolerance ±0.004 (0.1)

| PIN CONNECTION | | |
|---|---|---|
| PIN | SINGLE | DUAL |
| 1 | + INPUT | + INPUT |
| 2 | - INPUT | - INPUT |
| 4 | CTRL | CTRL |
| 5 | NO PIN | + OUTPUT |
| 6 | + OUTPUT | COMMON |
| 7 | - OUTPUT | - OUTPUT |
| 8 | TRIM | TRIM |

**EXTERNAL OUTPUT TRIMMING**

Output can be externally trimmed by using the method shown below.
( ) FOR DUAL OUTPUT TRIM





**Recommended Filter for EN55022 Class B Compliance**

The components used in the above figure, together with the manufacturers' part numbers for these components, are as follows:

| | C1 | C2 | C3 | C4 | C5 & C6 | L1 |
|---|---|---|---|---|---|---|
| FEC30-24xxxW | 6.8μF/50V 1812 MLCC | N/A | 6.8μF/50V 1812 MLCC | N/A | 1000pF/2KV MLCC | 450μH Common Choke PMT-048 |
| FEC30-48xxxW | 2.2μF/100V 1812 MLCC | 2.2μF/100V 1812 MLCC | 2.2μF/100V 1812 MLCC | 2.2μF/100V 1812 MLCC | 1000pF/2KV MLCC | 450μH Common Choke PMT-048 |




**Recommended EN55022 Class B Filter Circuit Layout**

LifeElectronics
Живое партнерство

**ООО «ЛайфЭлектроникс»** **“LifeElectronics” LLC**

*ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703*

*Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.*

*С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров*

*Мы предлагаем:*

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

*В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.*

*Конструкторский отдел помогает осуществить:*

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

*Тел: +7 (812) 336 43 04 (многоканальный)*
*Email: org@lifeelectronics.ru*

***www.lifeelectronics.ru***