


Features

- Fastest Propagation Speeds in the Industry T_{PD} (F grade) = 2.5 ns, T_{PD} (G grade) = 2.0 ns
- Maximum Derating for Capacitive Loads 1.5ns/100pF (F grade) and 1.1ns/100pF (G grade)
- Very Low Ground Bounce <0.6V @ $V_{CC}=5.00$ V, $T_a=25^{\circ}\text{C}$
- Excellent Noise Rejection
- Typical Output Skew ≤ 0.25 ns
- Bus Hold Circuitry to Retain Last Active State During Tri-State™
- Available in SSOP and TSSOP Packages

Description


Atmel's new family of high speed CMOS transceivers offers the best of all worlds to the user requiring stability and ultra fast speeds. These transceivers, which can function as two 8-bit devices or one 16-bit device, are capable of improving processing efficiency as much as 6% by reducing the number of wait states required during memory access. In addition, this family of parts has been designed to minimize ground bounce on the outputs while rejecting input spikes of up to 1.8V and 1 ns wide. This combination of ultra high speed and low noise is the next step in high speed performance.

Functional Block Diagram



Pin Configurations

Pin Names	Descriptions
$\overline{xOE}$	Output Enable Input (Active Low)
xDIR	Direction Control Input
xA_{χ}	Side A Inputs or Tri-State Outputs
xB_{χ}	Side B Inputs or Tri-State Outputs



Top View

AT16245 Fast Logic™ Bi-Directional Transceiver

AT16245F AT16245G

Function Table

Inputs		Outputs
$\overline{xOE}$	$xDIR$	
L	L	Bus B Data to Bus A
L	H	Bus A Data to Bus B
H	X ⁽¹⁾	High Z State

Note: 1. X = Don't Care

Absolute Maximum Ratings*

Operating Temperature 0°C to +70°C
Storage Temperature -65°C to +150°C
Voltage on any Pin
with Respect to Ground..... -2.0 V to +7.0V⁽¹⁾
Maximum Operating Voltage..... 6.0V

NOTICE: Stresses beyond those listed under “Absolute Maximum Ratings” may cause permanent damage to the device. This is a stress rating only and functional operation of the device at these or any other conditions beyond those indicated in the operational sections of this specification is not implied. Exposure to absolute maximum rating conditions for extended periods may affect device reliability.

Notes: 1. Minimum voltage is -0.6V dc which may undershoot to -2.0V for pulses of less than 20 ns. Maximum output pin voltage is VCC +0.75V dc which may overshoot to +7.0V for pulses of less than 20 ns.

5.0 Volt DC Characteristics

Applicable over recommended operating range from Ta=0°C to +70°C, VCC=+5.0V ±5% (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
ΔI_{CC}	Quiescent Power Supply Current	VCC=Max, VIN=3.4V		0.8	1.2	mA
V _{IH}	Input High Voltage		2.0			V
V _{IL}	Input Low Voltage				0.8	V
I _{IH}	Input High Current (I/O Pins)	VIN=VCC			±15	μA
I _{IL}	Input Low Current (I/O Pins)	VIN= GND			±15	μA
I _{OZ}	Output Leakage Current				±10	μA
V _{OH} ⁽¹⁾	Output High Voltage F Grade only	VCC=4.75 V I _{OH} =-10 mA	2.7			V
V _{OH} ⁽²⁾	Output High Voltage G Grade only	VCC=4.75 V I _{OH} =-12 mA	2.7			V
V _{OL}	Output Low Voltage (F Grade)	I _{OL} =10 mA			0.55	V
V _{OL}	Output Low Voltage (G Grade)	I _{OL} =12 mA			0.55	V

Note: 1. F grade: At VCC(max), the value of V_{OH}(max) = 3.75V and at VCC(min), V_{OH}(max) = 3.25V
2. G grade: At VCC(max), the value of V_{OH}(max) = 3.75V and at VCC(min), V_{OH}(max) = 3.35V

AC Characteristics AT16245F

Applicable over recommended operating range from $T_a=0^{\circ}\text{C}$ to $+70^{\circ}\text{C}$, $V_{CC}=5.0\text{V} \pm 5\%$ (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
t_{PHL} t_{PLH}	Propagation Delay	$CL=50\text{ pF}$			2.5	ns
t_{PZH} t_{PZL}	Output Enable Time	$CL=50\text{ pF}$			6.0	ns
t_{PHZ} t_{PLZ}	Output Disable Time	$CL=50\text{ pF}$			6.0	ns
$t_{SK}^{(1)}$	Output Skew	$CL=50\text{ pF}$			0.5	ns
$\Delta t_{PHL}^{(1)}$ Δt_{PLH}	Propagation Delay vs Output Loading			1.3	1.5	ns/100pF

Note: 1. This parameter is guaranteed but not 100% tested.


AT16245G

Applicable over recommended operating range from $T_a=0^{\circ}\text{C}$ to $+70^{\circ}\text{C}$, $V_{CC}=5.0\text{V} \pm 5\%$ (unless otherwise noted)

Symbol	Parameter	Test Conditions	Min	Typ	Max	Units
T_{PHL} T_{PLH}	Propagation Delay	$CL=50\text{ pF}$			2.0	ns
T_{PZH} T_{PZL}	Output Enable Time	$CL=50\text{ pF}$			6.0	ns
T_{PHZ} T_{PLZ}	Output Disable Time	$CL=50\text{ pF}$			5.0	ns
$T_{SK}^{(1)}$	Output Skew	$CL=50\text{ pF}$			0.5	ns
$\Delta t_{PHL}^{(1)}$ Δt_{PLH}	Propagation Delay vs Output Loading			0.9	1.1	ns/100pF

Note: 1. This parameter is guaranteed but not 100% tested.

Test Circuits^(1,2)



- Note:
1. Pulse Generator: Rate $\leq 1.0\text{ MHz}$, $t_r \leq 2.5\text{ ns}$, $t_f \leq 2.5\text{ ns}$.
 2. AC tests are done with a single bit switching, and timings need to be derated when multiple outputs are switching in the same direction simultaneously. This derating should not exceed 0.5 ns for 16 inputs switching simultaneously.


Switch Position

Test	Switch
Open Drain Disable Low Enable Low	Closed
All Other Tests	Open


Definitions:

- C_L = Load capacitance; Includes jig and probe capacitance.
 R_T = Termination resistance; Should be equal to Z_{OUT} of the Pulse Generator.


IOL Pull Down Current



Ground Bounce for High to Low Transitions⁽¹⁾



Supply Bounce for Low to High Transitions⁽²⁾




Typical Values


Parameter	Value	Units
V_{OLP}	0.4	V
V_{OLV}	-0.26	V
V_{OHV}	$V_{CC} - 0.13$	V
V_{OHP}	$V_{CC} + 0.6$	V

- Note:
1. When multiple outputs are switched at the same time, rapidly changing current on the ground and V_{CC} paths cause a voltage to develop across the parasitic inductance of the wire bond and package pins. This occurrence is called simultaneous switching noise. Atmel's AT16245 products have minimized this phenomenon as shown on the graph. Output data is for 15 outputs switching simultaneously at a frequency of 1 MHz. The ground data is measured on the one remaining output, which is set to logic low and will reflect any device ground movement.
 2. As on the graph for Ground Bounce, a similar condition occurs for low to high transitions. Output data is for 15 outputs switching simultaneously at a frequency of 1 MHz. V_{CC} droop is measured on the one remaining output pin, which is set to a logic high. This output will reflect any movement on the device V_{CC} .

Propagation Delay Waveforms



Enable and Disable Waveforms⁽¹⁾



Note: 1. Enable and disable waveforms are the same for both $\overline{xOE}$ and $xDIR$ inputs.



Ordering Information

T_{PD}	Ordering Code	Package	Operation Range
2.5 ns	AT16245F - 25YC AT16245F - 25XC	48Y 48X	Commercial
2.0 ns	AT16245G - 20YC AT16245G - 20XC	48Y 48X	Commercial

Package Type	
48X	48 Pin, Plastic Thin Shrink Small Outline Package (TSSOP)
48Y	48 Pin, Plastic Shrink Small Outline Package (SSOP)

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru