



**HERMETIC STRAIGHT MALE RECEPTACLE****R222.645.000****SOLDER TYPE - FULL DETENT**


Series : SMP



Scale 1:1



All dimensions are in mm.



| COMPONENTS     | MATERIALS | PLATINGS ( $\mu\text{m}$ ) |
|----------------|-----------|----------------------------|
| BODY           | DILVER P1 | GOLD 0.5 OVER NICKEL 2     |
| CENTER CONTACT | DILVER P1 | GOLD 0.5 OVER NICKEL 2     |
| OUTER CONTACT  |           |                            |
| INSULATOR      | GLASS     |                            |
| GASKET         |           |                            |
| OTHERS PARTS   |           |                            |
| -              | -         | -                          |
| -              | -         | -                          |

Issue : 0950 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



**HERMETIC STRAIGHT MALE RECEPTACLE****R222.645.000****SOLDER TYPE - FULL DETENT**

Series : SMP

**PACKAGING**

| Standard   | Unit              | Other             |
|------------|-------------------|-------------------|
| <b>100</b> | <b>'W' option</b> | <b>Contact us</b> |

**SPECIFICATION****ELECTRICAL CHARACTERISTICS**

|                                 |                      |                                |
|---------------------------------|----------------------|--------------------------------|
| Impedance                       | <b>50</b>            | $\Omega$                       |
| Frequency                       | <b>0-18</b>          | GHz                            |
| VSWR                            | <b>1.15 + 0,0000</b> | x F(GHz) Maxi                  |
| Insertion loss                  | <b>0.12</b>          | $\sqrt{F}(\text{GHz})$ dB Maxi |
| RF leakage                      | <b>NA</b>            | - F(GHz)) dB Maxi              |
| Voltage rating                  | <b>335</b>           | Veff Maxi                      |
| Dielectric withstanding voltage | <b>500</b>           | Veff mini                      |
| Insulation resistance           | <b>5000</b>          | M $\Omega$ mini                |

**ENVIRONMENTAL**

|                       |                 |                    |
|-----------------------|-----------------|--------------------|
| Operating temperature | <b>-65/+165</b> | $^{\circ}\text{C}$ |
| Hermetic seal         | <b>10-8</b>     | Atm.cm3/s          |
| Panel leakage         | <b>NA</b>       |                    |

**OTHERS CHARACTERISTICS**Assembly instruction **NA**

Others :

**MECHANICAL CHARACTERISTICS**

|                            |                        |
|----------------------------|------------------------|
| Center contact retention   |                        |
| Axial force – Mating end   | <b>6.8</b> N mini      |
| Axial force – Opposite end | <b>6.8</b> N mini      |
| Torque                     | <b>NA</b> N.cm mini    |
| Recommended torque         |                        |
| Mating                     | <b>NA</b> N.cm         |
| Panel nut                  | <b>NA</b> N.cm         |
| Mating life                | <b>100</b> Cycles mini |
| Weight                     | <b>0,2200</b> g        |


Issue : 0950 B

In the effort to improve our products, we reserve the right to make changes judged to be necessary.




**HERMETIC STRAIGHT MALE RECEPTACLE****SOLDER TYPE - FULL DETENT****R222.645.000**

Series : SMP



1. Degrease and clean connector and box
2. Solder the connector on the panel  
we advise SnAg4 Cu0.5, we recommend a low residue flux.  
Preheating at 100 °C. Take care not to exceed 260°C during solder operation
3. Solder the pin on the track  
we advise SnAg4 Cu0.5, we recommend a low residue flux.  
Preheating at 100 °C (only for ceramic substrate). Take care not to exceed 260°C during solder operation

**Issue : 0950 B**

In the effort to improve our products, we reserve the right to make changes judged to be necessary.



Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)