

swissbit®

Product fact sheet

Industrial CompactFlash™ Card

C-300 Series

up to UDMA4 / MDMA4 / PIO6

BU: Swissbit Group
Date: March 18, 2016
Revision: 1.00
File: C-300_fact_sheet_CF-
HxBK_Rev101.doc



C-300 SERIES – UDMA COMPACTFLASH™ CARD, 64MBYTE UP TO 4GBYTE, 3.3/5V SUPPLY

Main Features

- Highly-integrated memory controller
 - Fully compliant with CompactFlash™ specification 3.0, compatible with specification 4.1
 - Fully compatible with PCMCIA specification
 - PC Card ATA Interface supported
 - True IDE mode compatible
 - Up to PIO mode 6 supported
 - Up to MDMA4 supported
 - Up to UDMA4 supported
 - Hardware RS-code ECC (4 Bytes/528 Bytes correction)
 - Fix drive (IDE mode) & removable drive (PCMCIA mode) as default in the same card
- Small form factor
 - CFC Type I: 36.4mm x 42.8mm x 3.3mm
- Low-power CMOS technology
- 3.3V or 5.0V power supply
- Power saving mode (with automatic wake-up)
- S.M.A.R.T. support by *-SMA product type
- Wear Leveling: equal wear leveling of static and dynamic data
The wear leveling assures that dynamic data as well as static data is balanced evenly across the memory. With that the maximum write endurance of the device is guaranteed.
- Data Retention: 10 year (JESD47)
- Patented power-off reliability
 - No data loss of older sectors
 - Max. 16 sectors data loss (old data kept) for 2k Page flash respectively
 - All data written to the flash if card status is ready after write command
- High reliability
 - Best available SLC NAND Flash technology
 - Designed for embedded market
 - MTBF: > 3,000,000 hours
 - Data reliability: < 1 non-recoverable error per 10¹⁴ bits read
 - Number of insertions: > 10,000
- Hot swappable in PCMCIA modes
- High random performance
 - Up to 66MB/s burst transfer rate in UDMA4
 - Optimized for random access >150kB/s
 - Sustained Read/Write performance: up to 37/20MB/s (UDMA4)
- Available densities
 - up to 4GBytes (SLC NAND Flash)
- Operating System support
 - Standard Software Drivers operation CompactFlash™
- 2 Temperature ranges
 - Commercial Temperature range 0 ... +70°C
 - Industrial Temperature range -40 ... +85°C
- Controlled BOM



on request

System Performance

| Parameter | Typ. | Max. | Unit |
|---|---------------------------------|-----------------------------|-------------|
| Sleep to write | | 5 | ms |
| Sleep to read | | 5 | |
| Power up to Ready | <500 | 1000 | |
| Reset to Ready (IDE Master) | | 500 | MB/s |
| Data transfer Rate (UDMA4 burst) | | 66 (440X) ⁽¹⁾ | |
| Sustained Read/Write 64 to 256, (measured) | 20/13 ⁽¹⁾⁽²⁾ | 24/14 ⁽¹⁾ | |
| Sustained Read/Write 512 to 2048MB (measured) | 35/18 ⁽¹⁾⁽²⁾ | 37/20 ⁽¹⁾ | |
| 4k Random Read/Write 64 to 256MB (measured) | 11/0.13 (32) ⁽¹⁾⁽²⁾ | 13/0.20(50) ⁽¹⁾ | |
| 4k Random Read/Write 512 to 2048MB (measured) | 11/0.065 (16) ⁽¹⁾⁽²⁾ | 13/0.08 (20) ⁽¹⁾ | MB/s (IOPS) |
| Command to DRQ | Read | 100 | |
| | Write | 30 | |

- (1) All values refer to Micron Flash, CFC in UDMA mode 4, cycle time 30ns, write/read file sequential transfer 256 sectors/command or random 8 sector/command
(2) Sustained Speed depends on flash type and number, file size, and burst speed

| Current Consumption ⁽³⁾ @ 3.3V | Typ. | Max. | Unit |
|---|------|------|------|
| Read (UDMA4) | 80 | 130 | mA |
| Write (UDMA4) | 80 | 130 | |
| Idle Mode | 0.5 | 1.5 | |

- (3) All values are typical at 25° C and nominal supply voltage and refer to 4GByte 2 channel CFC.

Physical Dimensions

| Parameter | Value | Unit |
|---------------|-------|------|
| Width | 36.4 | mm |
| Height | 42.8 | |
| Thickness | 3.3 | |
| Weight (typ.) | 10 | g |

Environmental Specifications

| Parameter | Operating | Non Operating |
|---------------------------|---|---------------|
| Temperature (commercial) | 0 to 70°C | -40 to 85°C |
| Temperature (industrial) | -40 to 85°C | -50 to 100°C |
| Humidity (non-condensing) | 85% RH 85°C, 1000 hrs (JEDEC JESD22, method A101-B) | |
| Vibration (peak -to-peak) | 20 G peak, 20-2000Hz, 4 per direction (JEDEC JESD22, method B103), 5.35G RMS, 15 min per plane (IEC 68-2-6) | |
| Shock | 1.5k G peak, 0.5ms 5 times (JEDEC JESD22, method B110) 30 G, 11ms 1 time (IEC 68-2-27) | |

Capacity specification

| Capacity | cylinders | heads | Sectors/track | Sectors_drive | Total addressable capacity (Byte) |
|----------|-----------|-------|---------------|---------------|-----------------------------------|
| 64MB | 490 | 8 | 32 | 125,440 | 64,225,280 |
| 128MB | 937 | 8 | 32 | 239,872 | 122,814,464 |
| 256MB | 980 | 16 | 32 | 501,760 | 256,901,120 |
| 512MB | 993 | 16 | 63 | 1,000,944 | 512,483,328 |
| 1GB | 1,986 | 16 | 63 | 2,001,888 | 1,024,966,656 |
| 2GB | 3,970 | 16 | 63 | 4,001,760 | 2,048,901,120 |
| 4GB | 7,964 | 16 | 63 | 8,027,712 | 4,110,188,544 |

System Reliability

| System Reliability and Maintenance | |
|------------------------------------|--|
| MTBF (at 25°C) | > 3,000,000 hours |
| Data Reliability | < 1 Non-Recoverable Error per 10 ¹⁴ bits Read |

Why Swissbit?

Swissbit strives to create innovative technologies for future market opportunities utilizing a highly skilled in-house product research and development team. Swissbit maintains a marketing edge by continuing to manufacture world-class high quality memory products and providing customers with both high value and low cost of ownership achieved through efficient processes and procedures.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru