



No hassle warranty

No waiting.

No shipping charges.



Our commitment to high-quality products and customer service is demonstrated by our industry exclusive "No Hassle" warranty. In the unlikely event that an Amprobe Test Tool requires warranty service, any of our local dealers are authorized to replace it, on the spot.

(note: \$500 MSLP limit)

ACD-22SW Swivel Clamp Meter

New patented rotating head clamp design allows easy viewing of the measurements in tight or inconvenient to reach places. Simply rotate the body of meter to get an unobstructed view of the LCD display. Rich set of features and CAT III 600V safety reading for use in electrical and HVAC applications.

- TRMS Measurement
- 180 degree rotating head for the perfect display viewing
- Advanced VoltText non-contact voltage detection
- Slim jaw design with one hand operation
- Measures AC Current up to 400 ACA, AC/DC Voltage up to 600V, Resistance and Capacitance
- Audible continuity
- Auto and manual ranging respectively for quick checks and precise measurements
- Backlight
- Auto power off
- Data hold
- Accommodates conductors up to 1.18" (30mm) in diameter
- Safety CAT III 600 V
- Test leads, battery (installed), Users Manual, Carrying Case and type-K thermocouple are included with the product



ACD-22SW Swivel Clamp Meter

Data Sheet

General Specifications

Display	3¾ digit liquid crystal display (LCD) with a maximum reading of 3999.
Polarity	Automatic, positive implied, negative polarity indication.
Overrange	(OL) or (-OL) is displayed.
Zero	Automatic.
Low battery indication	The "□" is displayed when the battery voltage drops below the operating level.
Auto power off	Approx. 10 minutes.
Measurement rate	2 times per second, nominal.
Operating Environment	0°C to 50°C / 32°F to 122°F at <70% relative humidity.
Storage Temperature	-20°C to 60° / -4°F to 140°F, 0 to 80% R.H. with battery removed from meter.
Accuracy	Stated accuracy at 74°F ±8°F, <75% relative humidity.
Temperature Coefficient	0.1 × (specified accuracy) per °F, (32°F to 66°F, 82°F to 122°F).
Altitude	6561.7 Feet (2000m).
Jaw opening capability	30mm conductor.
Power	1.5 volt battery x2, R03/SIZE AAA.
Battery life	50 hours typical with carbon-zinc. 100 hours typical with alkaline.
Dimensions	240 × 70 × 41mm (9.5 × 2.8 × 1.6 in).
Weight	Approx. 220g (7.7oz.) including battery.
Safety	Designed to meet IEC 61010-1 (EN61010-1) and IEC 61010-2-032 (EN61010-2-032), CAT III 600V class II and pollution degree 2 indoor use comply with CE, CSA

Electrical Specifications

DC Volts

Ranges	400mV, 4V, 40V, 400V, 600V
Resolution	0.1mV
Accuracy	±(0.5% rdg + 2 dgts)
Input Impedance	400mV:>100MΩ; 4V:10MΩ; 40V~600V:9.1MΩ
Overload Protection	600VDC or AC rms To measure millivolts, use "RANGE " button to manually select 400mV range.

AC Volts (50Hz - 500Hz)

Ranges	4V, 40V, 400V, 600V
Resolution	1mV
Accuracy	±(1.2% rdg + 8 dgts) ±(1.5% rdg + 8 dgts) on 600V range
Crest Factor	≤ 3
AC coupled true rms specified from 5% to 100% range	
Input Impedance	4V:10MΩ; 40V~600V:9.1MΩ
Overload Protection	600 VDC or AC rms

AC Current (50Hz - 60Hz)

Ranges	40A, 400A
Resolution	0.01A
Accuracy	±(2.0% rdg + 10 dgts) 50 ~ 60Hz
Crest Factor	≤ 3
AC coupled true rms specified from 5% to 100% range	
Overload Protection	400A AC



ACD-22SW Swivel Clamp Meter

Data Sheet

Resistance

Ranges	400 Ω , 4k Ω , 40k Ω , 400k Ω , 4M Ω , 40M Ω
Resolution	0.1 Ω
Accuracy	$\pm(1.0\% \text{ rdg} + 5 \text{ dgts})$ on 400 Ω to 400k Ω ranges
	$\pm(1.5\% \text{ rdg} + 5 \text{ dgts})$ on 4M Ω range
	$\pm(3.0\% \text{ rdg} + 5 \text{ dgts})$ on 40M Ω range
Open Circuit Volts	-0.45V dc typical, (-1.2Vdc on 400 Ω range)
Overload Protection	600VDC or AC rms

Diode Test

Test Current	0.8mA (approximate)
Accuracy	$\pm(3.0\% \text{ rdg} + 3 \text{ dgts})$
Open Circuit Volts	3.0 Vdc typica
Overload Protection	600VDC or AC rms

Continuity

Range	400 Ω
Resolution	1 Ω
Audible Indication:	Less than 25 Ω
Response Time	500ms
Overload Protection	600VDC or AC rms

Non-Contact Voltage Indicator Sense voltage 70V to 600VAC (50Hz ~ 60Hz) beeper chirps and big bright red LED comes on, works when meter dial is on any ranges.

AUXILIARY FEATURES

Hold	Freeze the latest reading on the display.
Range	Excute manual range mode.
Disable Auto Power Off	Set the DMM to off position, press (RANGE) button, and hold the (RANGE) button while turning the rotary knob to the desired range position. Release the button when LCD displays normally. Note "APO" annunciator is missing from the LCD. The Auto Power Off mode is activated with an "APO" symbol indicating on LCD.



ACD-22SW Swivel Clamp Meter

Data Sheet

Included Accessories

One pair test leads
1.5V battery x2 (installed)
Carrying case
TPK01 thermocouple
Users Manual

Amprobe® Test Tools

website: www.Amprobe.com
email: info@amprobe.com
Everett, WA 98203
Tel: 877-AMPROBE

Amprobe® Test Tools Europe

In den Engematten 14
79286 Glottertal, Germany
Tel.: +49 (0) 7684 8009 - 0

©2010 Amprobe Test Tools. All rights reserved.
08/2010 ACD-22SW_DS Rev A

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru