



AMPROBE® Model GP-2

Ground Resistance and Resistivity Tester

Features

- Measures Earth Ground Resistance (Ω)
- Automatically Calculates Resistivity ($m\Omega$)
- Test leads, auxiliary electrodes and software are included for a complete instrument
- Voltage Measurement
- Automatically applies three testing frequencies for the most accurate readings
- Auto ranging
- Stores up to 999 measurements in the memory
- DATA download to a PC (RS-232)

Benefits

- Three point test (fall of potential) measures earth ground resistance as required by equipment manufacturer specifications and as mandated by national code requirements for proper grounding
- Two point test is used to test grounding wires resistance and resistance of connection points between ground system elements i.e., wires and electrodes
- Tests soil for a new ground system design
- Does not require any additional meters to test voltage before grounding test is performed
- Easy to operate
- Data can be stored for later viewing
- Durable
- Downloads data to a personal computer to generate reports and store historical data

GP-2 Geo Test

Applications

- Ground resistance of the electrode or grid system
- Cathodic protection
- Soil contamination
- Lighting protection
- Isolated grounding

put me to the test.

The largest selection of test measurement
equipment for electrical professionals



Miami, Florida

P(305) 423-7500 • F(305) 423-7554

www.amprobe.com

AAD-197



GP-2

Geo Test

Model GP-2

TECHNICAL SPECIFICATIONS

Resistance measurement

Range (**) (Ω)	Resolution (Ω)	Accuracy (*)
0.01 ÷ 19.99	0.01	
20.0 ÷ 199.9	0.1	$\pm(2\% \text{ reading} + 3 \text{ digits})$
200 ÷ 1999	1	

Resistivity measurement ρ

Range (**)	Resolution	Accuracy (*)
0.6-125.6 Ω m	0.1 Ω m	
0.125-1.256 k Ω m	0.001 k Ω m	$\pm(2\% \text{ reading} + 3 \text{ digits})$
1.25-19.99 k Ω m	0.01 k Ω m	
20.0-199.9 k Ω m	0.1 k Ω m	

(*) If $R_p > 100R_E$ and/or $R_C > 100R_E$, $R_p > 50k\Omega$ and/or $R_C > 50k\Omega$, if the instrument carries out the test the accuracy of the instrument is $\pm(10\% \text{ Reading})$

R_p = resistance of the voltage circuit

R_C = resistance of the current circuit

R_E = earth resistance

$\rho = 2\pi DR_E$ = calculated resistivity

(**) Automatic selection of the range

Testing frequency	125Hz/75Hz/41.66Hz
Testing current	10mA
Open-terminal measuring voltage	25Vrms
Waveform of measuring voltage:	sine wave

Interfering voltage:

- amperometric circuit: the measurement is taken with the stated accuracy if the interfering voltage is $\leq 3V$, while for interfering voltages between 3 and 30V inclusive, the accuracy decreases progressively; with an interfering voltage of about 30V the instrument does not perform the test.
- voltmetric circuit: the measurement is taken if the interfering voltage is $\leq 3V$; in case of higher voltages the instrument does not perform the test.

Interfering voltage measurement

Range (**) (V)	Resolution (V)	Accuracy
500	1	$\pm(2\% \text{ reading} + 2 \text{ digits})$

Safety Standards

This instrument complies with EN 61010, EN 61557-1, EN 61557-5 standards.

Insulation Class 2, double insulation

Pollution 2

Maximum altitude 2000m

Surge voltage category CAT III 250V (phase to earth)

General features

Mechanical features

Dimensions: 8.74" (L) x 6.38" (W) x 2.25" (H)

Weight (batteries included): About 2.2 lb (1000g)

Power supply

Batteries: 6 batteries 1.5 V size AA (LR6 -AM3-MN1500)

Low battery indication: The symbol \square appears on the display when the battery voltage is low.

Battery life: about 300 measurements

Fusible Link: F 100 mA (not accessible to the operator)

Auto Power Off: The instrument will automatically switch off 2 minutes after last selecting a function or PC command

Display

Features: standard LCD 65mm x 65mm.

Memory: 999 memory locations

Interfaces: opto-insulated serial output RS232 to transfer data to a PC.

OPERATING CONDITIONS

Environmental conditions

Reference temperature: $73 \pm 41F$ ($23^\circ C \pm 5^\circ C$)

Operating temperature: $14 \pm 122F$ ($-10^\circ C \div 50^\circ C$)

Relative humidity: <80%

Storage temperature: $-4F \pm 140F$ ($-20^\circ C \div 60^\circ C$)

Storage humidity: <70%

ECM

This instrument has been designed in compliance with the EMS standards in force and its compatibility has been tested for:

Irradiated emissions: EN55011

Immunity: EN50140, EN61000

Electrostatic discharges: EN61000-4-2

R.F. range: EN50140

Fast transient: EN61000-4-4

ACCESSORIES

Standard and optional accessories

Standard accessories*	Code
-1 carrying case containing: -4 earth rods -4 cables banana crocodile	GP-2CON
Carrying case	GP-2CC
Optical serial cable	C2000
Software and manual	www.amprobe.com

ООО "ЛайфЭлектроникс"

"LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибуторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибуторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помочь разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru