

**9936 Multi-Conductor - Low-Capacitance Computer Cable for EIA RS-232/423**

For more Information  
please call

1-800-Belden1

**Description:**

24 AWG stranded (7x32) TC conductors, Datalene® insulation, overall Beldfoil® (100% coverage) + TC braid shield (65% coverage), drain wire, PVC jacket.

**Physical Characteristics (Overall)****Conductor****AWG:**

| # Conductors | AWG | Stranding | Conductor Material |
|--------------|-----|-----------|--------------------|
| 15           | 24  | 7x32      | TC - Tinned Copper |

**Insulation****Insulation Material:**

| Insulation Trade Name | Insulation Material     |
|-----------------------|-------------------------|
| Datalene®             | FPE - Foam Polyethylene |

**Outer Shield****Outer Shield Material:**

| Layer # | Outer Shield Trade Name | Type  | Outer Shield Material        | Coverage (%) |
|---------|-------------------------|-------|------------------------------|--------------|
| 1       | Beldfoil®               | Tape  | Aluminum Foil-Polyester Tape | 100          |
| 2       |                         | Braid | TC - Tinned Copper           | 65           |

**Outer Shield Drain Wire AWG:**

| AWG | Stranding | Drain Wire Conductor Material |
|-----|-----------|-------------------------------|
| 24  | Stranded  | TC - Tinned Copper            |

**Outer Jacket****Outer Jacket Material:**

| Outer Jacket Material    |
|--------------------------|
| PVC - Polyvinyl Chloride |

**Overall Cabling****Overall Cabling Color Code Chart:**

| Number | Color        |
|--------|--------------|
| 1      | Black        |
| 2      | White        |
| 3      | Red          |
| 4      | Green        |
| 5      | Orange       |
| 6      | Blue         |
| 7      | White/Black  |
| 8      | Red/Black    |
| 9      | Green/Black  |
| 10     | Orange/Black |
| 11     | Blue/Black   |
| 12     | Black/White  |
| 13     | Red/White    |
| 14     | Green/White  |
| 15     | Blue/White   |

**Overall Nominal Diameter:**

8.763 mm

## 9936 Multi-Conductor - Low-Capacitance Computer Cable for EIA RS-232/423

**Mechanical Characteristics (Overall)**

|                                        |                          |
|----------------------------------------|--------------------------|
| Operating Temperature Range:           | -30°C To +80°C           |
| UL Temperature Rating:                 | 80°C (UL AWM Style 2919) |
| Bulk Cable Weight:                     | 108.639 Kg/Km            |
| Min. Bend Radius (Install)/Minor Axis: | 91.440 mm                |

**Applicable Specifications and Agency Compliance (Overall)****Applicable Standards & Environmental Programs**

|                                       |                           |
|---------------------------------------|---------------------------|
| NEC/(UL) Specification:               | CM                        |
| CEC/C(UL) Specification:              | CM                        |
| AWM Specification:                    | UL Style 2919 (30 V 80°C) |
| EU CE Mark:                           | Yes                       |
| EU Directive 2000/53/EC (ELV):        | Yes                       |
| EU Directive 2002/95/EC (RoHS):       | Yes                       |
| EU RoHS Compliance Date (mm/dd/yyyy): | 01/01/2004                |
| EU Directive 2002/96/EC (WEEE):       | Yes                       |
| EU Directive 2003/11/EC (BFR):        | Yes                       |
| CA Prop 65 (CJ for Wire & Cable):     | Yes                       |
| MII Order #39 (China RoHS):           | Yes                       |

**Flame Test**

|                |                    |
|----------------|--------------------|
| UL Flame Test: | UL 1685 UL Loading |
|----------------|--------------------|

**Plenum/Non-Plenum**

|               |    |
|---------------|----|
| Plenum (Y/N): | No |
|---------------|----|

**Electrical Characteristics (Overall)****Nom. Capacitance Conductor to Conductor:**

|                    |
|--------------------|
| Capacitance (pF/m) |
| 39.372             |

**Nom. Capacitance Cond. to Other Conductor & Shield:**

|                    |
|--------------------|
| Capacitance (pF/m) |
| 72.182             |

**Nominal Velocity of Propagation:**

|        |
|--------|
| VP (%) |
| 78     |

**Nom. Conductor DC Resistance:**

|                     |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 78.744              |

**Nominal Outer Shield DC Resistance:**

|                     |
|---------------------|
| DCR @ 20°C (Ohm/km) |
| 11.6804             |

**Max. Operating Voltage - UL:**

|                              |
|------------------------------|
| Voltage                      |
| 30 V RMS (UL AWM Style 2919) |
| 300 V RMS                    |

**Max. Recommended Current:**

|                               |
|-------------------------------|
| Current                       |
| 1.1 Amps per conductor @ 25°C |

## 9936 Multi-Conductor - Low-Capacitance Computer Cable for EIA RS-232/423

**Notes (Overall)**

**Notes:** Datalene® insulation features include a low dielectric constant and a low dissipation factor for high-speed, low-distortion data handling. Physical properties include good crush resistance and light weight.

**Related Documents:**

No related documents are available for this product

**Put Ups and Colors:**

| Item #       | Putup  | Ship Weight | Color  | Notes | Item Desc           |
|--------------|--------|-------------|--------|-------|---------------------|
| 9936 060100  | 30 MT  | 3.039 KG    | CHROME |       | 15 #24 FHDPE SH PVC |
| 9936 0601000 | 305 MT | 28.576 KG   | CHROME | C     | 15 #24 FHDPE SH PVC |
| 9936 060500  | 152 MT | 14.969 KG   | CHROME | C     | 15 #24 FHDPE SH PVC |

**Notes:**

C = CRATE REEL PUT-UP.

Revision Number: 3    Revision Date: 02-19-2008

© 2011 Belden, Inc.  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)