

Type 150 Axial Leaded Metallized Polyester Flame Retardant Wrap and Fill Axial Leaded Capacitors



The Type 150 series axial lead metallized polyester non inductive capacitors are available in bulk or on tape and reel for automatic insertion. Type 150 is a general purpose capacitor for use in blocking, bypass, decoupling, smoothing and some timing applications.

Highlights

- Available on tape and reel or bulk
- Epoxy end fill meets UL94V-0
- Non inductively wound
- Flame retardant outer wrap meets UL510
- Non polar

Specifications

Capacitance Range:	0.001 μ F to 10.0 μ F
Voltage Range:	63 to 1000 Vdc
Capacitance Tolerance:	\pm 5%, \pm 10%, \pm 20%
Operating Temperature Range:	-55 $^{\circ}$ C to +125 $^{\circ}$ C (derate linearly to 50% rated voltage at 125 $^{\circ}$ C)
Dielectric Withstand Voltage:	1.6 x rated voltage for 2 s @ +25 $^{\circ}$ C \pm 5 $^{\circ}$ C
Dissipation Factor (DF):	$\text{tg}\delta \times 10^{-4}$ at +25 $^{\circ}$ C \pm 5 $^{\circ}$ C

kHz	C \leq 0.1 μ F	0.1 μ F < C \leq 1 μ F	C > 1 μ F
1	80	80	100
10	150	150	—
100	250	—	—

Insulation Resistance:	10,000 M Ω x μ F, 30,000 M Ω Min.
Self Inductance:	1 nH max. per 1 mm lead and body length
Life Test:	1000 hrs @ 85 $^{\circ}$ C 1.25 x Vn
Damp Heat Test:	95% RH @ +45 $^{\circ}$ C for 21 days
Soldering:	260 $^{\circ}$ C \pm 5 $^{\circ}$ C for 10 s \pm 1 s
Long Term Storage Stability:	Δ C/C \leq \pm 3% after 2 years
Maximum Pulse Rise Time dv/dt and Pulse Characteristic (Wo):	

V/n	L Max				dV/dt (V/ μ sec) Wo (V ² / μ sec)
	16.5	19 - 20.5	26.5 - 5.28	31.5 - 33	
50 - 63	4	2	1.5	1	
	504	252	189	126	
100	5	3	2	1	
	1,000	600	400	300	
250	10	7	4	2.5	
	5,000	3,500	2,000	1,250	
400	13.5	10	6.5	4	
	10,800	8,000	5,200	3,200	
630	20	15	10	6	
	25,200	18,900	12,600	7,500	



Complies with the EU Directive 2002/95/EC requirement restricting the use of Lead (Pb), Mercury (Hg), Cadmium (Cd), Hexavalent chromium (Cr(VI)), PolyBrominated Biphenyls (PBB) and PolyBrominated Diphenyl Ethers (PBDE).

Type 150 Axial Leaded Metallized Polyester

Tape and Reel Specifications

Outline Drawing

L Max (Body Lengthy)		Lead Spacing		Distance Between Reel Flanges		Class
Inches	mm	Inches	mm	Inches	mm	
≤.433	≤11	2.06	52.4	3	75	1
.551 - .808	14 - 20.5	2.5	63.6	3.4	86	2
≥1.03	≥26	2.87	73	3.7	95	3

^Add class number (1, 2, or 3) to catalog number to indicate tape and reel

Diameter		Quantity per Reel
Inches	mm	
0.197	5	3,000
.236 thru .256	6.0 thru 6.5	1,200
0.276	7	1,100
.315 thru .346	8 thru 8.5	800
.354 thru .413	9 thru 10.5	500
.433 thru .512	11 thru 13	300
.551 thru .571	14 thru 14.5	200
>.571	>14.5	Not available



Ratings

Catalog Part Number	Cap (µF)	Inches Max			Millimeters Max		
		D	L	Ød	D	L	Ød
63 Vdc							
150154*63AA^	0.150	0.197	0.433	0.024	5.0	11.0	0.6
150154*63BB^	0.150	0.236	0.650	0.024	6.0	16.5	0.6
150184*63AA^	0.180	0.197	0.433	0.024	5.0	11.0	0.6
150184*63BB^	0.180	0.236	0.650	0.024	6.0	16.5	0.6
150224*63BB^	0.220	0.236	0.650	0.024	6.0	16.5	0.6
150274*63BB^	0.270	0.236	0.650	0.024	6.0	16.5	0.6
150334*63BB^	0.330	0.236	0.650	0.024	6.0	16.5	0.6
150394*63CB^	0.390	0.256	0.650	0.024	6.5	16.5	0.6
150474*63DB^	0.470	0.276	0.650	0.024	7.0	16.5	0.6
150564*63DB^	0.560	0.276	0.650	0.024	7.0	16.5	0.6
150684*63DC^	0.680	0.276	0.807	0.024	7.0	20.5	0.6
150824*63EC^	0.820	0.315	0.807	0.031	8.0	20.5	0.8
150105*63EC^	1.000	0.315	0.807	0.031	8.0	20.5	0.8
150155*63HC^	1.500	0.374	0.807	0.031	9.5	20.5	0.8
150225*63HE^	2.200	0.374	1.102	0.031	9.5	28.0	0.8
150335*63KE^	3.300	0.433	1.102	0.031	11.0	28.0	0.8
150475*63ME^	4.700	0.492	1.102	0.031	12.5	28.0	0.8
150685*63QF^	6.800	0.571	1.299	0.031	14.5	33.0	0.8
150106*63TF^	10.000	0.610	1.299	0.031	15.5	33.0	0.8
100 Vdc							
150683*100AA^	0.068	0.197	0.433	0.024	5.0	11.0	0.6
150683*100BB^	0.068	0.236	0.650	0.024	6.0	16.5	0.6
150823*100AA^	0.082	0.197	0.433	0.024	5.0	11.0	0.6
150823*100BB^	0.082	0.236	0.650	0.024	6.0	16.5	0.6
150104*100AA^	0.100	0.197	0.433	0.024	5.0	11.0	0.6
150104*100BB^	0.100	0.236	0.650	0.024	6.0	16.5	0.6
150124*100BB^	0.120	0.236	0.650	0.024	6.0	16.5	0.6
150154*100BB^	0.150	0.236	0.650	0.024	6.0	16.5	0.6
150184*100CB^	0.180	0.256	0.650	0.024	6.5	16.5	0.6
150224*100CB^	0.220	0.256	0.650	0.024	6.5	16.5	0.6

Catalog Part Number	Cap (µF)	Inches Max			Millimeters Max		
		D	L	Ød	D	L	Ød
150274*100CB^	0.270	0.256	0.650	0.024	6.5	16.5	0.6
150334*100EB^	0.330	0.315	0.650	0.031	8.0	16.5	0.8
150394*100EB^	0.390	0.315	0.650	0.031	8.0	16.5	0.8
150474*100DC^	0.470	0.276	0.807	0.031	7.0	20.5	0.8
150564*100EC^	0.560	0.315	0.807	0.031	8.0	20.5	0.8
150684*100FC^	0.680	0.335	0.807	0.031	8.5	20.5	0.8
150824*100HC^	0.820	0.374	0.807	0.031	9.5	20.5	0.8
150105*100IC^	1.000	0.394	0.807	0.031	10.0	20.5	0.8
100 Vdc							
150155*100IE^	1.500	0.394	1.102	0.031	10.0	28.0	0.8
150225*100LE^	2.200	0.453	1.102	0.031	11.5	28.0	0.8
150335*100PE^	3.300	0.531	1.102	0.031	13.5	28.0	0.8
150475*100RF^	4.700	0.591	1.299	0.031	15.0	33.0	0.8
150685*100WF^	6.800	0.689	1.299	0.031	17.5	33.0	0.8
150106*100YF^	10.000	0.807	1.299	0.031	20.5	33.0	0.8
250 Vdc							
150123*250AA^	0.012	0.197	0.433	0.024	5.0	11.0	0.6
150123*250BB^	0.012	0.236	0.650	0.024	6.0	16.5	0.6
150153*250AA^	0.015	0.197	0.433	0.024	5.0	11.0	0.6
150153*250BB^	0.015	0.236	0.650	0.024	6.0	16.5	0.6
150183*250AA^	0.018	0.197	0.433	0.024	5.0	11.0	0.6
150183*250BB^	0.018	0.236	0.650	0.024	6.0	16.5	0.6
150223*250AA^	0.022	0.197	0.433	0.024	5.0	11.0	0.6
150223*250BB^	0.022	0.236	0.650	0.024	6.0	16.5	0.6
150273*250AA^	0.027	0.197	0.433	0.024	5.0	11.0	0.6
150273*250BB^	0.027	0.236	0.650	0.024	6.0	16.5	0.6

* Indicates capacitance tolerance

^If ordering tape and reel,

J = ±5%, K = ±10%, M = ±20%

insert 1, 2, or 3.

See tape & reel specifications to determine which class applies.

Part Number highlighted in yellow, available until stock is depleted.

Replacement part number with "BB" case size.

Type 150 Axial Leaded Metallized Polyester

Catalog Part Number	Cap (μ F)	Inches Max			Millimeters Max		
		D	L	\varnothing d	D	L	\varnothing d
630 Vdc							
150682*630AA [^]	0.0068	0.197	0.433	0.024	5.5	11.0	0.6
150682*630BB [^]	0.0068	0.236	0.650	0.024	6.0	16.5	0.6
150822*630BB [^]	0.0082	0.236	0.650	0.024	6.0	16.5	0.6
150103*630BB [^]	0.0100	0.236	0.650	0.024	6.0	16.5	0.6
150123*630BB [^]	0.0120	0.236	0.650	0.024	6.0	16.5	0.6
150153*630BB [^]	0.0150	0.236	0.650	0.024	6.0	16.5	0.6
150183*630CB [^]	0.0180	0.256	0.650	0.024	6.5	16.5	0.6
150223*630DB [^]	0.0220	0.276	0.650	0.024	7.0	16.5	0.6
150273*630CC [^]	0.0270	0.256	0.807	0.024	6.5	20.5	0.6
150333*630EC [^]	0.0330	0.315	0.807	0.031	8.0	20.5	0.8
150393*630EC [^]	0.0390	0.315	0.807	0.031	8.0	20.5	0.8
150473*630EC [^]	0.0470	0.315	0.807	0.031	8.0	20.5	0.8
150563*630FC [^]	0.0560	0.335	0.807	0.031	8.5	20.5	0.8
150683*630GC [^]	0.0680	0.354	0.807	0.031	9.0	20.5	0.8
150823*630HC [^]	0.0820	0.374	0.807	0.031	9.5	20.5	0.8
150104*630FE [^]	0.1000	0.335	1.102	0.031	8.5	28.0	0.8
150124*630GE [^]	0.1200	0.354	1.102	0.031	9.0	28.0	0.8
150154*630IE [^]	0.1500	0.394	1.102	0.031	10.0	28.0	0.8
150184*630JE [^]	0.1800	0.413	1.102	0.031	10.5	28.0	0.8
150224*630LE [^]	0.2200	0.453	1.102	0.031	11.5	28.0	0.8
150274*630ME [^]	0.2700	0.492	1.102	0.031	12.5	28.0	0.8
150334*630NF [^]	0.3300	0.512	1.299	0.031	13.0	33.0	0.8
150394*630QF [^]	0.3900	0.571	1.299	0.031	14.5	33.0	0.8
150474*630RF [^]	0.4700	0.591	1.299	0.031	15.0	33.0	0.8
150564*630TF [^]	0.5600	0.610	1.299	0.031	15.5	33.0	0.8
150684*630WF [^]	0.6800	0.689	1.299	0.031	17.5	33.0	0.8
150824*630XF [^]	0.8200	0.728	1.299	0.031	18.5	33.0	0.8
150105*630YF [^]	1.0000	0.807	1.299	0.031	20.5	33.0	0.8

Catalog Part Number	Cap (μ F)	Inches Max			Millimeters Max		
		D	L	\varnothing d	D	L	\varnothing d
1000 Vdc							
150102*1000CB [^]	0.0010	0.256	0.650	0.031	6.5	16.5	0.6
150152*1000CB [^]	0.0015	0.256	0.650	0.031	6.5	16.5	0.6
150222*1000CB [^]	0.0022	0.256	0.650	0.031	6.5	16.5	0.6
150332*1000CB [^]	0.0033	0.256	0.650	0.031	6.5	16.5	0.6
150472*1000DB [^]	0.0047	0.276	0.650	0.031	7.0	16.5	0.6
150682*1000EB [^]	0.0068	0.315	0.650	0.031	8.0	16.5	0.8
150103*1000DC [^]	0.0100	0.276	0.807	0.031	7.0	20.5	0.6
150153*1000FC [^]	0.0150	0.335	0.807	0.031	8.5	20.5	0.8
150223*1000HC [^]	0.0220	0.374	0.807	0.031	9.5	20.5	0.8
150333*1000FE [^]	0.0330	0.335	1.102	0.031	8.5	28	0.8
150473*1000HE [^]	0.0470	0.374	1.102	0.031	9.5	28	0.8
150683*1000KE [^]	0.0680	0.433	1.102	0.031	11.0	28	0.8
150104*1000NE [^]	0.1000	0.512	1.102	0.031	13.0	28	0.8
150154*1000OF [^]	0.1500	0.551	1.299	0.031	14.0	33	0.8
150224*1000WF [^]	0.2200	0.689	1.299	0.031	17.5	33	0.8
150334*1000YF [^]	0.3300	0.807	1.299	0.031	20.5	33	0.8
150474*1000Z1F [^]	0.4700	0.945	1.299	0.031	24.0	33	0.8

* Indicates capacitance tolerance [^]If ordering tape and reel,
insert 1, 2, or 3.
J = \pm 5%, K = \pm 10%, M = \pm 20%

See tape & reel specifications to determine which class applies.
Part Number highlighted in yellow, available until stock is depleted.
Replacement part number with "BB" case size.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru