

Please read this notice before using the TAIYO YUDEN products.

## REMINDERS

- Product information in this catalog is as of October 2017. All of the contents specified herein are subject to change without notice due to technical improvements, etc. Therefore, please check for the latest information carefully before practical application or use of our products.

Please note that TAIYO YUDEN shall not be in any way responsible for any damages and defects in products or equipment incorporating our products, which are caused under the conditions other than those specified in this catalog or individual product specification sheets.

- Please contact TAIYO YUDEN for further details of product specifications as the individual product specification sheets are available.
- Please conduct validation and verification of our products in actual condition of mounting and operating environment before using our products.
- The products listed in this catalog are intended for use in general electronic equipment (e.g., AV equipment, OA equipment, home electric appliances, office equipment, information and communication equipment including, without limitation, mobile phone, and PC) and medical equipment classified as Class I or II by IMDRF. Please be sure to contact TAIYO YUDEN for further information before using the products for any equipment which may directly cause loss of human life or bodily injury (e.g., transportation equipment including, without limitation, automotive powertrain control system, train control system, and ship control system, traffic signal equipment, disaster prevention equipment, medical equipment classified as Class III by IMDRF, highly public information network equipment including, without limitation, telephone exchange, and base station).

Please do not incorporate our products into any equipment requiring high levels of safety and/or reliability (e.g., aerospace equipment, aviation equipment\*, medical equipment classified as Class IV by IMDRF, nuclear control equipment, undersea equipment, military equipment).

\*Note: There is a possibility that our products can be used only for aviation equipment that does not directly affect the safe operation of aircraft (e.g., in-flight entertainment, cabin light, electric seat, cooking equipment) if such use meets requirements specified separately by TAIYO YUDEN. Please be sure to contact TAIYO YUDEN for further information before using our products for such aviation equipment.

When our products are used even for high safety and/or reliability-required devices or circuits of general electronic equipment, it is strongly recommended to perform a thorough safety evaluation prior to use of our products and to install a protection circuit as necessary.

Please note that unless you obtain prior written consent of TAIYO YUDEN, TAIYO YUDEN shall not be in any way responsible for any damages incurred by you or third parties arising from use of the products listed in this catalog for any equipment requiring inquiry to TAIYO YUDEN or prohibited for use by TAIYO YUDEN as described above.

- Information contained in this catalog is intended to convey examples of typical performances and/or applications of our products and is not intended to make any warranty with respect to the intellectual property rights or any other related rights of TAIYO YUDEN or any third parties nor grant any license under such rights.
- Please note that the scope of warranty for our products is limited to the delivered our products themselves and TAIYO YUDEN shall not be in any way responsible for any damages resulting from a fault or defect in our products. Notwithstanding the foregoing, if there is a written agreement (e.g., supply and purchase agreement, quality assurance agreement) signed by TAIYO YUDEN and your company, TAIYO YUDEN will warrant our products in accordance with such agreement.
- The contents of this catalog are applicable to our products which are purchased from our sales offices or authorized distributors (hereinafter "TAIYO YUDEN's official sales channel"). Please note that the contents of this catalog are not applicable to our products purchased from any seller other than TAIYO YUDEN's official sales channel.
- Caution for Export  
Some of our products listed in this catalog may require specific procedures for export according to "U.S. Export Administration Regulations", "Foreign Exchange and Foreign Trade Control Law" of Japan, and other applicable regulations. Should you have any questions on this matter, please contact our sales staff.


# Wireless Module

Our recommended Line Up of *Bluetooth*<sup>®</sup>, W-LAN & GPS Module

■ For Smartphone Peripheral & IoT Solution

Electricity/Light


Security/Access



*Bluetooth*<sup>®</sup> low energy Module

■ For Industrial Market

Handy Terminal / Mobile Printer



WLAN (+BT)  
Original or ON-board Antenna & FPC Connector

■ For IoT Solution & Industrial

White Goods

Heating and Cooling



CPU Embedded  
WLAN Module



GPS Full Module

Alarm/Sensing



Support for 2.4GHz & 5GHz  
BT+WLAN Module

※As some of the Wireless Modules listed above are still under development, the specification is subject to change without prior notice.  
We also have Evaluation Kits for our modules.  
For the latest information, please visit our web site at <http://www.ty-top.com/> or feel free to contact our sales department.

※The *Bluetooth*<sup>®</sup> word mark and logos are owned by the Bluetooth SIG, Inc. and any use of such marks by TAIYO YUDEN CO., LTD. is under license.  
Other trademarks and trade names are those of their respective owners.

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).

■ Bluetooth® low energy Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
EYSHSNZWZ	○		○*	○							○				○	○	○		○		○	○	○	○	○*	Ultra Small,64k RAM
EYSHJNZWZ	○		○*	○							○				○	○	○		○		○	○	○	○	○*	64k RAM
EYSGJNZXX	○										○				○	○	○		○		○	○	○	○	○*	16k RAM
EYSGJNZWY	○										○				○	○	○		○		○	○	○	○	○*	32k RAM
EYSGJNAWY-1X	○										○				○	○	○		○		○	○	○	○	○*	TY's APP(Lite)
EYSGJNAWY-WX	○										○				○	○	○		○		○	○	○	○	○*	TY's APP
EYSHCNZWZ	○		○*	○							○				○	○	○		○		○	○	○	○	○*	32k X'tal,64k RAM
EYSGCNZXX	○										○				○	○	○		○		○	○	○	○	○*	32k X'tal,16k RAM
EYSGCNZWY	○										○				○	○	○		○		○	○	○	○	○*	32k X'tal,32k RAM
EYSGCNAWY-1X	○										○				○	○	○		○		○	○	○	○	○*	32k X'tal,TY's APP(Lite)
EYSGCNAWY-WX	○										○				○	○	○		○		○	○	○	○	○*	32k X'tal,TY's APP

\*Softdevice S332

\*CE Conducted test report available

■ Bluetooth® low energy & ANT Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
EYAGJNZXX	○		○								○				○	○	○		○		○	○	○	○	○*	32k RAM

\*CE Conducted test report available

■ Bluetooth® Dual Mode Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
EYSGCCAXX	○	○									○								○		○	○	○	○	○*	
EYSGCCSXX	○	○									○	○							○		○	○	○	○	○*	

\*CE Conducted test report available

■ CPU Embedded WLAN Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
WYSACVLXY-XZ						○	○	○			○								○		○	○	○	○	○*	
WYSACVLXY-XX						○	○	○			○								○		○	○	○	○	○*	TY's APP

\*CE Conducted test report available

■ WLAN or WLAN+BT Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
WYSBHVXGX	○	○			○	○	○	○	○									○	○		○	○	○	○		
WYSAGVDX7						○	○	○										○	○		○	○	○	○		
WYSAAVDXB		○			○	○	○	○										○	○		○	○	○	○		
WYSAAVDX7					○	○	○	○										○	○		○	○	○	○		
WYSBMVXGB		○			○	○	○	○										○	○		○	○	○	○		
WYSAGVDXG	○	○			○	○	○	○	○									○	○		○	○	○	○	○*	












\*CE Conducted test report available

■ GNSS Module

Part number	Function										I/F							Module type		Type approval				Remark		
	BLE	BT	ANT	NFC	802.11a	802.11b	802.11g	802.11n	802.11ac	GPS	GLONASS	UART	USB	PCM	SPI	I2C	I2S	SDIO	SMD	Connector	Antenna	Japan	FCC		IC	CE
GYSFFMAXB										○	○							○								
GYSFFMAXC										○	○							○								
GYSFDMAXB										○	○							○	○							

▶ This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).


Bluetooth® low energy Module

Part number	Function	Module type	I/F	Feature	Outline [mm](Height : Maximum)
EYSHSNZWZ (nRF52832)	Bluetooth® low energy v5.0 & NFC-A Type-2	BLE Slave and Master NFC-A Type-2 SMD type	UART I2C SPI I2S PDM 15 GPIO	w/CPU (Cortex M4F) Antenna 512KB Flash 64KB RAM FCC/IC/Japan certified CE Conducted test report available	8.55 x 3.25 x 0.9 
EYSHJNZWZ (nRF52832)	Bluetooth® low energy v5.0 & NFC-A Type-2	BLE Slave and Master NFC-A Type-2 SMD type	UART I2C SPI I2S PDM 15 GPIO	w/CPU (Cortex M4F) Antenna 512KB Flash 64KB RAM FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 
EYSGJNZXX (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type	UART I2C SPI 14 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 
EYSGJNZWY (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type	UART I2C SPI 14 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 
EYSGJNAWY-1X (nRF51822)	Bluetooth® low energy v4.1	BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version)	UART	w/CPU (Cortex M0) Antenna FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 
EYSGJNAWY-WX (nRF51822)	Bluetooth® low energy v4.1	BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Full Version)	UART	w/CPU (Cortex M0) Antenna FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 
EYSHCNZWZ (nRF52832)	Bluetooth® low energy v5.0 & NFC-A Type-2	BLE Slave and Master NFC-A Type-2 SMD type	UART I2C SPI I2S PDM 30 GPIO	w/CPU (Cortex M4F) Antenna 512KB Flash 64KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 
EYSGCNZXX (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type	UART I2C SPI 29 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash 16KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 
EYSGCNZWY (nRF51822)	Bluetooth® low energy v4.2 (*)	BLE Slave and Master SMD type	UART I2C SPI 29 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 
EYSGCNAWY-1X (nRF51822)	Bluetooth® low energy v4.1	BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Lite Version)	UART	w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 
EYSGCNAWY-WX (nRF51822)	Bluetooth® low energy v4.1	BLE Slave and Master SMD type TAIYO YUDEN Software Embedded (Full Version)	UART	w/CPU (Cortex M0) Antenna 32kHz Crystal FCC/IC/Japan certified CE Conducted test report available	12.9 x 9.6 x 2.0 



(\*)Supported by S130

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).



Bluetooth® low energy & ANT Module

Part number	Function	Module type	I/F	Feature	Outline [mm](Height : Maximum)
EYAGJNZXX (nRF51422)	Bluetooth® low energy v4.2 & ANT	BLE Slave ANT SMD type	UART I2C SPI 14 GPIO	w/CPU (Cortex M0) Antenna 256KB Flash 32KB RAM FCC/IC/Japan certified CE Conducted test report available	11.3 x 5.1 x 1.3 







Bluetooth® Dual Mode Module

Part number	Function	Module type	I/F	Feature	Outline [mm](Height : Maximum)
EYSGCCAXX	Bluetooth® Legacy and BLE	SMD type	UART	Integrated System Clock Antenna FCC/IC/Japan certified CE Conducted test report available	15.4 x 10.0 x 2.0 
EYSGCCSXX	Bluetooth® Legacy and BLE	SMD type	USB	Integrated System Clock Antenna FCC/IC/Japan certified CE Conducted test report available	15.4 x 10.0 x 2.0 




CPU Embedded WLAN Module

Part number	Function	Module type	I/F	Feature	Outline [mm](Height : Maximum)
WYSACVLXY-XZ	IEEE802.11b/g/n	SMD type	UART SPI	Integrated System Clock Antenna Supprt Micro AP Supprt WiFi Direct FCC/IC/Japan certified CE Conducted test report available	21.4 x 14.0 x 2.4 
WYSACVLXY-XX	IEEE802.11b/g/n	SMD type Original Software Embedded	UART SPI	Integrated System Clock Antenna Supprt Micro AP FCC/IC/Japan certified CE Conducted test report available	21.4 x 14.0 x 2.4 

■ WLAN or WLAN+BT Module

Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
WYSBHVXG	IEEE802.11ac/a/b/g/n+Bluetooth® 4.2	SMD type	SDIO PCM	Integrated System Clock 2.4GHz & 5GHz 11ac(HT80)	12.6 x 8.9 x 1.9 
WYSAGVDX7	IEEE802.11b/g/n	Connector type	SDIO	Integrated System Clock Antenna FCC/IC/Japan certified	20.0 x 11.0 x 2.15 
WYSAAVDXB	IEEE802.11 a/b/g/n+Bluetooth® 3.0	Connector type	SDIO PCM	Integrated System Clock Dual Band Antenna HT40 Japan certified	30.0 x 15.0 x 2.45 
WYSAAVDX7	IEEE802.11b/g/n	Connector type	SDIO	Integrated System Clock Antenna HT40 FCC/IC/Japan certified	35.0 x 15.0 x 2.9 
WYSBMVXGB	IEEE802.11 a/b/g/n+Bluetooth® 3.0	SMD type	SDIO PCM	2.4GHz & 5GHz HT40	13.1 x 6.1 x 1.35 
WYSAGVDXG	IEEE802.11ac/a/b/g/n+Bluetooth® 4.2	SMD type	SDIO PCM	Integrated System Clock 2.4GHz & 5GHz 11ac(HT80) Antenna FCC/IC/Japan certified CE Conducted test report available	24.0 x 11.5 x 2.0 

■ GNSS Module

Part number	Function	Module type	I/F	Feature	Outline [mm] (Height : Maximum)
GYSFFMAXB	GPS Full Module NMEA Output	SMD type	UART	TCXO RTC LNA SAW On-chip Logger	10.8 x 10.0 x 2.05 
GYSFFMAXC	GPS&GLONASS Full Module NMEA Output	SMD type	UART	TCXO RTC LNA SAW On-chip Logger	10.8 x 10.0 x 2.05 
GYSFDMAXB	GPS Full Module NMEA Output	Connector type	UART	Patch Antenna TCXO RTC LNA SAW On-chip Logger	23.2 x 15.3 x 6.9 

► This catalog contains the typical specification only due to the limitation of space. When you consider the purchase of our products, please check our product specification sheets. For details of each product (characteristics graph, reliability information, precautions for use, and so on), see our website (<http://www.ty-top.com/>).

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)