

		DESIGNED FOR USE WITH .085 DIA SEMI-RIGID CABLE		REVISIONS																																																																																																																										
		CABLE ENTRY DIAMETER MINIMUM		REV	DESCRIPTION	DATE	APPROVED																																																																																																																							
		CONTACT	.021	040	REVISED	6/28/93	M.A.																																																																																																																							
		HOUSING		.089		RECOMMENDED MOUNTING HOLE SCALE N.T.S.																																																																																																																								
<table><tr><td>ELECTRICAL</td><td>MECHANICAL</td><td>ENVIRONMENTAL</td></tr><tr><td>Nominal Impedance (Ohms) 50</td><td>Interface Dimensions Per OMNI SPECTRA CATALOG</td><td>Temperature Rating -65° to +125°C</td></tr><tr><td>Frequency Range (GHz) DC to 22</td><td>Mating Characteristics:</td><td>Vibration MIL-STD-202, Method 204, Condition D</td></tr><tr><td>Volt Rating (VRMS MAX) @ Sea Level 375</td><td>Insertion (MAX Lbs) 3</td><td>Shock MIL-STD-202, Method 213, Condition I</td></tr><tr><td>VSWR 1.05+.005f(GHz) dc to 18 GHz</td><td>Withdrawal (MIN Oz) 1</td><td>Thermal Shock MIL-STD-202, Method 107, Condition B except High Temp Shall Be +115°C</td></tr><tr><td>1.09+.009f(GHz) 18 to 22 GHz</td><td>OSP Force to Engage (Lbs MAX) 3 & Disengage (Lbs MAX) 1.5</td><td>Moisture Resistance MIL-STD-202, Method 106</td></tr><tr><td>Insertion Loss (dB MAX) .03x√f(GHz)</td><td>Center Contact Captivation</td><td>Corrosion - MIL-STD-202, Method 101, Condition B</td></tr><tr><td>RF Leakage (dB MIN) -(60-f(GHz))</td><td>Axial (Lbs MIN) 6</td><td></td></tr><tr><td>Corona, 70,000 Ft (VRMS MIN) 335</td><td>Cable Retention</td><td></td></tr><tr><td>Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000</td><td>Axial Force (lbs MIN) 30</td><td></td></tr><tr><td>Contact Resistance (Milliohms MAX)</td><td>Torque (In-Oz MIN) 16</td><td></td></tr><tr><td>Center Contact 2.0</td><td>Weight (Grams) TBD</td><td></td></tr><tr><td>Outer Contact 2.0</td><td></td><td></td></tr><tr><td>Cable to Housing 0.5</td><td></td><td></td></tr><tr><td>RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670</td><td></td><td></td></tr><tr><td>I.R.(Megohms MIN) 5000</td><td></td><td></td></tr></table>		ELECTRICAL	MECHANICAL	ENVIRONMENTAL	Nominal Impedance (Ohms) 50	Interface Dimensions Per OMNI SPECTRA CATALOG	Temperature Rating -65° to +125°C	Frequency Range (GHz) DC to 22	Mating Characteristics:	Vibration MIL-STD-202, Method 204, Condition D	Volt Rating (VRMS MAX) @ Sea Level 375	Insertion (MAX Lbs) 3	Shock MIL-STD-202, Method 213, Condition I	VSWR 1.05+.005f(GHz) dc to 18 GHz	Withdrawal (MIN Oz) 1	Thermal Shock MIL-STD-202, Method 107, Condition B except High Temp Shall Be +115°C	1.09+.009f(GHz) 18 to 22 GHz	OSP Force to Engage (Lbs MAX) 3 & Disengage (Lbs MAX) 1.5	Moisture Resistance MIL-STD-202, Method 106	Insertion Loss (dB MAX) .03x√f(GHz)	Center Contact Captivation	Corrosion - MIL-STD-202, Method 101, Condition B	RF Leakage (dB MIN) -(60-f(GHz))	Axial (Lbs MIN) 6		Corona, 70,000 Ft (VRMS MIN) 335	Cable Retention		Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000	Axial Force (lbs MIN) 30		Contact Resistance (Milliohms MAX)	Torque (In-Oz MIN) 16		Center Contact 2.0	Weight (Grams) TBD		Outer Contact 2.0			Cable to Housing 0.5			RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670			I.R.(Megohms MIN) 5000			<table><tr><td>BUSHING</td><td>STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303</td><td>PASSIVATE PER ASTM-A380</td></tr><tr><td>HOUSING OUTER MOUNTING NUT</td><td>STAINLESS STEEL TYPE 316</td><td>PASSIVATE PER ASTM-A380</td></tr><tr><td>HOUSING INNER</td><td>STAINLESS STEEL TYPE 316</td><td>GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290</td></tr><tr><td>DIELECTRIC</td><td>TFE FLUOROCARBON PER ASTM-D-1457</td><td>N/A</td></tr><tr><td>CENTER CONTACT CONTACT SLEEVE</td><td>BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H</td><td>GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290</td></tr><tr><td>CONTACT RING SHIM</td><td>BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H</td><td>GOLD PLATED PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550</td></tr><tr><td>SPRING</td><td>STAINLESS STEEL TYPE 302</td><td>PASSIVATE PER ASTM-A380</td></tr><tr><td>RETAINING RING</td><td>CARBON SPRING STEEL</td><td>NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550</td></tr><tr><td>LOCKWASHER</td><td>STAINLESS STEEL 300 SERIES</td><td>PASSIVATE PER ASTM-A380</td></tr></table>		BUSHING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380	HOUSING OUTER MOUNTING NUT	STAINLESS STEEL TYPE 316	PASSIVATE PER ASTM-A380	HOUSING INNER	STAINLESS STEEL TYPE 316	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290	DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A	CENTER CONTACT CONTACT SLEEVE	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290	CONTACT RING SHIM	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	GOLD PLATED PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550	SPRING	STAINLESS STEEL TYPE 302	PASSIVATE PER ASTM-A380	RETAINING RING	CARBON SPRING STEEL	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550	LOCKWASHER	STAINLESS STEEL 300 SERIES	PASSIVATE PER ASTM-A380	<table><tr><td>COMPONENT</td><td>MATERIAL</td><td>FINISH</td></tr><tr><td colspan="3">UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°</td></tr><tr><td colspan="3">DRAWN BY D. Camello DATE 1/27/93</td></tr><tr><td colspan="3">CHECKED BY</td></tr><tr><td colspan="3">APPD BY</td></tr><tr><td colspan="3">These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.</td></tr><tr><td colspan="3">USE ASS'Y PROCEDURE</td></tr><tr><td colspan="3">408-04596 (45-047) NO. A.P. _____</td></tr></table>		COMPONENT	MATERIAL	FINISH	UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°			DRAWN BY D. Camello DATE 1/27/93			CHECKED BY			APPD BY			These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.			USE ASS'Y PROCEDURE			408-04596 (45-047) NO. A.P. _____			<table><tr><td colspan="4">AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599</td></tr><tr><td colspan="4">TITLE OSP FLOATING BULKHEAD FEEDTHRU CABLE JACK DIRECT SOLDER ATTACHMENT</td></tr><tr><td>SIZE B</td><td>CODE IDENT NO. 26805</td><td colspan="2">4522-5027-02</td></tr><tr><td>SCALE 3:1</td><td colspan="2"></td><td>REV 040</td></tr><tr><td colspan="2"></td><td colspan="2">SHEET 1 OF 1</td></tr></table>		AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599				TITLE OSP FLOATING BULKHEAD FEEDTHRU CABLE JACK DIRECT SOLDER ATTACHMENT				SIZE B	CODE IDENT NO. 26805	4522-5027-02		SCALE 3:1			REV 040			SHEET 1 OF 1	
ELECTRICAL	MECHANICAL	ENVIRONMENTAL																																																																																																																												
Nominal Impedance (Ohms) 50	Interface Dimensions Per OMNI SPECTRA CATALOG	Temperature Rating -65° to +125°C																																																																																																																												
Frequency Range (GHz) DC to 22	Mating Characteristics:	Vibration MIL-STD-202, Method 204, Condition D																																																																																																																												
Volt Rating (VRMS MAX) @ Sea Level 375	Insertion (MAX Lbs) 3	Shock MIL-STD-202, Method 213, Condition I																																																																																																																												
VSWR 1.05+.005f(GHz) dc to 18 GHz	Withdrawal (MIN Oz) 1	Thermal Shock MIL-STD-202, Method 107, Condition B except High Temp Shall Be +115°C																																																																																																																												
1.09+.009f(GHz) 18 to 22 GHz	OSP Force to Engage (Lbs MAX) 3 & Disengage (Lbs MAX) 1.5	Moisture Resistance MIL-STD-202, Method 106																																																																																																																												
Insertion Loss (dB MAX) .03x√f(GHz)	Center Contact Captivation	Corrosion - MIL-STD-202, Method 101, Condition B																																																																																																																												
RF Leakage (dB MIN) -(60-f(GHz))	Axial (Lbs MIN) 6																																																																																																																													
Corona, 70,000 Ft (VRMS MIN) 335	Cable Retention																																																																																																																													
Dielectric Withstanding Voltage (VRMS MIN) @ Sea Level 1000	Axial Force (lbs MIN) 30																																																																																																																													
Contact Resistance (Milliohms MAX)	Torque (In-Oz MIN) 16																																																																																																																													
Center Contact 2.0	Weight (Grams) TBD																																																																																																																													
Outer Contact 2.0																																																																																																																														
Cable to Housing 0.5																																																																																																																														
RF High Potential @ Sea Level (VRMS MIN @ 5 MHz) 670																																																																																																																														
I.R.(Megohms MIN) 5000																																																																																																																														
BUSHING	STAINLESS STEEL PER ASTM-A484 AND ASTM-A582, TYPE 303	PASSIVATE PER ASTM-A380																																																																																																																												
HOUSING OUTER MOUNTING NUT	STAINLESS STEEL TYPE 316	PASSIVATE PER ASTM-A380																																																																																																																												
HOUSING INNER	STAINLESS STEEL TYPE 316	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290																																																																																																																												
DIELECTRIC	TFE FLUOROCARBON PER ASTM-D-1457	N/A																																																																																																																												
CENTER CONTACT CONTACT SLEEVE	BERYLLIUM COPPER PER ASTM B 196, ALLOY C17300, CONDITION H	GOLD PLATE PER MIL-G-45204 OVER NICKEL PLATE PER QQ-N-290																																																																																																																												
CONTACT RING SHIM	BERYLLIUM COPPER PER ASTM B 194, ALLOY C17200, CONDITION H	GOLD PLATED PER MIL-G-45204 OVER COPPER PLATE PER MIL-C-14550																																																																																																																												
SPRING	STAINLESS STEEL TYPE 302	PASSIVATE PER ASTM-A380																																																																																																																												
RETAINING RING	CARBON SPRING STEEL	NICKEL PLATE PER QQ-N-290 OVER COPPER PLATE PER MIL-C-14550																																																																																																																												
LOCKWASHER	STAINLESS STEEL 300 SERIES	PASSIVATE PER ASTM-A380																																																																																																																												
COMPONENT	MATERIAL	FINISH																																																																																																																												
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES TOLERANCE ON FRAC. DEC. ANGLES ± 1/64 ±.005 ± 1°																																																																																																																														
DRAWN BY D. Camello DATE 1/27/93																																																																																																																														
CHECKED BY																																																																																																																														
APPD BY																																																																																																																														
These drawings and specifications are the property of Omni Spectra Incorporated and shall not be reproduced or copied or used in whole or in part as the basis for the manufacture or sale of item(s) without written permission.																																																																																																																														
USE ASS'Y PROCEDURE																																																																																																																														
408-04596 (45-047) NO. A.P. _____																																																																																																																														
AMP Incorporated 140 Fourth Avenue Waltham, MA 02451-7599																																																																																																																														
TITLE OSP FLOATING BULKHEAD FEEDTHRU CABLE JACK DIRECT SOLDER ATTACHMENT																																																																																																																														
SIZE B	CODE IDENT NO. 26805	4522-5027-02																																																																																																																												
SCALE 3:1			REV 040																																																																																																																											
		SHEET 1 OF 1																																																																																																																												

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru