



**Full - Bridge  
CoolMOS & Trench + Field Stop® IGBT  
Power module**

**Trench & Field Stop® IGBT Q1, Q3:**  
 $V_{CES} = 600V$  ;  $I_C = 50A$  @  $T_c = 80^\circ C$

**CoolMOS™ Q2, Q4:**  
 $V_{DSS} = 600V$  ;  $I_D = 36A$  @  $T_c = 25^\circ C$



Top switches : Trench + Field Stop IGBT®  
Bottom switches : CoolMOS™



Pins 3/4 must be shorted together

## Application

- Solar converter

## Features

- $Q_2, Q_4$  CoolMOS™**
  - Ultra low  $R_{DSon}$
  - Low Miller capacitance
  - Ultra low gate charge
  - Avalanche energy rated
  - Very rugged
  - Fast intrinsic diode
- $Q_1, Q_3$  Trench & Field Stop IGBT®**
  - Low voltage drop
  - Switching frequency up to 20 kHz
  - RBSOA & SCSOA rated
  - Low tail current
- SiC Schottky Diode (CR1, CR3)**
  - Zero reverse recovery
  - Zero forward recovery
  - Temperature Independent switching behavior
  - Positive temperature coefficient on VF
- Very low stray inductance
- Internal thermistor for temperature monitoring
- High level of integration

## Benefits

- Outstanding performance at high frequency operation
- Direct mounting to heatsink (isolated package)
- Low junction to case thermal resistance
- Solderable terminals both for power and signal for easy PCB mounting
- Low profile
- RoHS Compliant

 **CAUTION:** These Devices are sensitive to Electrostatic Discharge. Proper Handling Procedures Should Be Followed. See application note APT0502 on [www.microsemi.com](http://www.microsemi.com)

**All ratings @  $T_j = 25^\circ C$  unless otherwise specified**

## 1. Top switches

### 1.1 Top Trench + Field Stop IGBT<sup>®</sup> characteristics

#### Absolute maximum ratings

Symbol	Parameter		Max ratings	Unit
V <sub>CES</sub>	Collector - Emitter Breakdown Voltage		600	V
I <sub>C</sub>	Continuous Collector Current	T <sub>C</sub> = 25°C	80	A
		T <sub>C</sub> = 80°C	50	
I <sub>CM</sub>	Pulsed Collector Current	T <sub>C</sub> = 25°C	100	
V <sub>GE</sub>	Gate – Emitter Voltage		±20	V
P <sub>D</sub>	Maximum Power Dissipation	T <sub>C</sub> = 25°C	176	W
RBSOA	Reverse Bias Safe Operating Area	T <sub>J</sub> = 150°C	100A @ 550V	

#### Electrical Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
I <sub>CES</sub>	Zero Gate Voltage Collector Current	V <sub>GE</sub> = 0V, V <sub>CE</sub> = 600V			250	µA
V <sub>CE(sat)</sub>	Collector Emitter Saturation Voltage	V <sub>GE</sub> = 15V	T <sub>J</sub> = 25°C	1.5	1.9	V
		I <sub>C</sub> = 50A	T <sub>J</sub> = 150°C	1.7		
V <sub>GE(th)</sub>	Gate Threshold Voltage	V <sub>GE</sub> = V <sub>CE</sub> , I <sub>C</sub> = 600µA	5.0	5.8	6.5	V
I <sub>GES</sub>	Gate – Emitter Leakage Current	V <sub>GE</sub> = 20V, V <sub>CE</sub> = 0V			600	nA

#### Dynamic Characteristics

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit	
C <sub>ies</sub>	Input Capacitance	V <sub>GE</sub> = 0V V <sub>CE</sub> = 25V f = 1MHz		3150		pF	
C <sub>oes</sub>	Output Capacitance			200			
C <sub>res</sub>	Reverse Transfer Capacitance			95			
T <sub>d(on)</sub>	Turn-on Delay Time	Inductive Switching (25°C) V <sub>GE</sub> = ±15V V <sub>Bus</sub> = 300V I <sub>C</sub> = 50A R <sub>G</sub> = 8.2Ω		110		ns	
T <sub>r</sub>	Rise Time			45			
T <sub>d(off)</sub>	Turn-off Delay Time			200			
T <sub>f</sub>	Fall Time			40			
T <sub>d(on)</sub>	Turn-on Delay Time	Inductive Switching (150°C) V <sub>GE</sub> = ±15V V <sub>Bus</sub> = 300V I <sub>C</sub> = 50A R <sub>G</sub> = 8.2Ω		120		ns	
T <sub>r</sub>	Rise Time			50			
T <sub>d(off)</sub>	Turn-off Delay Time			250			
T <sub>f</sub>	Fall Time			60			
E <sub>on</sub>	Turn-on Switching Energy	V <sub>GE</sub> = ±15V V <sub>Bus</sub> = 300V I <sub>C</sub> = 50A R <sub>G</sub> = 8.2Ω	T <sub>j</sub> = 25°C	0.3		mJ	
E <sub>off</sub>	Turn-off Switching Energy		T <sub>j</sub> = 150°C	0.43			
R <sub>thJC</sub>	Junction to Case Thermal resistance		T <sub>j</sub> = 25°C	1.35			
			T <sub>j</sub> = 150°C	1.75			
					0.85	°C/W	

## 1.2 Top SiC diode characteristics (CR1, CR3)

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
V <sub>RRM</sub>	Maximum Peak Repetitive Reverse Voltage	V <sub>R</sub> =600V	T <sub>j</sub> = 25°C	600	50	200	µA
I <sub>RM</sub>	Maximum Reverse Leakage Current		T <sub>j</sub> = 125°C		100	1000	
I <sub>F(AV)</sub>	Maximum Average Forward Current	50% duty cycle	T <sub>c</sub> = 100°C		10		A
V <sub>F</sub>	Diode Forward Voltage	I <sub>F</sub> = 10A	T <sub>j</sub> = 25°C		1.6	1.8	V
			T <sub>j</sub> = 175°C		2	2.4	
Q <sub>C</sub>	Total Capacitive Charge	I <sub>F</sub> = 10A, V <sub>R</sub> = 300V di/dt = 500A/µs			14		nC
C	Total Capacitance	f = 1MHz, V <sub>R</sub> = 200V			65		pF
		f = 1MHz, V <sub>R</sub> = 400V			50		
R <sub>thJC</sub>	Junction to Case Thermal resistance					2.5	°C/W

## 2. Bottom switches

### 2.1 Bottom CoolMOS™ characteristics

#### Absolute maximum ratings

Symbol	Parameter		Max ratings	Unit
V <sub>DSS</sub>	Drain - Source Breakdown Voltage		600	V
I <sub>D</sub>	Continuous Drain Current	T <sub>c</sub> = 25°C	36	A
		T <sub>c</sub> = 80°C	27	
I <sub>DM</sub>	Pulsed Drain current		115	
V <sub>GS</sub>	Gate - Source Voltage		±20	V
R <sub>DS(on)</sub>	Drain - Source ON Resistance		83	mΩ
P <sub>D</sub>	Maximum Power Dissipation	T <sub>c</sub> = 25°C	250	W
I <sub>AR</sub>	Avalanche current (repetitive and non repetitive)		20	A
E <sub>AR</sub>	Repetitive Avalanche Energy		1	mJ
E <sub>AS</sub>	Single Pulse Avalanche Energy		1800	

#### Electrical Characteristics

Symbol	Characteristic	Test Conditions		Min	Typ	Max	Unit
I <sub>DSS</sub>	Zero Gate Voltage Drain Current	V <sub>GS</sub> = 0V, V <sub>DS</sub> = 600V	T <sub>j</sub> = 25°C			100	µA
		V <sub>GS</sub> = 0V, V <sub>DS</sub> = 600V	T <sub>j</sub> = 125°C			5000	
R <sub>DS(on)</sub>	Drain – Source on Resistance	V <sub>GS</sub> = 10V, I <sub>D</sub> = 24.5A				83	mΩ
V <sub>GS(th)</sub>	Gate Threshold Voltage	V <sub>GS</sub> = V <sub>DS</sub> , I <sub>D</sub> = 3mA		3	4	5	V
I <sub>GSS</sub>	Gate – Source Leakage Current	V <sub>GS</sub> = ±20 V, V <sub>DS</sub> = 0V				100	nA

**Dynamic Characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$C_{iss}$	Input Capacitance	$V_{GS} = 0V ; V_{DS} = 25V$ $f = 1MHz$		7.2		nF
$C_{rss}$	Reverse Transfer Capacitance			0.041		
$Q_g$	Total gate Charge	$V_{GS} = 10V$ $V_{Bus} = 300V$ $I_D = 36A$		250		nC
$Q_{gs}$	Gate – Source Charge			43		
$Q_{gd}$	Gate – Drain Charge			135		
$T_{d(on)}$	Turn-on Delay Time	<b>Inductive Switching (125°C)</b> $V_{GS} = 10V$ $V_{Bus} = 400V$ $I_D = 36A$ $R_G = 5\Omega$		21		ns
$T_r$	Rise Time			30		
$T_{d(off)}$	Turn-off Delay Time			240		
$T_f$	Fall Time			52		
$E_{on}$	Turn-on Switching Energy	<b>Inductive switching @ 25°C</b> $V_{GS} = 10V ; V_{Bus} = 400V$ $I_D = 36A ; R_G = 5\Omega$		531		$\mu J$
$E_{off}$	Turn-off Switching Energy			590		
$E_{on}$	Turn-on Switching Energy	<b>Inductive switching @ 125°C</b> $V_{GS} = 10V ; V_{Bus} = 400V$ $I_D = 36A ; R_G = 5\Omega$		762		$\mu J$
$E_{off}$	Turn-off Switching Energy			725		
$R_{thJC}$	Junction to Case Thermal resistance				0.5	$^{\circ}C/W$

**Source - Drain diode ratings and characteristics**

Symbol	Characteristic	Test Conditions	Min	Typ	Max	Unit
$I_S$	Continuous Source current (Body diode)		$T_c = 25^{\circ}C$	36		A
			$T_c = 80^{\circ}C$	27		
$V_{SD}$	Diode Forward Voltage	$V_{GS} = 0V, I_S = -36A$			1.2	V
$dv/dt$	Peak Diode Recovery ①				40	V/ns
$t_{rr}$	Reverse Recovery Time	$I_S = -36A$ $V_R = 350V$ $di_S/dt = 100A/\mu s$	$T_j = 25^{\circ}C$	210		ns
			$T_j = 125^{\circ}C$	350		
$Q_{rr}$	Reverse Recovery Charge		$T_j = 25^{\circ}C$	2		$\mu C$
			$T_j = 125^{\circ}C$	5.4		

①  $dv/dt$  numbers reflect the limitations of the circuit rather than the device itself.

$I_S \leq -36A$      $di/dt \leq 100A/\mu s$      $V_R \leq V_{DSS}$      $T_j \leq 150^{\circ}C$

### 3. Temperature sensor

NTC (see application note APT0406 on [www.microsemi.com](http://www.microsemi.com) for more information).

Symbol	Characteristic	Min	Typ	Max	Unit
R <sub>25</sub>	Resistance @ 25°C		50		kΩ
B <sub>25/85</sub>	T <sub>25</sub> = 298.15 K		3952		K

$$R_T = \frac{R_{25}}{\exp\left[B_{25/85}\left(\frac{1}{T_{25}} - \frac{1}{T}\right)\right]} \quad T: \text{Thermistor temperature}$$


R<sub>T</sub>: Thermistor value at T

### 4. Package characteristics

Symbol	Characteristic	Min	Typ	Max	Unit
V <sub>ISOL</sub>	RMS Isolation Voltage, any terminal to case t=1 min, 50/60Hz	4000			V
T <sub>J</sub>	Operating junction temperature range	-40		150*	°C
T <sub>STG</sub>	Storage Temperature Range	-40		125	
T <sub>C</sub>	Operating Case Temperature	-40		100	
Torque	Mounting torque	To heatsink	M4	2	N.m
Wt	Package Weight			80	g

T<sub>j</sub>=175°C for Trench & Field Stop IGBT


### 5. SP1 Package outline (dimensions in mm)




See application note 1904 - Mounting Instructions for SP1 Power Modules on [www.microsemi.com](http://www.microsemi.com)

## 6. Top switches curves

### 6.1 Top Trench + Field Stop IGBT<sup>®</sup> typical performance curves














## 6.2 Top SiC diode typical performance curves









## 7. Bottom switches curves

### 7.1 Bottom CoolMOS™ typical performance curves







"COOLMOS™ comprise a new family of transistors developed by Infineon Technologies AG. "COOLMOS" is a trademark of Infineon Technologies AG".

### DISCLAIMER

The information contained in the document (unless it is publicly available on the Web without access restrictions) is PROPRIETARY AND CONFIDENTIAL information of Microsemi and cannot be copied, published, uploaded, posted, transmitted, distributed or disclosed or used without the express duly signed written consent of Microsemi. If the recipient of this document has entered into a disclosure agreement with Microsemi, then the terms of such Agreement will also apply. This document and the information contained herein may not be modified, by any person other than authorized personnel of Microsemi. No license under any patent, copyright, trade secret or other intellectual property right is granted to or conferred upon you by disclosure or delivery of the information, either expressly, by implication, inducement, estoppels or otherwise. Any license under such intellectual property rights must be approved by Microsemi in writing signed by an officer of Microsemi.

Microsemi reserves the right to change the configuration, functionality and performance of its products at anytime without any notice. This product has been subject to limited testing and should not be used in conjunction with life-support or other mission-critical equipment or applications. Microsemi assumes no liability whatsoever, and Microsemi disclaims any express or implied warranty, relating to sale and/or use of Microsemi products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright or other intellectual property right. Any performance specifications believed to be reliable but are not verified and customer or user must conduct and complete all performance and other testing of this product as well as any user or customers final application. User or customer shall not rely on any data and performance specifications or parameters provided by Microsemi. It is the customer's and user's responsibility to independently determine suitability of any Microsemi product and to test and verify the same. The information contained herein is provided "AS IS, WHERE IS" and with all faults, and the entire risk associated with such information is entirely with the User. Microsemi specifically disclaims any liability of any kind including for consequential, incidental and punitive damages as well as lost profit. The product is subject to other terms and conditions which can be located on the web at <http://www.microsemi.com/legal/tnc.asp>

#### Life Support Application

Seller's Products are not designed, intended, or authorized for use as components in systems intended for space, aviation, surgical implant into the body, in other applications intended to support or sustain life, or for any other application in which the failure of the Seller's Product could create a situation where personal injury, death or property damage or loss may occur (collectively "Life Support Applications").

Buyer agrees not to use Products in any Life Support Applications and to the extent it does it shall conduct extensive testing of the Product in such applications and further agrees to indemnify and hold Seller, and its officers, employees, subsidiaries, affiliates, agents, sales representatives and distributors harmless against all claims, costs, damages and expenses, and attorneys' fees and costs arising, directly or indirectly, out of any claims of personal injury, death, damage or otherwise associated with the use of the goods in Life Support Applications, even if such claim includes allegations that Seller was negligent regarding the design or manufacture of the goods.

Buyer must notify Seller in writing before using Seller's Products in Life Support Applications. Seller will study with Buyer alternative solutions to meet Buyer application specification based on Sellers sales conditions applicable for the new proposed specific part.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Microchip:](#)

[APTCV40H60CT1G](#)

ООО "ЛайфЭлектроникс"

"LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибуторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибуторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помочь разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: org@lifeelectronics.ru