




SECTION A-A



P.C.B LAYOUT (Top View)

SIGN	DATE	DESCRIPTION	APPROVER
△	10 / 31'08	Temperature changed from -40°C ~ +105°C to -40°C ~ +115°C	Kind
△	10 / 31'08	Screw Torque Value changed from 6.0kgf.cm to 8.6kgf.cm	Kind
△	10 / 31'08	Screw sort changed from M3.0 to #5-40.	Kind
△	04 / 30'09	Screw Torque Value changed from 8.6kgf.cm to 5.2lb-in	Eris
△	04 / 30'09	approved cULus	Eris
△	05 / 04'09	Structure changed	Eris
△	05 / 04'09	Dimension allowance	Eris
△	11 / 21'12	Change the screw plating specification	Jacky
△	11 / 21'12	Change the dimensional tolerance	Jacky
△	04 / 20'13	Update the drawing	Jacky

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

MATERIALS ELECTRICAL

RATED VOLTAGE & CURRENT:	300V, 15 A
WITHSTAND VOLTAGE:	AC 2000 V/Min
INSULATION RESISTANCE:	1000 MΩ OR MORE AT DC 500 V
△ OPERATING TEMPERATURE RANG:	-40 °C ~ +115 °C
△ △ SCREW TORQUE VALUE:	5.2 Lb-In
WIRE RANGE:	22 - 14 AWG
1) MOLDED PARTS:	THERMOPLASTIC, UL 94 V-0 BLACK
2) TERMINAL:	BRASS, 0.8t, Tin PLATED
△ △ 3) TERMINAL SCREWS:	STEEL, #5-40

△ Safety Approval:

PART NO.:
Critical dimension: ▽

YK 321 xx 0 x x 00G

NO. OF POLES
02: 2 POLES
03: 3 POLES
04: 4 POLES
...

30: 30 POLES

G:RoHS compliant(lead<4%)
in copper alloy

MARK

0: "@" MARK

1: "ANY" MARK

TERMINAL & SCREW PLATED

0: TERMINAL & SCREW: G/F

△ 1: TERMINAL: G/F, SCREW: Zinc

2: TERMINAL: Sn, SCREW: G/F

△ 3: TERMINAL: Sn, SCREW: Zinc

4: TERMINAL: Sn, SCREW: Blue Zn

N= Number of poles △

DIM		TOL		
		2P-4P	5P-21P	22P-30P
△ Dim A	(N-1)×7.62+8.48	±0.20	±0.30	±0.50
Dim B	(N-1)×7.62	±0.20	±0.30	±0.50

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		YK-321 W/O Flange Series				DWG NO.		8YK0001-321	
PART NO.		YK321xx0xx00G				DWG NO.		8YK0001-321	
APPROVED		CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance		
			Jacky 2013.04.20	Jacky 2013.04.20			UNIT: mm	X.	±0.50
							SCALE: NONE	X.X	±0.30
					SHEET: 01/01		REV: G	X°	±1°

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru