Spring Cage Installation Terminal Blocks STI 2,5 and STI 4

The asymmetrically arranged terminal foot makes the STI series stand out against standard terminal blocks. This foot makes it possible to route the neutral busbar past the terminal strip and to fix it in the insulated supports. The neutral busbar makes contact via the screwless neutral-disconnect slide by simple levering with a screwdriver. Considerable space savings in the control cabinet can be made by using the "mini-spring" spring cage system, without having to give up the familiar high quality features such as the generous labeling option, maximum connection space and the flexible plug-in bridge system.

Assembly

In order to achieve a reliable contact between the disconnect slide and the neutral busbar, the AB-STI supports must be mounted at the beginning and end of each terminal strip or, in the case of longer terminal strips, approx. every 20 cm.

Headquarters: © Phoenix Contact GmbH & Co. • Flachsmarktstraße 8 • 32825 Blomberg • Germany
Phone +49-(0) 52 35-3-00 • Fax +49-(0) 52 35-3-4 12 0 • http://www.phoenixcontact.com

Spring Cage
Installation Terminal Block
STI 2,5

(IEC) [mm²]	rigid solid	flexible stranded	AWG	I [A]	U [V]
IEC 60 947-7-1	0.2-4	0.2-2.5	24-12	32	400

Technical data

			Type		Order No.	Pcs. Pkt.
Spring cage installation terminal block, for mounting on ⊓	gray	terminal width 5.2	**STI 2,5**		**30 31 92 4**	**50**
	blue	terminal width 5.2	**STI 2,5 BU**		**31 36 21 7**	**50**
(1) **End cover**	gray		**D-STI 2,5**		**30 30 56 9**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections						
Cross section range:	0.2 mm²	white	**ISH 2,5/0,2**		**30 02 84 3**	**50**
	0.25-0.5 mm²	gray	**ISH 2,5/0,5**		**30 02 85 6**	**50**
	0.75-1 mm²	black	**ISH 2,5/1**		**30 02 86 9**	**50**
(3) **Plug-in bridge,** for cross connections in the terminal center	2-pos.		**FBS 2-5**	$I_{max.}$: 24 A	**30 30 16 1**	**10**
	3-pos.		**FBS 3-5**	24 A	**3/0 30 17 4**	**10**
	4-pos.		**FBS 4-5**	24 A	**30 30 18 7**	**10**
	5-pos.		**FBS 5-5**	24 A	**30 30 19 0**	**10**
	10-pos.		**FBS 10-5**	24 A	**30 30 21 3**	**10**
	20-pos.		**FBS 20-5**	24 A	**30 30 22 6**	**10**
(4) **Test adapter,** for 4 mm ∅ test connector PS and 4 mm ∅ safety test connector, making contact in the bridge shaft			**PAI 4**		**30 30 92 5**	**10**
(5) **2.3 mm ∅ test connector [1])**, consisting of metal part and red insulating sleeve			**MPS-RD**		**02 01 55 3**	**10**
(6) **Reducing plug**			**RPS**		**02 01 64 7**	**10**
(7) **Screwdriver,** for actuating the tension spring			**SZF 1 - 0,6 x 3,5**		**12 04 51 7**	**10**
(8) **Zack marker sheet,** flat, 120-section, for labeling the outer marker grooves		white	**ZBFM 5 /WH:UNPRINTED**		**08 03 59 5**	**10**
(9) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white		**ZB 5: UNPRINTED**		**10 50 00 4**	**10**

Dimensions		
Width / length /end cover width	[mm]	5.2 / 59.5 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	32 / 4
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 2.5
Stranded with ferrule without plastic sleeve	[mm²]	0.25 - 2.5
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 3
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

[1]) Further colors are available on request.

Spring Cage Ground Terminal Block
STI 2,5-PE

(IEC) [mm²]	rigid solid	flexible stranded	AWG
IEC 60 947-7-2	0.2-4	0.2-2.5	24-12

The current carrying capacity of the mounting rails should be observed.

Technical data

			Type	Order No.	Pcs. Pkt.
Spring cage ground terminal block, for mounting on ⊓	green-yellow	terminal width 5.2	**STI 2,5-PE**	**30 31 93 7**	**50**
(1) **End cover**	gray		**D-STI 2,5**	**30 30 56 9**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections					
Cross section range:	0.2 mm²	white	**ISH 2,5/0,2**	**30 02 84 3**	**50**
	0.25-0.5 mm²	gray	**ISH 2,5/0,5**	**30 02 85 6**	**50**
	0.75-1 mm²	black	**ISH 2,5/1**	**30 02 86 9**	**50**
(3) **Screwdriver,** for actuating the tension spring			**SZF 1 - 0,6 x 3,5**	**12 04 51 7**	**10**
(4) **Zack marker sheet,** flat, 120-section, for labeling the outer marker grooves		white	**ZBFM 5 /WH:UNPRINTED**	**08 03 59 5**	**10**
(5) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white		**ZB 5: UNPRINTED**	**10 50 00 4**	**10**

Dimensions		
Width / length /end cover width	[mm]	5.2 / 59.5 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	–
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 2.5
Stranded with ferrule without plastic sleeve	[mm²]	0.25 - 2.5
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 3
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

Spring Cage
Installation Terminal Block
STN 2,5

(IEC) [mm²]	rigid solid	flexible stranded	AWG	I [A]	U [V]
IEC 60 947-7-1	0.2-4	0.2-2.5	24-12	32	400

Technical data

		Type		Order No.	Pcs. Pkt.
Spring cage neutral disconnect terminal block, for mounting on ⊔	blue terminal width 5.2	**STN 2,5**		**30 31 94 0**	**50**
(1) **End cover**	gray	**D-STI 2,5**		**30 30 56 9**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections					
Cross section range:	0.2 mm² white	**ISH 2,5/0,2**		**30 02 84 3**	**50**
	0.25-0.5 mm² gray	**ISH 2,5/0,5**		**30 02 85 6**	**50**
	0.75-1 mm² black	**ISH 2,5/1**		**30 02 86 9**	**50**
(3) **Plug-in bridge,** for cross connections in the terminal center	2-pos.	**FBS 2-5**	$I_{max.}$: 24 A	**30 30 16 1**	**10**
	3-pos.	**FBS 3-5**	24 A	**3/0 30 17 4**	**10**
	4-pos.	**FBS 4-5**	24 A	**30 30 18 7**	**10**
	5-pos.	**FBS 5-5**	24 A	**30 30 19 0**	**10**
	10-pos.	**FBS 10-5**	24 A	**30 30 21 3**	**10**
	20-pos.	**FBS 20-5**	24 A	**30 30 22 6**	**10**
(4) **Test adapter,** for 4 mm ∅ test connector PS and 4 mm ∅ safety test connector, making contact in the bridge shaft		**PAI 4**		**30 30 92 5**	**10**
(5) **2.3 mm ∅ test connector**[1]**)**, consisting of metal part and red insulating sleeve		**MPS-RD**		**02 01 55 3**	**10**
(6) **Reducing plug**		**RPS**		**02 01 64 7**	**10**
(7) **Neutral busbar,** 3 x 10 mm, 1 m long, copper, tin-plated		**NLS-CU 3/10**		**04 02 17 4**	**10**
(8) **Support,** blue insulating material, for mounting the neutral busbar		**AB-STI**		**30 30 82 8**	**50**
(9) **Screwdriver,** for actuating the tension spring		**SZF 1 - 0,6 x 3,5**		**12 04 51 7**	**10**
(10) **Zack marker sheet,** flat, 120-section, for labeling the outer marker grooves	white	**ZBFM 5 /WH:UNPRINTED**		**08 03 59 5**	**10**
(11) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white	**ZB 5: UNPRINTED**		**10 50 00 4**	**10**

Dimensions		
Width / length /end cover width	[mm]	5.2 / 59.5 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	32 / 4
Current carrying capacity of the neutal busbar	[A]	140
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.25 - 2.5
Stranded with ferrule without plastic sleeve	[mm²]	0.25 - 2.5
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 3
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

[1]) Further colors are available on request.

Spring Cage
Installation Terminal Block
STI 4

(IEC) [mm²]	rigid solid	flexible stranded	AWG	I [A]	U [V]
IEC 60 947-7-1	0.5-6	0.5-4	20-10	41	400

Technical data

			Type		Order No.	Pcs. Pkt.
Spring cage installation terminal block, for mounting on ⊓	gray	terminal width 6.2	**STI 4**		**30 31 95 3**	**50**
	blue	terminal width 6.2	**STI 4 BU**		**31 36 22 0**	**50**
(1) **End cover**	gray		**D-STI 4**		**30 30 64 0**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections						
Cross section range:	0.25-0.5 mm²	gray	**ISH 4/0,5**		**30 02 88 5**	**50**
	0.75-1 mm²	black	**ISH 4/1**		**30 02 89 8**	**50**
(3) **Plug-in bridge,** for cross connections in the terminal center	2-pos.		**FBS 2-6**	$I_{max.}$: 32 A	**30 30 33 6**	**10**
	3-pos.		**FBS 3-6**	32 A	**30 30 24 2**	**10**
	4-pos.		**FBS 4-6**	32 A	**30 30 25 5**	**10**
	5-pos.		**FBS 5-6**	32 A	**30 30 34 9**	**10**
	10-pos.		**FBS 10-6**	32 A	**30 30 27 1**	**10**
	20-pos.		**FBS 20-6**	32 A	**30 30 36 5**	**10**
(4) **Test adapter,** for 4 mm ∅ test connector PS and 4 mm ∅ safety test connector, making contact in the bridge shaft			**PAI 4**		**30 30 92 5**	**10**
(5) **2.3 mm ∅ test connector** [1]**)**, consisting of metal part and red insulating sleeve			**MPS-RD**		**02 01 55 3**	**10**
(6) **Reducing plug**			**RPS**		**02 01 64 7**	**10**
(7) **Screwdriver,** for actuating the tension spring			**SZF 1 - 0,6 x 3,5**		**12 04 51 7**	**10**
(8) **Zack marker sheet,** flat, 100-section, for labeling the outer marker grooves		white	**ZBFM 6 /WH:UNPRINTED**		**08 03 61 8**	**10**
(9) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white		**ZB 6:UNPRINTED**		**10 51 00 3**	**10**

Dimensions		
Width / length /end cover width	[mm]	6.2 / 66 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	41 / 6
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.5 - 4
Stranded with ferrule without plastic sleeve	[mm²]	0.5 - 4
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 4
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

[1]) Further colors are available on request.

Spring Cage Ground Terminal Block
STI 4-PE

(IEC) [mm²]	rigid solid	flexible stranded	AWG
IEC 60 947-7-2	0.5-6	0.5-4	20-10

The current carrying capacity of the mounting rails should be observed.

Technical data

			Type	Order No.	Pcs. Pkt.
Spring cage ground terminal block, for mounting on ⊓	green-yellow	terminal width 6.2	**STI 4-PE**	**30 31 96 6**	**50**
(1) **End cover**	gray		**D-STI 4**	**30 30 64 0**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections					
Cross section range: 0.25-0.5 mm²		gray	**ISH 4/0,5**	**30 02 88 5**	**50**
0.75-1 mm²		black	**ISH 4/1**	**30 02 89 8**	**50**
(3) **Screwdriver,** for actuating the tension spring			**SZF 1 - 0,6 x 3,5**	**12 04 51 7**	**10**
(4) **Zack marker sheet,** flat, 100-section, for labeling the outer marker grooves		white	**ZBFM 6 /WH:UNPRINTED**	**08 03 61 8**	**10**
(5) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white		**ZB 6:UNPRINTED**	**10 51 00 3**	**10**

Dimensions		
Width / length /end cover width	[mm]	6.2 / 66 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	–
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.5 - 4
Stranded with ferrule without plastic sleeve	[mm²]	0.5 - 4
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 4
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

Spring Cage
Installation Terminal Block
STN 4

(IEC) [mm²]	rigid solid	flexible stranded	AWG	I [A]	U [V]
IEC 60 947-7-1	0.5-6	0.5-4	20-10	36	250

Technical data

			Type		Order No.	Pcs. Pkt.
Spring cage neutral disconnect terminal block, for mounting on ⊓	blue	terminal width 6.2	**STN 4**		**30 31 97 9**	**50**
(1) **End cover**	gray		**D-STI 4**		**30 30 64 0**	**50**
(2) **Insulating stop sleeve,** prevents unintentional clamping of insulation in the case of smaller cross sections						
Cross section range: 0.25-0.5 mm²		gray	**ISH 4/0,5**		**30 02 88 5**	**50**
0.75-1 mm²		black	**ISH 4/1**		**30 02 89 8**	**50**
(3) **Plug-in bridge,** for cross connections in the terminal center	2-pos.		**FBS 2-6**	I_{max}.: 32 A	**30 30 33 6**	**10**
	3-pos.		**FBS 3-6**	32 A	**30 30 24 2**	**10**
	4-pos.		**FBS 4-6**	32 A	**30 30 25 5**	**10**
	5-pos.		**FBS 5-6**	32 A	**30 30 34 9**	**10**
	10-pos.		**FBS 10-6**	32 A	**30 30 27 1**	**10**
	20-pos.		**FBS 20-6**	32 A	**30 30 36 5**	**10**
(4) **Test adapter,** for 4 mm ∅ test connector PS and 4 mm ∅ safety test connector, making contact in the bridge shaft			**PAI 4**		**30 30 92 5**	**10**
(5) **2.3 mm ∅ test connector** [1]**)**, consisting of metal part and red insulating sleeve			**MPS-RD**		**02 01 55 3**	**10**
(6) **Reducing plug**			**RPS**		**02 01 64 7**	**10**
(7) **Neutral busbar,** 3 x 10 mm, 1 m long, copper, tin-plated			**NLS-CU 3/10**		**04 02 17 4**	**10**
(8) **Support,** blue insulating material, for mounting the neutral busbar			**AB-STI**		**30 30 82 8**	**50**
(9) **Screwdriver,** for actuating the tension spring			**SZF 1 - 0,6 x 3,5**		**12 04 51 7**	**10**
(10) **Zack marker sheet,** flat, 100-section, for labeling the outer marker grooves		white	**ZBFM 6 /WH:UNPRINTED**		**08 03 61 8**	**10**
(11) **Zack strip,** 10-section, for labeling in the terminal center and on the plug-in bridges	white		**ZB 6:UNPRINTED**		**10 51 00 3**	**10**

Dimensions		
Width / length /end cover width	[mm]	6.2 / 66 / 2.2
Height (NS 35:7.5 / NS 35:15)	[mm]	43 / 50.5
Technical data in accordance with IEC/ DIN VDE		
Maximum load current / cross section	[A] / [mm²]	36 / 6
Current carrying capacity of the neutral busbar	[A]	140
Rated surge voltage / contamination class	[kV] / –	6 / 3
Surge voltage category / insulation material group	– / –	III / I
Connection capacity		
Stranded with ferrule with plastic sleeve	[mm²]	0.5 - 4
Stranded with ferrule without plastic sleeve	[mm²]	0.5 - 4
Stranded with TWIN ferrule with plastic sleeve	[mm²]	0.5 - 1
Stripping length	[mm]	10
Internal cylindrical gauge (IEC 60 947-1)		A 4
Insulation material		PA
Inflammability class in accordance with UL 94		V0
Approval data (UL and CSA/CUL)		
Nom. voltage / nom. current / conduc. sizes	UL: [V] / [A] / AWG	–
	CSA/CUL: [V] / [A] / AWG	–

[1]) Further colors are available on request.

© PHOENIX CONTACT 01.03.01 TNR: 5125058-00 http://www.phoenixcontact.com

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru