CRYSTEK CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CVHD-950 VCXO
Ultra-Low Phase Noise Oscillators

RoHS Compliant

CVHD-950 Model
9×14 mm SMD, **3.3V, CMOS**

50 MHz HCMOS 3.3V



80 MHz HCMOS 3.3V



100 MHz HCMOS 3.3V



130 MHz HCMOS 3.3V



Model CVHD-950 is a 50 MHz to 130 MHz CMOS Voltage Controlled Crystal Oscillator. High Q crystal and 3rd overtone technology provides Ultra-Low Phase Noise and Low-Jitter performance with a CMOS output. Features include -165 dBc/Hz phase noise floor with 3.3Vdc input voltage, -40°C to +85°C operating temperature, and 9×14 mm SMT package. The oscillator has no sub-harmonics.

Applications include High Definition TV, Avionics Low Phase Signal Sources, and Test and Measurement.

Rev: N
Date: 30-Jul-12
Page 1 of 2

CRYSTEK CORPORATION
12730 Commonwealth Drive • Fort Myers, Florida 33913
Phone: 239-561-3311 • 800-237-3061
Fax: 239-561-1025 • www.crystek.com

CRYSTEK CRYSTALS
A DIVISION OF CRYSTEK CORPORATION

CVHD-950 VCXO
Ultra-Low Phase Noise Oscillators

RoHS Compliant

CVHD-950 Model
9×14 mm SMD, **3.3V, CMOS**

Frequency Range:	**50 MHz to 130 MHz**
Temperature Range:	**0°C to +70°C (standard)**
(Option M)	**-20°C to +70°C**
(Option X)	**-40°C to +85°C**
Storage:	**-45°C to 90°C**
Input Voltage:	**3.3V ±0.3V**
Input Current:	**15mA Typical, 25mA Max**
Output:	**CMOS**
Symmetry:	**45/55% Max @ 50%Vdd**
Rise/Fall Time:	**3nsec Max @ 20% to 80% Vdd**
Logic:	**"0" = 10% Vdd Max**
	"1" = 90% Vdd Min
Load:	**15pF**
Output Current:	**±24mA Max**
Input:	
Modulation Bandwidth:	**>10kHz @ -3dB**
Impedance:	**51 kΩ**
Control Voltage:	**1.65V ±1.65V**
Tuning Sensitivity:	**+25ppm/V Typical**
Frequency Pulling:	**±20ppm APR Min**
	(Inclusive of frequency stability, calibration, and aging.)
Linearity:	**±10% Max**
Phase Jitter (12kHz~80MHz):	**0.13psec Typical @100MHz**
Phase Noise Floor:	**-165dBc/Hz Typical, -160dBc/Hz Max**
Sub-harmonics:	**None**
Aging:	**<3ppm 1st year, <1ppm thereafter**

Typical Phase Noise:

1kHz	**-135 dBc/Hz**
10kHz	**-155 dBc/Hz**
100kHz	**-164 dBc/Hz**
1MHz	**-165 dBc/Hz**

Mechanical:

Shock:	MIL-STD-883, Method 2002, Condition B
Solderability:	MIL-STD-883, Method 2003
Vibration:	MIL-STD-883, Method 2007, Condition A
Solvent Resistance:	MIL-STD-202, Method 215
Resistance to Soldering Heat:	MIL-STD-202, Method 210, Condition I or J

Environmental:

Thermal Shock:	MIL-STD-883, Method 1011, Condition A
Moisture Resistance:	MIL-STD-883, Method 1004

Part Number Example: CVHD-950X-100.000 = 3.3V, 45/55, -40°C to +85°C (±20ppmAPR), 100 MHz



RECOMMENDED REFLOW SOLDERING PROFILE



NOTE: Reflow Profile with 240°C peak also acceptable.

Pad	Connection
1	Volt Cntrl.
2	GND
3	OUT
4	Vdd

Rev: N
Date: 30-Jul-12

CRYSTEK CORPORATION
12730 Commonwealth Drive • Fort Myers, Florida 33913
Phone: 239-561-3311 • 800-237-3061
Fax: 239-561-1025 • www.crystek.com

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru