

FREEPORT, ILLINOIS, U S A
A DIVISION OF HONEYWELL
FED. MFG. CODE 91929

CATALOG LISTING
14TL1-12 SERIES
CHART 1

THIS DRAWING COVERS A PROPRIETARY ITEM AND IS THE PROPERTY OF MICRO SWITCH, A DIVISION OF HONEYWELL. THIS DRAWING IS NOT TO BE COPIED OR USED WITHOUT THE APPROVAL OF MICRO SWITCH.

.06 ± .008 WIDE KEYWAY
 .240 DIA
 .427
STYLE I LEVER
 17° ± 4°
 34° ± 8° TOTAL TRAVEL
 .68
 .47
 .24
 1.10
 1.35
 .130 MIN
 .250
 .130 MIN
 .03 (12)
 .185 ± .015 (12)
 .18 DIA (12)
 .09 DIA (12)
 1.32
 .28
 .75
 .38
 .26
 .37
 .37
 .37
 .37
 1.64
 12
 11
 10
 9
 8
 7
 6
 5
 4
 3
 2
 1
 SEaled TO PREVENT ENTRANCE OF LIQUIDS OR DUST
 15/32-32 UNS-2 THREAD TO WITHIN .060 OF SHOULDER
 34° ± 8° TOTAL TRAVEL
 17° ± 4°
 .42 DIA
 .090
















SCALE		FULL	
DO NOT SCALE PRINT			
UNLESS OTHERWISE NOTED			
DIMENSIONS ARE IN INCHES			
TOLERANCES ARE:			
ONE PLACE	(.0)	±	.030
TWO PLACE	(.00)	±	.015
THREE PLACE	(.000)	±	.005
ANGLES		±	
WEIGHT			





15A-125, 250 OR 277 VAC
 1/2HP-125VAC; 1HP-250, 277VAC
 5A-125VAC "L" CODE L191

34° ± 8°
TOTAL TRAVEL
17° ± 4°
.42 DIA
.090
APPROX PULLOUT TO
1.05 CHANGE
POSITION
STYLE 2 LEVER

MS NUMBER	CATALOG LISTING	AVAILABLE LOCKING COMBINATIONS FOR CONFIGURATION SEE LETTERED DETAILS	STYLE NUMBER	CURRENT CAPACITY (AMPS)								
				RESISTIVE LOAD					LAMP LOAD		INDUCTIVE LOAD	
				DC VOLTS		AC VOLTS						
				28	125	250	125	250	28 VDC	125 VAC	28 VDC	125 VAC
27736-1	14TLI-12	NONE	1									
27739-1	14TLI-12	A,B,D,E,F,G,H,J,K,L,M,N,P	2	20	.75	.5	15	6	5	4	12	15
"A" 	"B" 	"D" 	"E" 	"F" 	 LOCKWASHER  LOCKING RING  HEX NUT (2)							
LOCKED IN THREE POSITIONS	LOCKED IN CENTER AND EXTREME POSITION (KEYWAY SIDE)	LOCKED OUT OF CENTER POSITION	LOCKED IN CENTER POSITION	LOCKED IN EXTREME POSITION (OPPOSITE KEYWAY)								
"G" 	"H" 	"J" 	"K" 	"L" 								
LOCKED IN EXTREME POSITION (KEYWAY SIDE)	LOCKED OUT OF CENTER AND EXTREME POSITION (KEYWAY SIDE)	LOCKED OUT OF CENTER AND EXTREME POSITION (OPPOSITE KEYWAY)	LOCKED IN CENTER AND EXTREME POSITION (OPPOSITE KEYWAY)	LOCKED OUT OF EXTREME POSITION (KEYWAY SIDE)								
"M" 	"N" 	"P" 										
LOCKED OUT OF AND INTO EXTREME POSITION (OPPOSITE KEYWAY)	LOCKED OUT OF EXTREME POSITION (OPPOSITE KEYWAY)	LOCKED OUT OF AND INTO EXTREME POSITION (KEYWAY SIDE)										
CIRCUIT MADE WITH TOGGLE LEVER IN												
KEYWAY SIDE			CENTER			OPPOSITE KEYWAY						
												
MAINTAINED POSITION			MAINTAINED POSITION			MAINTAINED POSITION						

- 1 - SWITCHES ARE CAPABLE OF WITHSTANDING A TEMPERATURE OF 160°F CONTINUOUSLY AT FULL RATED LOAD
- 2 - CIRCUIT DESIGNATION AND MICRO SWITCH CATALOG LISTING AND MS NUMBER STAMPED ON SIDE OF SWITCH
- ③ FURNISHED UNASSEMBLED
- 4 - FOR TERMINAL COVER SEE MICRO SWITCH CAT. LIST. 5PA9
- ⑤ KEYWAY SHOWN ON LEFT SIDE
- ⑥ SUFFIX LETTER MUST BE ADDED FOR DESIRED TYPE OF TOGGLE LOCKING. SEE CHART FOR AVAILABLE LOCKING COMBINATIONS

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru