

D

C

B


A

D

C

B

A



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- FOLLOWING CONTACTS ARE INCLUDED AND LOADED:
SIZE 22 SOCKET: TE P/N 1-211431-4; QTY=250 (-1 ONLY)
SIZE 22 SOCKET: NON-REMOVABLE STAMPED & FORMED; QTY=250 (-4 ONLY)
SIZE 20 PIN CONTACT: TE P/N 2-448138-7; QTY=4
SIZE 16 PIN: TE P/N 2-448139-2; QTY: 3
SIZE 12 PIN: TE P/N 1-148140-9; QTY: 4
SIZE 5 COAX: TE P/N 1484201-4; QTY=2
ALL SOLDER POSTS ARE SOLDER DIPPED.
- POLARIZING KEYS ARE INSTALLED IN POSITION 40.
- INSERT MATERIAL: DIE CAST ALUMINUM PER ASTM-B-85.
INSERT FINISH: CLASS 1A CHROMATE PER MIL-STD-5541
- INSERT MATERIAL: THERMOPLASTIC OR THERMOSET EPOXY.
- SIZE 1 COAX CONTACTS NOT INCLUDED, MUST BE ORDERED SEPARATELY
- THE C4 INSERT BACKUP PLATES AND SCREWS ARE ASSEMBLED TO CONNECTOR
- TE LOGO APPEARS IN THIS APPROXIMATE LOCATION ON MACHINED FROM BILLET SHELLS.
- ASSEMBLY SHOWN WITH DIE CAST SHELL. ASSEMBLIES WITH MACHINED SHELLS MAY VARY SLIGHTLY IN APPEARANCE.

MODULE E & F: MONOBLOCK INSERTS WITH NON-REMOVABLE STAMPED & FORMED SIZE 22 SOCKET CONTACTS	1484510-4
MODULE E & F: FRONT RELEASE INSERTS WITH STANDARD SIZE 22 SOCKET CONTACTS	1484510-1
REMARKS	PART NUMBER


THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. HOFFMAN 10/14/02	TE Connectivity				
DIMENSIONS: INCHES		CHK S. GLATFELTER 10-24-02	NAME				
		APVD S. GLATFELTER 10-24-02	PRODUCT SPEC				
		APPLICATION SPEC					
		WEIGHT 0					
MATERIAL SEE CALLOUTS		FINISH SEE CALLOUTS		SIZE A1	CAGE CODE 00779	DRAWING NO 1484510	RESTRICTED TO
CUSTOMER DRAWING		SCALE 3:2		SHEET 1 OF 3		REV N	

D


C

B

A



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- FOLLOWING CONTACTS ARE INCLUDED AND LOADED:
SIZE 22 SOCKET: TE P/N 1-211431-4; QTY=400 (-2 ONLY)
SIZE 22 SOCKET: NON-REMOVABLE STAMPED & FORMED; QTY=400 (-5 ONLY)
SIZE 20 PIN CONTACT: TE P/N 1663533-3; QTY=4
SIZE 16 PIN: TE P/N 1663128-6; QTY: 3
SIZE 12 PIN: TE P/N 1663129-6; QTY: 4
SIZE 5 COAX: P/N 1663535-1; QTY=1 (POSTED CONTACT) IN POSN 12
SIZE 5 COAX: P/N 1663389-1; QTY=1 (SIZE 5 TO SMB ADAPTER) IN POSN 13
ALL SOLDER POSTS ARE SOLDER DIPPED.
- POLARIZING KEYS ARE INSTALLED IN POSITION 52.
- INSERT MATERIAL: DIE CAST ALUMINUM PER ASTM-B-85.
INSERT FINISH: CLASS 1A CHROMATE PER MIL-STD-5541
- INSERT MATERIAL: THERMOPLASTIC OR THERMOSET EPOXY.
- SIZE 1 COAX CONTACTS NOT INCLUDED,
MUST BE ORDERED SEPARATELY
- THE C4 INSERT BACKUP PLATES AND SCREWS ARE ASSEMBLED
TO CONNECTOR
- TE LOGO APPEARS IN THIS APPROXIMATE LOCATION ON
MACHINED FROM BILLET SHELLS.
- ASSEMBLY SHOWN WITH DIE CAST SHELL. ASSEMBLIES WITH
MACHINED SHELLS MAY VARY SLIGHTLY IN APPEARANCE.



MODULE D, E & F: MONOBLOCK INSERTS WITH NON-REMOVABLE STAMPED & FORMED SIZE 22 SOCKET CONTACTS	1484510-5
MODULE D, E & F: FRONT RELEASE INSERTS WITH STANDARD SIZE 22 SOCKET CONTACTS	1484510-2
REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. HOFFMAN 10/14/02	TE Connectivity	
DIMENSIONS: INCHES		CHK S. GLATFELTER 10-24-02	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S. GLATFELTER 10-24-02	PRODUCT SPEC	
1 PLC ± .005		APPLICATION SPEC		
2 PLC ± .005		WEIGHT		
3 PLC ± .005		SIZE		
4 PLC ± .005		CAGE CODE		
MATERIAL SEE CALLOUTS		DRAWING NO		
FINISH SEE CALLOUTS		RESTRICTED TO		
CUSTOMER DRAWING		SCALE 3:2		
		SHEET 2 OF 3		
		REV N		

D

C

B




A

D

C

B

A



- CONNECTOR DIMENSIONS ARE PER ARINC 600 SPECIFICATION
- FOLLOWING CONTACTS ARE INCLUDED AND LOADED:
SIZE 22 SOCKET: TE P/N 1-211431-4; QTY=400 (-3 ONLY)
SIZE 22 SOCKET: NON-REMOVABLE STAMPED & FORMED; QTY=400 (-6 ONLY)
SIZE 20 PIN CONTACT: TE P/N 1663533-3; QTY=4
SIZE 16 PIN: TE P/N 1663128-6; QTY: 3
SIZE 12 PIN: TE P/N 1663129-6; QTY: 4
SIZE 5 COAX: TE P/N 1484201-4; QTY=2
ALL SOLDER POSTS ARE SOLDER DIPPED.
- POLARIZING KEYS ARE INSTALLED IN POSITION 52.
- INSERT MATERIAL: DIE CAST ALUMINUM PER ASTM-B-85.
INSERT FINISH: CLASS 1A CHROMATE PER MIL-STD-5541
- INSERT MATERIAL: THERMOPLASTIC OR THERMOSET EPOXY.
- SIZE 1 COAX CONTACTS NOT INCLUDED,
MUST BE ORDERED SEPARATELY
- THE C4 INSERT BACKUP PLATES AND SCREWS ARE ASSEMBLED
TO CONNECTOR
- TE LOGO APPEARS IN THIS APPROXIMATE LOCATION ON
MACHINED FROM BILLET SHELLS.
- ASSEMBLY SHOWN WITH DIE CAST SHELL. ASSEMBLIES WITH
MACHINED SHELLS MAY VARY SLIGHTLY IN APPEARANCE.

MODULE D, E & F: MONOBLOCK INSERTS WITH NON-REMOVABLE STAMPED & FORMED SIZE 22 SOCKET CONTACTS	1484510-6
MODULE D, E & F: FRONT RELEASE INSERTS WITH STANDARD SIZE 22 SOCKET CONTACTS	1484510-3
REMARKS	PART NUMBER

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN S. HOFFMAN 10/14/02	TE Connectivity	
DIMENSIONS: INCHES		CHK S. GLATFELTER 10-24-02	NAME	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD S. GLATFELTER 10-24-02	PRODUCT SPEC	
0 PLC ± - 1 PLC ± - 2 PLC ± - 3 PLC ± .005 4 PLC ± - ANGLES ± -		APPLICATION SPEC		
MATERIAL SEE CALLOUTS		WEIGHT -	SIZE A1	
SEE CALLOUTS		CAGE CODE 00779		
CUSTOMER DRAWING		DRAWING NO 1484510		
SCALE 3:2		SHEET 3 OF 3		
REV N		RESTRICTED TO		

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru