

74LVCH162374A

16-bit edge-triggered D-type flip-flop with 30 Ω series termination resistors; 5 V input/output tolerant; 3-state

Rev. 4 — 22 January 2013

Product data sheet

1. General description

The 74LVCH162374A is a 16-bit edge triggered flip-flop featuring separate D-type inputs for each flip-flop and 3-state outputs for bus-oriented applications. The device consists of two sections of 8 edge-triggered flip-flops. A clock (CP) input and an output enable (\overline{OE}) are provided for each octal. Inputs can be driven from either 3.3 V or 5 V devices. When disabled, up to 5.5 V can be applied to the outputs. These features allow the use of these devices in mixed 3.3 V and 5 V applications. The flip-flops store the state of their individual D-inputs that meet the set-up and hold time requirements on the LOW to HIGH CP transition. When \overline{OE} is LOW, the contents of the flip-flops are available at the outputs. When \overline{OE} is HIGH, the outputs go to the high-impedance OFF-state. Operation of the \overline{OE} input does not affect the state of the flip-flops.

Bus hold on data inputs eliminates the need for external pull-up resistors to hold unused inputs.

To reduce line noise, 30 Ω series termination resistors are included in both high and low output stages.

2. Features and benefits

- 5 V tolerant inputs/outputs for interfacing with 5 V logic
- Wide supply voltage range from 1.2 V to 3.6 V
- CMOS low power consumption
- Multibyte flow-through standard pinout architecture
- Multiple low inductance supply pins for minimum noise and ground bounce
- Direct interface with TTL levels
- All data inputs have bus hold
- High-impedance outputs when $V_{CC} = 0$ V
- Complies with JEDEC standard:
 - ◆ JESD8-7A (1.65 V to 1.95 V)
 - ◆ JESD8-5A (2.3 V to 2.7 V)
 - ◆ JESD8-C/JESD36 (2.7 V to 3.6 V)
- ESD protection:
 - ◆ HBM JESD22-A114F exceeds 2000 V
 - ◆ MM JESD22-A115-B exceeds 200 V
 - ◆ CDM JESD22-C101E exceeds 1000 V
- Specified from -40 °C to $+85$ °C and -40 °C to $+125$ °C

3. Ordering information

Table 1. Ordering information

| Type number | Package | | | Version |
|------------------|-------------------|---------|--|----------|
| | Temperature range | Name | Description | |
| 74LVCH162374ADGG | -40 °C to +125 °C | TSSOP48 | plastic thin shrink small outline package; 48 leads; body width 6.1 mm | SOT362-1 |
| 74LVCH162374ADL | -40 °C to +125 °C | SSOP48 | plastic shrink small outline package; 48 leads; body width 7.5 mm | SOT370-1 |

4. Functional diagram




Fig 1. Logic symbol




Fig 2. IEC logic symbol




Fig 3. Logic diagram




Fig 4. Bus hold circuit

5. Pinning information

5.1 Pinning




Fig 5. Pin configuration SSOP48 and TSSOP48

5.2 Pin description

Table 2. Pin description

| Symbol | Pin | Description |
|------------------|--------------------------------|----------------------------------|
| $1\overline{OE}$ | 1 | output enable input (active LOW) |
| $2\overline{OE}$ | 24 | output enable input (active LOW) |
| 1CP | 48 | clock input |
| 2CP | 25 | clock input |
| GND | 4, 10, 15, 21, 28, 34, 39, 45 | ground (0 V) |
| V _{CC} | 7, 18, 31, 42 | supply voltage |
| 1Q[0:7] | 2, 3, 5, 6, 8, 9, 11, 12 | data output |
| 2Q[0:7] | 13, 14, 16, 17, 19, 20, 22, 23 | data output |
| 1D[0:7] | 47, 46, 44, 43, 41, 40, 38, 37 | data input |
| 2D[0:7] | 36, 35, 33, 32, 30, 29, 27, 26 | data input |

6. Functional description

Table 3. Function selection^[1]

| Operation modes | Input | | | Internal flip-flop | Output nQ0 to nQ7 |
|------------------------------------|-------|-----|------------|--------------------|----------------------|
| | nOE | nCP | nD0 to nD7 | | |
| Load and read register | L | ↑ | l | L | L |
| | L | ↑ | h | H | H |
| Latch register and disable outputs | H | ↑ | l | L | Z |
| | H | ↑ | h | H | Z |

- [1] H = HIGH voltage level
 h = HIGH voltage level one set-up time prior to the HIGH to LOW LE transition
 L = LOW voltage level
 l = LOW voltage level one set-up time prior to the HIGH to LOW LE transition
 Z = high-impedance OFF-state
 ↑ = LOW to HIGH CP transition

7. Limiting values

Table 4. Limiting values

In accordance with the Absolute Maximum Rating System (IEC 60134). Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | Min | Max | Unit |
|-----------|-------------------------|-------------------------------|---------------------|----------------|------|
| V_{CC} | supply voltage | | -0.5 | +6.5 | V |
| I_{IK} | input clamping current | $V_I < 0$ V | -50 | - | mA |
| V_I | input voltage | | ^[1] -0.5 | +6.5 | V |
| I_{OK} | output clamping current | $V_O > V_{CC}$ or $V_O < 0$ V | - | ± 50 | mA |
| V_O | output voltage | output HIGH or LOW state | ^[2] -0.5 | $V_{CC} + 0.5$ | V |
| | | output 3-state | ^[2] -0.5 | +6.5 | V |
| I_O | output current | $V_O = 0$ V to V_{CC} | - | ± 50 | mA |
| I_{CC} | supply current | | - | 100 | mA |
| I_{GND} | ground current | | -100 | - | mA |
| T_{stg} | storage temperature | | -65 | +150 | °C |
| P_{tot} | total power dissipation | $T_{amb} = -40$ °C to +125 °C | ^[3] - | 500 | mW |

- [1] The minimum input voltage ratings may be exceeded if the input current ratings are observed.
 [2] The output voltage ratings may be exceeded if the output current ratings are observed.
 [3] Above 60 °C, the value of P_{tot} derates linearly with 5.5 mW/K.

8. Recommended operating conditions

Table 5. Operating conditions

| Symbol | Parameter | Conditions | Min | Typ | Max | Unit |
|---------------------|-------------------------------------|--|------|-----|----------|--------------------|
| V_{CC} | supply voltage | | 1.65 | - | 3.6 | V |
| | | functional | 1.2 | - | 3.6 | V |
| V_I | input voltage | | 0 | - | 5.5 | V |
| V_O | output voltage | output HIGH or LOW state | 0 | - | V_{CC} | V |
| | | output 3-state | 0 | - | 5.5 | V |
| T_{amb} | ambient temperature | in free air | -40 | - | +125 | $^{\circ}\text{C}$ |
| $\Delta t/\Delta V$ | input transition rise and fall rate | $V_{CC} = 1.65\text{ V to }2.7\text{ V}$ | 0 | - | 20 | ns/V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | 0 | - | 10 | ns/V |

9. Static characteristics

Table 6. Static characteristics

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | -40 $^{\circ}\text{C}$ to +85 $^{\circ}\text{C}$ | | | -40 $^{\circ}\text{C}$ to +125 $^{\circ}\text{C}$ | | Unit |
|----------|---------------------------|---|--|--------------------|----------------------|---|----------------------|---------------|
| | | | Min | Typ ^[1] | Max | Min | Max | |
| V_{IH} | HIGH-level input voltage | $V_{CC} = 1.2\text{ V}$ | 1.08 | - | - | 1.08 | - | V |
| | | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | $0.65 \times V_{CC}$ | - | - | $0.65 \times V_{CC}$ | - | V |
| | | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$ | 1.7 | - | - | 1.7 | - | V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | 2.0 | - | - | 2.0 | - | V |
| V_{IL} | LOW-level input voltage | $V_{CC} = 1.2\text{ V}$ | - | - | 0.12 | - | 0.12 | V |
| | | $V_{CC} = 1.65\text{ V to }1.95\text{ V}$ | - | - | $0.35 \times V_{CC}$ | - | $0.35 \times V_{CC}$ | V |
| | | $V_{CC} = 2.3\text{ V to }2.7\text{ V}$ | - | - | 0.7 | - | 0.7 | V |
| | | $V_{CC} = 2.7\text{ V to }3.6\text{ V}$ | - | - | 0.8 | - | 0.8 | V |
| V_{OH} | HIGH-level output voltage | $V_I = V_{IH}$ or V_{IL} | | | | | | |
| | | $I_O = -100\ \mu\text{A}$; $V_{CC} = 1.65\text{ V to }3.6\text{ V}$ | $V_{CC} - 0.2$ | - | - | $V_{CC} - 0.3$ | - | V |
| | | $I_O = -2\text{ mA}$; $V_{CC} = 1.65\text{ V}$ | 1.2 | - | - | 1.05 | - | V |
| | | $I_O = -4\text{ mA}$; $V_{CC} = 2.3\text{ V}$ | 1.7 | - | - | 1.55 | - | V |
| | | $I_O = -6\text{ mA}$; $V_{CC} = 2.7\text{ V}$ | 2.2 | - | - | 2.05 | - | V |
| V_{OL} | LOW-level output voltage | $V_I = V_{IH}$ or V_{IL} | | | | | | |
| | | $I_O = 100\ \mu\text{A}$; $V_{CC} = 1.65\text{ V to }3.6\text{ V}$ | - | - | 0.2 | - | 0.3 | V |
| | | $I_O = 2\text{ mA}$; $V_{CC} = 1.65\text{ V}$ | - | - | 0.45 | - | 0.65 | V |
| | | $I_O = 4\text{ mA}$; $V_{CC} = 2.3\text{ V}$ | - | - | 0.6 | - | 0.8 | V |
| | | $I_O = 6\text{ mA}$; $V_{CC} = 2.7\text{ V}$ | - | - | 0.4 | - | 0.6 | V |
| I_I | input leakage current | $V_{CC} = 3.6\text{ V}$; $V_I = 5.5\text{ V}$ or GND ^[2] | - | ± 0.1 | ± 5 | - | ± 20 | μA |

Table 6. Static characteristics ...continued

At recommended operating conditions. Voltages are referenced to GND (ground = 0 V).

| Symbol | Parameter | Conditions | -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|-----------------|---------------------------------|---|------------------|--------------------|----------|-------------------|----------|---------|
| | | | Min | Typ ^[1] | Max | Min | Max | |
| I_{OZ} | OFF-state output current | $V_I = V_{IH}$ or V_{IL} ; $V_{CC} = 3.6$ V; $V_O = 5.5$ V or GND ^[2] | - | ± 0.1 | ± 5 | - | ± 20 | μ A |
| I_{OFF} | power-off leakage current | $V_{CC} = 0$ V; V_I or $V_O = 5.5$ V | - | ± 0.1 | ± 10 | - | ± 20 | μ A |
| I_{CC} | supply current | $V_{CC} = 3.6$ V; $V_I = V_{CC}$ or GND; $I_O = 0$ A | - | 0.1 | 20 | - | 80 | μ A |
| ΔI_{CC} | additional supply current | per input pin; $V_{CC} = 2.7$ V to 3.6 V; $V_I = V_{CC} - 0.6$ V; $I_O = 0$ A | - | 5 | 500 | - | 5000 | μ A |
| C_I | input capacitance | $V_{CC} = 0$ V to 3.6 V; $V_I =$ GND to V_{CC} | - | 5.0 | - | - | - | pF |
| I_{BHL} | bus hold LOW current | $V_{CC} = 1.65$; $V_I = 0.58$ V ^{[3][4]} | 10 | - | - | 10 | - | μ A |
| | | $V_{CC} = 2.3$; $V_I = 0.7$ V | 30 | - | - | 25 | - | μ A |
| | | $V_{CC} = 3.0$; $V_I = 0.8$ V | 75 | - | - | 60 | - | μ A |
| I_{BHH} | bus hold HIGH current | $V_{CC} = 1.65$; $V_I = 1.07$ V ^{[3][4]} | -10 | - | - | -10 | - | μ A |
| | | $V_{CC} = 2.3$; $V_I = 1.7$ V | -30 | - | - | -25 | - | μ A |
| | | $V_{CC} = 3.0$; $V_I = 2.0$ V | -75 | - | - | -60 | - | μ A |
| I_{BHLO} | bus hold LOW overdrive current | $V_{CC} = 1.95$ V ^{[3][5]} | 200 | - | - | 200 | - | μ A |
| | | $V_{CC} = 2.7$ V | 300 | - | - | 300 | - | μ A |
| | | $V_{CC} = 3.6$ V | 500 | - | - | 500 | - | μ A |
| I_{BHHO} | bus hold HIGH overdrive current | $V_{CC} = 1.95$ V ^{[3][5]} | -200 | - | - | -200 | - | μ A |
| | | $V_{CC} = 2.7$ V | -300 | - | - | -300 | - | μ A |
| | | $V_{CC} = 3.6$ V | -500 | - | - | -500 | - | μ A |

[1] All typical values are measured at $V_{CC} = 3.3$ V (unless stated otherwise) and $T_{amb} = 25$ °C.

[2] The bus hold circuit is switched off when $V_I > V_{CC}$ allowing 5.5 V on the input pin.

[3] For data inputs only; control inputs do not have a bus hold circuit.

[4] The specified sustaining current at the data inputs do not have a bus hold circuit.

[5] The specified overdrive current at the data input forces the data input to the opposite logic input state.

10. Dynamic characteristics

Table 7. Dynamic characteristics

Voltages are referenced to GND (ground = 0 V). For test circuit see [Figure 9](#).

| Symbol | Parameter | Conditions | T _{amb} = -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit |
|------------------|-------------------|---|-------------------------------------|--------------------|------|-------------------|------|------|
| | | | Min | Typ ^[1] | Max | Min | Max | |
| t _{pd} | propagation delay | nCP to nQn; see Figure 6 ^[2] | | | | | | |
| | | V _{CC} = 1.2 V | - | 14 | - | - | - | ns |
| | | V _{CC} = 1.65 V to 1.95 V | 2.6 | 8.3 | 18.0 | 2.6 | 20.8 | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 1.8 | 4.4 | 8.8 | 1.8 | 10.2 | ns |
| | | V _{CC} = 2.7 V | 1.5 | 4.0 | 7.8 | 1.5 | 10.0 | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | 3.7 | 6.8 | 1.5 | 8.5 | ns |
| t _{en} | enable time | nOE to nQn; see Figure 8 ^[2] | | | | | | |
| | | V _{CC} = 1.2 V | - | 20 | - | - | - | ns |
| | | V _{CC} = 1.65 V to 1.95 V | 1.9 | 7.5 | 17.1 | 1.9 | 19.7 | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 1.5 | 4.2 | 9.0 | 1.5 | 10.3 | ns |
| | | V _{CC} = 2.7 V | 1.5 | 4.5 | 8.3 | 1.5 | 10.0 | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | 3.4 | 6.6 | 1.5 | 8.5 | ns |
| t _{dis} | disable time | nOE to nQn; see Figure 8 ^[2] | | | | | | |
| | | V _{CC} = 1.2 V | - | 12 | - | - | - | ns |
| | | V _{CC} = 1.65 V to 1.95 V | 2.7 | 4.5 | 8.0 | 2.7 | 9.3 | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 1.0 | 2.5 | 4.3 | 1.0 | 5.0 | ns |
| | | V _{CC} = 2.7 V | 1.5 | 3.3 | 4.6 | 1.5 | 6.0 | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | 3.1 | 4.4 | 1.5 | 5.5 | ns |
| t _W | pulse width | nCP HIGH; see Figure 6 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 5.0 | - | - | 5.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 4.0 | - | - | 4.0 | - | ns |
| | | V _{CC} = 2.7 V | 3.0 | - | - | 3.0 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 3.0 | 1.5 | - | 3.0 | - | ns |
| t _{su} | set-up time | nDn to nCP; see Figure 7 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 4.0 | - | - | 4.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 3.0 | - | - | 3.0 | - | ns |
| | | V _{CC} = 2.7 V | 1.9 | - | - | 1.9 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.9 | 0.3 | - | 1.9 | - | ns |
| t _h | hold time | nDn to nCP; see Figure 7 | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 3.0 | - | - | 3.0 | - | ns |
| | | V _{CC} = 2.3 V to 2.7 V | 2.5 | - | - | 2.5 | - | ns |
| | | V _{CC} = 2.7 V | 1.5 | - | - | 1.5 | - | ns |
| | | V _{CC} = 3.0 V to 3.6 V | 1.5 | -0.3 | - | 1.5 | - | ns |


Table 7. Dynamic characteristics ...continued


Voltages are referenced to GND (ground = 0 V). For test circuit see [Figure 9](#).

| Symbol | Parameter | Conditions | T _{amb} = -40 °C to +85 °C | | | -40 °C to +125 °C | | Unit | |
|--------------------|-------------------------------|--|-------------------------------------|--------------------|-----|-------------------|-----|------|----|
| | | | Min | Typ ^[1] | Max | Min | Max | | |
| f _{max} | maximum frequency | see Figure 6 | | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | 100 | - | - | 80 | - | MHz | |
| | | V _{CC} = 2.3 V to 2.7 V | 125 | - | - | 100 | - | MHz | |
| | | V _{CC} = 2.7 V | 150 | - | - | 120 | - | MHz | |
| | | V _{CC} = 3.0 V to 3.6 V | 150 | 330 | - | 120 | - | MHz | |
| t _{sk(o)} | output skew time | V _{CC} = 3.0 V to 3.6 V | ^[3] | - | - | 1.0 | - | 1.5 | ns |
| C _{PD} | power dissipation capacitance | per input; V _I = GND to V _{CC} | ^[4] | | | | | | |
| | | V _{CC} = 1.65 V to 1.95 V | - | 9.6 | - | - | - | - | pF |
| | | V _{CC} = 2.3 V to 2.7 V | - | 11.7 | - | - | - | - | pF |
| | | V _{CC} = 3.0 V to 3.6 V | - | 13.5 | - | - | - | - | pF |

- [1] Typical values are measured at T_{amb} = 25 °C and V_{CC} = 1.2 V, 1.8 V, 2.5 V, 2.7 V and 3.3 V respectively.
- [2] t_{pd} is the same as t_{PLH} and t_{PHL}.
t_{en} is the same as t_{PZL} and t_{PZH}.
t_{dis} is the same as t_{PLZ} and t_{PHZ}.
- [3] Skew between any two outputs of the same package switching in the same direction. This parameter is guaranteed by design.
- [4] C_{PD} is used to determine the dynamic power dissipation (P_D in μW).
P_D = C_{PD} × V_{CC}² × f_i × N + Σ(C_L × V_{CC}² × f_o) where:
f_i = input frequency in MHz; f_o = output frequency in MHz
C_L = output load capacitance in pF
V_{CC} = supply voltage in Volts
N = number of inputs switching
Σ(C_L × V_{CC}² × f_o) = sum of the outputs


11. AC waveforms





Measurement points are given in [Table 8](#).
 V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.
 The shaded areas indicate when the input is permitted to change for predictable output performance.

Fig 7. Data set-up and hold times for the nDn input to the nCP input





Measurement points are given in [Table 8](#).
 V_{OL} and V_{OH} are typical output voltage levels that occur with the output load.

Fig 8. 3-state enable and disable times

Table 8. Measurement points

| Supply voltage | Input | | Output | | |
|------------------|-----------------|-----------------------|-----------------------|--------------------------|--------------------------|
| V _{CC} | V _I | V _M | V _M | V _X | V _Y |
| 1.2 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 1.65 V to 1.95 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 2.3 V to 2.7 V | V _{CC} | 0.5 × V _{CC} | 0.5 × V _{CC} | V _{OL} + 0.15 V | V _{OH} - 0.15 V |
| 2.7 V | 2.7 V | 1.5 V | 1.5 V | V _{OL} + 0.3 V | V _{OH} - 0.3 V |
| 3.0 V to 3.6 V | 2.7 V | 1.5 V | 1.5 V | V _{OL} + 0.3 V | V _{OH} - 0.3 V |



001aae331

Test data is given in [Table 9](#).

Definitions for test circuit:

R_L = Load resistance.

C_L = Load capacitance including jig and probe capacitance.

R_T = Termination resistance should be equal to output impedance Z_o of the pulse generator.

V_{EXT} = External voltage for measuring switching times.

Fig 9. Test circuit for measuring switching times

Table 9. Test data

| Supply voltage | Input | | Load | | V _{EXT} | | |
|------------------|-----------------|---------------------------------|----------------|----------------|-------------------------------------|-------------------------------------|-------------------------------------|
| | V _I | t _r , t _f | C _L | R _L | t _{PLH} , t _{PHL} | t _{PLZ} , t _{PZL} | t _{PHZ} , t _{PZH} |
| 1.2 V | V _{CC} | ≤ 2 ns | 30 pF | 1 kΩ | open | 2 × V _{CC} | GND |
| 1.65 V to 1.95 V | V _{CC} | ≤ 2 ns | 30 pF | 1 kΩ | open | 2 × V _{CC} | GND |
| 2.3 V to 2.7 V | V _{CC} | ≤ 2 ns | 30 pF | 500 Ω | open | 2 × V _{CC} | GND |
| 2.7 V | 2.7 V | ≤ 2.5 ns | 50 pF | 500 Ω | open | 2 × V _{CC} | GND |
| 3.0 V to 3.6 V | 2.7 V | ≤ 2.5 ns | 50 pF | 500 Ω | open | 2 × V _{CC} | GND |

12. Package outline

TSSOP48: plastic thin shrink small outline package; 48 leads; body width 6.1 mm

SOT362-1




Fig 10. Package outline SOT362-1 (TSSOP48)

SSOP48: plastic shrink small outline package; 48 leads; body width 7.5 mm

SOT370-1




Fig 11. Package outline SOT370-1 (SSOP48)

13. Abbreviations

Table 10. Abbreviations

| Acronym | Description |
|---------|-----------------------------|
| CDM | Charged Device Model |
| DUT | Device Under Test |
| ESD | ElectroStatic Discharge |
| HBM | Human Body Model |
| MM | Machine Model |
| TTL | Transistor-Transistor Logic |

14. Revision history

Table 11. Revision history

| Document ID | Release date | Data sheet status | Change notice | Supersedes |
|-----------------------|--|-----------------------|---------------|-----------------------|
| 74LVCH162374A v.4 | 20130122 | Product data sheet | - | 74LVCH162374A v.3 |
| Modifications: | <ul style="list-style-type: none"> The format of this data sheet has been redesigned to comply with the new identity guidelines of NXP Semiconductors. Legal texts have been adapted to the new company name where appropriate. Table 4, Table 5, Table 6, Table 7, Table 8 and Table 9: values added for lower voltage ranges. | | | |
| 74LVCH162374A v.3 | 20040519 | Product specification | - | 74LVC_LVCH162374A v.2 |
| 74LVC_LVCH162374A v.2 | 20040325 | Product specification | - | 74LVC_LVCH162374A v.1 |
| 74LVC_LVCH162374A v.1 | 19990805 | Product specification | - | - |

15. Legal information

15.1 Data sheet status

| Document status ^{[1][2]} | Product status ^[3] | Definition |
|-----------------------------------|-------------------------------|---|
| Objective [short] data sheet | Development | This document contains data from the objective specification for product development. |
| Preliminary [short] data sheet | Qualification | This document contains data from the preliminary specification. |
| Product [short] data sheet | Production | This document contains the product specification. |

[1] Please consult the most recently issued document before initiating or completing a design.

[2] The term 'short data sheet' is explained in section "Definitions".

[3] The product status of device(s) described in this document may have changed since this document was published and may differ in case of multiple devices. The latest product status information is available on the Internet at URL <http://www.nexperia.com>.

15.2 Definitions

Draft — The document is a draft version only. The content is still under internal review and subject to formal approval, which may result in modifications or additions. Nexperia does not give any representations or warranties as to the accuracy or completeness of information included herein and shall have no liability for the consequences of use of such information.

Short data sheet — A short data sheet is an extract from a full data sheet with the same product type number(s) and title. A short data sheet is intended for quick reference only and should not be relied upon to contain detailed and full information. For detailed and full information see the relevant full data sheet, which is available on request via the local Nexperia sales office. In case of any inconsistency or conflict with the short data sheet, the full data sheet shall prevail.

Product specification — The information and data provided in a Product data sheet shall define the specification of the product as agreed between Nexperia and its customer, unless Nexperia and customer have explicitly agreed otherwise in writing. In no event however, shall an agreement be valid in which the Nexperia product is deemed to offer functions and qualities beyond those described in the Product data sheet.

15.3 Disclaimers

Limited warranty and liability — Information in this document is believed to be accurate and reliable. However, Nexperia does not give any representations or warranties, expressed or implied, as to the accuracy or completeness of such information and shall have no liability for the consequences of use of such information. Nexperia takes no responsibility for the content in this document if provided by an information source outside of Nexperia.

In no event shall Nexperia be liable for any indirect, incidental, punitive, special or consequential damages (including - without limitation - lost profits, lost savings, business interruption, costs related to the removal or replacement of any products or rework charges) whether or not such damages are based on tort (including negligence), warranty, breach of contract or any other legal theory.

Notwithstanding any damages that customer might incur for any reason whatsoever, Nexperia's aggregate and cumulative liability towards customer for the products described herein shall be limited in accordance with the *Terms and conditions of commercial sale* of Nexperia.

Right to make changes — Nexperia reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.

Suitability for use — Nexperia products are not designed, authorized or warranted to be suitable for use in life support, life-critical or safety-critical systems or equipment, nor in applications where failure or malfunction of a Nexperia product can reasonably be expected to result in personal injury, death or severe property or environmental damage. Nexperia and its suppliers accept no liability for inclusion and/or use of Nexperia products in such equipment or applications and therefore such inclusion and/or use is at the customer's own risk.

Applications — Applications that are described herein for any of these products are for illustrative purposes only. Nexperia makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.

Customers are responsible for the design and operation of their applications and products using Nexperia products, and Nexperia accepts no liability for any assistance with applications or customer product design. It is customer's sole responsibility to determine whether the Nexperia product is suitable and fit for the customer's applications and products planned, as well as for the planned application and use of customer's third party customer(s). Customers should provide appropriate design and operating safeguards to minimize the risks associated with their applications and products.

Nexperia does not accept any liability related to any default, damage, costs or problem which is based on any weakness or default in the customer's applications or products, or the application or use by customer's third party customer(s). Customer is responsible for doing all necessary testing for the customer's applications and products using Nexperia products in order to avoid a default of the applications and the products or of the application or use by customer's third party customer(s). Nexperia does not accept any liability in this respect.

Limiting values — Stress above one or more limiting values (as defined in the Absolute Maximum Ratings System of IEC 60134) will cause permanent damage to the device. Limiting values are stress ratings only and (proper) operation of the device at these or any other conditions above those given in the Recommended operating conditions section (if present) or the Characteristics sections of this document is not warranted. Constant or repeated exposure to limiting values will permanently and irreversibly affect the quality and reliability of the device.

Terms and conditions of commercial sale — Nexperia products are sold subject to the general terms and conditions of commercial sale, as published at <http://www.nexperia.com/profile/terms>, unless otherwise agreed in a valid written individual agreement. In case an individual agreement is concluded only the terms and conditions of the respective agreement shall apply. Nexperia hereby expressly objects to applying the customer's general terms and conditions with regard to the purchase of Nexperia products by customer.

No offer to sell or license — Nothing in this document may be interpreted or construed as an offer to sell products that is open for acceptance or the grant, conveyance or implication of any license under any copyrights, patents or other industrial or intellectual property rights.

Export control — This document as well as the item(s) described herein may be subject to export control regulations. Export might require a prior authorization from competent authorities.

Non-automotive qualified products — Unless this data sheet expressly states that this specific Nexperia product is automotive qualified, the product is not suitable for automotive use. It is neither qualified nor tested in accordance with automotive testing or application requirements. Nexperia accepts no liability for inclusion and/or use of non-automotive qualified products in automotive equipment or applications.

In the event that customer uses the product for design-in and use in automotive applications to automotive specifications and standards, customer (a) shall use the product without Nexperia's warranty of the product for such automotive applications, use and specifications, and (b) whenever customer uses the product for automotive applications beyond

Nexperia's specifications such use shall be solely at customer's own risk, and (c) customer fully indemnifies Nexperia for any liability, damages or failed product claims resulting from customer design and use of the product for automotive applications beyond Nexperia's standard warranty and Nexperia's product specifications.

Translations — A non-English (translated) version of a document is for reference only. The English version shall prevail in case of any discrepancy between the translated and English versions.

15.4 Trademarks

Notice: All referenced brands, product names, service names and trademarks are the property of their respective owners.

16. Contact information

For more information, please visit: <http://www.nexperia.com>

For sales office addresses, please send an email to: salesaddresses@nexperia.com

17. Contents

| | | |
|-----------|---|-----------|
| 1 | General description | 1 |
| 2 | Features and benefits | 1 |
| 3 | Ordering information | 2 |
| 4 | Functional diagram | 2 |
| 5 | Pinning information | 4 |
| 5.1 | Pinning | 4 |
| 5.2 | Pin description | 4 |
| 6 | Functional description | 5 |
| 7 | Limiting values | 5 |
| 8 | Recommended operating conditions | 6 |
| 9 | Static characteristics | 6 |
| 10 | Dynamic characteristics | 8 |
| 11 | AC waveforms | 9 |
| 12 | Package outline | 12 |
| 13 | Abbreviations | 14 |
| 14 | Revision history | 14 |
| 15 | Legal information | 15 |
| 15.1 | Data sheet status | 15 |
| 15.2 | Definitions | 15 |
| 15.3 | Disclaimers | 15 |
| 15.4 | Trademarks | 16 |
| 16 | Contact information | 16 |
| 17 | Contents | 17 |

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru