HLMP-LG71, HLMP-LM71, HLMP-LB71

Red, Green and Blue 4 mm Standard Oval LEDs



Data Sheet



Description

These Precision Optical Performance Oval LEDs are specifically designed for full color/video and passenger information signs. The oval shaped radiation pattern and high luminous intensity ensure that these devices are excellent for wide field of view outdoor applications where a wide viewing angle and readability in sunlight are essential. The package epoxy contains UV inhibitors to reduce the effects of long term exposure to direct sunlight.

Applications


- Billboard signs
- Full color signs

Features

- Well defined spatial radiation pattern
- High brightness material
- Available in red, green and blue color.
 - Red AllnGaP 626 nm
 - Green InGaN 525 nm
 - Blue InGaN 470 nm
- Superior resistance to moisture
- Standoff Package
- Tinted and diffused
- Typical viewing angle 40° x 100°

CAUTION: In GaN devices are Class 1C HBM ESD sensitive per JEDEC Standard. Please observe appropriate precautions during handling and processing. Refer to Application Note AN-1142 for additional details.

Package Dimensions



Notes:

All dimensions in millimeters (inches).

Tolerance is \pm 0.20 mm unless other specified


Device Selection Guide

Part Number	Color and Dominant Wavelength λ_d (nm) Typ $^{[3]}$	Luminous Intensity Iv (mcd) at 20 mA ^[1,2,4]	Luminous Intensity Iv (mcd) at 20 mA [1,2,4]
HLMP-LG71-VY0DD	Red 626	1150	2400
HLMP-LM71-Z30DD	Green 525	2400	5040
HLMP-LB71-SV0DD	Blue 470	660	1380

Notes:

- 1. The luminous intensity is measured on the mechanical axis of the lamp package and it is tested with pulsing condition.
- 2. The optical axis is closely aligned with the package mechanical axis.
- 3. Dominant wavelength, λ_d , is derived from the CIE Chromaticity Diagram and represents the color of the lamp.
- 4. Tolerance for each bin limit is \pm 15%.

Part Numbering System



Note: Please refer to AB 5337 for complete information about part numbering system.

Absolute Maximum Ratings

 $T_A = 25^{\circ} C$

Parameter	Red	Green/ Blue	Unit
DC Forward Current [1]	50	30	mA
Peak Forward Current	100 [2]	100 [3]	mA
Power Dissipation	120	110	mW
LED Junction Temperature	130	110	°C
Operating Temperature Range	-40 to +100	-40 to +85	°C
Storage Temperature Range	-	-40 to +100	°C

Notes:

- 1. Derate linearly as shown in Figures 4 and 8.
- 2. Duty Factor 30%, frequency 1 kHz.
- 3. Duty Factor 10%, frequency 1 kHz.

Electrical / Optical Characteristics

 $T_A = 25^{\circ} C$

Parameter	Symbol	Min.	Тур.	Max.	Units	Test Conditions
Forward Voltage	V _F				V	I _F = 20 mA
Red		1.8	2.1	2.4		
Green		2.8	3.1	3.6		
Blue		2.8	3.1	3.6		
Reverse Voltage [1]	V_{R}				V	
Red		5				$I_R = 100 \mu A$
Green and Blue		5				$I_R = 10 \mu A$
Dominant Wavelength [2]					nm	I _F = 20 mA
Red		618	626	630		
Green		520	525	540		
Blue		460	470	480		
Peak Wavelength	λ_{PEAK}				nm	Peak of Wavelength of Spectral
Red			634			Distribution at $I_F = 20 \text{ mA}$
Green			517			
Blue			461			
Thermal Resistance	$R\theta_{J-PIN}$		240		°C/W	LED Junction-to-Pin
Luminous Efficacy [3]	ην				lm/W	Emitted Luminous Power/
Red	1*		190			Emitted Radiant Power
Green			475			
Blue			68			
Luminous Efficiency [4]	$\eta_{ m e}$				lm/W	Luminous Flux/Electrical Power
Red	10		50			
Green			60			
Blue			13			

Notes:

- 1. Indicates product final testing condition, long term reverse bias is not recommended.
- 2. The dominant wavelength is derived from the chromaticity Diagram and represents the color of the lamp.
- 3. The radiant intensity, I_e in watts per steradian, may be found from the equation $I_e = I_V/\eta_V$ where I_V is the luminous intensity in candelas and η_V is the luminous efficacy in lumens/watt.
- 4. $\eta_e = \phi_V / I_F \times V_F$, where ϕ_V is the emitted luminous flux, I_F is electrical forward current and V_F is the forward voltage.

AlinGaP Red




Figure 1. Relative Intensity vs Wavelength




Figure 2. Forward Current vs Forward Voltage




Figure 3. Relative Intensity vs Forward Current




Figure 4. Maximum Forward Current vs Ambient Temperature

InGaN Blue and Green




Figure 5. Relative Intensity vs Wavelength




Figure 7. Relative Intensity vs Forward Current




Figure 9. Relative dominant wavelength vs Forward Current




Figure 6. Forward Current vs Forward Voltage




Figure 8. Maximum Forward Current vs Ambient Temperature




Figure 10. Radiation pattern-Major Axis




Figure 11. Radiation pattern-Minor Axis




Figure 13. Forward Voltage Shift vs Junction Temperature

Intensity Bin Limit Table (1.2: 1 lv Bin Ratio)

	Intensity (mc	Intensity (mcd) at 20 mA				
Bin	Min	Max				
S	660	800				
Т	800	960				
U	960	1150				
V	1150	1380				
W	1380	1660				
Χ	1660	1990				
Υ	1990	2400				
Z	2400	2900				
1	2900	3500				
2	3500	4200				
3	4200	5040				

Tolerance for each bin limit is ±15%

Figure 12. Relative Light Output vs Junction Temperature

V_F Bin Table (V at 20 mA)

Bin ID	Min	Max	
VD	1.8	2.0	
VA	2.0	2.2	
VB	2.2	2.4	

Notes:

- 1. Tolerance for each bin limit is $\pm 0.05 \, V$
- 2. V_F binning only applicable to Red color.

Red Color Range

Min Dom	Max Dom	Chromaticity Coordinate				
618.0	630.0	Х	0.6872	0.3126	0.6890	0.2943
		У	0.6690	0.3149	0.7080	0.2920

Tolerance for each bin limit is $\pm\,0.5~\text{nm}$

Green Color Bin Table

Bin	Min Dom	Max Dom	Xmin	Ymin	Xmax	Ymax
1	520.0	524.0	0.0743	0.8338	0.1856	0.6556
			0.1650	0.6586	0.1060	0.8292
2	524.0	528.0	0.1060	0.8292	0.2068	0.6463
			0.1856	0.6556	0.1387	0.8148
3	528.0	532.0	0.1387	0.8148	0.2273	0.6344
			0.2068	0.6463	0.1702	0.7965
4	532.0	536.0	0.1702	0.7965	0.2469	0.6213
			0.2273	0.6344	0.2003	0.7764
5	536.0	540.0	0.2003	0.7764	0.2659	0.6070
			0.2469	0.6213	0.2296	0.7543

Tolerance for each bin limit is $\pm\,0.5~\text{nm}$

Blue Color Bin Table


Bin	Min Dom	Max Dom	Xmin	Ymin	Xmax	Ymax
1	460.0	464.0	0.1440	0.0297	0.1766	0.0966
			0.1818	0.0904	0.1374	0.0374
2	464.0	468.0	0.1374	0.0374	0.1699	0.1062
			0.1766	0.0966	0.1291	0.0495
3	468.0	472.0	0.1291	0.0495	0.1616	0.1209
			0.1699	0.1062	0.1187	0.0671
4	472.0	476.0	0.1187	0.0671	0.1517	0.1423
			0.1616	0.1209	0.1063	0.0945
5	476.0	480.0	0.1063	0.0945	0.1397	0.1728
			0.1517	0.1423	0.0913	0.1327

Tolerance for each bin limit is \pm 0.5 nm

Note:

1. All bin categories are established for classification of products. Products may not be available in all bin categories. Please contact your Avago representative for further information.

Avago Color Bin on CIE 1931 Chromaticity Diagram




Precautions:

Lead Forming:

- The leads of an LED lamp may be preformed or cut to length prior to insertion and soldering on PC board.
- For better control, it is recommended to use proper tool to precisely form and cut the leads to applicable length rather than doing it manually.
- If manual lead cutting is necessary, cut the leads after the soldering process. The solder connection forms a mechanical ground which prevents mechanical stress due to lead cutting from traveling into LED package. This is highly recommended for hand solder operation, as the excess lead length also acts as small heat sink.

Soldering and Handling:

- Care must be taken during PCB assembly and soldering process to prevent damage to the LED component.
- LED component may be effectively hand soldered to PCB. However, it is only recommended under unavoidable circumstances such as rework. The closest manual soldering distance of the soldering heat source (soldering iron's tip) to the body is 1.59 mm. Soldering the LED using soldering iron tip closer than 1.59 mm might damage the LED.



- ESD precaution must be properly applied on the soldering station and personnel to prevent ESD damage to the LED component that is ESD sensitive. Do refer to Avago application note AN 1142 for details. The soldering iron used should have grounded tip to ensure electrostatic charge is properly grounded.
- Recommended soldering condition:

	Wave Soldering ^[1, 2]	Manual Solder Dipping
Pre-heat temperature	105° C Max.	-
Preheat time	60 sec Max	-
Peak temperature	260° C Max.	260° C Max.
Dwell time	5 sec Max.	5 sec Max


Note:

- Above conditions refers to measurement with thermocouple mounted at the bottom of PCB.
- 2. It is recommended to use only bottom preheaters in order to reduce thermal stress experienced by LED.
- Wave soldering parameters must be set and maintained according to the recommended temperature and dwell time. Customer is advised to perform daily check on the soldering profile to ensure that it is always conforming to recommended soldering conditions.

Note:

- PCB with different size and design (component density) will have different heat mass (heat capacity). This might cause a change in temperature experienced by the board if same wave soldering setting is used. So, it is recommended to re-calibrate the soldering profile again before loading a new type of PCB.
- 2. Avago Technologies' AllnGaP high brightness LED are using high efficiency LED die with single wire bond as shown below. Customer is advised to take extra precaution during wave soldering to ensure that the maximum wave temperature does not exceed 260° C and the solder contact time does not exceeding 5 sec. Over-stressing the LED during soldering process might cause premature failure to the LED due to delamination.

Avago Technologies LED configuration




- Any alignment fixture that is being applied during wave soldering should be loosely fitted and should not apply weight or force on LED. Non metal material is recommended as it will absorb less heat during wave soldering process.
- At elevated temperature, LED is more susceptible to mechanical stress. Therefore, PCB must allowed to cool down to room temperature prior to handling, which includes removal of alignment fixture or pallet.
- If PCB board contains both through hole (TH) LED and other surface mount components, it is recommended that surface mount components be soldered on the top side of the PCB. If surface mount need to be on the bottom side, these components should be soldered using reflow soldering prior to insertion the TH LED.
- Recommended PC board plated through holes (PTH) size for LED component leads.

LED component lead size	Diagonal	Plated through hole diameter
0.45 x 0.45 mm	0.636 mm	0.98 to 1.08 mm
(0.018x 0.018 inch)	(0.025 inch)	(0.039 to 0.043 inch)
0.50 x 0.50 mm	0.707 mm	1.05 to 1.15 mm
(0.020x 0.020 inch)	(0.028 inch)	(0.041 to 0.045 inch)

• Over-sizing the PTH can lead to twisted LED after clinching. On the other hand under sizing the PTH can cause difficulty inserting the TH LED.

Refer to application note AN5334 for more information about soldering and handling of high brightness TH LED lamps.

Example of Wave Soldering Temperature Profile for TH LED



Recommended solder: Sn63 (Leaded solder alloy) SAC305 (Lead free solder alloy)


Flux: Rosin flux

Solder bath temperature: 255° C \pm 5° C (maximum peak temperature = 260° C)


Dwell time: 3.0 sec - 5.0 sec (maximum = 5 sec)

Note: Allow for board to be sufficiently cooled to room temperature before exerting mechanical force.

Ammo Packs Drawing



Packaging Box for Ammo Packs



Note: For InGaN device, the ammo pack packaging box contain ESD logo

Packaging Label

(i) Avago Mother Label: (Available on packaging box of ammo pack and shipping box)



(ii) Avago Baby Label (Only available on bulk packaging)



Acronyms and Definition:

BIN:

(i) Color bin only or VF bin only(Applicable for part number with color bins but without VF bin OR part number with VF bins and no color bin)

OR

(ii) Color bin incorporated with VF Bin(Applicable for part number that have both color bin and VF bin)

Example:

(i) Color bin only or VF bin onlyBIN: 2 (represent color bin 2 only)BIN: VB (represent VF bin "VB" only)

(ii) Color bin incorporate with VF Bin



DISCLAIMER: Avago's products and software are not specifically designed, manufactured or authorized for sale as parts, components or assemblies for the planning, construction, maintenenace or direct operation of a nuclear facility or for use in medical devices or applications. Customer is solely responsible, and waives all rights to make claims against avago or its suppliers, for all loss, damage, expense or liability in connection with such use.

For product information and a complete list of distributors, please go to our web site: www.avagotech.com





OOO «ЛайфЭлектроникс" "LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 P/C 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 3010181090000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный) Email: org@lifeelectronics.ru