Is Now Part of

ON Semiconductor®

To learn more about ON Semiconductor, please visit our website at
www.onsemi.com

Please note: As part of the Fairchild Semiconductor integration, some of the Fairchild orderable part numbers will need to change in order to meet ON Semiconductor's system requirements. Since the ON Semiconductor product management systems do not have the ability to manage part nomenclature that utilizes an underscore (_), the underscore (_) in the Fairchild part numbers will be changed to a dash (-). This document may contain device numbers with an underscore (_). Please check the ON Semiconductor website to verify the updated device numbers. The most current and up-to-date ordering information can be found at www.onsemi.com. Please email any questions regarding the system integration to Fairchild_questions@onsemi.com.

ON Semiconductor and the ON Semiconductor logo are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent-Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

June 2014

NC7SV126
TinyLogic® ULP-A Buffer with Three-State Output

Features

- 0.9 V to 3.6 V V_{CC} Supply Operation
- 3.6 V Over-Voltage Tolerant I/O's at V_{CC} from 0.9 V to 3.6 V
- Extremely High Speed t_{PD}
  - 1.0 ns: Typical for 2.7 V to 3.6 V V_{CC}
  - 1.8 ns: Typical for 2.3 V to 2.7 V V_{CC}
  - 3.0 ns: Typical for 1.65 V to 1.95 V V_{CC}
  - 3.5 ns: Typical for 1.4 V to 1.6 V V_{CC}
  - 6.0 ns: Typical for 1.1 V to 1.3 V V_{CC}
  - 13.0 ns:Typical for 0.9 V V_{CC}
- Power-Off High-Impedance Inputs and Outputs
- High Static Drive (I_{OH}/I_{OL})
  - ±24 mA at 3.00 V V_{CC}
  - ±18 mA at 2.30 V V_{CC}
  - ±6 mA at 1.65 V V_{CC}
  - ±4 mA at 1.4V V_{CC}
  - ±2 mA at 1.1 V V_{CC}
  - ±0.1 mA at 0.9 V V_{CC}
- Uses Proprietary Quiet Series™ Noise/EMI Reduction Circuitry
- Ultra-Small MicroPak™ Leadfree Package
- Ultra-Low Dynamic Power

Description

The NC7SV126 is a single buffer with 3-STATE output from Fairchild's Ultra-Low Power-A (ULP-A) Series of TinyLogic®. ULP-A is ideal for applications that require extreme high speed, high drive, and low power. This product is designed for a wide low-voltage operating range (0.9 V to 3.6 V V_{CC}) and applications that require more drive and speed than the TinyLogic® ULP series, but still offer best in class low power operation.

The NC7SV126 is uniquely designed for optimized power and speed, and is fabricated with an advanced CMOS technology to achieve high-speed operation while maintaining low CMOS power dissipation.

Ordering Information

Part Number	Top Mark	Package	Packing Method
NC7SV126P5X	V26	5-Lead SC70, EIAJ SC-88a, 1.25 mm Wide	3000 Units on Tape & Reel
NC7SV126L6X	H7	6-Lead MicroPak™, 1.00 mm Wide	5000 Units on Tape & Reel

For Fairchild's definition of "green" Eco Status, please visit: http://www.fairchildsemi.com/company/green/rohs_green.html.

TinyLogic® is a registered trademark of Fairchild Semiconductor Corporation.
MicroPak™ and Quiet Series™ are trademarks of Fairchild Semiconductor Corporation.

Battery Life



Notes:

1. TinyLogic® ULP and ULP-A with up to 50% less power consumption can extend your battery life significantly.
   Battery Life = $(V_{battery} \bullet I_{battery} \bullet .9)/(P_{device})/24hrs/day$
   Where, $P_{device} = (I_{CC} \bullet V_{CC}) + (C_{PD} + C_L) \bullet V_{CC2} \bullet f$.
2. Assumes ideal 3.6 V Lithium Ion battery with current rating of 900 mAH and derated 90% and device frequency at 10 MHz, with C_L = 15 pF load.

Figure 1. Battery Life vs. V_{CC} Supply Voltage

Connection Diagram



Figure 2. Logic Symbol

Pin Configurations



Figure 3. SC70 (Top View)



Figure 4. MicroPak (Top Through View)

Pin Definitions

Pin # SC70	Pin # MicroPak	Name	Description
1	1	OE	Input
2	2	A	Input
3	3	GND	Ground
4	4	Y	Output
5	6	V_{CC}	Supply Voltage
	5	NC	No Connect

Function Table

Inputs		Output
OE	**A**	**Out Y**
H	L	L
H	H	H
L	X	Z

H = HIGH Logic Level
L = LOW Logic Level
X = HIGH or LOW Logic Level
Z = HIGH Impedance State

© 1996 Fairchild Semiconductor Corporation

Absolute Maximum Ratings

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only.

Symbol	Parameter		Min.	Max.	Unit
V_{CC}	Supply Voltage		-0.5	4.6	V
V_{IN}	DC Input Voltage		-0.5	4.6	V
V_{OUT}	DC Output Voltage	HIGH or LOW State[3]	-0.5	V_{CC} + 0.5	V
		V_{CC} = 0 V	-0.5	4.6	
I_{IK}	DC Input Diode Current	V_{IN} < 0 V		-50	mA
I_{OK}	DC Output Diode Current	V_{OUT} < 0 V		-50	mA
		V_{OUT} > V_{CC}		+50	
I_{OH}/I_{OL}	DC Output Source/Sink Current			±50	mA
I_{CC} or I_{GND}	DC V_{CC} or Ground Current per Supply Pin			±50	mA
T_{STG}	Storage Temperature Range		-65	+150	°C
P_D	Power Dissipation at +85°C	SC70-5		150	mW
		MicroPak-6		130	
ESD	Human Body Model, JEDEC:JESD22-A114			4000	V
	Charge Device Model, JEDEC:JESD22-C101			2000	

Note:

3. IO absolute maximum rating must be observed.

Recommended Operating Conditions

The Recommended Operating Conditions table defines the conditions for actual device operation. Recommended operating conditions are specified to ensure optimal performance to the datasheet specifications. Fairchild does not recommend exceeding them or designing to Absolute Maximum Ratings.

Symbol	Parameter	Conditions	Min.	Max.	Unit
V_{CC}	Supply Voltage Operating		0.9	3.6	V
V_{IN}	Input Voltage		0	3.6	V
V_{OUT}	Output Voltage	V_{CC} = 0 V	0	3.6	V
		HIGH or LOW State	0	V_{CC}	
I_{OH}/I_{OL}	Output Current	V_{CC} = 3.0 V to 3.6 V		±24	mA
		V_{CC} = 2.3 V to 3.6 V		±18	
		V_{CC} = 1.65 V to 1.95 V		±6	
		V_{CC} = 1.4 V to 1.6 V		±4	
		V_{CC} = 1.1 V to 1.3 V		±2	
		V_{CC} = 0.9 V		±0.1	
T_A	Operating Temperature, Free Air		-40	+85	°C
$\Delta t/\Delta V$	Minimum Input Edge Rate	V_{IN} = 0.8 V to 2.0, V_{CC} = 3.0 V		10	ns/V
θ_{JA}	Thermal Resistance	SC70-5		425	°C/W
		MicroPak-6		500	

Note:

4. Unused inputs must be held HIGH or LOW. They may not float.

© 1996 Fairchild Semiconductor Corporation

DC Electrical Characteristics

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C		T_A=-40 to 85°C		Units
				Min.	Max.	Min.	Max.	
V_{IH}	HIGH Level Input Voltage	0.90		.65 x V_{CC}		.65 x V_{CC}		V
		1.10 ≤ V_{CC} ≤ 1.30		.65 x V_{CC}		.65 x V_{CC}		
		1.40 ≤ V_{CC} ≤ 1.60		.65 x V_{CC}		.65 x V_{CC}		
		1.65 ≤ V_{CC} ≤ 1.95		.65 x V_{CC}		.65 x V_{CC}		
		2.30 ≤ V_{CC} ≤ 2.70		1.6		1.6		
		2.70 ≤ V_{CC} ≤ 3.60		2.0		2.0		
V_{IL}	LOW Level Input Voltage	0.90			.35 x V_{CC}		.35 x V_{CC}	V
		1.10 ≤ V_{CC} ≤ 1.30			.35 x V_{CC}		.35 x V_{CC}	
		1.40 ≤ V_{CC} ≤ 1.60			.35 x V_{CC}		.35 x V_{CC}	
		1.65 ≤ V_{CC} ≤ 1.95			.35 x V_{CC}		.35 x V_{CC}	
		2.30 ≤ V_{CC} ≤ 2.70			0.7		0.7	
		2.70 ≤ V_{CC} ≤ 3.60			0.8		0.8	
V_{OH}	HIGH Level Output Voltage	0.90	I_{OH}=-100 µA	V_{CC}-0.1		V_{CC}-0.1		V
		1.10 ≤ V_{CC} ≤ 1.30		V_{CC}-0.1		V_{CC}-0.1		
		1.40 ≤ V_{CC} ≤ 1.60		V_{CC}-0.2		V_{CC}-0.2		
		1.65 ≤ V_{CC} ≤ 1.95		V_{CC}-0.2		V_{CC}-0.2		
		2.30 ≤ V_{CC} ≤ 2.70		V_{CC}-0.2		V_{CC}-0.2		
		2.70 ≤ V_{CC} ≤ 3.60		V_{CC}-0.2		V_{CC}-0.2		
		1.10 ≤ V_{CC} ≤ 1.30	I_{OH}=-2 mA	.75 x V_{CC}		.75 x V_{CC}		
		1.40 ≤ V_{CC} ≤ 1.60	I_{OH}=-4 mA	.75 x V_{CC}		.75 x V_{CC}		
		1.65 ≤ V_{CC} ≤ 1.95	I_{OH}=-6 mA	1.25		1.25		
		2.30 ≤ V_{CC} ≤ 2.70		2.0		2.0		
		2.30 ≤ V_{CC} ≤ 2.70	I_{OH}=-12 mA	1.8		1.8		
		2.70≤ V_{CC} ≤ 3.60		2.2		2.2		
		2.30 ≤ V_{CC} ≤ 2.70	I_{OH}=-18 mA	1.7		1.7		
		2.70 ≤ V_{CC} ≤ 3.60		2.4		2.4		
		2.70 ≤ V_{CC} ≤ 3.60	I_{OH}=-24 mA	2.2		2.2		

Continued on following page…

© 1996 Fairchild Semiconductor Corporation

DC Electrical Characteristics (Continued)

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C		T_A=-40 to 85°C		Units
				Min.	Max.	Min.	Max.	
V_{OL}	LOW Level Output Voltage	0.90	I_{OL}=100 µA		0.1		0.1	V
		1.10 ≤ V_{CC} ≤ 1.30			0.1		0.1	
		1.40 ≤ V_{CC} ≤ 1.60			0.2		0.2	
		1.65 ≤ V_{CC} ≤ 1.95			0.2		0.2	
		2.30 ≤ V_{CC} ≤ 2.70			0.2		0.2	
		2.70 ≤ V_{CC} ≤ 3.60			0.2		0.2	
		1.10 ≤ V_{CC} ≤ 1.30	I_{OL}=2 mA		0.25 x V_{CC}		0.25 x V_{CC}	
		1.40 ≤ V_{CC} ≤ 1.60	I_{OL}=4 mA		0.25 x V_{CC}		0.25 x V_{CC}	
		1.65 ≤ V_{CC} ≤ 1.95	I_{OL}=6 mA		0.3		0.3	
		2.30 ≤ V_{CC} ≤ 2.70	I_{OL}=12 mA		0.4		0.4	
		2.70 ≤ V_{CC} ≤ 3.60			0.4		0.4	
		2.30≤ V_{CC} ≤ 2.70	I_{OL}=18 mA		0.6		0.6	
		2.70 ≤ V_{CC} ≤ 3.60			0.4		0.4	
		2.70 ≤ V_{CC} ≤ 3.60	I_{OL}=24 mA		0.55		0.55	
I_{IN}	Input Leakage Current	0.90 to 3.60	0 ≤ V_{IN} ≤ 3.60		±0.1		±0.5	µA
I_{OZ}	3-STATE Output Leakage	0.90 to 3.6	V_{IN}=V_{IH} or V_{IL} 0 ≤ V_{IN} ≤ 3.60		±0.5		±0.5	µA
I_{OFF}	Power Off	0	0 ≤ ($V_{IN,}$ v_o) ≤ 3.60		0.5		0.5	µA
I_{CC}	Quiescent Supply Current	0.90 to 3.60	V_{IN}=V_{CC}, or GND		0.9		0.9	µA
			V_{CC} ≤ V_{IN} ≤ 3.6 V				±0.9	

© 1996 Fairchild Semiconductor Corporation

AC Electrical Characteristics

Symbol	Parameter	V_{CC}	Conditions	T_A=25°C			T_A=-40 to 85°C		Units	Figure
				Min.	Typ.	Max.	Min.	Max.		
t_{PHL}, t_{PLH}	Propagation Delay	0.90	C_L=15 pF, R_L=1 MΩ		13				ns	Figure 5 Figure 6
		1.10 ≤ V_{CC} ≤ 1.30	C_L=15 pF, R_L=2 kΩ	3.0	6.0	9.8	1.9	14.9		
		1.40 ≤ V_{CC} ≤ 1.60		1.0	3.5	5.3	0.8	5.7		
		1.65 ≤ V_{CC} ≤ 1.95	C_L=30 pF, R_L=500 Ω	0.9	3.0	4.3	0.8	4.6		
		2.30 ≤ V_{CC} ≤ 2.60		0.8	1.8	2.8	0.7	3.0		
		2.70 ≤ V_{CC} ≤ 3.60		0.5	1.0	2.6	0.3	2.8		
t_{PZL},t_{PZH}	Output Enable Time	0.90	C_L=30 pF, R_U=1 kΩ R_D=1 kΩ		12				ns	
		1.10 ≤ V_{CC} ≤ 1.30		3.0	6.0	9.7	2.0	16.4	ns	Figure 5 Figure 6
		1.40 ≤ V_{CC} ≤ 1.60		1.2	4.0	6.0	1.0	7.5		
		1.65 ≤ V_{CC} ≤ 1.95		1.0	3.0	4.5	0.9	5.0		
		2.30 ≤ V_{CC} ≤ 2.60		0.8	2.0	3.0	0.7	3.4		
		2.70 ≤ V_{CC} ≤ 3.60		0.5	1.2	2.6	0.4	2.9		
t_{PHZ},t_{PLZ}	Output Disable Time	0.90	C_L=30 pF, R_U=1 kΩ R_D=1 kΩ		14				ns	Figure 5 Figure 6
		1.10 ≤ V_{CC} ≤ 1.30		2.0	5.0	9.5	2.0	14.0		
		1.40 ≤ V_{CC} ≤ 1.60		1.2	3.0	5.5	1.1	7.0		
		1.65 ≤ V_{CC} ≤ 1.95		1.0	2.0	5.6	0.8	5.8		
		2.30 ≤ V_{CC} ≤ 2.60		0.6	1.3	4.2	0.5	5.0		
		2.70 ≤ V_{CC} ≤ 3.60		0.5	1.0	3.9	0.4	4.2		
C_{IN}	Input Capacitance	0.00			2				pF	
C_{OUT}	Output Capacitance	0.00			4.5				pF	
C_{PD}	Power Dissipation Capacitance	0.90 to 3.60	V_I=0 V or V_{CC}, f=10 MHz		10				pF	

© 1996 Fairchild Semiconductor Corporation

AC Loadings and Waveforms



Figure 5. AC Test Circuit



Figure 6. AC Waveforms

Physical Dimensions



Figure 7. 5-Lead, SC70, EIAJ SC-88a, 1.25 mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

Tape and Reel Specification

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications:
http://www.fairchildsemi.com/products/analog/pdf/sc70-5_tr.pdf.

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
P5X	Leader (Start End)	125 (Typical)	Empty	Sealed
	Carrier	3000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

© 1996 Fairchild Semiconductor Corporation

Physical Dimensions



Notes:

1. CONFORMS TO JEDEC STANDARD M0-252 VARIATION UAAD
2. DIMENSIONS ARE IN MILLIMETERS
3. DRAWING CONFORMS TO ASME Y14.5M-1994

MAC06AREVC

Figure 8. 6-Lead, MicroPak™, 1.0mm Wide

Package drawings are provided as a service to customers considering Fairchild components. Drawings may change in any manner without notice. Please note the revision and/or date on the drawing and contact a Fairchild Semiconductor representative to verify or obtain the most recent revision. Package specifications do not expand the terms of Fairchild's worldwide terms and conditions, specifically the warranty therein, which covers Fairchild products.

Always visit Fairchild Semiconductor's online packaging area for the most recent package drawings:
http://www.fairchildsemi.com/packaging/.

Tape and Reel Specification

Please visit Fairchild Semiconductor's online packaging area for the most recent tape and reel specifications:
http://www.fairchildsemi.com/products/logic/pdf/micropak_tr.pdf.

Package Designator	Tape Section	Cavity Number	Cavity Status	Cover Type Status
L6X	Leader (Start End)	125 (Typical)	Empty	Sealed
	Carrier	5000	Filled	Sealed
	Trailer (Hub End)	75 (Typical)	Empty	Sealed

© 1996 Fairchild Semiconductor Corporation

TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™
AX-CAP®*
BitSiC™
Build it Now™
CorePLUS™
CorePOWER™
CROSSVOLT™
CTL™
Current Transfer Logic™
DEUXPEED®
Dual Cool™
EcoSPARK®
EfficientMax™
ESBC™
Fairchild®
Fairchild Semiconductor®
FACT Quiet Series™
FACT®
FAST®
FastvCore™
FETBench™
FPS™
F-PFS™
FRFET®
Global Power Resource℠
GreenBridge™
Green FPS™
Green FPS™ e-Series™
Gmax™
GTO™
IntelliMAX™
ISOPLANAR™
Making Small Speakers Sound Louder and Better™
MegaBuck™
MICROCOUPLER™
MicroFET™
MicroPak™
MicroPak2™
MillerDrive™
MotionMax™
mWSaver®
OptoHiT™
OPTOLOGIC®
OPTOPLANAR®
PowerTrench®
PowerXS™
Programmable Active Droop™
QFET®
QS™
Quiet Series™
RapidConfigure™
Saving our world, 1mW/W/kW at a time™
SignalWise™
SmartMax™
SMART START™
Solutions for Your Success™
SPM®
STEALTH™
SuperFET®
SuperSOT™-3
SuperSOT™-6
SuperSOT™-8
SupreMOS®
SyncFET™
Sync-Lock™
SYSTEM GENERAL®*
TinyBoost®
TinyBuck®
TinyCalc™
TinyLogic®
TINYOPTO™
TinyPower™
TinyPWM™
TinyWire™
TranSiC™
TriFault Detect™
TRUECURRENT®*
µSerDes™
SerDes
UHC®
Ultra FRFET™
UniFET™
VCX™
VisualMax™
VoltagePlus™
XS™
仙童™

* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS, SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

ANTI-COUNTERFEITING POLICY

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.

Rev. I68

© 1996 Fairchild Semiconductor Corporation

ON Semiconductor and ON are trademarks of Semiconductor Components Industries, LLC dba ON Semiconductor or its subsidiaries in the United States and/or other countries. ON Semiconductor owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of ON Semiconductor's product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. ON Semiconductor reserves the right to make changes without further notice to any products herein. ON Semiconductor makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does ON Semiconductor assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using ON Semiconductor products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by ON Semiconductor. "Typical" parameters which may be provided in ON Semiconductor data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. ON Semiconductor does not convey any license under its patent rights nor the rights of others. ON Semiconductor products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use ON Semiconductor products for any such unintended or unauthorized application, Buyer shall indemnify and hold ON Semiconductor and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that ON Semiconductor was negligent regarding the design or manufacture of the part. ON Semiconductor is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

PUBLICATION ORDERING INFORMATION

LITERATURE FULFILLMENT:
Literature Distribution Center for ON Semiconductor
19521 E. 32nd Pkwy, Aurora, Colorado 80011 USA
Phone: 303−675−2175 or 800−344−3860 Toll Free USA/Canada
Fax: 303−675−2176 or 800−344−3867 Toll Free USA/Canada
Email: orderlit@onsemi.com

N. American Technical Support: 800−282−9855 Toll Free USA/Canada
Europe, Middle East and Africa Technical Support:
Phone: 421 33 790 2910
Japan Customer Focus Center
Phone: 81−3−5817−1050

ON Semiconductor Website: **www.onsemi.com**

Order Literature: http://www.onsemi.com/orderlit

For additional information, please contact your local Sales Representative

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

ON Semiconductor:

NC7SV126P5X NC7SV126L6X

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru