THIS DRAWING AND THE INFORMATION SET FORTH HERE-ON ARE THE PROPERTY OF TYPE ELECTRONICS AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE, OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY TYCO ELECTRONICS IS PROHIBITED.

REVISIONS

LTR	DESCRIPTION	DATE	APPROVED
C2	ADMINISTRATIVE CHANGE ECO-11-012135	Jun/13/2011	M.HIGGY
D	REVISED PER ECO-12-021589	Dec/11/2012	G.WELLS

If this document is printed it becomes uncontrolled. Check for the latest revision

SCOPE:
THIS SPECIFICATION PROVIDES A DESCRIPTION OF HEAT SHRINKABLE METAL RINGS FOR TERMINATING BRAIDED SHIELD ONTO ADAPTORS DESIGNED FOR THAT PURPOSE.



PART DESCRIPTION:

TR XX X I

- I — INSULATING LINING
- X — BRAID DES1GNATOR
  - A–36 AWG BRAID, 1 LAYER
  - B–36 AWG BRAID, 2 LAYERS
  - B–30 AWG BRAID, 1 LAYER
  - C–32 AWG BRAID, 2 LAYERS
  - REFER TO MSG–101 FOR RING AND BRAID SELECTION
- XX — RING SIZE (MATCHES TXR ADAPTER ENTRY SIZE)
- TR — PRODUCT DESIGNATOR

NOTES:

1. MATERIAL: NICKEL/TITANIUM HEAT RECOVERABLE SHAPE MEMORY ALLOY
2. THE OUTSIDE SURFACE OF THE RING IS MARKED WITH TWO STRIPES OF THERMOCHROMIC PAINT WHICH CHANGE COLOR WHEN THE APPROPRIATE INSTALLATION TEMPERATURE IS REACHED.
3. "AI" RINGS ARE IDENTIFIED BY THE ABSENCE OF A RED OR BLUE DOT. REFER TO NOTE 4.
4. "BI" RINGS ARE MARKED WITH A RED DOT. "CI" RINGS ARE MARKED WITH A BLUE DOT.
5. REFER TO MIP-101 FOR INSTALLATION PROCEDURE.
6. REFER TO MPS-101 FOR PEFORMANCE REQUIRMENTS.

DIMENSIONING AND TOLERANCING PER ASME Y14.5M (ISO STANDARDS)

© 2008–2012 Tyco Electronics. All Rights Reserved.

Raychem Adapters
CUSTOMER DRAWING

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE INCHES. METRIC DIMENSIONS ARE IN BRACKETS.

DECIMAL TOLERANCES

.XXX ± -- [mm]
.XX ± -- [mm]
.X ± -- [mm]

ANGLE TOLERANCE

.X ± --

DRAWN	DATE
E. Goldy	05–17–93
CHECKED	DATE
———	———
APPROVED	DATE
W.C. Gay	5–26–93
CAD FILE: TR–CD	

THIRD ANGLE PROJECTION

TE Connectivity

TITLE

TINEL–LOCK RING

SIZE	CAGE CODE:	DWG. NO.	REV:
A	06090	TR	D

SCALE: NONE

SHEET 1 OF 2

PART DESCRIPTION	ØA				ØD	
	MIN AS SUPPLIED		MAX FREE RECOVERED			
TR04AI	.397	[10.08]	.379	[9.63]	.073±.005	[1.85±.13]
TR04BI	.416	[10.57]	.398	[10.11]	.073±.005	[1.85±.13]
TR05AI	.460	[11.68]	.440	[11.18]	.073±.005	[1.85±.13]
TR05BI	.479	[12.17]	.458	[11.63]	.073±.005	[1.85±.13]
TR06AI	.523	[13.28]	.499	[12.68]	.073±.005	[1.85±.13]
TR06BI	.548	[13.92]	.523	[13.28]	.073±.005	[1.85±.13]
TR07AI	.586	[14.88]	.559	[14.20]	.073±.005	[1.85±.13]
TR07BI	.606	[15.39]	.578	[14.68]	.073±.005	[1.85±.13]
TR08AI	.650	[16.51]	.620	[15.75]	.073±.005	[1.85±.13]
TR08BI	.670	[17.02]	.639	[16.23]	.073±.005	[1.85±.13]
TR10AI	.782	[19.86]	.744	[18.90]	.073±.005	[1.85±.13]
TR10BI	.802	[20.37]	.763	[19.38]	.073±.005	[1.85±.13]
TR10CI	.830	[21.08]	.791	[20.09]	.073±.005	[1.85±.13]
TR12AI	.912	[23.17]	.867	[22.02]	.073±.005	[1.85±.13]
TR12BI	.931	[23.65]	.886	[22.50]	.073±.005	[1.85±.13]
TR12CI	.960	[24.38]	.912	[23.17]	.073±.005	[1.85±.13]
TR14AI	1.040	[26.42]	.988	[25.10]	.073±.005	[1.85±.13]
TR14BI	1.060	[26.92]	1.007	[25.58]	.073±.005	[1.85±.13]
TR14CI	1.089	[27.66]	1.033	[26.24]	.073±.005	[1.85±.13]
TR16AI	1.171	[29.74]	1.111	[28.22]	.073±.005	[1.85±.13]
TR16BI	1.191	[30.25]	1.129	[28.68]	.073±.005	[1.85±.13]
TR16CI	1.216	[30.89]	1.154	[29.31]	.073±.005	[1.85±.13]
TR18AI	1.301	[33.05]	1.234	[31.34]	.073±.005	[1.85±.13]
TR18BI	1.320	[33.53]	1.252	[31.80]	.073±.005	[1.85±.13]
TR20AI	1.430	[36.32]	1.357	[34.47]	.073±.005	[1.85±.13]
TR20BI	1.450	[36.83]	1.376	[34.95]	.073±.005	[1.85±.13]
TR22AI	1.543	[39.19]	1.463	[37.16]	.084±.005	[2.13±.13]
TR22BI	1.561	[39.65]	1.481	[37.62]	.084±.005	[2.13±.13]
TR24AI	1.673	[42.49]	1.587	[40.31]	.084±.005	[2.13±.13]
TR24BI	1.691	[42.95]	1.605	[40.77]	.084±.005	[2.13±.18]
TR28AI	1.932	[49.07]	1.838	[46.68]	.084±.005	[2.13±.13]
TR28BI	1.950	[49.53]	1.858	[47.19]	.084±.005	[2.13±.13]

If this document is printed it becomes uncontrolled. Check for the latest revision

© 2008–2012 Tyco Electronics. All Rights Reserved.

Raychem Adapters
CUSTOMER DRAWING

DRAWN	DATE	SIZE	CAGE CODE:	DWG. NO.	REV:
E. Goldy	05–17–1993	A	06090	TR	D
CAD FILE: TR–CD		SCALE: NONE			SHEET 2 OF 2

ООО «ЛайфЭлектроникс» “LifeElectronics” LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru