


179DT Coax - Sub-Miniature



For more Information
please call

1-800-Belden1

**Description:**

28.5 AWG solid .012" bare copper conductor, gas-injected foam HDPE insulation, Duofoil® foil + tinned copper braid shield (95% coverage), PVC jacket.

Usage (Overall)

Suitable Applications: Broadcast Mobil Trucks, Digital Video, Precision Video, Telecommunications

Physical Characteristics (Overall)**Conductor**

AWG:

# Coax	AWG	Stranding	Conductor Material	Dia. (in.)
1	28.5	Solid	BC - Bare Copper	.0122

Total Number of Conductors: 1

Insulation

Insulation Material:

Insulation Material	Dia. (in.)
Gas-injected FHDPE - Foam High Density Polyethylene	.056

Outer Shield

Outer Shield Material:

Layer #	Outer Shield Trade Name	Type	Outer Shield Material	Coverage (%)
1	Duofoil®	Tape	Aluminum Foil-Polyester Tape-Aluminum Foil	100
2		Braid	TC - Tinned Copper	95

Outer Jacket

Outer Jacket Material:

Outer Jacket Material
PVC - Polyvinyl Chloride

Overall Cable

Overall Nominal Diameter: 0.100 in.

Mechanical Characteristics (Overall)

Operating Temperature Range:	-20°C To +75°C
UL Temperature Rating:	75°C
Bulk Cable Weight:	8 lbs/1000 ft.
Max. Recommended Pulling Tension:	15 lbs.
Min. Bend Radius/Minor Axis:	0.500 in.

Applicable Specifications and Agency Compliance (Overall)**Applicable Standards & Environmental Programs**

NEC/(UL) Specification:	CMR
CEC/C(UL) Specification:	CMG
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes

EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	01/01/2004
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
RG Type:	179/U

Flame Test

UL Flame Test:	UL1666 Vertical Shaft
----------------	-----------------------

Suitability

Suitability - Indoor:	Yes
Suitability - Outdoor:	No
Suitability - Aerial:	No

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Electrical Characteristics (Overall)**Nom. Characteristic Impedance:**

Impedance (Ohm)
75

Nom. Inductance:

Inductance (μH/ft)
.106

Nom. Capacitance Conductor to Shield:

Capacitance (pF/ft)
17.4

Nominal Velocity of Propagation:

VP (%)
77

Nominal Delay:

Delay (ns/ft)
1.32

Nom. Conductor DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
108

Nominal Outer Shield DC Resistance:

DCR @ 20°C (Ohm/1000 ft)
8.9

Nom. Attenuation:

Freq. (MHz)	Attenuation (dB/100 ft.)
1.000	1.180
5.000	1.850
6.000	1.990
7.000	2.150
10.000	2.390
12.000	3.830
67.500	5.890
71.500	5.980
88.500	6.610
100.000	6.890
135.000	7.850

179DT Coax - Sub-Miniature

143.000	8.070
180.000	8.930
270.000	10.800
360.000	12.500
540.000	15.400
720.000	17.900
750.000	18.300
1000.000	21.300
1500.000	26.300
2000.000	30.800
2250.000	32.800
3000.000	38.300
4500.000	47.500

Max. Operating Voltage - UL:

Voltage
300 V RMS

Other Electrical Characteristic 1:

Impedance tested in accordance with ASTM D-4566 paragraph 43.2, option 2 using a 75 Ohm fixed bridge and termination. 75 +/- 3 Ohms

Other Electrical Characteristic 2:

Return Loss tested in accordance with ASTM D-4566 paragraph 45.3, using a 75 Ohm fixed bridge and termination.

Minimum Return Loss:

Start Freq. (MHz)	Stop Freq. (MHz)	Min. RL (dB)
5	1600	23
1600	4500	21

Sweep Test**Sweep Testing:**

100% Sweep tested 5 MHz to 4.5 GHz.

Misc. Information (Overall)**Put Ups and Colors:**

Item #	Putup	Ship Weight	Color	Notes	Item Desc
179DT N3U1000	1,000 FT	9.000 LB	GREEN, MIL	C	#28H PE/GIFPE SH PVC
179DT 0011000	1,000 FT	9.000 LB	BROWN		#28H PE/GIFPE SH PVC
179DT 0021000	1,000 FT	9.000 LB	RED	C	#28H PE/GIFPE SH PVC
179DT 0031000	1,000 FT	9.000 LB	ORANGE	C	#28H PE/GIFPE SH PVC
179DT 0041000	1,000 FT	9.000 LB	YELLOW	C	#28H PE/GIFPE SH PVC
179DT 0061000	1,000 FT	9.000 LB	BLUE, LIGHT		#28H PE/GIFPE SH PVC
179DT 0071000	1,000 FT	9.000 LB	VIOLET		#28H PE/GIFPE SH PVC
179DT 0081000	1,000 FT	9.000 LB	GRAY	C	#28H PE/GIFPE SH PVC
179DT 0091000	1,000 FT	9.000 LB	WHITE		#28H PE/GIFPE SH PVC
179DT 0101000	1,000 FT	9.000 LB	BLACK		#28H PE/GIFPE SH PVC
179DT 010500	500 FT	4.500 LB	BLACK		#28H PE/GIFPE SH PVC
179DTBHD1	1 EA	0.032 LB	CHROME, BRIGHT	Q	CONN, LCK, 179 DIGI-/50PK
179DTBHD1	1 EA	0.032 LB	CHROME, BRIGHT	Q	CONN, 1PC, 179 DIGI-/50PK
179DTBHD3	1 EA	0.032 LB	CHROME, BRIGHT	Q	CONN, 3PC, 179 DIGI-/50PK

Notes:

C = CRATE REEL PUT-UP.

Q = STANDARD PACKAGES CANNOT BE BROKEN.

Revision Number: 10 Revision Date: 09-30-2009

© 2012 Belden, Inc
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract,

179DT Coax - Sub-Miniature

negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru