


**Product:** [9059M](#) 



CATV Video, RG6, 18 AWG BCCS, Tri Shield, Messenger

## Product Description

18 AWG Solid .040" bare copper-covered steel conductor, gas-injected foam Polyethylene insulation, Duobond Plus® and 75% Aluminum braid shield, PVC jacket with messenger.

## Technical Specifications

### Physical Characteristics (Overall)

#### Conductor

AWG	Stranding	Material	Nominal Diameter	No. of Coax
18	Solid	BCCS - Bare Copper Covered Steel	0.04 in	1

Conductor Count:	1
------------------	---

#### Insulation

Material	Nominal Diameter
PE - Polyethylene (Foam)	0.18 in

Table Notes:	Gas Injected
--------------	--------------

#### Outer Shield Material

Type	Layer	Material	Material Trade Name	Coverage [%]
Tape	1	Alum / Poly / Alum	Bonded Duofoil®	100%
Braid	2	Aluminum		75%
Tape	3	Alum / Poly		100%

Table Notes:	Tape has shorting fold and is bonded to jacket
--------------	--

#### Outer Jacket Material

Material	Nominal Diameter
PVC - Polyvinyl Chloride	0.275 x 0.416 in

### Construction and Dimensions

OuterJacket1, Messenger Diameter:	0.051 in
OuterJacket1, Messenger Material:	Galvanized Steel

### Electrical Characteristics

#### Conductor DCR

Nominal Conductor DCR	Nominal Outer Shield DCR	Outer Conductor DCR
28 Ohm/1000ft	5.6 Ohm/1000ft	5.6 Ohm/1000ft

#### Capacitance

Nom. Capacitance Conductor to Shield
16.2 pF/ft

#### Inductance

Nominal Inductance
0.097 µH/ft

## Impedance

### Nominal Characteristic Impedance

75 Ohm

## Return Loss (RL)

### Frequency [MHz] | Min. Structural Return Loss (SRL)

5-1000 MHz | 20 dB

## Delay

### Nominal Delay | Nominal Velocity of Propagation (VP) [%]

1.2 ns/ft | 83%

## High Freq

### Frequency [MHz] | Max. Insertion Loss (Attenuation)

5 MHz | 0.58 dB/100ft

55 MHz | 1.60 dB/100ft

211 MHz | 3.05 dB/100ft

270 MHz | 3.37 dB/100ft

300 MHz | 3.55 dB/100ft

350 MHz | 3.85 dB/100ft

400 MHz | 4.15 dB/100ft

450 MHz | 4.40 dB/100ft

550 MHz | 4.90 dB/100ft

750 MHz | 5.65 dB/100ft

870 MHz | 6.11 dB/100ft

1000 MHz | 6.55 dB/100ft

## Voltage

### Non-UL Voltage Rating

350 V RMS

## Temperature Range

Operating Temp Range: -40°C To +80°C

## Mechanical Characteristics

Bulk Cable Weight: 42 lbs/1000ft

Max. Pull Tension: 110 lbs

Min Bend Radius/Minor Axis: 3 in

## Standards

RG Type: 6/U Type

Series Type: 6

## Applicable Environmental and Other Programs

Environmental Space: Outdoor

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2003/96/EC (BFR): Yes

EU Directive 2011/65/EU (ROHS II): Yes

EU Directive 2012/19/EU (WEEE): Yes

EU Directive 2015/863/EU: Yes

EU Directive Compliance: EU Directive 2003/11/EC (BFR)

EU RoHS Compliance Date (yyyy-mm-dd): 2004-01-01

MII Order #39 (China RoHS): Yes

## Suitability

Suitability - Aerial: Yes

Suitability - Indoor: Yes

## Plenum/Non-Plenum

Plenum (Y/N): No

## Part Number

---

### Variants

Item #	Color	Putup Type	Length	UPC
9059M 0101000	Black	Reel	1,000 ft	612825224143

### History

Update and Revision:	Revision Number: 0.293 Revision Date: 04-28-2020
----------------------	--

© 2020 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)