



Single-Line ESD-Protection Diode in SOD-523



20278



19344

MARKING (example only)



20279

Bar = cathode marking

X = date code

Y = type code (see table below)

FEATURES

- Compact SOD-523 package
- Low package height < 0.7 mm
- 1-line unidirectional ESD-protection
- AEC-Q101 qualified available
- Working range 1 V to 33 V
- ESD immunity acc. IEC 61000-4-2
±15 kV to ±30 kV contact discharge
±15 kV to ±30 kV air discharge
- Lead plating: Sn (e3)
- soldering can be checked by standard vision inspection
- AOI = Automated Optical Inspection
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912

 AUTOMOTIVE
GRADE
Available

RoHS
COMPLIANT
HALOGEN
FREE
GREEN
(5-2008)

DESIGN SUPPORT TOOLS click logo to get started



| ORDERING INFORMATION | | | | | |
|--------------------------|-----------------------|--|------------|-------------------------------|----------------------------|
| PART NUMBER (EXAMPLE) | AEC-Q101 QUALIFIED | ENVIRONMENTAL AND QUALITY CODE | | | ORDERING CODE (EXAMPLE) |
| | | RoHS COMPLIANT + LEAD (Pb)-FREE TERMINATIONS | TIN PLATED | 8K PER 7" REEL (8 mm TAPE) | |
| | | GREEN | | MOQ = 8K/BOX | |
| VESD05C1-02V | - | G | 3 | -08 | VESD05C1-02V-G3-08 |
| VESD05C1-02V | H | G | 3 | -08 | VESD05C1-02VHG3-08 |

| PACKAGE DATA | | | | | | |
|---------------|--------------|-----------|---------|---|--------------------------------------|------------------------------|
| DEVICE NAME | PACKAGE NAME | TYPE CODE | WEIGHT | MOLDING COMPOUND FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL | SOLDERING CONDITIONS |
| VESD01C1-02V | SOD-523 | . V | 1.32 mg | UL 94 V-0 | MSL level 1 (according J-STD-020) | Peak temperature max. 260 °C |
| VESD03C1-02V | | . B | | | | |
| VESD05C1-02V | | . C | | | | |
| VESD08C1-02V | | . D | | | | |
| VESD012C1-02V | | . E | | | | |
| VESD016C1-02V | | . G | | | | |
| VESD026C1-02V | | . X | | | | |
| VESD033C1-02V | | A | | | | |



| ABSOLUTE MAXIMUM RATINGS VESD01C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 14.6 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD03C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 11.6 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD05C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 8.7 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD08C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 6.60 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |



| ABSOLUTE MAXIMUM RATINGS VESD12C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 4.4 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD16C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 3.6 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 30 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 30 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD26C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 2.1 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 20 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 20 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |

| ABSOLUTE MAXIMUM RATINGS VESD33C1-02V (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|--|---|------------------|-------------|------|
| PARAMETER | TEST CONDITIONS | SYMBOL | VALUE | UNIT |
| Peak pulse current | Acc. IEC 61000-4-5, 8/20 μs/single shot | I _{PPM} | 1.6 | A |
| Peak pulse power | Acc. IEC 61000-4-5, 8/20 μs/single shot | P _{PP} | 100 | W |
| ESD immunity | Contact discharge acc. IEC 61000-4-2; 10 pulses | V _{ESD} | 15 | kV |
| | Air discharge acc. IEC 61000-4-2; 10 pulses | | 15 | kV |
| Operating temperature | Junction temperature | T _J | -55 to +150 | °C |
| Storage temperature | | T _{stg} | -55 to +150 | °C |



| ELECTRICAL CHARACTERISTICS VESD01C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|---|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 1 | V |
| Reverse voltage | at $I_R = 100\text{ }\mu\text{A}$ | V_R | 1 | 1.2 | - | V |
| Reverse current | at $V_R = 1\text{ V}$ | I_R | - | 20 | 100 | μA |
| Reverse breakdown voltage | at $I_R = 20\text{ mA}$ | V_{BR} | 2.5 | 2.65 | 2.8 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 14.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 6.2 | 6.9 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 14.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 3 | 3.92 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.13 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 153 | 192 | 230 | pF |

| ELECTRICAL CHARACTERISTICS VESD03C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|---|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 3 | V |
| Reverse voltage | at $I_R = 20\text{ }\mu\text{A}$ | V_R | 3 | - | - | V |
| Reverse current | at $V_R = 3\text{ V}$ | I_R | - | 8 | 20 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 4.4 | 4.65 | 4.9 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 11.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 7.8 | 8.70 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 11.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 2.6 | 3.32 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.19 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 89 | 112 | 135 | pF |

| ELECTRICAL CHARACTERISTICS VESD05C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 5 | V |
| Reverse voltage | at $I_R = 1\text{ }\mu\text{A}$ | V_R | 5 | - | - | V |
| Reverse current | at $V_R = 5\text{ V}$ | I_R | - | 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 6.85 | 7.26 | 7.65 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 8.7\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 10.3 | 11.5 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 8.7\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 2.2 | 2.74 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.2 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 53 | 67 | 81 | pF |



| ELECTRICAL CHARACTERISTICS VESD08C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 8 | V |
| Reverse voltage | at $I_R = 0.1\text{ }\mu\text{A}$ | V_R | 8 | - | - | V |
| Reverse current | at $V_R = 8\text{ V}$ | I_R | - | 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 9.5 | 10 | 10.5 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 6.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 13.7 | 15.3 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 6.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 1.9 | 2.32 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.23 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 37 | 47 | 57 | pF |

| ELECTRICAL CHARACTERISTICS VESD12C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 12 | V |
| Reverse voltage | at $I_R = 0.1\text{ }\mu\text{A}$ | V_R | 12 | - | - | V |
| Reverse current | at $V_R = 12\text{ V}$ | I_R | - | 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 13.9 | 14.7 | 15.5 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 4.4\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 20.5 | 22.7 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 4.4\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 1.6 | 1.88 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.4 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 26 | 33 | 40 | pF |

| ELECTRICAL CHARACTERISTICS VESD16C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 16 | V |
| Reverse voltage | at $I_R = 0.1\text{ }\mu\text{A}$ | V_R | 16 | - | - | V |
| Reverse current | at $V_R = 16\text{ V}$ | I_R | - | 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 17 | 17.9 | 18.8 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 3.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 25.3 | 28 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 3.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 1.5 | 1.72 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 0.53 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 21 | 27 | 33 | pF |



| ELECTRICAL CHARACTERISTICS VESD26C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|--------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 26 | V |
| Reverse voltage | at $I_R = 0.1\text{ }\mu\text{A}$ | V_R | 26 | - | - | V |
| Reverse current | at $V_R = 26\text{ V}$ | I_R | - | < 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 27.6 | 29.1 | 30.6 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 2.1\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 43 | 48 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 2.1\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 1.3 | 1.42 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 1.9 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 14 | 17.5 | 21 | pF |

| ELECTRICAL CHARACTERISTICS VESD33C1-02V ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified) | | | | | | |
|--|--|---------------|------|--------|------|---------------|
| PARAMETER | TEST CONDITIONS / REMARKS | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| Protection paths | Number of lines which can be protected | $N_{channel}$ | - | - | 1 | lines |
| Reverse stand off voltage | Max. reverse working voltage | V_{RWM} | - | - | 33 | V |
| Reverse voltage | at $I_R = 0.1\text{ }\mu\text{A}$ | V_R | 33 | - | - | V |
| Reverse current | at $V_R = 33\text{ V}$ | I_R | - | < 0.01 | 0.1 | μA |
| Reverse breakdown voltage | at $I_R = 1\text{ mA}$ | V_{BR} | 35.5 | 37.4 | 39.3 | V |
| Reverse clamping voltage | at $I_{PP} = I_{PPM} = 1.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_C | - | 56 | 62.5 | V |
| Forward clamping voltage | at $I_{PP} = 1\text{ A}$, $t_p = 300\text{ }\mu\text{s}$ | V_F | 0.9 | 1.1 | 1.2 | V |
| | at $I_{PP} = I_{PPM} = 1.6\text{ A}$, $t_p = 8/20\text{ }\mu\text{s}$ | V_F | - | 1.22 | 1.32 | V |
| Dynamic resistance | $t_p = 100\text{ ns}$ (TLP; pin 2-1) | r_{dyn} | - | 3.6 | - | Ω |
| Capacitance | at $V_R = 0\text{ V}$; $f = 1\text{ MHz}$ | C_D | 12 | 15 | 18 | pF |




Fig. 1 - ESD Discharge Current Wave Form acc. IEC 61000-4-2 (330 Ω / 150 pF)




Fig. 4 - Typical Capacitance vs. Reverse Voltage




Fig. 2 - 8/20 μs Peak Pulse Current Wave Form acc. IEC 61000-4-5




Fig. 5 - Typical Reverse Voltage vs. Reverse Current




Fig. 3 - Typical Peak Clamping Voltage vs. Peak Pulse Current




Fig. 6 - Typical Clamping Voltage vs. Peak Pulse Current




Fig. 7 - Typical Forward Voltage vs. Forward Current





Fig. 8 - Typical Forward Voltage vs. Forward Current


PACKAGE DIMENSIONS in millimeters (Inches): SOD-523



Document no.: S8-V-3880.02-003 (4)
 Rev.2 - Date: 18. Aug. 2017
 23093




CARRIER TAPE SOD-523



S8-V-3717.03-005 (4)
05.07.2018
22959

ORIENTATION IN CARRIER TAPE SOD-523



S8-V-3717.03-006 (4)
05.07.2018
22958



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru