FAIRCHILD SEMICONDUCTOR™

FDH700

ULTRA FAST DIODE

DISCRETE POWER AND SIGNAL TECHNOLOGIES


Information Only Data Sheet

FINAL REVERSE CURRENT & FORWARD VOLTAGE LIMITS MIGHT BE INCREASED SLIGHTLY

Absolute Maximum Ratings (note 1) TA = 25°C unless otherwise noted

Parameter	Value	Units
Storage Temperature	-65 to +200	°C
Maximum Junction Temperature	-65 to +175	°C
Total Power Dissipation at 25°C	250	mW
Derate above 25°C	1.67	mW/°C
Working Inverse Voltage	20	V
DC Forward Current	150	mA

Note 1: These ratings are limiting values above which the serviceability of any semiconductor device may be impaired



Electrical Characteristics TA = 25°C unless otherwise noted

SYM	CHARACTERISTICS	MIN	MAX	UNITS	TEST CONDITIONS
B_V	Breakdown Voltage	30		V	I_R = 5.0 uA
I_R	Reverse Leakage		50 50	nA uA	V_R = 20 V V_R = 20 V T_A = 150°C
V_F	Forward Voltage	420 520 640 760 810 0.89	500 610 740 900 990 1.25	mV mV mV mV mV V	I_F = 10 uA I_F = 100 uA I_F = 1.0 mA I_F = 10 mA I_F = 20 mA I_F = 50 mA
T_{RR}	Reverse Recovery Time		900	ps	I_F= I_R = 10 mA I_{RR} = 1.0 mA R_{Loop} = 100 Ohm
C_T	Diode Capacitance		1.5	pF	V_R = 0 V, f = 1.0 MHz


© 1999 Fairchild Semiconductor Corporation

FAIRCHILD SEMICONDUCTOR™

DISCRETE POWER AND SIGNAL TECHNOLOGIES

STANDARD DIGITAL MARKING CRITERIA

MAXIMUM CHARACTERS PER LINE: 3 MAXIMUM NUMBER OF LINES: 4
LOGO AND CHARACTERS M & W COUNT AS 2 CHARACTERS EACH



NOTE 1:

LEAD DIAMETER NOT CONTROLLED IN THIS ZONE TO ALLOW FOR FLASH, LEAD FINISH BUILD-UP, & MINOR IRREGULARITIES OTHER THAN SLUGS.

DO-35 PACKAGE

Fairchild Semiconductor's Criteria

11-MAR-97

FAIRCHILD SEMICONDUCTOR™

DISCRETE POWER AND SIGNAL TECHNOLOGIES

FD700


Ultra Fast Diode Diode

Absolute Maximum Ratings (note 1) TA = 25°C unless otherwise noted

Parameter	Value	Units
Storage Temperature	-65 to +200	°C
Maximum Junction Temperature	-65 to +175	°C
Total Power Dissipation at 25°C	250	mW
Derate above 25°C	1.67	mW/°C
Working Inverse Voltage	20	V
DC Forward Current	150	mA

Note 1: These ratings are limiting values above which the serviceability of any semiconductor device may be impaired

DO-7 PACKAGE




Electrical Characteristics TA = 25°C unless otherwise noted

SYM	CHARACTERISTICS	MIN	MAX	UNITS	TEST CONDITIONS
B_V	Breakdown Voltage	30		V	I_R = 5.0 uA
I_R	Reverse Leakage		50 50	nA uA	V_R = 20 V V_R = 20 V T_A = 150°C
V_F	Forward Voltage	420 520 640 760 810 0.89	500 610 740 880 950 1.10	mV mV mV mV mV V	I_F = 10 uA I_F = 100 uA I_F = 1.0 mA I_F = 10 mA I_F = 20 mA I_F = 50 mA
T_{RR}	Reverse Recovery Time		700	ps	I_F= I_R = 10 mA I_{RR} = 1.0 mA R_{Loop} = 100 Ohm
C_T	Diode Capacitance		1.0	pF	V_R = 0 V, f = 1.0 MHz

© 1997 Fairchild Semiconductor Corporation

FAIRCHILD SEMICONDUCTOR™

DISCRETE POWER AND SIGNAL TECHNOLOGIES



NOTE 1:

LEAD DIAMETER NOT CONTROLLED IN THIS ZONE TO ALLOW FOR FLASH, LEAD FINISH BUILD-UP, & MINOR IRREGULARITIES OTHER THAN SLUGS.

DO-7 PACKAGE

Fairchild Semiconductor's Criteria
13-APR-93

TRADEMARKS

The following are registered and unregistered trademarks Fairchild Semiconductor owns or is authorized to use and is not intended to be an exhaustive list of all such trademarks.

ACEx™	FAST ®	OPTOPLANAR™	STAR*POWER™
Bottomless™	FASTr™	PACMAN™	Stealth™
CoolFET™	FRFET™	POP™	SuperSOT™-3
CROSSVOLT™	GlobalOptoisolator™	Power247™	SuperSOT™-6
DenseTrench™	GTO™	PowerTrench®	SuperSOT™-8
DOME™	HiSeC™	QFET™	SyncFET™
EcoSPARK™	ISOPLANAR™	QS™	TinyLogic™
E^2CMOS™	LittleFET™	QT Optoelectronics™	TruTranslation™
EnSigna™	MicroFET™	Quiet Series™	UHC™
FACT™	MICROWIRE™	SILENT SWITCHER®	UltraFET®
FACT Quiet Series™	OPTOLOGIC™	SMART START™	VCX™

STAR*POWER is used under license

DISCLAIMER

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION OR DESIGN. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS.

LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.
As used herein:

1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body, or (b) support or sustain life, or (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in significant injury to the user.

2. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

PRODUCT STATUS DEFINITIONS

Definition of Terms

Datasheet Identification	Product Status	Definition
Advance Information	Formative or In Design	This datasheet contains the design specifications for product development. Specifications may change in any manner without notice.
Preliminary	First Production	This datasheet contains preliminary data, and supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
No Identification Needed	Full Production	This datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice in order to improve design.
Obsolete	Not In Production	This datasheet contains specifications on a product that has been discontinued by Fairchild semiconductor. The datasheet is printed for reference information only.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru