






PART NUMBER SEE SHEET 2



spec ref		dr	Rainbow Zhan	2016/10/10	projection	MM	size	A3	scale	3:2
tolerance std		eng	Vicking Liu	2016/10/31			ecn no		rel level	
ISO 406 ISO 1101		chr	Fancy Zhang	2016/10/31			-		Released	
TOLERANCES UNLESS OTHERWISE SPECIFIED		appr	Pei-Ming Zheng	2016/10/31	product family		PwrBlade+		-	
surface	linear	Amphenol FCI			9HP + 4S VERTICAL PLUG PF		dwg no 10106267-9001001		rev A	
	angular									
ISO 1302		cat. no.			Product - Customer Drw			sheet 1 of 3		

PRODUCT NO. 10106267-9001001LF	ROWS DCBA	HIGH POWER											S
		E1	P1	P2	P3	P4	P5	P6	P7	P8	P9	1	E2

CODE	DESCRIPTION
G	STD SIGNAL CONTACT
H4	STD HIGH POWER CONTACT



Amphenol
FCi

© 2016 AFCI

spec ref	dr	2016/10/10	projection	MM	size	A3	scale	3:2
tolerance std	eng	2016/10/31			ecn no	-	rel level	Released
ISO 406 ISO 1101	chr	2016/10/31						
surface	linear	0.X	±0.5		9HP + 4S VERTICAL PLUG PF	dwg no 10106267-9001001	rev A	
		0.XX	±0.25					
ISO 1302	angular	0°	±2°					
cat. no.				Product - Customer Drw		sheet 2 of 3		

NOTES:

- 1) PRODUCT MARK:
PART NUMBER AND DATE CODE TO BE MARKED ON THIS SURFACE .
THE MARK CAN BE OMITTED IF THERE IS NOT ENOUGH SPACE ON THIS SURFACE.
- 2) MATERIALS:
-HOUSING : HIGH TEMP THERMOPLASTIC WITH GLASS FIBER, UL94V-0, BLACK.
-POWER CONTACT : HIGH CONDUCTIVITY COPPER ALLOY.
-SIGNAL CONTACT : COPPER ALLOY.
- 3) PLATING SPECIFICATION : 10116351
- 4) DENOTES CONNECTOR KEEP OUT ZONE.
- 5) DATUM AND BASIC DIMENIONS ARE ESTABLISHED BY CUSTOMER.
- 6) ALL HOLE DIAMETERS ARE FINISHED HOLE SIZES.
- 7) 1.15+/-0.025MM DRILLED HOLE PLATED WITH 0.00762MM MIN SN
OVER 0.0254-0.0762MM CU PLATING TO ACHIEVE A 1.02+/-0.07MM HOLE.
- 8) THIS PRODUCT MEETS EUROPEAN UNION DIRECTIVES AND OTHER COUNTRY
REGULATIONS AS DESCRIBED IN GS-47-0004.
- 9)PRODUCT SPECIFICATION : GS-12-658.
APPLICATION SPECIFICATION : GS-20-141.
PRODUCT PACKAGE SPECIFICATION: GS-14-1502.

Amphenol
FCi

© 2016 AFCI

spec ref		dr	Rainbow Zhan	2016/10/10	projection	MM	size	A3	scale	3:2	
tolerance std		eng	Vicking Liu	2016/10/31		← →	ecn no		-		
ISO 406 ISO 1101		chr	Fancy Zhang	2016/10/31			rel level		Released		
TOLERANCES UNLESS OTHERWISE SPECIFIED		appr	Pei-Ming Zheng	2016/10/31	product family		PwrBlade+				
surface	linear	0.X	±0.5	Amphenol FCi	9HP + 4S VERTICAL PLUG PF		dwg no	10106267-9001001		rev	A
		0.XX	±0.25								
	0.XXX	±0.10									
ISO 1302	angular	0°	±2°	cat. no.	Product - Customer Drw		sheet 3 of 3				

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru