

MCR716, MCR718




Description

Designed for high volume, low cost, industrial and consumer applications such as motor control; process control; temperature, light and speed control.

Features

- Small Size
- Passivated Die for Reliability and Uniformity
- Low Level Triggering and Holding Characteristics
- Epoxy Meets UL 94 V-0 @ 0.125 in
- ESD Ratings: Human Body Model, 3B > 8000 V
Machine Model, C > 400 V
- Pb-Free Packages are Available

Pin Out



Functional Diagram



Additional Information



Datasheet



Resources



Samples

Maximum Ratings ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Rating	Symbol	Value	Unit
Peak Repetitive Off-State Voltage (Note 1) ($T_J = -40$ to 125°C , Sine Wave, 50 to 60 Hz, Gate Open)	V_{DRM} V_{RRM}	400 600	V
On-State RMS Current (All Conduction Angles; $T_C = 90^\circ\text{C}$)	$I_{\text{T(RMS)}}$	4.0	A
Average On-State Current (180° Conduction Angles; $T_C = 90^\circ\text{C}$)	$I_{\text{T(AV)}}$	2.6	A
Peak Non-Repetitive Surge Current (1/2 Cycle, Sine Wave 60 Hz, $T_J = 110^\circ\text{C}$)	I_{TSM}	25	A
Circuit Fusing Consideration ($t = 8.3$ ms)	I^2t	2.6	A ² sec
Forward Peak Gate Power (Pulse Width ≤ 10 μsec , $T_C = 90^\circ\text{C}$)	P_{GM}	0.5	W
Forward Average Gate Power ($t = 8.3$ msec, $T_C = 90^\circ\text{C}$)	$P_{\text{GM(AV)}}$	0.1	W
Forward Peak Gate Current (Pulse Width ≤ 1.0 μsec , $T_C = 90^\circ\text{C}$)	I_{GM}	0.2	A
Operating Junction Temperature Range	T_J	-40 to +110	$^\circ\text{C}$
Storage Temperature Range	T_{stg}	-40 to +150	$^\circ\text{C}$

Stresses exceeding Maximum Ratings may damage the device. Maximum Ratings are stress ratings only. Functional operation above the Recommended Operating Conditions is not implied. Extended exposure to stresses above the Recommended Operating Conditions may affect device reliability.

1. V_{DRM} and V_{RRM} for all types can be applied on a continuous basis. Ratings apply for zero or negative gate voltage; however, positive gate voltage shall not be applied concurrent with negative potential on the anode. Blocking voltages shall not be tested with a constant current source such that the voltage ratings of the devices are exceeded.

Thermal Characteristics

Rating	Symbol	Value	Unit
Thermal Resistance, Junction-to-Case	R_{JC}	3.0	$^\circ\text{C/W}$
Thermal Resistance, Junction-to-Ambient (Note 2)	R_{JA}	80	
Maximum Lead Temperature for Soldering Purposes 1/8" from Case for 10 Seconds	T_L	260	$^\circ\text{C}$

Electrical Characteristics - OFF ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
Peak Repetitive Forward or Reverse Blocking Current (Note 3) ($V_{AK} = \text{Rated } V_{DRM} \text{ or } V_{RRM}, R_{GK} = 1.0 \text{ k}\Omega$)	$T_J = 25^\circ\text{C}$	I_{DRM}	-	-	10	μA
	$T_J = 110^\circ\text{C}$	I_{RRM}	-	-	200	

Electrical Characteristics - ON ($T_J = 25^\circ\text{C}$ unless otherwise noted)

Characteristic		Symbol	Min	Typ	Max	Unit
Peak Reverse Gate Blocking Voltage ($I_{GR} = 10 \mu\text{A}$)		V_{GRM}	10	12.5	18	V
Peak Reverse Gate Blocking Current ($V_{GR} = 10 \text{ V}$)		I_{RGM}	-	-	1.2	μA
Peak Forward On-State Voltage (Note 4)	($I_{TM} = 5.0 \text{ A Peak}$)	V_{TM}	-	1.3	1.5	V
	($I_{TM} = 8.2 \text{ A Peak}$)		-	1.5	2.2	
Gate Trigger Current (Continuous dc) (Note 5) ($V_{AK} = 12 \text{ Vdc}, R_L = 30 \Omega$)	($T_J = 25^\circ\text{C}$)	I_{GT}	1.0	25	75	μA
	($T_J = -40^\circ\text{C}$)		-	-	300	
Gate Trigger Voltage (Continuous dc) ($V_D = 12 \text{ V}_{DC}, R_L = 30 \Omega$) (Note 5)	($T_J = 25^\circ\text{C}$)	V_{GT}	0.3	0.55	0.8	V
	($T_J = -40^\circ\text{C}$)		-	-	1.0	
	($T_J = 110^\circ\text{C}$)		0.2	-	-	
Holding Current ($V_D = 12 \text{ V}$, Initiating Current = 200 mA, $R_{GK} = 1 \text{ k}\Omega$)	($T_J = 25^\circ\text{C}$)	I_H	0.4	1.0	5.0	mA
	($T_J = -40^\circ\text{C}$)		-	-	10	
Latching Current ($V_D = 12 \text{ V}_{DC}, I_G = 2.0 \text{ mA}, T_C = 25^\circ\text{C}$) ($V_D = 12 \text{ V}_{DC}, I_G = 2.0 \text{ mA}, T_C = -40^\circ\text{C}$)		I_L	-	-	5.0	mA
			-	-	10	
Total Turn-On Time (Source Voltage = 12 V, $R_S = 6.0 \text{ k}\Omega$, $I_T = 8 \text{ A(pk)}$, $R_{GK} = 1.0 \text{ k}\Omega$) ($V_D = \text{Rated } V_{DRM}$, Rise Time = 20 ns, Pulse Width = 10 μs)		tgt	-	2.0	5.0	μs

Dynamic Characteristics

Characteristic	Symbol	Min	Typ	Max	Unit
Critical Rate of Rise of Off-State Voltage ($V_D = 0.67 \times \text{Rated } V_{DRM}$, Exponential Waveform, $R_{GK} = 1.0 \text{ k}\Omega$, $T_J = 110^\circ\text{C}$)	dv/dt	5.0	10	-	V/ μs
Critical Rate of Rise of On-State Current ($I_{PK} = 50 \text{ A}$, $P_w = 40 \text{ sec}$, $di/dt = 1 \text{ A/sec}$, $I_{gt} = 50 \text{ mA}$)	di/dt	-	-	100	A/ μs

2. Case 369C, when surface mounted on minimum recommended pad size.

3. Ratings apply for negative gate voltage or $R_{GK} = 1.0 \text{ k}\Omega$. Devices shall not have a positive gate voltage concurrently with a negative voltage on the anode. Devices should not be tested with a constant current source for forward and reverse blocking capability such that the voltage applied exceeds the rated blocking voltage.

4. Pulse Test; Pulse Width $\leq 2.0 \text{ msec}$, Duty Cycle $\leq 2\%$.

5. R_{GK} current not included in measurements.

Voltage Current Characteristic of SCR

Symbol	Parameter
V_{DRM}	Peak Repetitive Forward Off State Voltage
I_{DRM}	Peak Forward Blocking Current
V_{RRM}	Peak Repetitive Reverse Off State Voltage
I_{RRM}	Peak Reverse Blocking Current
V_{TM}	Maximum On State Voltage
I_H	Holding Current




Figure 1. RMS Current Derating




Figure 2. On-State Power Dissipation




Figure 3. On-State Characteristics




Figure 4. Transient Thermal Response




Figure 5. Typical Gate Trigger Current vs Junction Temperature




Figure 6. Typical Gate Trigger Voltage vs Junction Temperature




Figure 7. Typical Holding Current vs Junction Temperature







Figure 8. Typical Latching Current vs Junction Temperature




Dimensions



Soldering Footprint



Part Marking System



Pin Assignment

1	Cathode
2	Anode
3	Gate
4	Anode

Ordering Information

Device	Package	Shipping
MCR716T4	DPAK	2500 / Tape & Reel
MCR716T4G	DPAK (Pb-Free)	
MCR718T4	DPAK	
MCR718T4G	DPAK (Pb-Free)	

1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
2. CONTROLLING DIMENSION: INCH.

Disclaimer Notice - Information furnished is believed to be accurate and reliable. However, users should independently evaluate the suitability of and test each product selected for their own applications. Littelfuse products are not designed for, and may not be used in, all applications. Read complete Disclaimer Notice at: www.littelfuse.com/disclaimer-electronics

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru