

## Fuse Holders for Low-Peak CUBEFuse Finger-Safe, 1-100A, 600Vac/dc



**Catalog Symbols:** TCFH30N (1-30A)  
TCFH60N (1-60A)  
TCFH100N (1-100A)

**Construction:** Finger-safe

**Mounting:** DIN Rail or panel mount

**Ampacities:** TCFH30N - holds any 1-30A CUBEFuse  
TCFH60N - holds any 1-60A CUBEFuse  
TCFH100N - holds any 1-100A CUBEFuse

**Voltage Rating:** 600Vac/dc

**Withstand Rating:** 300kA RMS Sym. (UL)  
200kA RMS Sym. (CSA)  
100kA DC (UL & CSA)

**Agency Information:**

- UL Listed Fuse Holder: Guide IZLT, File E14853
- CSA Certified Fuse Holder: Class 6225-01, File 47235
- CE compliance for the European Union low voltage directive

**Operating and Storage Temperature Range:** -40 to 80°C

**Material Specifications:**

- Holder case: Glass filled PBT
- Interface clips: Copper alloy
- Interface clip plating: Tin
- Terminals: Steel
- DIN Rail spring: Stainless steel

**Features and Product Benefits**

- Holder for the world's first finger-safe power fuse system.
- Holder and CUBEFuse together deliver Class CF and Class J fuse performance in a time-delay or fast-acting version. See Data Sheet 9000 for time-delay indicating and non-indicating CUBEFuse performance characteristics. See data sheet 2147 for fast-acting CUBEFuse performance characteristics.
- Smallest fuse and holder footprint of any class fuse installation including Class J, CC, T and RK.
- DIN Rail or panel mount for easy installation.
- Holders dovetail together to easily achieve the required number of poles.
- All holders (TCFH30N, TCFH60N and TCFH100N) dovetail together to permit mixing ampacities.
- All holders accept equal and lower amp rated TCF\_ indicating and TCF\_RN non-indicating time-delay CUBEFuse or FCF\_RN fast-acting CUBEFuse - no need for a fuse reducer.
- Dual wire rated terminals for wiring ease.
- High 300kA withstand rating stands up to high fault currents.

**Conductors/Wire Range - 75°C Cu Wire Only**

Holder/ Ampacity	No. of Poles*	Single Wire	Dual Wire
TCFH30N	1	18 to 8 AWG	18 to 10 AWG
TCFH60N	1	18 to 4 AWG	18 to 6 AWG
TCFH100N	1	18 to 1 AWG	6 AWG

\* Holders dovetail together to achieve the desired number of poles for the application.


**Carton Quantity and Weight**

Part Number	Carton Qty.	Weight Per Carton	
		lbs	kg
TCFH30N	12	2.42	1.10
TCFH60N	12	2.57	1.17
TCFH100N	6	1.38	0.63

**Terminal Torque Ratings by Conductor and Holder Size (75°C Cu only)**

TCFH30N		TCFH60N		TCFH100N	
Single	Dual	Single	Dual	Single	Dual
10-8 AWG 25lb-in	18-10 AWG 25lb-in	18-10 AWG 20lb-in	18-10 AWG 20lb-in	18-10 AWG 25lb-in	6 AWG 45lb-in
18-12 AWG 20lb-in		8-4 AWG 35lb-in	8-6 AWG 35lb-in	8-1 AWG 40lb-in	

**TCFH Dimensions – in (mm)**



Holder	A	B	C	D	E	F
TCFH30N	2.30 (58.50)	0.76 (19.37)	1.357 (34.24)	0.15 (3.76)	- -	- -
TCFH60N	2.60 (66.12)	1.03 (26.23)	1.60 (40.64)	0.17 (4.34)	- -	- -
TCFH100N	2.91 (73.81)	1.05 (26.74)	2.01 (50.93)	0.15 (3.81)	0.80 (20.39)	2.51 (63.65)

**CUBEFuse Availability and Applications**

The indicating Low-Peak time-delay CUBEFuse (TCF\_) and non-indicating Low-Peak time-delay CUBEFuse (TCF\_RN) are available in amp ratings from 1-100A. See Data Sheet 9000. The non-indicating, fast-acting Low-Peak

CUBEFuse is available in amp ratings from 1-100A. See data sheet 2147. The CUBEFuse is also used in these other Cooper Bussmann circuit protection solutions.



TCF\_100RN      FCF\_100RN



CCP\_CF  
1-, 2- & 3-Pole switched disconnects  
Data Sheet 1157



CCPB  
1-, 2- & 3-Pole disconnects for the Quik-Spec™  
Coordination Panelboard. Data Sheet 1160



CF\_ Quik-Spec™ Safety  
Switch disconnect (optional  
window). Data Sheet 1156

The only controlled copy of this Data Sheet is the electronic read-only version located on the Cooper Bussmann Network Drive. All other copies of this document are by definition uncontrolled. This bulletin is intended to clearly present comprehensive product data and provide technical information that will help the end user with design applications. Cooper Bussmann reserves the right, without notice, to change design or construction of any products and to discontinue or limit distribution of any products. Cooper Bussmann also reserves the right to change or update, without notice, any technical information contained in this bulletin. Once a product has been selected, it should be tested by the user in all possible applications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)