

4

3





2

1

NOTES: SEE SHEET 2.

If this document is printed it becomes uncontrolled. Check for the latest revision

| REVISIONS | | | |
|-----------|--------------------------|-------------|----------|
| LTR | DESCRIPTION | DATE | APPROVED |
| H | REVISED PER DCR# C061468 | Jan/11/07 | M.HIGGY |
| J | PER ECO-09-004669 | Feb/24/09 | M.HIGGY |
| K | PER ECO-11-008915 | Apr/28/2011 | M.HIGGY |



THE POST CAN BE .01 [0.3] MAX. ABOVE THE SHELL EDGE OR .02 [0.6] MAX. BELOW THE SURFACE.

VIEW A ASSEMBLED HARDWARE

THIS DRAWING AND THE INFORMATION SET FORTH HEREON ARE THE PROPERTY OF TYCO ELECTRONICS AND ARE TO BE HELD IN TRUST AND CONFIDENCE. PUBLICATION, DUPLICATION, DISCLOSURE OR USE FOR ANY PURPOSE NOT EXPRESSLY AUTHORIZED IN WRITING BY TYCO ELECTRONICS IS PROHIBITED.

© 2006-2011 Tyco Electronics. All rights reserved

| | | | |
|---|------------|----------|---------|
| UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS. | DRAWN | T.SEATON | 96JUN28 |
| | CHECKED | | |
| | APPROVED | P.DUTTON | 96JUL03 |
| | APPROVED | | |
| DECIMALS | .XXX ±.005 | .13 mm | |
| | .XX ±.02 | .5 mm | |
| ANGLES | .X ± | | |
| WEIGHT: | | | |

| | | | |
|------------------------------|------------------|------------------------------|---------|
| DRAWN | | T.SEATON | 96JUN28 |
| CHECKED | | | |
| APPROVED | | P.DUTTON | 96JUL03 |
| APPROVED | | | |
| CAD NAME MTC100Q-SHX-X2X-XXX | | | |
| THIRD ANGLE PROJECTION | | | |
| SIZE C | CAGE CODE: 06090 | DWG. NO. MTC100Q-SHX-X2X-XXX | REV K |
| SCALE: NONE | | SHEET 1 OF 3 | |

Raychem MTC CUSTOMER DRAWING



TITLE SHELL, PLUG AND RECEPTACLE MTC100Q SERIES

4

3

2

1

DWG. NO. MTC100Q-SHX-X2X-XXX 1

A

4

3


2

1

NOTES:

1. SHELL PART NUMBER VARIABLES: (NOT ALL POSSIBLE CONFIGURATIONS SHOWN ON THIS DRAWING ARE AVAILABLE AS STANDARD PRODUCTS. PLEASE CHECK WITH RAYCHEM TO CONFIRM AVAILABILITY.)

MTC100Q-SHX-X2X-XXX



2. MATERIAL:

- A) SHELL ALUMINUM ALLOY PER ASTM B85
- B) RETENTION CLIP COPPER ALLOY 172 PER ASTM B194
- C) CAP SCREW STAINLESS STEEL PER SAE-AMS-QQ-S-763, 300 SERIES
- D) POST * STAINLESS STEEL , PER AISI 17-4 PH
- E) ROLL PIN STAINLESS STEEL PER SAE-AMS 5673, 400 SERIES
- F) KEYING PIN HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
- G) KEY PINS INSERT HIGH GRADE POLYARYLENE THERMOPLASTIC, MOLDED
- H) CLAMP BAR STAINLESS STEEL PER SAE-AMS-QQ-S-763, 300 SERIES
- J) CLAMP INSERT SILICONE ELASTOMER PER MIL-DTL-25988B
- K) DRIVER * STAINLESS STEEL , PER AISI 17-4 PH
- L) SPRING STAINLESS STEEL PER AMS 5673, 17-7 PH
- L) HELIX * STAINLESS STEEL , PER AISI 17-4 PH

* ACCEPTABLE ALTERNATE, STAINLESS STEEL, PER MPIF STD 35, MIM-17-4 PH

3. FINISH:

APPLIES TO NICKEL PLATED CONNECTORS

- A) SHELL NICKEL PLATED PER SAE-AMS-C-26074 CLASS 3, GRADE B
- B) RETENTION CLIP NICKEL PLATED PER SAE-AMS-C-26074 CLASS 2, .00002 MINIMUM
- C) POST CAP SCREW PASSIVATED PER SAE-AMS-QQ-P-35
- D) POST NICKEL TEFLON PLATED PER TECHMETALS 117C
- E) HELIX NICKEL TEFLON PLATED PER TECHMETALS 117C
- F) ROLL PIN PASSIVATED PER SAE-AMS-QQ-P-35
- G) DRIVER PASSIVATED PER SAE-AMS-QQ-P-35

- 4 KEYING PIN IS SUPPLIED UNINSTALLED, USER TO PRESS INTO PROPER KEYING POSITION. SEE TABLE 5 FOR STANDARD KEYING PIN POSITIONS. FOR ADDITIONAL KEYING OPTIONS REFER TO D-659-0080.
- 5 STANDARD (RED) DUST CAP ARE SUPPLIED WITH EACH PLUG AND RECEPTACLE. SEE TABLE VI FOR MORE INFORMATION.
- 6 APPROPRIATE PART NUMBERS AND DATE CODES ARE STAMPED APPROXIMATELY AS SHOWN ON "B" SIDE. ALL "A" SIDE MARKINGS ARE OPTIONAL.
- 7. THESE PARTS MEET THE REQUIREMENTS OF TE SPECIFICATION C-6114.
- 8 THESE ITEMS ARE SUPPLIED UNASSEMBLED.
- 9 SEE TABLE II SHEET 3, WEIGHTS ARE WITHOUT DUST CAP.
- 10 RECEPTACLE POST SCREWS (CAP SCREWS) ARE TO BE TORQUED TO 15±1 INCH-LBS (1.0±0.07 N-M)
- 11 PLUG AND RECEPTACLE SHELLS ARE DESIGNED TO ACCEPT EITHER PIN OR SOCKET INSERTS. OR MIXED IN THE TWO INCHES STYLE.
- 12 THIS RECEPTACLE IS RECOMMENDED FOR REAR PANEL MOUNTING APPLICATION. REMOVING AS MANY PANEL WASHERS AS REQUIRED TO ACCOMMODATE THE THICKNESS OF THE PANEL BEING USED. SEE SHEET 3, TABLE 4, FIGURE 1. USE ONLY SCREWS SUPPLIED WITH CONNECTOR. POST TO BE FLUSH WITHIN TOLERANCE AS SHOWN SEE VIEW 'A' PAGE # 1.
- 13 WHEN MOUNTING FLANGELESS CONNECTORS ADJACENT TO ONE ANOTHER AND USING THE .400 MINIMUM CENTERLINE LOCATION, THERE WILL BE NO WEB BETWEEN PANEL CUT-OUTS. SEE SHEET 3, TABLE 3, FOR DETAILS.
- 14 THE HARDWARE FOR THIS CONNECTOR IS DESIGNED TO BE USED ON 0.063 INCH PANEL THICKNESS. OTHERWISE 2 THIN WASHERS (PANEL WASHERS) ARE REQUIRED FOR EACH POST. USE PART D-659-0042.

| TABLE 1 (MODIFICATIONS) | |
|--------------------------|--|
| MODIFICATION DASH NUMBER | DESCRIPTION |
| -022 | SAME AS STANDARD ASSEMBLY, EXCEPT CONTACTS AND SEALING PLUGS ARE INCLUDED. |
| -023 | SAME AS STANDARD ASSEMBLY, EXCEPT CONTACTS SEALING PLUGS AND INSERTION / EXTRACTION TOOL ARE INCLUDED. |
| | |
| | |
| | |

If this document is printed it becomes uncontrolled. Check for the latest revision

© 2006-2011 Tyco Electronics. All rights reserved

Roychem MTC CUSTOMER DRAWING

| | |
|-------------------------------|--------------|
| DWG. NO. | REV |
| MTC100Q-SHX-X2X-XXX | K |
| CAD FILE: MTC100Q-SHX-X2X-XXX | SHEET 2 OF 3 |

4


3


2

1

DWG NO. MTC100Q-SHX-X2X-XXX SHEET 2

THE FOLLOWING TABLE CONSISTS OF WEIGHTS FOR THESE SPECIFIC PART NUMBERS.

| TABLE II  | |
|--|----------------------|
| PART NUMBER | WEIGHT MAXIMUM GRAMS |
| MTC100Q-SH1-F22 | 29.9 |
| MTC100Q-SH1-P22 | 29.5 |
| MTC100Q-SH1-R22 | 26.2 |
| MTC100Q-SH2-F22 | 40.5 |
| MTC100Q-SH2-P22 | 39.7 |
| MTC100Q-SH2-R22 | 36.4 |
| MTC100Q-SH1-F23 | 19.0 |
| MTC100Q-SH1-P23 | 21.9 |
| MTC100Q-SH1-R23 | 18.6 |
| MTC100Q-SH2-F23 | 28.9 |
| MTC100Q-SH2-P23 | 28.1 |
| MTC100Q-SH2-R23 | 24.7 |

| TABLE IV  | |
|---|---|
| PANEL THICKNESS | NUMBER OF PANEL WASHERS FOR EACH FASTENER |
| 0 | 2 |
| 0.031/0.036 [0.8]/[0.9] | 1 |
| 0.062/0.067 [1.5]/[1.7] | 0 |







































FIGURE 1

| TABLE III  | | | | |
|---|------------|--------------|--------------|---------------|
| CONNECTOR SIZE | TYPE: | "X" | "Y" | "Z" (MIN) |
| 1 INCH | FLANGELESS | 1.750 [44.5] | 1.520 [38.6] | 0.400 [10.16] |
| | FLANGED | 1.750 [44.5] | 1.520 [38.6] | 0.600 [15.24] |
| 2 INCH | FLANGELESS | 2.750 [69.9] | 2.520 [64.0] | 0.400 [10.16] |
| | FLANGED | 2.750 [69.9] | 2.520 [64.0] | 0.600 [15.24] |

| TABLE VI  | | | | | |
|--|-------------|-----------------|------------|-------------------|--------------------|
| RECOMMENDED DUST CAP | | | | | |
| ITEM | PART NUMBER | USED WITH SHELL | | DUCT CAP MATERIAL | |
| | | SIZE | TYPE | POLYETHYLENE RED | ELECTROSTATIC PINK |
| 1 | D-659-0060 | 1" | PLUG | X | |
| 2 | D-659-0062 | 2" | PLUG | X | |
| 3 | CHA-1603 | 1" | RECEPTACLE | X | |
| 4 | CHA-1604 | 2" | RECEPTACLE | X | |
| 5 | CHA-0098 | 1" | PLUG | | X |
| 6 | CHA-0100 | 2" | PLUG | | X |
| 7 | CHA-0311 | 1" | RECEPTACLE | | X |
| 8 | CHA-0312 | 2" | RECEPTACLE | | X |

| TABLE V  | | |
|---|-------|---|
| SUGGESTED KEYING CODES | | |
|  | -A A- |  |
|  | -A B- |  |
|  | -A C- |  |
|  | -A D- |  |
|  | -B A- |  |
|  | -B B- |  |
|  | -B C- |  |
|  | -B D- |  |
|  | -C A- |  |
|  | -C B- |  |
|  | -C C- |  |
|  | -C D- |  |
|  | -D A- |  |
|  | -D B- |  |
|  | -D C- |  |
|  | -D D- |  |

RECEPTACLE FACE PLUG FACE

WHEN USING STANDARD RECTANGULAR KEYING PINS

If this document is printed it becomes uncontrolled. Check for the latest revision

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru