

1	2	3	4	5	6	7																														
E				<table><tr><td>SIGN</td><td>DATE</td><td>DESCRIPTION</td><td>APPROVER</td></tr><tr><td>△</td><td>10/20'08</td><td>Add APPROVAL: : CQC</td><td>Kind</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the screw plating specification</td><td>Jacky</td></tr><tr><td>△</td><td>12/05'12</td><td>Change the dimensional tolerance</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Add the view</td><td>Jacky</td></tr><tr><td>△</td><td>12/12'13</td><td>Change the withstand voltage and current</td><td>Jacky</td></tr><tr><td colspan="4"></td><td colspan="2">THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!</td></tr></table>		SIGN	DATE	DESCRIPTION	APPROVER	△	10/20'08	Add APPROVAL: : CQC	Kind	△	12/05'12	Change the screw plating specification	Jacky	△	12/05'12	Change the dimensional tolerance	Jacky	△	12/12'13	Add the view	Jacky	△	12/12'13	Change the withstand voltage and current	Jacky					THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!		E
				SIGN	DATE	DESCRIPTION	APPROVER																													
				△	10/20'08	Add APPROVAL: : CQC	Kind																													
				△	12/05'12	Change the screw plating specification	Jacky																													
				△	12/05'12	Change the dimensional tolerance	Jacky																													
△	12/12'13	Add the view	Jacky																																	
△	12/12'13	Change the withstand voltage and current	Jacky																																	
				THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!																																
D	MATERIALS ELECTRICAL		cULus	CQC																																
	RATED VOLTAGE & CURRENT:		250 V, 10 A	/ 250 V, 9A△5																																
	WITHSTAND VOLTAGE:		AC 2000 V/Min																																	
	INSULATION RESISTANCE:		1000 MΩOR MORE AT DC 500 V																																	
	OPERATING TEMPERATURE RANG:		-40 °C ~ +115 °C																																	
C				SCREW TORQUE VALUE:		5.3 Lb-In.																														
				WIRE RANGE:		22 - 18 AWG																														
				1) MOLDED PARTS:		Thermoplastic, UL 94 V-0 BLACK																														
				2) TERMINAL:		BRASS, 0.8t, Tin PLATED																														
				△ 3) TERMINAL SCREWS:		STEEL, M3																														
B				△ APPROVAL:																																
				PART NO.:																																
				Critical dimension:																																
				YK 223 xx 0 x x 00G																																
				NO. OF POLES		G: RoHS compliant (lead<4%) In copper Alloy																														
02: 2 POLES		MARK																																		
03: 3 POLES		0: "@" MARK																																		
04: 4 POLES		1: "ANY" MARK																																		
...		TERMINAL & SCREW PLATED																																		
30: 30 POLES		0: TERMINAL & SCREW: G/F																																		
		△ 1: TERMINAL: G/F, SCREW: Zinc																																		
		2: TERMINAL: Sn, SCREW: G/F																																		
		△ 3: TERMINAL: Sn, SCREW: Zinc																																		
A	N = Number of poles△ Dim A=Nx6.35+1.0 Dim B=(N-1)x6.35 <table><tr><td>Poles</td><td>Tol.</td><td>Dim A&B</td></tr><tr><td>2-5p</td><td>±0.20</td><td></td></tr><tr><td>6-10p</td><td>±0.25</td><td></td></tr><tr><td>11-16p</td><td>±0.35</td><td></td></tr><tr><td>17-24p</td><td>±0.40</td><td></td></tr><tr><td>25-30p</td><td>±0.50</td><td></td></tr></table>			Poles	Tol.	Dim A&B	2-5p	±0.20		6-10p	±0.25		11-16p	±0.35		17-24p	±0.40		25-30p	±0.50		<table><tr><td colspan="2">ANYTEK</td><td colspan="2">CUSTOMER COPY</td></tr><tr><td colspan="4">ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD</td></tr></table>		ANYTEK		CUSTOMER COPY		ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD								
				Poles	Tol.	Dim A&B																														
				2-5p	±0.20																															
				6-10p	±0.25																															
				11-16p	±0.35																															
17-24p	±0.40																																			
25-30p	±0.50																																			
ANYTEK		CUSTOMER COPY																																		
ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD																																				
TITLE		YK-223 Series																																		
PART NO.		YK223xx0xx00G																																		
DWG NO.		8YK0001-223																																		
APPROVED		CHECKED																																		
DESIGNED		DRAWN																																		
CUST NO.		Tolerance																																		
UNIT: mm		X. ±0.50																																		
SCALE: NONE		X.X ±0.30																																		
SHEET: 01/01		X.XX ±0.10																																		
REV.: F		X° ±1°																																		

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru