

CAT IV Insulation Tester/MultiMeter with Wireless PC Interface

Combines a 1000V Insulation Tester

With a full-featured True RMS MultiMeter in a single, compact instrument

Features:

- Wireless USB interface transmits measurement data to a PC
- Backlit super large triple display
- 125V, 250V, 500V, and 1000V test voltages
- Insulation Resistance from 0.001M Ω to 4000M Ω
- Auto discharge of capacitive voltage
- Lock Power On Function for hands-free operation
- Data Hold and Auto Power Off
- Min/Max and Relative mode
- Waterproof (IP67) rugged double-molded design
- Complete with remote receiver with USB cable, Windows[®] compatible software, heavy duty test leads, alligator clip test lead, Type K bead wire temperature probe with adapter, carrying case, and 6 x AA batteries



Measure the insulation resistance of transformer windings



Only a True RMS meter can give accurate readings of distorted waveforms



WIRELESS Transmitter

Continuous data streaming to your PC in real time

Specifications	Range	Resolution	Accuracy
Insulation Tester			
Insulation Resistance	4M Ω , 40M Ω , 400M Ω , 4000M Ω	0.001M Ω	$\pm 3\%$
Insulation Test Voltages	125V, 250V, 500V, 1000V		
Multimeter			
AC Voltage	1000V	0.1mV	$\pm 1\%$
DC Voltage	1000V	0.01mV	$\pm 0.06\%$
AC Current	10A	0.1 μ A	$\pm 1.5\%$
DC Current	10A	0.01 μ A	$\pm 1.0\%$
Resistance	40M Ω	0.01 Ω	$\pm 0.3\%$
Capacitance	40mF	0.001nF	$\pm 3.5\%$
Frequency	100MHZ	0.001HZ	$\pm 0.1\%$
Duty Cycle	0.1 to 99.9%	0.01	$\pm 1.2\%$
Temperature	-58 to 2192°F	0.1°F	$\pm 1\% + 4.5^\circ\text{F}$
	-50 to 1200°C	0.1°C	$\pm 1\% + 2.5^\circ\text{C}$
4-20mA%	-25 to 125%	0.01%	
Continuity/Diode	Yes		
Power source	6 x AA batteries		
Dimensions	7.8 x 3.6 x 1.9" (200 x 92 x 50mm)		
Weight	20.5oz (582g)		

Ordering Information:

MG300CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (915MHz)

MG300-NISTMG300 with Certificate of Calibration Traceable to NIST

MG302CAT IV Insulation Tester/True RMS MultiMeter w/Wireless PC Interface (433MHz)

MG302-NISTMG302 with Certificate of Calibration Traceable to NIST

TL805Double Injected Test Leads

(NOTE: USA, Mexico, and Canada use 915MHz model and majority of other countries use 433MHz model)



UL listed on MG300 only

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru