

Control Knobs

INSTRUMENT KNOBS



5200E, 5205E



5210E, 5220E



5240E, 5250E



5300E



5302E



5304E



5450E




5475E

FEATURES

- Phenolic material provides heat and impact resistance for durability
- Can be customized with decorative inlays, indicator lines, or slots
- Engraving, hot stamping, and pad printing available for a distinct appearance

Ohmite Part	A	Dimensions (inches)					Set screw	Shaft hole*	Finish **
5200E	25/32	15/32	21/32	13/32	7/32		M3 x 0.5	BB	SDL
5205E	1	27/32	29/32	1/2	37/64		M4 x 0.7	BB	SDL
5210E	19/32	11/32	15/32	33/64	21/32		M4 x 0.7	BB	SDL
5220E	13/4	115/32	11/2	45/64	13/16		M4 x 0.7	BB	SDL
5240E	19/32	35/64	31/64	27/64	23/64		M3 x 0.5	BB	L
5250E	15/16	25/32	3/4	19/32	19/32		M4 x 0.7	BB	L
5300E	17/32	5/8	3/8	7/32	7/16		6-32	PH	SCL
5302E	25/32	5/8	17/32	17/32	9/32		8-32	PH	SCL
5304E	11/32	11/16	7/8	17/32	9/32		8-32	PH	SCL
5450E	11/16	13/32	5/8	11/32	3/16		8-32	PH	-
5475E	1	1/2	15/16	7/16	9/32		8-32	PH	

*PH=Plain Hole BB=Brass Bushing **SDL=Silver Disc Lined; L=Lined; SCL=Silver Cap Lined



Material type: Thermoset
Inset diam.: 1/4 in.

POINTER KNOBS



5400E



5470E



5500E, 5520E,
5521E



5510E, 5511E



5522E



5600E, 5601E, 5602E




5610E

FEATURES

- Phenolic material provides heat and impact resistance for durability
- Terrific range of styles and sizes
- Indicator line available on several of the pointer knobs for precise settings
- Samples available

Ohmite Part	A	Dimensions (inches)				Set screw	Insert diam.	Shaft hole*	Finish **
5400E	27/32	13/32	11/32	3/16		8-32	1/4	PH	-
5470E	1	1/2	7/16	9/32		8-32	1/4	PH	L
5500E	11/8	9/16	9/32	9/32		8-32	1/4	PH	L
5510E	3/4	9/16	13/32	7/32		8-32	1/4	PH	L
5511E	3/4	9/16	7/16	-	-	1/4***		Spring	L
5520E	11/2	3/4	5/8	5/16		8-32	1/4	PH	L
5521E	11/2	3/4	7/16	5/16		8-32	1/4	BB	L
5522E	11/8	5/8	7/16	9/32		8-32	1/4	PH	L
5600E	17/32	5/8	1/2	9/32		8-32	1/4	PH	-
5601E	17/32	5/8	1/2	9/32		8-32	1/4	PH	L
5602E	17/32	5/8	9/32	9/32		8-32	1/4	BB	L
5610E	13/16	1/2	7/16	7/32		8-32	1/4	PH	-

*PH=Plain Hole BB=Brass Bushing **L=Lined ***1/4" flatted to 5/32"



Material type: Thermoset

Control Knobs

SKIRTED KNOBS

FEATURES


- Available in phenolic to provide appearance, strength, and heat resistance for a variety of applications
- Sizes, shapes, decorative inlays, and graphics to enhance your products
- Engraving, hot stamping, and pad printing available
- Skirt adds level of decoration
- Samples available



Ohmite Part	A	Dimensions (inches)					Set screw	Shaft hole*	Finish**
		B	C	D	E				
5700E	1/2	5/8	15/32	1/2	3/16	6-32	PH	-	
5701E	1/2	5/8	15/32	1/2	3/16	6-32	PH	L	
5710E	3/4	1/2	17/32	13/32	7/32	8-32	PH	L	
5713E	1 1/8	5/8	13/16	1/2	9/32	8-32	PH	L	
5719E	1 1/8	5/8	1 1/4	1/2	9/32	8-32	BB	L	
5730E	1 1/2	7/8	1 1/64	3/4	9/32	8-32	PH	SDL	
5740E	2 1/32	15/16	1 3/8	13/16	5/16	8-32 (2)	PH	SDL	
5800E	1 1/2	11/16	5/8	9/16	9/32	8-32	PH	L	

*PH=Plain Hole BB=Brass Bushing

**L=Lined SD=Silver Disc SDL=Silver Disc Lined



Material type: Thermoset
Inset diam.: 1/4 in.

TRANSILLUMINATED/SOFT TOUCH KNOBS

FEATURES

- Soft thermoplastic elastomer
- Two shot molding process enables multiple materials to be embedded into one part
- Available in black TPE over white or clear indicator to provide comfort and style to your application
- Call for any other color or combination
- Matte finish




5940E, 5920E, 5930E

Ohmite Part	A	Dimensions (inches)			
		B	C	D	E
Soft Touch Knobs					
5940E	1 3/8	27/32	1 3/8	23/32	1/4
5920E	1 5/8	61/64	1 5/8	7/8	9/32
5930E	1 57/64	1	1 57/64	7/8	5/16



5941E, 5921E, 5931E

Ohmite Part	A	Dimensions (inches)			
		B	C	D	E
Transilluminated Knobs					
5941E	1 3/8	27/32	1 3/8	23/32	1/4
5921E	1 5/8	61/64	1 5/8	7/8	1/4
5931E	1 57/64	1	1 57/64	7/8	9/32



Material type: Thermoplastic overmold

Inset diam.: 1/4 in.

Set screw: 8-32

Shaft hole: Brass bushing

Finish: Matte

CUSTOMIZATION



In order to save you time and money, Ohmite offers a wide array of secondary operations and finishing services. Most of our parts can be customized to your specific need. Our secondary operations and finishing services include:

- Hot Stamping
- Drilling
- Pad Printing
- Engraving
- Ultrasonic Welding
- Branding
- Paint Fill
- Decorative Pointers
- Machining
- Turning
- Tapping
- Bagging
- Buff and Polish
- Sand Blasting
- 3-D CAD Imaging
- Assembly
- Packaging
- Custom Color
- Matching
- Kitting
- Silk Screen
- Decorative Inlays
- Plating
- Vacuum Metalizing
- Paint Coatings

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru