REVISIONS			
LTR	DESCRIPTION	DATE	APPROVED
NC	RELEASED PER E.C.N. T-8409	87-7	I.M.
A	REVISED PER E.C.N. T-8576	87-9-2	I.M.
B	REVISED PER E.C.N. T-9548	88-4-7	I.M.
C	REVISED PER E.C.N. T-10386	88-7-15	Z.T.
D	REVISED PER E.C.N. T-14157	90-4-10	Z.T.
E	REVISED PER E.C.N. T-16949 "WAS" D-621-XXXX[-L]	92-1-6	Z.T.

-XXXX(-L) *

-0112(-L)
-0406(-L)
-0407(-L)
-0413(-L)
-0415(-L)
-0417(-L)
-0418(-L)
-0423(-L)
-0424(-L)



TRIAXIAL CONNECTOR, PLUG

SPECIFICATION CONTROL DRAWING

If this document is printed it becomes uncontrolled.
Check for the latest revision.

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES. METRIC DIMENSIONS ARE IN BRACKETS.

DECIMALS
.XXX ± .005 { mm }
.XX ± .01 { mm }

ANGLES
.X ±

WEIGHT: (2)

DRAWN	terry	87-6-22
CHECKED		
APPROVED		
APPROVED		
CAD NAME	003375-1	

THIRD ANGLE PROJECTION

tyco Electronics
Tyco Electronics Corporation
300 Constitutional Drive
Menlo Park, CA 94025 USA
Raychem

TITLE
THREADED
CORROSION RESISTANT CONNECTORIZED, RESISTOR TERMINATOR INCLUDING USAF NUMBERS

SIZE	CODE IDENT. NO.	DWG. NO.	REV
A	06090	D-621-0112/04XX[-L] *	E

DO NOT SCALE THIS DRAWING



MOUNTING HOLE DIMENSION



TRIAXIAL CONNECTOR, JACK

If this document is printed it becomes uncontrolled.
Check for the latest revision.

CAD NAME: 003375-2	DRAWN	J.B.K.	91 DEC 3	SIZE A	CODE IDENT. NO. 06090	DWG. NO. D-621-0112/04XX[-L]	REV E
	ISSUED			DO NOT SCALE THIS DRAWING		SHEET 2 OF 6	



TRIAXIAL CONNECTOR, PLUG

If this document is printed it becomes uncontrolled.
Check for the latest revision.

CAD NAME: 003375-3	DRAWN	J.B.K.	91 DEC 3	SIZE A	CODE IDENT. NO. 06090	DWG. NO. D-621-0112/04XX[-L]	REV E
	ISSUED			DO NOT SCALE THIS DRAWING		SHEET 3 OF 6	



TRIAXIAL CONNECTOR, JACK

If this document is printed it becomes uncontrolled.
Check for the latest revision.

CAD NAME: 003375-4	DRAWN	J.B.K.	91 DEC 3	SIZE A	CODE IDENT. NO. 06090	DWG. NO. D-621-0112/04XX[-L]	REV E
	ISSUED			DO NOT SCALE THIS DRAWING		SHEET 4 OF 6	

SEE SHEET 1 FOR REVISION

1.0 MATERIALS

1.1 PLUG BODY AND COUPLING NUT:	BRASS ALLOY PER ASTM B16
1.2 JACK BODY:	BECU PER QQ-C-530, ALLOY 173 CONDITION A OR H
1.3 PANEL NUT:	BRASS ALLOY PER ASTM B16
1.4 WAVE WASHER:	SPRING STEEL OR BECU, TIN PLATED PER MIL-T-10727
1.5 RESISTOR COVER:	STAINLESS STEEL TYPE 303 PER ASTM A582
1.6 LANYARD:	CORROSION RESISTANT STEEL
1.7 SEALING WASHER:	
1.7.1 ELASTOMER:	SILICONE PER AMS-3304
1.7.2 WASHER:	CORROSION RESISTANT STEEL PER MIL-S-5059 HALF HARD OR ANNEALED PASSIVATED PER QQ-P-35

2.0 FINISHES

2.1 1.1 THRU 1.6:	TIN PLATED PER MIL-T-10727 TYPE 1, OVER SUITABLE NICKEL UNDERPLATE TO WITHSTAND 500 HOUR SALT SPRAY TEST

3.0 INTERMATEABILITY

3.1 SEE TABLE

3.2 REFER TO RAYCHEM D-602-0126 AND D-602-0127 FOR CONTACT INTERMATEABILITY, MATERIAL AND DIMENSIONS.

4.0 PERFORMANCE CHARACTERISTICS

4.1 OPERATING TEMPERATURE: -65°C TO +125°C

4.2 POWER RATING: 1 WATT MAX.

4.3 INSULATION RESISTANCE: GREATER THAN 5K MEG

4.4 HIGH POTENTIAL, MATED, SEA LEVEL: 900 VOLTS AT 60 HZ

4.5 TERMINATOR RESISTANCE: SEE TABLE

4.6 REFER TO RAYCHEM SPECIFICATIONS D-6025 AND D-6020 FOR OTHER APPLICABLE PERFORMANCE AND QUALIFICATION REQUIREMENTS.

4.7 SALT SPRAY CORROSION RESISTANCE: 500 HOURS



R=SEE TABLE FOR RESISTANCE VALUE, SHEET 6 OF 6

If this document is printed it becomes uncontrolled.
Check for the latest revision.

CAD NAME: 003375-5	DRAWN	J.B.K.	91 DEC 3	SIZE A	CODE IDENT. NO. 06090	DWG. NO. D-621-0112/04XX[-L]	REV E
	ISSUED			DO NOT SCALE THIS DRAWING			SHEET 5 OF 6

NOTES:

1. SUFFIX "L" INDICATES PARTS WITH LANYARD.
2. WEIGHT: PLUG: 19 GRAMS MAX., WITH LANYARD 24 GRAMS MAX.
   JACK: 14 GRAMS MAX., WITH LANYARD 19 GRAMS MAX.

1 DRAWING NO.	CONN.	INSTALLED CONTACT	MATING CONNECTOR	MATING CONTACT	RESISTANCE VALUE ±2%
D-621-0112(-L)	PLUG	PIN	D-621-0412	SOCKET	50 OHMS
D-621-0406(-L)	JACK	SOCKET	D-621-0411	PIN	78 OHMS
D-621-0407(-L)	PLUG	SOCKET	D-621-0412	PIN	3000 OHMS
D-621-0413(-L)	PLUG	PIN	D-621-0412	SOCKET	78 OHMS
D-621-0415(-L)	PLUG	SOCKET	D-621-0412	PIN	78 OHMS
D-621-0417(-L)	PLUG	PIN	D-621-0412	SOCKET	3000 OHMS
D-621-0418(-L)	JACK	PIN	D-621-0411	SOCKET	78 OHMS
D-621-0423(-L)	JACK	PIN	D-621-0411	SOCKET	3000 OHMS
D-621-0424(-L)	JACK	SOCKET	D-621-0411	PIN	3000 OHMS

U.S. AIR FORCE SPECIAL MARKING	
AIR FORCE TERMINATOR	AIR FORCE DRAWING NO.
D-621-0406	8421525-00-04
D-621-0407	8421524-00-02
D-621-0413	8421524-00-03
D-621-0415	8421524-00-04
D-621-0417	8421524-00-01
D-621-0418	8421525-00-03
D-621-0423	8421525-00-01
D-621-0424	8421525-00-02

If this document is printed it becomes uncontrolled.
Check for the latest revision.

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru