

Asymmetric Dual N-Channel 30V (D-S) Power MOSFET

FEATURES

- Low $R_{DS(ON)}$ to minimize conductive losses
- Low gate charge for fast power switching
- 100% UIS and R_g tested
- Compliant to RoHS directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21

APPLICATIONS

- IPC
- VGA
- NB VCORE

KEY PERFORMANCE PARAMETERS



PARAMETER	TYPE	VALUE	UNIT
V_{DS}	Q1	30	V
	Q2	30	
$R_{DS(on)}$ (max)	$V_{GS} = 10V$	11.7	mΩ
		14.9	
	$V_{GS} = 4.5V$	3.6	
		5.5	
Q_g	Q1	4.6	nC
	Q2	25	



✓
RoHS
COMPLIANT

HALOGEN
FREE

PDFN56 Asymmetric Dual



Note: MSL 1 (Moisture Sensitivity Level) per J-STD-020

ABSOLUTE MAXIMUM RATINGS ($T_A = 25^\circ C$ unless otherwise noted)

PARAMETER	SYMBOL	Q1	Q2	UNIT
Drain-Source Voltage	V_{DS}	30	30	V
Gate-Source Voltage	V_{GS}	± 20	± 20	V
Continuous Drain Current ^(Note 1)	I_D	38	107	A
		10	20	
Pulsed Drain Current	I_{DM}	152	428	A
Single Pulse Avalanche Current ^(Note 2)	I_{AS}	16	26	A
Single Pulse Avalanche Energy ^(Note 2)	E_{AS}	38	101	mJ
Total Power Dissipation	P_D	30	69	W
		6	14	
Total Power Dissipation	P_D	2.2	2.4	W
		0.4	0.5	
Operating Junction and Storage Temperature Range	T_J, T_{STG}	- 55 to +150		°C

THERMAL PERFORMANCE

PARAMETER	SYMBOL	LIMIT		UNIT
		Q1	Q2	
Thermal Resistance – Junction to Case	$R_{\Theta JC}$	4.2	1.8	°C/W
Thermal Resistance – Junction to Ambient	$R_{\Theta JA}$	56	52	

Thermal Performance Note: $R_{\Theta JA}$ is the sum of the junction-to-case and case-to-ambient thermal resistances. The case-thermal reference is defined at the solder mounting surface of the drain pins. $R_{\Theta JA}$ is guaranteed by design while $R_{\Theta CA}$ is determined by the user's board design.

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)							
PARAMETER	CONDITIONS	SYMBOL	TYPE	MIN	TYP	MAX	UNIT
Static							
Drain-Source Breakdown Voltage	$V_{GS} = 0V, I_D = 250\mu\text{A}$	BV_{DSS}	Q1	30	--	--	V
	$V_{GS} = 0V, I_D = 250\mu\text{A}$		Q2	30	--	--	
Gate Threshold Voltage	$V_{GS} = V_{DS}, I_D = 250\mu\text{A}$	$V_{GS(\text{TH})}$	Q1	1.2	1.9	2.5	V
	$V_{GS} = V_{DS}, I_D = 250\mu\text{A}$		Q2	1.2	1.6	2.5	
Gate-Source Leakage Current	$V_{GS} = \pm 20V, V_{DS} = 0V$	I_{GSS}	Q1	--	--	± 100	nA
	$V_{GS} = \pm 20V, V_{DS} = 0V$		Q2	--	--	± 100	nA
Drain-Source Leakage Current	$V_{GS} = 0V, V_{DS} = 30V$	I_{DSS}	Q1	--	--	1	μA
	$V_{GS} = 0V, V_{DS} = 30V$			--	--	100	
	$T_J = 125^\circ\text{C}$		Q2	--	--	1	
	$V_{GS} = 0V, V_{DS} = 30V$			--	--	100	
	$V_{GS} = 0V, V_{DS} = 30V$			--	--		
Drain-Source On-State Resistance ^(Note 3)	$V_{GS} = 10V, I_D = 10A$	$R_{DS(\text{on})}$	Q1	--	8.8	11.7	$\text{m}\Omega$
	$V_{GS} = 4.5V, I_D = 9A$			--	12.8	14.9	
	$V_{GS} = 10V, I_D = 20A$		Q2	--	2.7	3.6	
	$V_{GS} = 4.5V, I_D = 16A$			--	3.7	5.5	
Forward Transconductance ^(Note 3)	$V_{DS} = 5V, I_D = 10A$	g_{fs}	Q1	--	27	--	S
	$V_{DS} = 5V, I_D = 20A$		Q2	--	47	--	
Dynamic ^(Note 4)							
Total Gate Charge	Q1 $V_{DS} = 15V, I_D = 10A$ Q2 $V_{DS} = 15V, I_D = 20A$	$Q_g(V_{GS}=10V)$	Q1	--	9.3	--	nC
			Q2	--	49	--	
Total Gate Charge	Q1 $V_{DS} = 15V, I_D = 9A$	$Q_g(V_{GS}=4.5V)$	Q1	--	4.6	--	nC
Gate-Source Charge			Q2	--	25	--	
Gate-Drain Charge	$V_{DS} = 15V, I_D = 16A$	Q_{gs}	Q1	--	2.1	--	nC
			Q2	--	7.3	--	
Input Capacitance	Q1 $V_{GS} = 0V, V_{DS} = 15V$ $f = 1.0\text{MHz}$	C_{iss}	Q1	--	1.8	--	pF
			Q2	--	12	--	
Output Capacitance	Q2 $V_{GS} = 0V, V_{DS} = 15V$ $f = 1.0\text{MHz}$	C_{oss}	Q1	--	142	--	pF
			Q2	--	388	--	
Reverse Transfer Capacitance	$V_{GS} = 0V, V_{DS} = 15V$ $f = 1.0\text{MHz}$	C_{rss}	Q1	--	26	--	pF
			Q2	--	276	--	
Gate Resistance	$f = 1.0\text{MHz}$	R_g	Q1	0.5	1.6	3.2	Ω
			Q2	0.5	1.5	3	

ELECTRICAL SPECIFICATIONS ($T_A = 25^\circ\text{C}$ unless otherwise noted)							
PARAMETER	CONDITIONS	SYMBOL	TYPE	MIN	TYP	MAX	UNIT
Switching <small>(Note 4)</small>							
Turn-On Delay Time	Q1 $V_{GS} = 10V, V_{DS} = 15V, I_D = 10A, R_G = 2\Omega$	$t_{d(on)}$	Q1	--	4.8	--	ns
			Q2	--	11	--	
Turn-On Rise Time	Q1 $V_{GS} = 10V, V_{DS} = 15V, I_D = 10A, R_G = 2\Omega$	t_r	Q1	--	65	--	
			Q2	--	79	--	
Turn-Off Delay Time	Q2 $V_{GS} = 10V, V_{DS} = 15V, I_D = 20A, R_G = 2\Omega$	$t_{d(off)}$	Q1	--	8.2	--	
			Q2	--	32	--	
Turn-Off Fall Time	Q1 $V_{GS} = 0V, I_S = 10A$	t_f	Q1	--	14	--	
			Q2	--	49	--	
Source-Drain Diode							
Forward Voltage <small>(Note 3)</small>	$V_{GS} = 0V, I_S = 10A$	V_{SD}	Q1	--	--	1.2	V
			Q2	--	--	1	
Reverse Recovery Time	Q1 $I_S = 10A, dI/dt = 100A/\mu\text{s}$	t_{rr}	Q1	--	33	--	ns
			Q2	--	14	--	
Reverse Recovery Charge	Q2 $I_S = 20A, dI/dt = 100A/\mu\text{s}$	Q_{rr}	Q1	--	19	--	nC
			Q2	--	8	--	

Notes:

1. Silicon limited current only.
2. Q1 : $L = 0.3mH, V_{GS} = 10V, V_{DD} = 30V, R_G = 25\Omega, I_{AS} = 16A$, Starting $T_J = 25^\circ\text{C}$
 Q2 : $L = 0.3mH, V_{GS} = 10V, V_{DD} = 30V, R_G = 25\Omega, I_{AS} = 26A$, Starting $T_J = 25^\circ\text{C}$
3. Pulse test: Pulse Width $\leq 300\mu\text{s}$, duty cycle $\leq 2\%$.
4. Switching time is essentially independent of operating temperature.


ORDERING INFORMATION

PART NO.	PACKAGE	PACKING
TSM5055DCR RLG	PDFN56 Asymmetric Dual	2,500pcs / 13" Reel


CHARACTERISTICS CURVES (Q1)

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature








On-Resistance vs. Gate-Source Voltage



CHARACTERISTICS CURVES (Q1)


($T_A = 25^\circ\text{C}$ unless otherwise noted)




CHARACTERISTICS CURVES (Q2)

($T_A = 25^\circ\text{C}$ unless otherwise noted)


Output Characteristics




Transfer Characteristics




On-Resistance vs. Drain Current




Gate-Source Voltage vs. Gate Charge



On-Resistance vs. Junction Temperature








On-Resistance vs. Gate-Source Voltage





CHARACTERISTICS CURVES (Q2)

($T_A = 25^\circ\text{C}$ unless otherwise noted)



PACKAGE OUTLINE DIMENSIONS (Unit: Millimeters)

PDFN56 Asymmetric Dual

SUGGESTED PAD LAYOUT (Unit: Millimeters)

MARKING DIAGRAM


- G** = Halogen Free
- Y** = Year Code
- WW** = Week Code (01~52)
- F** = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

ООО "ЛайфЭлектроникс"

"LifeElectronics" LLC

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибуторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибуторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помочь разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru