

PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

Part Number: [0878240015](#)
Status: **Active**
Description: 1.27mm (.050") Signal Pitch, 0.80mm (.031") SCSI Pitch, 1.27mm (.050") Power Pitch
SAS Receptacle, Vertical, Surface Mount, with Surface Mount Solder Tab, 2.54mm
(.100") PCB Thickness, 29 Circuits, with Cap, Embossed Tape on Reel, Leadfree

Documents:


[3D Model](#) [Product Specification PS-87824-029 \(PDF\)](#)
[Drawing \(PDF\)](#) [RoHS Certificate of Compliance \(PDF\)](#)

General

Product Family	I/O Connectors
Series	87824
Application	Board-to-Board
Comments	With Pick-and-Place Cap
Component Type	Receptacle
Product Name	SAS
Type	N/A

Physical

Boot Color	N/A
Circuits (Loaded)	29
Circuits (maximum)	29
Circuits Detail	Signal 7, SCSI 7, Power 15
Color - Resin	Black
Durability (mating cycles max)	500
Gender	Female
Keying to Mating Part	Yes
Lock to Mating Part	None
Material - Metal	Brass, Phosphor Bronze
Material - Plating Mating	Gold
Material - Plating Termination	Tin
Number of Rows	2
Orientation	Vertical
PC Tail Length (in)	0.000 In
PC Tail Length (mm)	0.00 mm
PCB Locator	Yes
PCB Retention	Yes
PCB Thickness Recommended (in)	0.100 In
PCB Thickness Recommended (mm)	2.54 mm
Packaging Type	Embossed Tape on Reel
Panel Mount	Yes
Pitch - Mating Interface (in)	0.031 In, 0.050 In
Pitch - Mating Interface (mm)	0.80 mm, 1.27 mm
Pitch - Term. Interface (in)	0.031 In, 0.050 In
Pitch - Term. Interface (mm)	0.80 mm, 1.27 mm
Plating min: Mating (µin)	30
Plating min: Mating (µm)	0.76
Plating min: Termination (µin)	102
Plating min: Termination (µm)	2.54
Polarized to Mating Part	Yes
Polarized to PCB	Yes
Surface Mount Compatible (SMC)	N/A
Temperature Range - Operating	0°C to +55°C
Termination Interface: Style	Surface Mount
Waterproof / Dustproof	No



EU RoHS

**ELV and RoHS
Compliant**

REACH SVHC

Not Reviewed

Halogen-Free

Status

Not Halogen-Free

China RoHS



**Need more information on product
environmental compliance?**

Email productcompliance@molex.com
For a multiple part number RoHS Certificate of
Compliance, [click here](#)

Please visit the [Contact Us](#) section for any
non-product compliance questions.

Search Parts in this Series

[87824Series](#)

Mates With



SFF-8482 Hard Disk Drive and Backplane
Plug. [87679](#) Serial ATA Device Plug with
Latch. [87703](#) Serial ATA Device Plug
without Jumper. [87799](#) Serial ATA Device
Plug with Jumper

Wire Size AWG	N/A
Electrical	
Current - Maximum per Contact	1.5A
Shielded	No
Voltage - Maximum	30V
Solder Process Data	
Duration at Max. Process Temperature (seconds)	10
Lead-free Process Capability	Reflow Capable (SMT only)
Max. Cycles at Max. Process Temperature	1
Process Temperature max. C	260
Material Info	
Reference - Drawing Numbers	
Product Specification	PS-87824-029
Sales Drawing	SD-87824-031

This document was generated on 04/09/2010


PLEASE CHECK WWW.MOLEX.COM FOR LATEST PART INFORMATION

PART NO	PACKAGING	QUANTITY	PICK & PLACE CAP	DIM S (2X) PEG HEIGHT	PCB THICKNESS
87824-0004	TRAY	50/TRAY	YES	3.70	4.57±0.10
87824-0008	TRAY	30/TRAY	NO	3.70	4.57±0.10
87824-0010	TAPE AND REEL	350/REEL	YES	3.70	4.57±0.10
87824-0013	TRAY	50/TRAY	YES	2.00	2.54±0.10
87824-0014	TRAY	30/TRAY	NO	2.00	2.54±0.10
87824-0015	TAPE AND REEL	350/REEL	YES	2.00	2.54±0.10




REVISED EC NO: S2009--0197 DRWN:KHLIM CHKD:CGOH APPR:BOXOK A	DESCRIPTION REV	QUALITY SYMBOLS ▽=0 ◇=0	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE MM ONLY		SCALE NTS	DESIGN UNITS METRIC	 THIRD ANGLE PROJECTION	
				mm	INCH	DRAWN BY KHLIM	DATE 2005/07/07	TITLE SERIAL ATTACH SCSI STD HEIGHT BACKPLANE SMT RECEPT (WITH SOLDER TAB)  MOLEX INCORPORATED		
			4 PLACES	± ---	± ---	CHECKED BY SHFONG	DATE 2005/07/15			
			3 PLACES	± ---	± ---	APPROVED BY SKTOH	DATE 2005/07/15			
			2 PLACES	± 0.20	± ---	MATERIAL NO. SEE TABLE				DOCUMENT NO. SD-87824-031
			1 PLACE	± ---	± ---	SHEET NO. 3 OF 4				
			ANGULAR ± 3 °		DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			

TRAY PACKAGING




NOTES:

1. PACKAGING QTY: 30PCS/TRAY
2. NO PICK AND PLACE CAP




DETAIL 4

- ## 1. LEADER AND TRAILER TAPE



2. PEELING OFF FORCE OF THE TOP TAPE: 80gf MAX.
(PEELING DIRECTION AS SHOWN IN FOLLOWING FIGURE)



3. PACKAGING QTY: 350 PCS/REEL
4. PACKAGING STANDARD IS AS PER EIA-481.
5. CONNECTOR COMES WITH PICK AND PLACE CAP.

REVISED	EC NO: S2009-0197	2008/09/15	DESCRIPTION	▽=0 ▽=0	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)	DIMENSION STYLE		SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION	
	DRWNS:KHL IM	2008/09/16					MM ONLY		NTS	METRIC		
	CHKD:CGH						DRAWN BY DATE		TITLE			
	APPR:BOBOK						CHECKED BY DATE		SERIAL ATTACH SCSI STD HEIGHT BACKPLANE SMT RECEPT (WITH SOLDER TAB)			
A	REV					4 PLACES ± --- ± --- 3 PLACES ± --- ± --- 2 PLACES ± 0.20 ± --- 1 PLACE ± --- ± --- ANGULAR ± 3 °	INCH	SKTOH	2005/07/15	MOLEX INCORPORATED		SHEET NO. 4 OF 4
								APPROVED BY DATE				
								MATERIAL NO.		DOCUMENT NO.		
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS						SEE TABLE		SD-87824-031				
						SIZE A3		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru