


## Ground modular terminal block - UT 4-PE/L/L - 3214360

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Ground modular terminal block, Connection method: Screw connection, Cross section: 0.14 mm<sup>2</sup> - 6 mm<sup>2</sup>, AWG: 26 - 10, Width: 6.2 mm, Height: 60.1 mm, Color: gray, Mounting type: NS 35/7,5, NS 35/15

### Product Features



### Key commercial data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 pc     |
| Minimum order quantity               | 50 pc    |
| Weight per Piece (excluding packing) | 31.2 GRM |
| Custom tariff number                 | 85369010 |
| Country of origin                    | Poland   |

### Technical data

#### General

|                                         |                                                       |
|-----------------------------------------|-------------------------------------------------------|
| Number of levels                        | 3                                                     |
| Number of connections                   | 5                                                     |
| Color                                   | gray                                                  |
| Insulating material                     | PA                                                    |
| Inflammability class according to UL 94 | V0                                                    |
| Maximum load current                    | 16 A (with 4 mm <sup>2</sup> conductor cross section) |
| Rated surge voltage                     | 6 kV                                                  |
| Pollution degree                        | 3                                                     |
| Surge voltage category                  | III                                                   |
| Insulating material group               | I                                                     |
| Connection in acc. with standard        | IEC 60947-7-1 / IEC 60947-7-2                         |
| Maximum load current                    | 36 A (with 6 mm <sup>2</sup> conductor cross section) |

# Ground modular terminal block - UT 4-PE/L/L - 3214360

## Technical data

### General

|                                                                       |                                                       |
|-----------------------------------------------------------------------|-------------------------------------------------------|
| Nominal current $I_N$                                                 | 30 A                                                  |
| Nominal voltage $U_N$                                                 | 500 V                                                 |
| Connection in acc. with standard                                      | IEC 60947-7-1                                         |
| Maximum load current                                                  | 36 A (with 6 mm <sup>2</sup> conductor cross section) |
| Nominal current $I_N$                                                 | 30 A (with 4 mm <sup>2</sup> conductor cross section) |
| Nominal voltage $U_N$                                                 | 500 V                                                 |
| Open side panel                                                       | nein                                                  |
| Shock protection test specification                                   | DIN EN 50274 (VDE 0660-514):2002-11                   |
| Back of the hand protection                                           | guaranteed                                            |
| Finger protection                                                     | guaranteed                                            |
| Test specification, oscillation, broadband noise                      | DIN EN 50155 (VDE 0115-200):2008-03                   |
| Test spectrum                                                         | Service life test category 1, class B, body mounted   |
| Test frequency                                                        | $f_1 = 5 \text{ Hz}$ to $f_2 = 150 \text{ Hz}$        |
| ASD level                                                             | $0.964 \text{ (m/s}^2\text{)}^2/\text{Hz}$            |
| Acceleration                                                          | 0.58 g                                                |
| Test duration per axis                                                | 5 h                                                   |
| Test directions                                                       | X-, Y- and Z-axis                                     |
| Oscillation, broadband noise test result                              | Test passed                                           |
| Test specification, shock test                                        | DIN EN 50155 (VDE 0115-200):2008-03                   |
| Shock form                                                            | Half-sine                                             |
| Acceleration                                                          | 5 g                                                   |
| Shock duration                                                        | 30 ms                                                 |
| Number of shocks per direction                                        | 3                                                     |
| Test directions                                                       | X-, Y- and Z-axis (pos. and neg.)                     |
| Shock test result                                                     | Test passed                                           |
| Temperature index, insulating material (DIN EN 60216-1 (VDE 0304-21)) | 130 °C                                                |
| Static insulating material application in cold                        | -60 °C                                                |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 6.2 mm  |
| End cover width  | 3.1 mm  |
| Length           | 92.7 mm |
| Height           | 60.1 mm |
| Height NS 35/7,5 | 61.7 mm |
| Height NS 35/15  | 69.2 mm |

### Connection data

|      |                                                                |
|------|----------------------------------------------------------------|
| Note | Please observe the current carrying capacity of the DIN rails. |
|------|----------------------------------------------------------------|

# Ground modular terminal block - UT 4-PE/L/L - 3214360

## Technical data

### Connection data

|                                                                                         |                               |
|-----------------------------------------------------------------------------------------|-------------------------------|
| Connection in acc. with standard                                                        | IEC 60947-7-1 / IEC 60947-7-2 |
| Connection method                                                                       | Screw connection              |
| Conductor cross section solid min.                                                      | 0.14 mm <sup>2</sup>          |
| Conductor cross section solid max.                                                      | 6 mm <sup>2</sup>             |
| Conductor cross section AWG/kcmil min.                                                  | 26                            |
| Conductor cross section AWG/kcmil max                                                   | 10                            |
| Conductor cross section flexible min.                                                   | 0.14 mm <sup>2</sup>          |
| Conductor cross section flexible max.                                                   | 6 mm <sup>2</sup>             |
| Min. AWG conductor cross section, stranded                                              | 26                            |
| Max. AWG conductor cross section, stranded                                              | 10                            |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup>          |
| Conductor cross section stranded, with ferrule without plastic sleeve max.              | 4 mm <sup>2</sup>             |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup>          |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 4 mm <sup>2</sup>             |
| 2 conductors with same cross section, solid min.                                        | 0.14 mm <sup>2</sup>          |
| 2 conductors with same cross section, solid max.                                        | 1.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, stranded min.                                     | 0.14 mm <sup>2</sup>          |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm <sup>2</sup>           |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.14 mm <sup>2</sup>          |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>           |
| Stripping length                                                                        | 9 mm                          |
| Internal cylindrical gage                                                               | A4                            |
| Screw thread                                                                            | M3                            |
| Tightening torque, min                                                                  | 0.6 Nm                        |
| Tightening torque max                                                                   | 0.8 Nm                        |
| Connection in acc. with standard                                                        | IEC 60947-7-1                 |
| Connection method                                                                       | Screw connection              |
| Conductor cross section solid min.                                                      | 0.14 mm <sup>2</sup>          |
| Conductor cross section solid max.                                                      | 6 mm <sup>2</sup>             |
| Conductor cross section AWG/kcmil min.                                                  | 26                            |
| Conductor cross section AWG/kcmil max                                                   | 10                            |
| Conductor cross section flexible min.                                                   | 0.14 mm <sup>2</sup>          |

## Ground modular terminal block - UT 4-PE/L/L - 3214360

### Technical data

#### Connection data

|                                                                                         |                      |
|-----------------------------------------------------------------------------------------|----------------------|
| Conductor cross section flexible max.                                                   | 6 mm <sup>2</sup>    |
| Min. AWG conductor cross section, stranded                                              | 26                   |
| Max. AWG conductor cross section, stranded                                              | 10                   |
| Conductor cross section flexible, with ferrule without plastic sleeve min.              | 0.14 mm <sup>2</sup> |
| Conductor cross section stranded, with ferrule without plastic sleeve max.              | 4 mm <sup>2</sup>    |
| Conductor cross section flexible, with ferrule with plastic sleeve min.                 | 0.14 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.                 | 4 mm <sup>2</sup>    |
| 2 conductors with same cross section, solid min.                                        | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, solid max.                                        | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded min.                                     | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded max.                                     | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, min. | 0.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, TWIN ferrules with plastic sleeve, max. | 1.5 mm <sup>2</sup>  |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, min.   | 0.14 mm <sup>2</sup> |
| 2 conductors with same cross section, stranded, ferrules without plastic sleeve, max.   | 1.5 mm <sup>2</sup>  |
| Stripping length                                                                        | 9 mm                 |
| Screw thread                                                                            | M3                   |
| Tightening torque, min                                                                  | 0.6 Nm               |
| Tightening torque max                                                                   | 0.8 Nm               |

### Classifications

#### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 5.1 | 27141141 |
| eCl@ss 6.0 | 27141120 |

#### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000901 |
| ETIM 5.0 | EC000901 |

### Approvals

#### Approvals

# Ground modular terminal block - UT 4-PE/L/L - 3214360

## Approvals

Approvals

UL Recognized / cUL Recognized / EAC / cULus Recognized

Ex Approvals

Approvals submitted

## Approval details

| UL Recognized  |       |       |       |   |
|-------------------------------------------------------------------------------------------------|-------|-------|-------|---|
|                                                                                                 |       | B     | C     | D |
| mm²/AWG/kcmil                                                                                   | 26-10 | 26-10 | 26-10 |   |
| Nominal current I <sub>N</sub>                                                                  | 16 A  | 16 A  |       |   |
| Nominal voltage U <sub>N</sub>                                                                  | 300 V | 300 V |       |   |


| cUL Recognized  |       |       |       |   |
|----------------------------------------------------------------------------------------------------|-------|-------|-------|---|
|                                                                                                    |       | B     | C     | D |
| mm²/AWG/kcmil                                                                                      | 26-10 | 26-10 | 26-10 |   |
| Nominal current I <sub>N</sub>                                                                     | 16 A  | 16 A  |       |   |
| Nominal voltage U <sub>N</sub>                                                                     | 300 V | 300 V |       |   |

|     |
|-----|
| EAC |
|-----|

|                                                                                                      |
|------------------------------------------------------------------------------------------------------|
| cULus Recognized  |
|------------------------------------------------------------------------------------------------------|

## Drawings

Circuit diagram





Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)