

Thermofit[®] Molded Parts
Specification Control Drawing

NOTES

1. All dimensions are in $\frac{\text{inches}}{[\text{millimeters}]}$; $\frac{\text{lbs}}{[\text{gms}]}$
2. Dimensions appearing in table are as follows:
- a - As Supplied
 - b - After Unrestricted Recovery
3. Coating is optional. As supplied dimensions appearing in table are for uncoated parts. When coating is added, entry diameters will be reduced by .06 max.
4. Molding ports are optional. When -00 modification number is specified molding ports will be located as shown.
5. Weight shown in table of dimensions is based on polyolefin part.





TABLE OF DIMENSIONS																
PART NUMBER	H		J			P	R	S	T	U	JO	PP	RR	HW	JW	Weight
	Min	Max	Min -3,-4, -25	Min -5,-6,-8, -12,-100	Max											
	a	b	a	a	b	±10%	Ref	Ref	Ref	Ref	±10%	±10%	±10%	±20%	±20%	Nom
222D211	.88	.45	.88	.55	.25	4.14	.73	.47	.12	.04	3.45	.27	.49	.06	.045	.01
	[22,4]	[11,4]	[22,4]	[14,0]	[6,4]	[105,2]	[18,5]	[11,9]	[3,05]	[1,02]	[87,6]	[6,9]	[12,4]	[1,52]	[1,14]	[5,0]
222D221	1.01	.59	1.01	.63	.29	4.88	.78	.60	.12	.04	3.90	.33	.59	.06	.045	.02
	[25,7]	[15,0]	[25,7]	[16,0]	[7,4]	[124,0]	[19,8]	[15,2]	[3,05]	[1,02]	[99,1]	[8,4]	[15,0]	[1,52]	[1,14]	[9,0]
222D232	1.16	.74	1.16	.72	.33	5.76	.82	.75	.12	.04	4.50	.41	.61	.07	.045	.02
	[29,5]	[18,8]	[29,5]	[18,3]	[8,4]	[146,3]	[20,8]	[19,1]	[3,05]	[1,02]	[114,3]	[10,4]	[15,5]	[1,78]	[1,14]	[9,0]
222D242	1.34	.90	1.34	.84	.38	6.78	.86	.90	.12	.04	5.22	.48	.62	.07	.045	.03
	[34,0]	[22,9]	[34,0]	[21,3]	[9,7]	[172,2]	[21,8]	[22,9]	[3,05]	[1,02]	[132,6]	[12,2]	[15,7]	[1,78]	[1,14]	[14,0]
222D253	1.47	1.16	1.47	.91	.41	7.29	.96	1.15	.12	.065	5.66	.61	.70	.08	.045	.03
	[37,3]	[29,5]	[37,3]	[23,1]	[10,4]	[185,2]	[24,4]	[29,2]	[3,05]	[1,65]	[143,8]	[15,5]	[17,8]	[2,03]	[1,14]	[14,0]
222D263	1.72	1.34	1.72	1.07	.48	8.41	1.08	1.32	.12	.065	6.66	.72	.78	.08	.045	.05
	[43,7]	[34,0]	[43,7]	[27,2]	[12,2]	[213,6]	[27,4]	[33,5]	[3,05]	[1,65]	[169,2]	[18,3]	[19,8]	[2,03]	[1,14]	[24,0]
222D274	1.97	1.62	1.97	1.24	.56	8.84	1.16	1.59	.12	.065	6.82	.83	.82	.09	.055	.10
	[50,0]	[41,1]	[50,0]	[31,5]	[14,2]	[224,5]	[29,5]	[40,4]	[3,05]	[1,65]	[173,2]	[21,1]	[20,8]	[2,29]	[1,40]	[46,0]
222D285	2.47	1.85	2.47	1.54	.69	8.95	1.31	1.81	.12	.08	6.62	.95	.92	.10	.055	.10
	[62,7]	[47,0]	[62,7]	[39,1]	[17,5]	[227,3]	[33,3]	[46,0]	[3,05]	[2,03]	[168,1]	[24,1]	[23,4]	[2,54]	[1,40]	[46,0]
222D296	2.73	2.35	2.73	1.70	.77	9.19	1.38	2.28	.12	.08	6.19	1.18	.93	.10	.055	.10
	[69,3]	[59,7]	[69,3]	[43,2]	[19,6]	[233,4]	[35,1]	[57,9]	[3,05]	[2,03]	[157,2]	[30,0]	[23,6]	[2,54]	[1,40]	[46,0]
222D299	3.22	2.64	3.22	2.01	.90	9.33	1.75	2.55	.12	.08	5.95	1.31	1.23	.10	.055	.11
	[81,8]	[67,1]	[81,8]	[51,1]	[22,9]	[237,0]	[44,5]	[64,8]	[3,05]	[2,03]	[151,1]	[33,3]	[31,2]	[2,54]	[1,40]	[48,0]

STE Raychem
TE Connectivity
TE CONNECTIVITY
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025
(415) 361-6055

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED.
CHECK FOR THE LATEST REVISION.

Revision : R
Date : 20APR11

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

Thermofit[®] Molded Parts
Specification Control Drawing

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

COMPATABILITY CHART					
MATERIAL DASH NO.	MATERIAL DESCRIPTION	RT SPEC	COATING SLASH NO.	COATING S NO.	COATING DESCRIPTION
-3	Polyolefin, Semi-rigid	RT-301	/42; /86; /87; /180	S-1017; S-1048; S-1052; S-1030	Adhesive
-4	Polyolefin, Flexible	RT-1304	/42; /86; /87; /180	S-1017; S-1048; S-1052; S-1030	Adhesive
-5	Elastomer, Flexible	RT-501	N/A		
-6	Silicone	RT-602	N/A		
-8	Polyolefin, Space	RT-1308	N/A		
-12	*VITON, Flexible	RT-1312	N/A		
-25	Elastomer, Fluid Resistant	RT-1325	/42; /86	S-1017; S-1048	Adhesive
-100	Polyolefin, Semi-flexible ZEROHAL™	RT-1323	/184	S-1030	Adhesive

*VITON is a Registered Trademark of Dupont

ORDERING INFORMATION

222D2XX -X -XX /XXX

Base part number _____

Material dash number _____
(See Compatability Chart)

Modification number _____
(If necessary, see front of scd binder
for a complete list)

Adhesive slash number _____
(If necessary, see Compatability Chart)

THIS DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE; CONSULT YOUR
NEAREST FIELD REPRESENTATIVE FOR CURRENT REVISION

STE Raychem
TE Connectivity
TE CONNECTIVITY
300 CONSTITUTION DRIVE
MENLO PARK, CALIFORNIA 94025
(415) 361-6055

Revision : R
Date : 20APR11

Part Number : 222D211 thru 299
Description : Boot, 90°, With Lip

CAD FILE MP92422

IF THIS DOCUMENT IS PRINTED IT BECOMES UNCONTROLLED.
CHECK FOR THE LATEST REVISION.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru