


Fiber Optic MT and MTP / MPO Cable Assemblies



Features & Benefits

- Provides connectorized interface for ribbon or ribbonized fiber
- Connector alignment is made with precision alignment pins
- Fanouts to simplex fiber connectors available
- Low loss interconnect
- Push-pull mating of MTP* for quick connections
- NTT compatible
- Consistent and repeatable performance

Applications

- High density interconnects for:
 - Telephony central office and local loop
 - Data communications
- Provides interconnect for parallel optical transmitters and receivers

Molex MT and MTP connectorized ribbon fiber cable assemblies provide reliable high performance interconnects of up to 12 fibers in a minimum footprint. The MT connectors utilize the precision molded NTT compatible ferrule that connects 4 to 12 fibers using bare ribbon or ruggedized ribbon cable. Alignment between mating ferrules is accomplished using 2 precision guide pins that are pre-installed in a designated male connector. Two holes in the female connector locate the pins providing repeatable core to core alignment of the fibers. The MT ferrules are kept in the mated condition with the aid of a spring clip.

The MTP assemblies utilize the same MT ferrules and package them in a push-pull keyed connector housing for quick and easy connection using the MTP adapter. Guide pins in the male connector maintain alignment with holes in the female connector while the adapter retains the connectors in the mated position.

Back reflection for singlemode assemblies is controlled by using an 8 degree angle polishing process. Fanouts to single fiber leads connectorized with Molex industry standard SC, FC, and ST[†] connectors are available to interconnect with the current installed base of transmitters, receivers and patch panels.

An "enhanced" version of the multifiber connector has been developed to provide a quick and reliable connection for multiple optical fibers. The "enhanced" connector is a more precise NTT compatible ferrule, connecting the fibers using bare ribbon or ruggedized ribbon cable. The "enhanced" version will incorporate the same footprint and alignment as the standard MT/MTP.

This "enhanced" connector will solve customers needs for a high density solution with minimal insertion loss. The "enhanced" MTP housing is yellow and the MT ferrule is keyed with a yellow line.

*MTP is a registered trademark of US Conec Ltd.

†ST, STII are trademarks of Lucent Technologies

Performance and Specifications


Characteristics	Units	Min.	Avg.	Max.	Comments
Insertion Loss:					
9/125μm SM fiber	dB	-	.35	0.75	-
62.5/125μm MM fiber	dB	-	.3	0.75	-
Enhanced 9/125μm SM fiber	dB	-	.14	0.45	-
Return Loss:					
Singlemode	dB	-	-	< 60	Angle polish
Temperature Range	°C	-40	-	+80	40 cycles, 0.05 dB maximum change
Durability	dB	-	-	<0.2	1000 mate/unmate cycles

Fiber Optic MT and MTP* / MPO Cable Assemblies




Mechanical Dimensions


MT Connector




MTP Connector



MTP Connector, 8 Degree



MTP Adapter




All dimensions in **INCHES**
mm

Fiber Optic MT and MTP* / MPO Cable Assemblies



Ordering Guide



1. Optical Fiber

A - Multimode, 50/125µm
B - Multimode, 62.5/125µm
D - Singlemode, 9/125µm

2. Cable Construction

RA - Bare ribbon fiber, 4 fibers
RB - Bare ribbon fiber, 8 fibers
RC - Bare ribbon fiber, 10 fibers
RD - Bare ribbon fiber, 12 fibers
RE - Ribbon cable, OFNR, 4 fibers
RF - Ribbon cable, OFNR, 8 fibers
RG - Ribbon cable, OFNR, 10 fibers
RH - Ribbon cable, OFNR, 12 fibers

3. Connector Style End 1

MM - MT compatible, male
MF - MT compatible, female
PM - MTP/MPO compatible, male
PF - MTP/MPO compatible, female

4. Finish End 1

M - Flat
P - Angle (singlemode)
Q - "Enhanced" angle (singlemode)

5. Connector Style End 2

AA - ST[†] compatible, polymer coupling nut
AB - ST compatible, metal coupling nut
AC - ST compatible, 90° boot, metal coupling nut
BA - STII[†] compatible
DA - FDDI, black housing
DB - ESCON[‡] compatible
EA - FC
EB - FC/APC, standard key
EC - FC/APC, tight fit key
FA - SC, standard
FB - SC, black housing, black boot
FC - SC, red housing, red boot
FD - SC, black housing, 90° black boot
FE - SC, red housing, 90° red boot
FF - SC/APC, green housing, green boot
FG - SC Duplex
GA - BSC
GB - BSC/APC
GC - BSCII
GD - BSCII/APC
HC - LC connector
MM - MT compatible, male
MF - MT compatible, female
PH - BMTP pin holder, male
PM - MTP/MPO compatible, male
PF - MTP/MPO compatible, female
ZZ - No connector (for End 2 only)

6. Finish End 2

A - Multimode, ceramic ferrule, standard PC⁺
B - Multimode, ceramic ferrule, enhanced PC
C - Singlemode, RL > 45 dB, super PC
D - Singlemode, RL > 55 dB, ultra PC
E - Singlemode, RL > 70 dB, APC
F - Multimode, stainless steel
M - Flat
P - Angle (SM)
Q - "Enhanced" angle (SM)
Z - No connector (for End 2 only)

7. Unit of Measure*

*Numeric values must be consistent
C - Centimeters
F - Feet
I - Inches
M - Meters

Conversion Chart

From	to	Multiply by
meter	inch	39.37
meter	foot	3.281
centimeter	inch	.394
meter	centimeter	100

8. Breakout Style End 2

A - No breakout
R - Ribbon to 900µm

[†]ST and STII are registered trademarks of Lucent Technologies

[‡]ESCON is a registered trademark of International Business Machines Corporation

Example 1

Customer desires a 62.5/125µm 12 fiber ribbon cable type OFNR jumper terminated with a male MTP connector and 12 SC connectors. The overall length is 20 meters with a break out length of 0.5 meters using 900µm jacketed fanout.

Ordering Format:

MXBRH-PMM-FAB-M020-A000-R0.5

Example 2

Customer desires a 62.5/125µm 8 fiber bare ribbon jumper terminated with a male MT and a female MT connector. The length is 3 feet.

Ordering Format:


MXBRB-MMM-MFM-F003-A000-A000

Fiber Optic MT and MTP* / MPO Cable Assemblies




Assembly Construction & Breakout Detail


MT to MT




MT to Simplex Fanout



MTP to MTP



MTP to Simplex Fanout



Standard Part Numbers

Order Number	Description
86181-0000	MTP adapter
86180-3001	MT spring clip (8 fibers or less)
86180-3201	MT spring clip (greater than 8 fibers)
86780-0010	MT spring fastener tool

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru