

3M™ Normal DIN 41612 Boardmount Socket

3 Row Type C (Rows A, B & C or A & C Filled)

73XX Series



- High density (64 or 96 position)
- Low mating force minimizes plating wear on contact surfaces
- High reliability contact design
- Solder tail options
- Individual connector coding with the 3435-1 keying plug
- Normal, straight boardmount socket

Date Modified: September 6, 2005

TS-0809-05
Sheet 1 of 2

Physical

Insulation
Material: Glass Filled Polyester (PBT)
Flammability: UL 94V-0
Color: Gray

Contact
Material: Phosphor Bronze
Plating
Underplate: 79 μ " (2.00 μ m) Nickel — QQ-N-290, Class 2
Wiping Area: 15 μ " (0.38 μ m) Gold — MIL-G-45204, Type II, Grade C
Solder Tails: 200 μ " (5.08 μ m) 90/10 Tin Lead — MIL-P-81728

File Replace by consolidated ts file:

Electrical

Current Rating: 3 A
Insulation Resistance: $> 1 \times 10^{12} \Omega$ at 1000 Vdc
Withstanding Voltage: 1000 Vrms at Sea Level
Contact Resistance: < 15 Milliohms


Environmental

Temperature Rating: -55°C to +125°C

UL File No.: E68080

3M™ Normal DIN 41612 Boardmount Socket 3 Row Type C (Rows A, B & C or A & C Filled)

73XX Series



Ordering Information

73XX-60XXTH

Contact Quantity
64
96

Row Filled
C = A, B & C
D = A & C

Soldertail Length
Dim A
2 = 2.5 [.10]
3 = 4.0 [.16]
5 = 13.0 [.51]

Keying Plug
(Order Separately)
3435-1000

TS-0809-05
Sheet 2 of 2

Important Notice

All statements, technical information, and recommendations related to 3M's products are based on information believed to be reliable, but the accuracy or completeness is not guaranteed. Before using this product, you must evaluate it and determine if it is suitable for your intended application. You assume all risks and liability associated with such use. Any statements related to the product which are not contained in 3M's current publications, or any contrary statements contained on your purchase order shall have no force or effect unless expressly agreed upon, in writing, by an authorized officer of 3M.



Electronics

6801 River Place Blvd.
Austin, TX 78726-9000
800/328-1368
www.3M.com/electronics

Warranty; Limited Remedy; Limited Liability.

This product will be free from defects in material and manufacture for a period of one (1) year from the time of purchase. **3M MAKES NO OTHER WARRANTIES INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE.** If this product is defective within the warranty period stated above, your exclusive remedy shall be, at 3M's option, to replace or repair the 3M product or refund the purchase price of the 3M product. **Except where prohibited by law, 3M will not be liable for any indirect, special, incidental or consequential loss or damage arising from this 3M product, regardless of the legal theory asserted.**



*Minimum 10%
Post-Consumer Fiber*

Printed in USA.

© 3M 2005

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru