


ASMB-MTB0-0A3A2

PLCC4 Tricolor Black Surface LED



Data Sheet



Description

For easy pick & place, the LEDs are shipped in EIA-compliant tape and reel. Every reel is shipped from a single intensity and color bin; except red color for better uniformity.

These LEDs are compatible with the reflow soldering process.

This super wide viewing angle at 115° together with the built-in reflector pushing up the intensity of the light output makes these LEDs suitable to be used in interior electronics signs.

The black top surface of the LED provides better contrast enhancement, especially in full color display.

Features




- Standard PLCC-4 package (Plastic Leaded Chip Carrier)
- LED package with diffused silicone encapsulation
- Using AlInGaP and InGaN dice technologies
- Typical viewing angle at 115°
- Compatible with reflow soldering process
- JEDEC MSL 3

Applications

- Indoor full color display

CAUTION: LEDs are ESD-sensitive. Please observe appropriate precautions during handling and processing. Refer to Avago Application Note AN-1142 for additional details.


Package Dimensions



Notes:

1. All Dimensions are in millimeters
2. Tolerance = ± 0.2 mm, unless otherwise specified
3. Terminal Finish: Ag plating

Lead Configuration		
1	Common Anode	
2	Cathode	Blue
3	Cathode	Green
4	Cathode	Red



Part Numbering System

A S M B - M T B 0 - 0 X₂ X₃ X₄ X₅




Table 1. Device Selection Guide

Parameter	Option Code	ASMB-MTB0-0A3A2		
		Red	Green	Blue
Intensity Bin	X ₂ X ₃ = A3	U1, U2, V1	W1, W2, X1	T1, T 2, U1
Color Bin	X ₄ = A	Full Range	A,B,D	A,B,C
Packaging Option	X ₅ = 2	Test Current: 20 mA		

Intensity Bin Limits

Bin ID	Min (mcd)	Max (mcd)
T1	285.0	355.0
T2	355.0	450.0
U1	450.0	560.0
U2	560.0	715.0
V1	715.0	900.0
V2	900.0	1125.0
W1	1125.0	1400.0
W2	1400.0	1800.0
X1	1800.0	2240.0

Tolerance of each bin limit $\pm 12\%$

Color Bin Limits

Red Color Bin Table

Bin ID	Dominant Wavelength		Chromaticity Coordinate				
	Min	Max					
Full range	619.0	629.0	x	0.6894	0.6752	0.6916	0.7066
			y	0.3104	0.3113	0.2950	0.2934

Tolerance of each bin limit is ± 1 nm

Green Color Bin Table

Bin ID	Dominant Wavelength		Chromaticity Coordinate				
	Min	Max					
A	525	531	x	0.1142	0.1624	0.2001	0.1625
			y	0.8262	0.7178	0.6983	0.8012
B	528	534	x	0.1387	0.1815	0.2179	0.1854
			y	0.8148	0.7089	0.687	0.7867
C	531	535	x	0.1625	0.2001	0.2238	0.1929
			y	0.8012	0.6983	0.683	0.7816

Tolerance of each bin limit is ± 1 nm

Blue Color Bin Table

Bin ID	Dominant Wavelength		Chromaticity Coordinate				
	Min	Max					
A	465	469	x	0.1355	0.1751	0.1680	0.1267
			y	0.0399	0.0986	0.1094	0.0534
B	467	471	x	0.1314	0.1718	0.1638	0.1215
			y	0.0459	0.1034	0.1167	0.0626
C	469	473	x	0.1267	0.168	0.1593	0.1158
			y	0.0534	0.1094	0.1255	0.0736

Tolerance of each bin limit is ± 1 nm

Table 2. Absolute Maximum Ratings ($T_A = 25\text{ }^{\circ}\text{C}$)

Parameter	Red	Green and Blue	Unit
DC forward current ^[1]	25	25	mA
Peak forward current ^[2]	100	100	mA
Power dissipation	65	90	mW
Reverse voltage	Not recommended for reverse bias		V
Maximum junction temperature T_j max	110		$^{\circ}\text{C}$
Operating temperature range	-40 to +100		$^{\circ}\text{C}$
Storage temperature range	-40 to +100		$^{\circ}\text{C}$

Notes:

1. Derate linearly as shown in Figure 4a and Figure 4b
2. Duty Factor = 10% Frequency = 1 kHz

Table 3. Optical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$)

Color	Luminous Intensity, I_v , mcd ^[1]			Dominant Wavelength, λ_d (nm) ^[2]			Peak Wavelength, λ_p (nm)	Viewing Angle $2\theta_{1/2}$ ($^{\circ}$) ^[3]
	Min.	Typ.	Max.	Min.	Typ.	Max.	Typ.	Typ.
Red	450	540	900	619.0	625.0	629.0	634	115
Green	1125	1600	2240	525.0	530.0	535.0	522	115
Blue	285	350	560	465.0	470.0	473.0	465	115

Notes:

1. The luminous intensity I_v is measured at the mechanical axis of LED package and it is tested in pulsing condition. The actual peak of the spatial radiation pattern may not be aligned with the axis.
2. The dominant wavelength is derived from the CIE Chromaticity Diagram and represents the perceived color of the device.
3. $\theta_{1/2}$ is the off-axis angle where the luminous intensity is $1/2$ the peak intensity

Table 4. Electrical Characteristics ($T_A = 25\text{ }^{\circ}\text{C}$)

Color	Forward Voltage, V_F (V) ^[1]			Reverse Voltage V_R @ 100 μA ^[2]	Reverse Voltage V_R @ 10 μA ^[2]	Thermal Resistance $R\theta_{J-P}$ ($^{\circ}\text{C}/\text{W}$)	
	Min.	Typ.	Max.	Min.	Min.	Single chip on	3 chips on
Red	1.8	2.1	2.6	4	-	609	653
Green	2.8	3.1	3.6	-	4	320	430
Blue	2.8	3.1	3.6	-	4	320	430

Notes:

1. Tolerance $\pm 0.1\text{ V}$.
2. Indicates product final testing condition. Reverse bias is not recommended.




Figure 1. Relative Intensity vs. Wavelength




Figure 2. Forward Current vs. Forward Voltage




Figure 3. Relative Intensity vs. Forward Current




Figure 4a. Maximum forward current vs. ambient temperature. (3 chips)




Figure 4b. Maximum forward current vs. ambient temperature. (single chip)




Figure 5a. Radiation Pattern for X axis




Figure 5a. Radiation Pattern for Y axis




Figure 5c. Component Axis for Radiation Patterns




Figure 6. Relative Intensity vs. Junction Temperature




Figure 7. Forward Voltage vs. Junction Temperature




Figure 8a. Recommended soldering land pattern




Figure 8b. LED configuration on land pattern




Figure 9. Recommended Pick and Place Nozzle Tip




Figure 10. Recommended leaded reflow soldering profile




Figure 11. Recommended Pb-free reflow soldering profile




Figure 12. Carrier Tape Dimension




Figure 13. Reel Dimension




Figure 14. Reel Orientation

Packaging Label


(i) Avago Mother Label (Available on MBB bags)

Avago TECHNOLOGIES STANDARD LABEL LS0002 RoHS Compliant Halogen Free e4 Max Temp 260C MSL3 (Q) QTY: Quantity	
(1P) Item: Part Number [Barcode]	
(1T) Lot: Lot Number [Barcode]	
LPN: [Barcode]	CAT: Intensity Bin [Barcode]
(9D)MFG Date: Manufacturing Date [Barcode]	BIN: Color Bin [Barcode]
(P) Customer Item: [Barcode]	
(V) Vendor ID: [Barcode]	(9D) Date Code: Date Code [Barcode]
DeptID: [Barcode]	Made In: Country of Origin [Barcode]


(ii) Avago Baby Label (Available on reel)

Avago TECHNOLOGIES BABY LABEL COSB001B	
(1P) PART #: Part Number [Barcode]	
(1T) LOT #: Lot Number [Barcode]	
(9D)MFG DATE: Manufacturing Date [Barcode]	QUANTITY: Packing Quantity [Barcode]
C/O: Country of Origin [Barcode]	(9D): DATE CODE: [Barcode]
(1T) TAPE DATE: [Barcode]	D/C: Date Code VF: CAT: INTENSITY BIN BIN: COLOR BIN

Example indicates luminous Intensity information for Red, Green and Blue, respectively, from label:



Example indicates color bin information for Green and Blue from label:



Note:

There will be no red color bin information appear on label as it is not binned and support with full distribution range.

Handling Precaution

The encapsulation material of the LED is made of silicone for better product reliability. Because silicone is a soft material, please avoid pressing on the silicone or poking it with a sharp object; this can damage the product and cause premature failure. When handling during assembly, hold the unit only by its body. For additional handling information and proper procedures, refer to Avago Application Note AN 5288.

Moisture Sensitivity

This product has a Moisture Sensitive Level 3 rating per JEDEC J-STD-020. For additional details and a review of proper handling procedures, refer to Avago Application Note AN5305, *Handling of Moisture Sensitive Surface Mount Devices*.

A. Storage before use

- An unopened moisture barrier bag (MBB) can be stored at <40 °C/90% RH for 12 months. If the actual shelf life has exceeded 12 months and the Humidity Indicator Card (HIC) indicates that baking is not required, then it is safe to reflow the LEDs per the original MSL rating.
- It is recommended that you do not open the MBB before assembly (e.g., for IQC).

B. Control after opening the MBB

- The Humidity Indicator Card (HIC) shall be read immediately upon opening of MBB.
- The LEDs must be kept at < 30 °C / 60% RH at all times and all high temperature related processes including soldering, curing or rework need to be completed within 168 hours.

C. Control for unfinished reel

- Unused LEDs must be stored in a sealed MBB with a desiccant or desiccator at < 5% RH.

D. Control of assembled boards

- If the PCB soldered with the LEDs is to be subjected to other high temperature processes, the PCB needs to be stored in a sealed MBB with a desiccant or desiccator at < 5% RH to ensure that all LEDs have not exceeded their floor life of 168 hours.

E. Baking is required if:

- The HIC indicator is not BROWN at 10% and is AZURE at 5%.
- The LEDs are exposed to condition of > 30 °C / 60% RH at any time.
- The LED floor life exceeded 168 hours.

The recommended baking condition is: 60 ± 5 °C for 20 hours.

Note:

All bin categories are established for classification of products. Products may not be available in all bin categories. Please contact your Avago representative for further information

DISCLAIMER: Avago's products and software are not specifically designed, manufactured or authorized for sale as parts, components or assemblies for the planning, construction, maintenance or direct operation of a nuclear facility or for use in medical devices or applications. Customer is solely responsible, and waives all rights to make claims against Avago or its suppliers, for all loss, damage, expense or liability in connection with such use.

For product information and a complete list of distributors, please go to our web site: www.avagotech.com

Avago, Avago Technologies, and the A logo are trademarks of Avago Technologies in the United States and other countries. Data subject to change. Copyright © 2005-2013 Avago Technologies. All rights reserved.
AV02-4186EN - June 19, 2013

Avago
TECHNOLOGIES

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru