

For more Information  
please call

1-800-Belden1



## Description:

Stranded silver-coated copper conductor insulation with extruded TFE Teflon.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

# Conductors	AWG	Stranding	Conductor Material
1	28	7x36	SPC - Silver Plated Copper

### Insulation

#### Insulation Material:

Insulation Material	Wall Thickness (mm)
TFE - Tetrafluoroethylene	0.254

### Overall Insulation

#### Overall Cabling

Overall Nominal Diameter: 0.889 mm

## Mechanical Characteristics (Overall)

Bulk Cable Weight: 1.935 Kg/Km

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

UL AWM Style:	1213
UL Rating:	105°C
EU CE Mark:	Yes
EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2002/95/EC (RoHS):	Yes
EU RoHS Compliance Date (mm/dd/yyyy):	04/01/2005
EU Directive 2002/96/EC (WEEE):	Yes
EU Directive 2003/11/EC (BFR):	Yes
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes
Military Specification:	MIL-W-16878/4 (Except For Stranding)
MIL Spec Rating:	600 V, 200°C

### Flame Test

UL Flame Test: VW-1

### Plenum/Non-Plenum

Plenum (Y/N): No

## Electrical Characteristics (Overall)

### Max. Recommended Current:

Description	Current
-------------	---------

Single conductor in ambient air of 30C	1.8 amps
--	----------

## Related Documents:

No related documents are available for this product

## Put Ups and Colors:

Item #	Putup	Ship Weight	Color	Notes	Item Desc
83001 001100	30 MT	0.045 KG	BROWN	E	#28 STR TFE BRN
83001 0011000	305 MT	0.454 KG	BROWN	E S	#28 STR TFE BRN
83001 002100	30 MT	0.045 KG	RED	E	#28 STR TFE RED
83001 0021000	305 MT	0.454 KG	RED	E S	#28 STR TFE RED
83001 003100	30 MT	0.045 KG	ORANGE	E	#28 STR TFE ORG
83001 0031000	305 MT	0.454 KG	ORANGE	E S	#28 STR TFE ORG
83001 004100	30 MT	0.045 KG	YELLOW	E	#28 STR TFE YEL
83001 0041000	305 MT	0.454 KG	YELLOW	E S	#28 STR TFE YEL
83001 005100	30 MT	0.045 KG	GREEN, DARK	E	#28 STR TFE GRNDK
83001 0051000	305 MT	0.454 KG	GREEN, DARK	E S	#28 STR TFE GRNDK
83001 006100	30 MT	0.045 KG	BLUE, LIGHT	E	#28 STR TFE BLULT
83001 0061000	305 MT	0.454 KG	BLUE, LIGHT	E S	#28 STR TFE BLULT
83001 007100	30 MT	0.045 KG	VIOLET	E	#28 STR TFE VIO
83001 0071000	305 MT	0.454 KG	VIOLET	E S	#28 STR TFE VIO
83001 008100	30 MT	0.045 KG	GRAY	E	#28 STR TFE GRY
83001 0081000	305 MT	0.454 KG	GRAY	E S	#28 STR TFE GRY
83001 009100	30 MT	0.045 KG	WHITE	E	#28 STR TFE WHT
83001 0091000	305 MT	0.454 KG	WHITE	E S	#28 STR TFE WHT
83001 010100	30 MT	0.045 KG	BLACK	E	#28 STR TFE BLK
83001 0101000	305 MT	0.454 KG	BLACK	E S	#28 STR TFE BLK

**Notes:**

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'  
 S = STRIPING ADDERS FOR TYPES E AND EE: 123 STRIPES. MINIMUM ORDER 10

Revision Number: 2    Revision Date: 03-04-2009

© 2011 Belden, Inc  
 All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale. Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product. Belden declares this product to be in compliance with EU LVD (Low Voltage Directive 73/23/EEC), as amended by directive 93/68/EEC.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)