



PROPRIETARY INFORMATION NOTICE

This document and the designs, specifications, and engineering information disclosed herein are the property of Parlex Corp., and are not to be disseminated or reproduced without expressed written consent. This document is loaned in confidence and then only for consideration of the matter disclosed hereon. In accepting loan of this document, the recipient agrees to keep it and the matter disclosed hereon in confidence and not to use or permit their use in any way detrimental to Parlex Corp.

Non RoHS Part Numbering System

PS-1635-XX B

↑ CHARACTER INDICATING REVISION
LEVEL OF SPECIFICATION DRAWING.
↑ SPACE
↑ TWO DIGIT NUMBER INDICATING TOTAL
NUMBER OF CONDUCTORS.
↑ DASH
↑ INDICATES DRAWING SPECIFICATION
FOR 2.54MM PITCH BULK CABLE
WITH PIN #1 DESIGNATED AS TINNED.

i.e. PS-1635-20 B
(INDICATES 20 POS. CABLE, 2.54MM PITCH,
COND. #1 TINNED)

RoHS Part Numbering System

PSR1635-XX B

↑ CHARACTER INDICATING REVISION
LEVEL OF SPECIFICATION DRAWING.
↑ SPACE
↑ TWO DIGIT NUMBER INDICATING TOTAL
NUMBER OF CONDUCTORS.
↑ DASH
↑ "R" INDICATES CABLE IS RoHS COMPLIANT
↑ INDICATES DRAWING SPECIFICATION
FOR 2.54MM PITCH BULK CABLE
WITH PIN #1 DESIGNATED AS TINNED.

i.e. PSR1635-20 B
(INDICATES 20 POS. CABLE, 2.54MM PITCH,
COND. #1 TINNED, RoHS COMPLIANT)

- 1) BULK CABLE SPECIFICATION FOR 2.54MM PITCH FLAT LAMINATED CABLE.
- 2) NUMBER OF CONDUCTORS AVAILABLE 1 THROUGH 99
- 3) CONDUCTOR NUMBER 1 IS DISTINGUISHED FROM REMAINING CONDUCTORS BY TIN PLATING. IT IS VISIBLE, AS SUCH, THROUGH POLYESTER INSULATION.
- 4) INSULATION: 0.002" THICK POLYESTER WITH FLAME RETARDANT ADHESIVE.
- 5) CONDUCTORS: 0.003" X 0.050" FLAT COPPER, POS. #1 IS TIN PLATED (27 AWG EQUIVALENT)
- 6) U.L. RATING: AWM STYLE 2643, 105°C, VW-1, 300V
- 7) CURRENT RATING: 3A MAXIMUM
- 8) DIELECTRIC STRENGTH: 2500V/MIL
- 9) WHEN ORDERING, USE PART NUMBERING SYSTEM DESCRIBED TO DETERMINE NUMBER OF CONDUCTORS REQUIRED
- 10) CABLE WIDTH= (NUMBER OF CONDUCTORS +1) X 0.100"

PARLEX CORPORATION
One Parlex Place
Methuen, Ma 01844
LAMINATED CABLE DIVISION

SPECIFICATION DRAWING FOR BULK
CABLE, 2.54MM PITCH, COND. #1 TINNED,
MATCHING STANDARD AMP REQUIREMENTS
FOR .100" CENTERLINE FFC

SIZE	FSCM	PS-1635	Rev.
B	18377		B
SCALE	NA		SHEET 1 OF 1

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru