



For more Information  
please call

1-800-Belden1



## Description:

19 AWG solid .037" silver-coated copper-covered steel conductor, plenum, TFE Teflon® insulation, double silver-coated copper braid shield (96% coverage), FEP jacket.

## Physical Characteristics (Overall)

### Conductor

#### AWG:

| # Coax | AWG | Stranding | Conductor Material                         | Dia. (mm) |
|--------|-----|-----------|--|-----------|
| 1      | 19  | Solid     | SCCCS - Silver-coated Copper-covered Steel | 0.940     |

### Insulation

#### Insulation Material:

| Insulation Trade Name | Insulation Material       | Dia. (mm) |
|-----------------------|---------------------------|-----------|
| Teflon®               | TFE - Tetrafluoroethylene | 2.9464    |

### Outer Shield

#### Outer Shield Material:

| Layer # | Type  | Outer Shield Material | Coverage (%) |
|---------|-------|-----------------------|--------------|
| 1       | Braid | Silver-coated Copper  | 96           |
| 1       | Braid | Silver-coated Copper  | 94           |

### Outer Jacket

#### Outer Jacket Material:

| Outer Jacket Material                |
|--------------------------------------|
| FEP - Fluorinated Ethylene Propylene |

### Overall Cabling

Overall Nominal Diameter: 4.953 mm

## Mechanical Characteristics (Overall)

Operating Temperature Range: -70°C To +200°C

UL Temperature Rating: 200°C

Bulk Cable Weight: 63.993 Kg/Km

Max. Recommended Pulling Tension: 649.437 N

Min. Bend Radius (Install)/Minor Axis: 50.800 mm

## Applicable Specifications and Agency Compliance (Overall)

### Applicable Standards & Environmental Programs

NEC/(UL) Specification: CMP

CEC/C(UL) Specification: CMP

EU CE Mark: No

EU Directive 2000/53/EC (ELV): Yes

EU Directive 2002/95/EC (RoHS): Yes

EU RoHS Compliance Date (mm/dd/yyyy): 04/01/2005

EU Directive 2002/96/EC (WEEE): Yes

|                                   |                          |
|-----------------------------------|--------------------------|
| EU Directive 2003/11/EC (BFR):    | Yes                      |
| CA Prop 65 (CJ for Wire & Cable): | Yes                      |
| MII Order #39 (China RoHS):       | Yes                      |
| Military Specification:           | MIL-C-17G, M17/158-00001 |
| RG Type:                          | 142B/U                   |

### Flame Test

|                                 |                               |
|---------------------------------|-------------------------------|
| UL Flame Test:                  | VW-1, NFPA 262                |
| C(UL) Flame Test:               | FT6                           |
| Other Information (Trademarks): | Teflon® is a DuPont trademark |

### Plenum/Non-Plenum

|               |     |
|---------------|-----|
| Plenum (Y/N): | Yes |
|---------------|-----|

## Electrical Characteristics (Overall)

#### Nom. Characteristic Impedance:

| Impedance (Ohm) |
|-----------------|
| 50              |

#### Nom. Inductance:

| Inductance (µH/m) |
|-------------------|
| 0.219827          |

#### Nom. Capacitance Conductor to Shield:

| Capacitance (pF/m) |
|--------------------|
| 95.149             |

#### Nominal Velocity of Propagation:

| VP (%) |
|--------|
| 70%    |

#### Nominal Delay:

| Delay (ns/m) |
|--------------|
| 4.85588      |

#### Nom. Conductor DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 63.3233             |

#### Nominal Outer Shield DC Resistance:

| DCR @ 20°C (Ohm/km) |
|---------------------|
| 7.5463              |

#### Nom. Attenuation:

| Freq. (MHz) | Attenuation (dB/100m) |
|-------------|-----------------------|
| 10          | 3.6091                |
| 50          | 8.5306                |
| 100         | 12.4678               |
| 200         | 17.7174               |
| 400         | 25.9199               |
| 700         | 35.1067               |
| 900         | 40.3563               |
| 1000        | 42.9811               |
| 2000        | 63.3233               |
| 3000        | 79.4002               |
| 5000        | 106.961               |
| 8000        | 141.739               |

#### Max. Operating Voltage - UL:

| Voltage   |
|-----------|
| 150 V RMS |

#### Max. Operating Voltage - Other:

| Voltage    | Description |
|------------|-------------|
| 1400 V RMS | Military    |

## Misc. Information (Overall)

## Notes (Overall)

**Notes:** Non-SWR swept version of RG-142. Teflon® is a registered trademark of E. I. duPont de Nemours and Co. used under license by Belden, Inc.

## Related Documents:

No related documents are available for this product

## Put Ups and Colors:

| Item #        | Putup  | Ship Weight | Color | Notes | Item Desc          |
|---------------|--------|-------------|-------|-------|--------------------|
| 83242 001100  | 30 MT  | 2.359 KG    | BROWN | C E   | M17/158-00001 COAX |
| 83242 0011000 | 305 MT | 19.958 KG   | BROWN | C E   | M17/158-00001 COAX |
| 83242 001500  | 152 MT | 9.979 KG    | BROWN | C E   | M17/158-00001 COAX |

**Notes:**

C = CRATE REEL PUT-UP.

E = MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'

Revision Number: 3    Revision Date: 03-07-2008

© 2011 Belden, Inc  
All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described herein are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "AS IS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with EU RoHS (Directive 2002/95/EC, 27-Jan-2003). Material manufactured prior to the compliance date may be in stock at Belden facilities and in our Distributor's inventory. The information provided in this Product Disclosure, and the identification of materials listed as reportable or restricted within the Product Disclosure, is correct to the best of Belden's knowledge, information, and belief at the date of its publication. The information provided in this Product Disclosure is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. This Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)  
Email: org@lifeelectronics.ru