



Doc. Number: TTDS-239
Issue: 1
Date: July 2011

TECHNICAL DATASHEET

T200-LABEL-PRINTER

APPLICATION / USE

This is our budget label printer designed for low volume printing of TE Connectivity label products.



ORDER INFORMATION

T200-LABEL-PRINTER (Standard Printer)

Part number: [ED8415-000](#)

T200-LABEL-SWARE-PRINTER (Print System with PEP-5-Express included)

Part number: [ED8416-000](#)

Author: P A Crofts
Print date: 6-Jul-11
Issue date: July 2011:
Page: 1 of 3

While TE Connectivity has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Doc. Number: TTDS-239
Issue: 1
Date: July 2011

TECHNICAL DATASHEET

T200-LABEL-PRINTER

SOFTWARE

WINTOTAL-5
PEP-5- (Express, Pro, Suite)

APPROVALS

FCC, CE, C-tick, TUV, UL, CCC.

The printer's 200dpi resolution combined with recommended media and Thermal Transfer ribbons, meet all relevant TE Connectivity RW specifications.

OPERATING TEMPERATURE

5°C to 40°C (40°F to 104°F). 25 to 85% non-condensing RH.

PRINTER PROPERTIES	PERFORMANCE
PRINT SPEED	Max 127mm/s (recommended 50mm/s).
PRINT WIDTH MAX:	108.0 mm
PRINT LENGTH MIN	8.0 mm
PRINT LENGTH MAX	995mm
PRINTING METHOD	203 dpi Thermal Transfer
LABEL WIDTH	25.4 to 112mm (backing paper width)
INK RIBBONS	See TE Connectivity ribbons below, ink side out
CUT MODE	Full cutter available as extra
ELECTRICAL REQUIREMENTS:	100 to 240V AC, 50/60Hz, with universal power supply
PHYSICAL CHARACTERISTICS:	Depth: 258mm Height: 173mm Width: 198mm Weight: 2.4 kg
INTERFACES:	RS-232C (max. 115,200 bps), Centronics (Parallel), USB 2.0 (Full Speed), LAN 10/100 Base (Ethernet)

Author: P A Crofts
Print date: 6-Jul-11
Issue date: July 2011:
Page: 2 of 3

While TE Connectivity has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.



Doc. Number: TTDS-239
Issue: 1
Date: July 2011

TECHNICAL DATASHEET

T200-LABEL-PRINTER

APPROVED LABEL PRODUCTS

PRODUCT	Ribbon
HPK	1330-0607-T200
Tedlar (TTVF/PVF)	1330-3300-101TT
Decals (TTP)	1330-0607-T200
SOLAR LABELS	1330-0607-T200
Self Lams (SBP)	TMS-RJS-RIBBON-4RPSCE
Self Lams (PVF)	1330-3300-101TT
Self Lams (SP)	1330-0607-T200
Kapton (T1K/T2K)	1330-0619-T200
Nylon Cloth (NC)	1330-0607-T200
Polyesters (WP/MP/HW/HM/MV/HMM)	1330-0607-T200
Destructible Polyethylene (TN)	1330-0607-T200
White Vinyl (WV)	1330-0607-T200
Paper (EP)	1330-0600-T200
EET (P-8A, P-9, P-4)	1330-TTB-T200
EET (PY-9)	1330-TTB-T200
EET (G-4)	1330-TTB-T200
EET (V-8A, V-4-W, SL..., V-4-W)	1330-TTB-T200
EET (V-9)	1330-TTB-T200
EET (K-9)	1330-TTB-T200

Product is compliant to EU RoHS Directive 2002/95/EC. This compliance information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information provided by our suppliers. This information is subject to change. For the latest compliance status, visit the TE Connectivity RoHS Customer Support Center - <http://www.tycoelectronics.com/customersupport/rohssupportcenter>

TE Connectivity (Logo) is a trademark.

Other logos, product and Company names mentioned herein may be trademarks of their respective owners.

Author: P A Crofts
Print date: 6-Jul-11
Issue date: July 2011:
Page: 3 of 3

While TE Connectivity has made every reasonable effort to ensure the accuracy of the information in this datasheet, TE does not guarantee that it is error-free, nor does TE make any other representation, warranty or guarantee that the information is accurate, correct, reliable or current. TE reserves the right to make any adjustments to the information contained herein at any time without notice. TE expressly disclaims all implied warranties regarding the information contained herein, including, but not limited to, any implied warranties of merchantability or fitness for a particular purpose. The dimensions in this document are for reference purposes only and are subject to change without notice. Specifications are subject to change without notice. Consult TE for the latest dimensions and design specifications.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru

www.lifeelectronics.ru