64Mbit DDR SDRAM

1M x 16Bit x 4 Banks
Double Data Rate Synchronous DRAM

Revision 1.1

August 2002

Samsung Electronics reserves the right to change products or specification without notice.

Revision History

Revision 1.1 (August 6, 2002)
• Typo corrected

Revision 1.0 (June 17, 2002)
• Defined DC spec

Revision 0.1 (May 20, 2002) - *Target Spec*
• Typo corrected

Revision 0.0 (April 30, 2002) - *Target Spec*
• Defined Target Specification

1M x 16Bit x 4 Banks Double Data Rate Synchronous DRAM with Bi-directional Data Strobe and DLL

FEATURES

- 3.3V ± 5% power supply for device operation
- 2.5V ± 5% power supply for I/O interface
- SSTL_2 compatible inputs/outputs
- 4 banks operation
- MRS cycle with address key programs
  - -. Read latency 3 (clock)
  - -. Burst length (2, 4 and 8)
  - -. Burst type (sequential & interleave)
- All inputs except data & DM are sampled at the positive going edge of the system clock
- Differential clock input
- No Wrtie-Interrupted by Read Function
- 2 DQS's (1DQS / Byte)
- Data I/O transactions on both edges of Data strobe
- DLL aligns DQ and DQS transitions with Clock transition
- Edge aligned data & data strobe output
- Center aligned data & data strobe input
- DM for write masking only
- Auto & Self refresh
- 64ms refresh period (4K cycle)
- 66pin TSOP-II
- Maximum clock frequency up to 300MHz
- Maximum data rate up to 600Mbps/pin

ORDERING INFORMATION


Part NO.	Max Freq.	Max Data Rate	Interface	Package
K4D64163HF-TC33	300MHz	600Mbps/pin	SSTL_2	66 pin TSOP-II
K4D64163HF-TC36	275MHz	550Mbps/pin		
K4D64163HF-TC40	250MHz	500Mbps/pin		
K4D64163HF-TC50	200MHz	400Mbps/pin		
K4D64163HF-TC60	166MHz	333Mbps/pin		

GENERAL DESCRIPTION

FOR 1M x 16Bit x 4 Bank DDR SDRAM

The K4D64163H is 67,108,864 bits of hyper synchronous data rate Dynamic RAM organized as 4 x1,048,576 words by 16 bits, fabricated with SAMSUNG's high performance CMOS technology. Synchronous features with Data Strobe allow extremely high performance up to 1.2GB/s/chip. I/O transactions are possible on both edges of the clock cycle. Range of operating frequencies, programmable burst length and programmable latencies allow the device to be useful for a variety of high performance memory system applications.

PIN CONFIGURATION (Top View)



PIN DESCRIPTION


CK,$\overline{CK}$	Differential Clock Input	BA_0, BA_1	Bank Select Address
CKE	Clock Enable	A_0 ~A_{11}	Address Input
$\overline{CS}$	Chip Select	DQ_0 ~ DQ_{15}	Data Input/Output
$\overline{RAS}$	Row Address Strobe	V_{DD}	Power
$\overline{CAS}$	Column Address Strobe	V_{SS}	Ground
WE	Write Enable	V_{DDQ}	Power for DQ's
LDQS,UDQS	Data Strobe	V_{SSQ}	Ground for DQ's
LDM,UDM	Data Mask	NC	No Connection

INPUT/OUTPUT FUNCTIONAL DESCRIPTION

Symbol	Type	Function
CK, $\overline{CK}$*1	Input	The differential system clock Input. All of the inputs are sampled on the rising edge of the clock except DQ's and DM's that are sampled on both edges of the DQS.
CKE	Input	Activates the CK signal when high and deactivates the $\overline{CK}$ signal when low. By deactivating the clock, CKE low indicates the Power down mode or Self refresh mode.
$\overline{CS}$	Input	$\overline{CS}$ enables the command decoder when low and disabled the command decoder when high. When the command decoder is disabled, new commands are ignored but previous operations continue.
$\overline{RAS}$	Input	Latches row addresses on the positive going edge of the CK with $\overline{RAS}$ low. Enables row access & precharge.
$\overline{CAS}$	Input	Latches column addresses on the positive going edge of the CK with $\overline{CAS}$ low. Enables column access.
$\overline{WE}$	Input	Enables write operation and row precharge. Latches data in starting from $\overline{CAS}$, $\overline{WE}$ active.
LDQS,(U)DQS	Input/Output	Data Strobe : Output with read data, input with write data. Edge-aligned with read data, centered in write data. Used to capture write data. For the x16, LDQS corresponds to the data on DQ0-DQ7 ; UDQS corresponds to the data on DQ8-DQ15.
LDM,UDM	Input	Input Data Mask : DM is an input mask signal for write data. Input data is masked when DM is sampled HIGH along with that input data during a WRITE access. DM is sampled on both edges of DQS. DM pins include dummy loading internally, to matches the DQ and DQS loading. For the x16, LDM corresponds to the data on DQ0-DQ7 ; UDM correspons to the data on DQ8-DQ15.
DQ_0 ~ DQ_{15}	Input/Output	Data inputs/Outputs are multiplexed on the same pins.
BA_0, BA_1	Input	Selects which bank is to be active.
A_0 ~ A_{11}	Input	Row/Column addresses are multiplexed on the same pins. Row addresses : RA_0 ~ RA_{11}, Column addresses : CA_0 ~ CA_7.
V_{DD}/V_{SS}	Power Supply	Power and ground for the input buffers and core logic.
V_{DDQ}/V_{SSQ}	Power Supply	Isolated power supply and ground for the output buffers to provide improved noise immunity.
V_{REF}	Power Supply	Reference voltage for inputs, used for SSTL interface.
NC/RFU	No connection/ Reserved for future use	This pin is recommended to be left "No connection" on the device

*1 : The timing reference point for the differential clocking is the cross point of CK and $\overline{CK}$.
For any applications using the single ended clocking, apply V_{REF} to $\overline{CK}$ pin.

BLOCK DIAGRAM (1Mbit x 16I/O x 4 Bank)



FUNCTIONAL DESCRIPTION

• Power-Up Sequence

DDR SDRAMs must be powered up and initialized in a predefined manner to prevent undefined operations.

1. Apply power and keep CKE at low state (All other inputs may be undefined)
   - Apply VDD before VDDQ .
   - Apply VDDQ before VREF & VTT
2. Start clock and maintain stable condition for minimum 200us.
3. The minimum of 200us after stable power and clock(CK,$\overline{CK}$), apply NOP and take CKE to be high .
4. Issue precharge command for all banks of the device.
5. Issue a EMRS command to enable DLL

*1 6. Issue a MRS command to reset DLL. The additional 200 clock cycles are required to lock the DLL.


*1,2 7. Issue precharge command for all banks of the device.

8. Issue at least 2 or more auto-refresh commands.
9. Issue a mode register set command with A8 to low to initialize the mode register.

*1 The additional 200cycles of clock input is required to lock the DLL after enabling DLL.


*2 Sequence of 6&7 is regardless of the order.

Power up & Initialization Sequence



MODE REGISTER SET(MRS)

The mode register stores the data for controlling the various operating modes of DDR SDRAM. It programs $\overline{CAS}$ latency, addressing mode, burst length, test mode, DLL reset and various vendor specific options to make DDR SDRAM useful for variety of different applications. The default value of the mode register is not defined, therefore the mode register must be written after EMRS setting for proper operation. The mode register is written by asserting low on $\overline{CS}$, $\overline{RAS}$, $\overline{CAS}$ and $\overline{WE}$(The DDR SDRAM should be in active mode with CKE already high prior to writing into the mode register). The state of address pins A_0 ~ A_{11} and BA_0, BA_1 in the same cycle as $\overline{CS}$, $\overline{RAS}$, $\overline{CAS}$ and $\overline{WE}$ going low is written in the mode register. Minimum two clock cycles are requested to complete the write operation in the mode register. The mode register contents can be changed using the same command and clock cycle requirements during operation as long as all banks are in the idle state. The mode register is divided into various fields depending on functionality. The burst length uses A_0 ~ A_2, addressing mode uses A_3, $\overline{CAS}$ latency(read latency from column address) uses A_4 ~ A_6. A_7 is used for test mode. A_8 is used for DLL reset. A_7,A_8, BA_0 and BA_1 must be set to low for normal MRS operation. Refer to the table for specific codes for various burst length, addressing modes and $\overline{CAS}$ latencies.



DLL

A_8	DLL Reset
0	No
1	Yes

Test Mode

A_7	mode
0	Normal
1	Test

Burst Type

A_3	Type
0	Sequential
1	Interleave

BA_0	A_n ~ A_0
0	MRS
1	EMRS

* RFU(Reserved for future use) should stay "0" during MRS cycle.


CAS Latency

A_6	A_5	A_4	Latency
0	0	0	Reserved
0	0	1	Reserved
0	1	0	Reserved
0	1	1	3
1	0	0	Reserved
1	0	1	Reserved
1	1	0	Reserved
1	1	1	Reserved

Burst Length

A_2	A_1	A_0	Burst Type	
			Sequential	Interleave
0	0	0	Reserve	Reserve
0	0	1	2	2
0	1	0	4	4
0	1	1	8	8
1	0	0	Reserve	Reserve
1	0	1	Reserve	Reserve
1	1	0	Reserve	Reserve
1	1	1	Reserve	Reserve


MRS Cycle



*1 : MRS can be issued only at all banks precharge state.
*2 : Minimum t_{RP} is required to issue MRS command.

EXTENDED MODE REGISTER SET(EMRS)

The extended mode register stores the data for enabling or disabling DLL and selecting output driver strength. The default value of the extended mode register is not defined, therefore the extened mode register must be written after power up for enabling or disabling DLL. The extended mode register is written by asserting low on $\overline{CS}$, $\overline{RAS}$, $\overline{CAS}$, $\overline{WE}$ and high on BA0(The DDR SDRAM should be in all bank precharge with CKE already high prior to writing into the extended mode register). The state of address pins A0, A2 ~ A5, A7 ~ A11 and BA1 in the same cycle as $\overline{CS}$, $\overline{RAS}$, $\overline{CAS}$ and $\overline{WE}$ going low are written in the extended mode register. A1 and A6 are used for setting driver strength to normal, weak or matched impedance. Two clock cycles are required to complete the write operation in the extended mode register. The mode register contents can be changed using the same command and clock cycle requirements during operation as long as all banks are in the idle state. A0 is used for DLL enable or disable. "High" on BA0 is used for EMRS. All the other address pins except A0,A1,A6 and BA0 must be set to low for proper EMRS operation. Refer to the table for specific codes.



BA_0	A_n ~ A_0
0	MRS
1	EMRS

A_6	A_1	Output Driver Impedence Control
0	1	Weak
1	1	Matched

A_0	DLL Enable
0	Enable
1	Disable

*1 : RFU(Reserved for future use) should stay "0" during EMRS cycle.

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Voltage on any pin relative to Vss	V_{IN}, V_{OUT}	-0.5 ~ 3.6	V
Voltage on V_{DD} supply relative to Vss	V_{DD}	-1.0 ~ 3.6	V
Voltage on V_{DD} supply relative to Vss	V_{DDQ}	-0.5 ~ 3.6	V
Storage temperature	T_{STG}	-55 ~ +150	°C
Power dissipation	P_D	1.0	W
Short circuit current	I_{OS}	50	mA

Note : Permanent device damage may occur if ABSOLUTE MAXIMUM RATINGS are exceeded.
Functional operation should be restricted to recommended operating condition.
Exposure to higher than recommended voltage for extended periods of time could affect device reliability.

POWER & DC OPERATING CONDITIONS(SSTL_2 In/Out)

Recommended operating conditions(Voltage referenced to V_{SS}=0V, T_A=0 to 65°C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Device Supply voltage	V_{DD}	3.135	3.3	3.465	V	1
Output Supply voltage	V_{DDQ}	2.375	2.50	2.625	V	1
Reference voltage	V_{REF}	0.49*V_{DDQ}	-	0.51*V_{DDQ}	V	2
Termination voltage	Vtt	V_{REF}-0.04	V_{REF}	V_{REF}+0.04	V	3
Input logic high voltage	$V_{IH(DC)}$	V_{REF}+0.15	-	V_{DDQ}+0.30	V	4
Input logic low voltage	$V_{IL(DC)}$	-0.30	-	V_{REF}-0.15	V	5
Output logic high voltage	V_{OH}	Vtt+0.76	-	-	V	I_{OH}=-15.2mA
Output logic low voltage	V_{OL}	-	-	Vtt-0.76	V	I_{OL}=+15.2mA
Input leakage current	I_{IL}	-5	-	5	uA	6
Output leakage current	I_{OL}	-5	-	5	uA	6

Note : 1. Under all conditions V_{DDQ} must be less than or equal to V_{DD}.
2. V_{REF} is expected to equal 0.50*V_{DDQ} of the transmitting device and to track variations in the DC level of the same. Peak to peak noise on the V_{REF} may not exceed + 2% of the DC value. Thus, from 0.50*V_{DDQ}, V_{REF} is allowed + 25mV for DC error and an additional + 25mV for AC noise.
3. V_{tt} of the transmitting device must track V_{REF} of the receiving device.
4. V_{IH}(max.)= V_{DDQ} +1.5V for a pulse width and it can not be greater than 1/3 of the cycle rate.
5. V_{IL}(mim.)= -1.5V for a pulse width and it can not be greater than 1/3 of the cycle rate.
6. For any pin under test input of 0V $\leq$ V_{IN} $\leq$ V_{DD} is acceptable. For all other pins that are not under test V_{IN}=0V.

DC CHARACTERISTICS

Recommended operating conditions Unless Otherwise Noted, T_A=0 to 65°C)

Parameter	Symbol	Test Condition	Version					Unit	Note
			-33	-36	-40	-50	-60		
Operating Current (One Bank Active)	I_{CC1}	Burst Lenth=2 $t_{RC} \geq t_{RC}$(min) I_{OL}=0mA, t_{CC}= t_{CC}(min)	210	200	190	170	160	mA	1
Precharge Standby Current in Power-down mode	I_{CC2P}	CKE ≤ V_{IL}(max), t_{CC}= t_{CC}(min)	5					mA	
Precharge Standby Current in Non Power-down mode	I_{CC2N}	CKE ≥ V_{IH}(min), CS ≥ V_{IH}(min), t_{CC}= t_{CC}(min)	110	105	95	80	70	mA	
Active Standby Current power-down mode	I_{CC3P}	CKE ≤ V_{IL}(max), t_{CC}= t_{CC}(min)	110	105	95	80	70	mA	
Active Standby Current in in Non Power-down mode	I_{CC3N}	CKE ≥ VIH(min), CS ≥ VIH(min), t_{CC}= t_{CC}(min)	160	150	140	120	100	mA	
Operating Current (Burst Mode)	I_{CC4}	$t_{RC} \geq t_{RFC}$(min)$t_{RC} \geq t_{RFC}$(min) Page Burst, All Banks activated.	390	370	350	320	300	mA	
Refresh Current	I_{CC5}	$t_{RC} \geq t_{RFC}$(min)	210	200	190	180	170	mA	2
Self Refresh Current	I_{CC6}	CKE ≤ 0.2V	2					mA	

Note : 1. Measured with outputs open.
2. Refresh period is 64ms.

AC INPUT OPERATING CONDITIONS


Recommended operating conditions(Voltage referenced to V_{SS}=0V, V_{DD}=3.3V± 5%, V_{DDQ}=2.5V± 5%,T_A=0 to 65°C)

Parameter	Symbol	Min	Typ	Max	Unit	Note
Input High (Logic 1) Voltage; DQ	V_{IH}	V_{REF}+0.35	-	-	V	
Input Low (Logic 0) Voltage; DQ	V_{IL}	-	-	V_{REF}-0.35	V	
Clock Input Differential Voltage; CK and $\overline{CK}$	V_{ID}	0.7	-	V_{DDQ}+0.6	V	1
Clock Input Crossing Point Voltage; CK and $\overline{CK}$	V_{IX}	0.5*V_{DDQ}-0.2	-	0.5*V_{DDQ}+0.2	V	2

Note : 1. V_{ID} is the magnitude of the difference between the input level on CK and the input level on $\overline{CK}$
2. The value of V_{IX} is expected to equal 0.5*V_{DDQ} of the transmitting device and must track variations in the DC level of the same

AC OPERATING TEST CONDITIONS (V_{DD}=3.3V±5%, T_A= 0 to 65°C)

Parameter	Value	Unit	Note
Input reference voltage for CK(for single ended)	0.50*V_{DDQ}	V	
CK and $\overline{CK}$ signal maximum peak swing	1.5	V	
CK signal minimum slew rate	1.0	V/ns	
Input Levels(V_{IH}/V_{IL})	V_{REF}+0.35/V_{REF}-0.35	V	
Input timing measurement reference level	V_{REF}	V	
Output timing measurement reference level	V_{tt}	V	
Output load condition	See Fig.1		



(Fig. 1) Output Load Circuit

CAPACITANCE (V_{DD}=3.3V, T_A= 25°C, f=1MHz)

Parameter	Symbol	Min	Max	Unit
Input capacitance(CK, $\overline{CK}$)	C_{IN1}	1.0	5.0	pF
Input capacitance(A_0~A_{11}, BA_0~BA_1)	C_{IN2}	1.0	4.0	pF
Input capacitance (CKE, $\overline{CS}$, $\overline{RAS}$,$\overline{CAS}$, $\overline{WE}$)	C_{IN3}	1.0	4.0	pF
Data & DQS input/output capacitance(DQ_0~DQ_{31})	C_{OUT}	1.0	6.5	pF
Input capacitance(DM0 ~ DM3)	C_{IN4}	1.0	6.5	pF

DECOUPLING CAPACITANCE GUIDE LINE

Recommended decoupling capacitance added to power line at board.

Parameter	Symbol	Value	Unit
Decoupling Capacitance between V_{DD} and V_{SS}	C_{DC1}	0.1 + 0.01	uF
Decoupling Capacitance between V_{DDQ} and V_{SSQ}	C_{DC2}	0.1 + 0.01	uF

Note : 1. V_{DD} and V_{DDQ} pins are separated each other.
All V_{DD} pins are connected in chip. All V_{DDQ} pins are connected in chip.
2. V_{SS} and V_{SSQ} pins are separated each other
All V_{SS} pins are connected in chip. All V_{SSQ} pins are connected in chip.

C CHARACTERISTICS

Parameter		Sym-bol	-33		-36		-40		-50		-60		Unit	Note
			Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
K cycle time	CL=3	t_{CK}	3.3	4.0	3.6	6	4.0	7	5.0	10	6.0	10	ns	
K high level width		t_{CH}	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	tCK	
K low level width		t_{CL}	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	0.45	0.55	tCK	
QS out access time from CK		t_{DQSCK}	-0.6	0.6	-0.6	0.6	-0.6	0.6	-0.7	0.7	-0.75	0.75	ns	
utput access time from CK		t_{AC}	-0.6	0.6	-0.6	0.6	-0.6	0.6	-0.7	0.7	-0.75	0.75	ns	
ata strobe edge to Dout edge		t_{DQSQ}	-	0.4	-	0.4	-	0.4	-	0.45	-	0.5	ns	1
ead preamble		t_{RPRE}	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	0.9	1.1	tCK	
ead postamble		t_{RPST}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
K to valid DQS-in		t_{DQSS}	0.8	1.25	0.85	1.15	0.85	1.15	0.8	1.2	0.75	1.25	tCK	
QS-In setup time		t_{WPRES}	0	-	0	-	0	-	0	-	0	-	ns	
QS-in hold time		t_{WPREH}	0.45	-	0.35	-	0.35	-	0.3	-	0.25	-	tCK	
QS write postamble		t_{WPST}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
QS-In high level width		t_{DQSH}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
QS-In low level width		t_{DQSL}	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	0.4	0.6	tCK	
ddress and Control input setup		t_{IS}	0.9	-	0.9	-	0.9	-	1.0	-	1.1	-	ns	
ddress and Control input hold		t_{IH}	0.9	-	0.9	-	0.9	-	1.0	-	1.1	-	ns	
Q and DM setup time to DQS		t_{DS}	0.4	-	0.4	-	0.4	-	0.45	-	0.5	-	ns	
Q and DM hold time to DQS		t_{DH}	0.4	-	0.4	-	0.4	-	0.45	-	0.5	-	ns	
lock half period		t_{HP}	tCLmin or tCHmin	-	tCLmin or tCHmin	-	tCLmin or tCHmin	-	tCLmin or tCHmin	-	tCLmin or tCHmin	-	ns	1
ata output hold time from DQS		t_{QH}	tHP-0.4		tHP-0.4	-	tHP-0.4	-	tHP-0.45	-	tHP-0.5	-	ns	1

ote 1 :

The JEDEC DDR specification currently defines the output data valid window(tDV) as the time period when the data strobe and all data associated with that data strobe are coincidentally valid.

- The previously used definition of tDV(=0.35tCK) artificially penalizes system timing budgets by assuming the worst ase

output vaild window even then the clock duty cycle applied to the device is better than 45/55%

A new AC timing term, tQH which stands for data output hold time from DQS is difined to account for clock duty cycle variation and replaces tDV

tQHmin = tHP-X where

. tHP=Minimum half clock period for any given cycle and is defined by clock high or clock low time(tCH,tCL)

. X=A frequency dependent timing allowance account for tDQSQmax

AC CHARACTERISTICS (I)

Parameter	Symbol	-33		-36		-40		-50		-60		Unit	Note
		Min	Max	Min	Max	Min	Max	Min	Max	Min	Max		
Row cycle time	t_{RC}	17	-	16	-	14	-	12	-	10	-	tCK	
Refresh row cycle time	t_{RFC}	20	-	18	-	16	-	14	-	12	-	tCK	
Row active time	t_{RAS}	11	100K	10	100K	9	100K	8	100K	7	100K	tCK	
RAS to CAS delay	t_{RCD}	6	-	5	-	5	-	4	-	3	-	tCK	
Row precharge time	t_{RP}	6	-	5	-	5	-	4	-	3	-	tCK	
Row active to Row active	t_{RRD}	2	-	2	-	2	-	2	-	2	-	tCK	
Last data in to Row precharge @Normal Precharge	t_{WR}	3	-	3	-	3	-	2	-	2	-	tCK	1
Last data in to Row precharge @Auto Precharge	t_{WR_A}	3	-	3	-	3	-	3	-	3	-	tCK	1
Last data in to Read command	t_{CDLR}	2	-	2	-	2	-	2	-	2	-	tCK	1
Col. address to Col. address	t_{CCD}	1	-	1	-	1	-	1	-	1	-	tCK	
Mode register set cycle time	t_{MRD}	3	-	2	-	2	-	2	-	2	-	tCK	
Auto precharge write recovery + Precharge	t_{DAL}	9	-	8	-	8	-	7	-	6	-	tCK	
Exit self refresh to read com-	t_{XSR}	200	-	200	-	200	-	200	-	200	-	tCK	
Power down exit time	t_{PDEX}	2tCK +tIS	-	2tCK +tIS	-	1tCK +tIS	-	1tCK +tIS	-	1tCK +tIS	-	ns	
Refresh interval time	t_{REF}	15.6		15.6	-	15.6	-	15.6	-	15.6	-	us	

Note : 1. For normal write operation, even numbers of Din are to be written inside DRAM

AC CHARACTERISTICS (II)

(Unit : Number of Clock)

K4D64163HF-TC33

Frequency	Cas Latency	tRC	tRFC	tRAS	tRCD	tRP	tRRD	tDAL	Unit
300MHz (3.0ns)	3	17	20	11	6	6	2	9	tCK
275MHz (3.6ns)	3	16	18	10	5	5	2	8	tCK
250MHz (4.0ns)	3	14	16	9	5	5	2	8	tCK
200MHz (5.0ns)	3	12	14	8	4	4	2	7	tCK
166MHz (6.0ns)	3	10	12	7	3	3	2	6	tCK

K4D64163HF-TC36

Frequency	Cas Latency	tRC	tRFC	tRAS	tRCD	tRP	tRRD	tDAL	Unit
275MHz (3.6ns)	3	16	18	10	5	5	2	8	tCK
250MHz (4.0ns)	3	14	16	9	5	5	2	8	tCK
200MHz (5.0ns)	3	12	14	8	4	4	2	7	tCK
166MHz (6.0ns)	3	10	12	7	3	3	2	6	tCK

K4D64163HF-TC40

Frequency	Cas Latency	tRC	tRFC	tRAS	tRCD	tRP	tRRD	tDAL	Unit
250MHz (4.0ns)	3	14	16	9	5	5	2	8	tCK
200MHz (5.0ns)	3	12	14	8	4	4	2	7	tCK
166MHz (6.0ns)	3	10	12	7	3	3	2	6	tCK


K4D64163HF-TC50

Frequency	Cas Latency	tRC	tRFC	tRAS	tRCD	tRP	tRRD	tDAL	Unit
200MHz (5.0ns)	3	12	14	8	4	4	2	7	tCK
166MHz (6.0ns)	3	10	12	7	3	3	2	6	tCK

K4D64163HF-TC60

Frequency	Cas Latency	tRC	tRFC	tRAS	tRCD	tRP	tRRD	tDAL	Unit
166MHz (6.0ns)	3	10	12	7	3	3	2	6	tCK

Simplified Timing @ BL=4




Normal Write Burst (@ BL=4)

Multi Bank Interleaving Write Burst (@ BL=4)

PACKAGE DIMENSIONS (66pin TSOP-II)

Units : Millimeters



NOTE
1. ( ) IS REFERENCE
2. [ ] IS ASS'Y OUT QUALITY

LifeElectronics
Живое партнерство

ООО «ЛайфЭлектроникс» **“LifeElectronics” LLC**

ИНН 7805602321 КПП 780501001 Р/С 40702810122510004610 ФАКБ "АБСОЛЮТ БАНК" (ЗАО) в г.Санкт-Петербурге К/С 30101810900000000703 БИК 044030703

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- *Конкурентоспособные цены и скидки постоянным клиентам.*
- *Специальные условия для постоянных клиентов.*
- *Подбор аналогов.*
- *Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.*

- *Приемлемые сроки поставки, возможна ускоренная поставка.*
- *Доставку товара в любую точку России и стран СНГ.*
- *Комплексную поставку.*
- *Работу по проектам и поставку образцов.*
- *Формирование склада под заказчика.*

- *Сертификаты соответствия на поставляемую продукцию (по желанию клиента).*
- *Тестирование поставляемой продукции.*
- *Поставку компонентов, требующих военную и космическую приемку.*
- *Входной контроль качества.*
- *Наличие сертификата ISO.*

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- *Регистрацию проекта у производителя компонентов.*
- *Техническую поддержку проекта.*
- *Защиту от снятия компонента с производства.*
- *Оценку стоимости проекта по компонентам.*
- *Изготовление тестовой платы монтаж и пусконаладочные работы.*

Тел: +7 (812) 336 43 04 (многоканальный)
Email: org@lifeelectronics.ru

www.lifeelectronics.ru