

---

# THERMO-SENSITIVE PAPER

---

## FTP-020P / 030P / 040P Series

---

### ■ FEATURES

- Brings our features of thermal printer to the optimum
- Paper supply in small quantities is available

### ■ STORAGE CHARACTERISTICS

- Black density in white part is 0.2 or less. Recording part (black density: 1.3) is 1.1 or more.
- Testing conditions:
  - Light resistance: 1000 hours under 5000 LUX of fluorescent light
  - Moisture resistance: +40°C, 90% RH. 24 hours
  - Heat resistance: +50°C, 24 hours

### ■ PRECAUTIONS

- Avoid locations of high temperature and high humidity
- Do not expose paper to direct sun light for an extended period
- Do not use solvent paster
- Do not contact plasticizer
- Do not contact diazo copy paper immediately after copying
- Protect from wetting and scratching

# FTP-020P / 030P / 040P Series

## ■ SPECIFICATIONS

Printer Series Number	Paper Feed	Paper Quality	Paper Part Number	Paper Specifications					Minimum unit (rolls)		
				Paper width (mm)	Paper thickness (μm)	Length of roll (m)	Outer diameter of roll (Ø mm max.)	Inner diameter of core (Ø mm)			
FTP-020 FTP-040	Top	Standard (TF50KS-E)	FTP-020P001	60	65	30	56	12±0.5	100		
			FTP-040P001	110	65	30	56	12±0.5	50		
FTP-628WSL	Top	Mini Roll	FTP-020P0704	58	65	13.5	36	8	100		
FTP-622MCL	Front	Small Roll (TF50KS-E)	FTP-020PU004	58	65	25	48	12±0.5	100		
FTP-624MCL			FTP-030PU004	80	65	25	48	12±0.5	100		
FTP-627MCL FTP-628MCL	All		FTP-040PU004	112	65	25	48	12±0.5	50		
	Front		Thick Paper (TF60KS-E)	FTP-020PU001	58	75	25	56	12±0.5	100	
FTP-030PU001		80		75	25	56	12±0.5	100			
FTP-040PU001		112		75	25	56	12±0.5	50			
FTP-632MCL FTP-634MCL FTP-637MCL FTP-638MCL FTP-642MCL FTP-644MCL FTP-648MCL		Rear		Standard (TF50KS-E)	FTP-020P0020	60	65	30	56	12±0.5	100
FTP-030P0020					85	65	30	56	12±0.5	100	
FTP-040P0020	114		65		30	56	12±0.5	50			
FTP-622MCL FTP-624MCL	Front	Standard (TF50KS-E)	FTP-020P0104	58	65	65	83	12±0.5	36		
FTP-627MCL FTP-628MCL	All										
FTP-629MCL	Front										
FTP-632MCL FTP-634MCL FTP-637MCL FTP-638MCL	Front All										
FTP-639MCL	Front										
FTP-642MCL FTP-644MCL FTP-648MCL	Front Top		FTP-030P0104	80	65	65	83	12±0.5	27		
			FTP-040P0104	112	65	65	83	12±0.5	18		

## ■ SHELF LIFE OF THERMAL PAPER

### 1. SHELF LIFE OF UNPRINTED PAPER

Storage conditions:

- Store in dark place at 23°C and 50% RH without removing original packaging (not in direct sunlight)
- Do not store in area that maybe subjected to the presence of NOx, SOx, or Ozone

Under the above conditons, we guarantee the original image development capability at time of manufacture will be maintained for 5 years minimum.

### 2. IMAGE LIFE AFTER DEVELOPMENT

Storage conditions:

- Store in dark place at 23°C and 50% RH (not in direct sunlight)
- Must not come into contact with plastic matter (plastic file, desk mat, etc.)
- Must not come into contact with NOx, SOx, and Ozone
- Must not come into contact with oils, fats, solvents, chemicals (drugs, cosmetics)
- Must not come into contact with stationary such as adhesive tape, fluorescent pens, oil-based pens, non-starch glue, etc
- Must not come into contact with water
- Must not be stamped on either side

Under the above circumstances, we guarantee the thermal image developed at a sensitiveness of OD 1.10 will maintain its legibility for 5 years minimum.

## Fujitsu Components International Headquarter Offices

### Japan

Fujitsu Component Limited  
Gotanda-Chuo Building  
3-5, Higashigotanda 2-chome, Shinagawa-ku  
Tokyo 141 8630, Japan  
Tel: (81-3) 5449-7010  
Fax: (81-3) 5449-2626  
Email: [promothq@fcl.fujitsu.com](mailto:promothq@fcl.fujitsu.com)  
Web: [www.fcl.fujitsu.com](http://www.fcl.fujitsu.com)

### North and South America

Fujitsu Components America, Inc.  
250 E. Caribbean Drive  
Sunnyvale, CA 94089 U.S.A.  
Tel: (1-408) 745-4900  
Fax: (1-408) 745-4970  
Email: [components@us.fujitsu.com](mailto:components@us.fujitsu.com)  
Web: <http://us.fujitsu.com/components/>

### Europe

Fujitsu Components Europe B.V.  
Diamantlaan 25  
2132 WV Hoofddorp  
Netherlands  
Tel: (31-23) 5560910  
Fax: (31-23) 5560950  
Email: [info@fceu.fujitsu.com](mailto:info@fceu.fujitsu.com)  
Web: [emea.fujitsu.com/components/](http://emea.fujitsu.com/components/)

### Asia Pacific

Fujitsu Components Asia Ltd.  
102E Pasir Panjang Road  
#01-01 Citilink Warehouse Complex  
Singapore 118529  
Tel: (65) 6375-8560  
Fax: (65) 6273-3021  
Email: [fcal@fcal.fujitsu.com](mailto:fcal@fcal.fujitsu.com)  
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2009 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.  
Rev. February 26, 2009.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)