
THERMO-SENSITIVE PAPER

FTP-020P / 030P / 040P Series

■ FEATURES

- Brings our features of thermal printer to the optimum
- Paper supply in small quantities is available

■ STORAGE CHARACTERISTICS

- Black density in white part is 0.2 or less. Recording part (black density: 1.3) is 1.1 or more.
- Testing conditions:
 - Light resistance: 1000 hours under 5000 LUX of fluorescent light
 - Moisture resistance: +40°C, 90% RH. 24 hours
 - Heat resistance: +50°C, 24 hours

■ PRECAUTIONS

- Avoid locations of high temperature and high humidity
- Do not expose paper to direct sun light for an extended period
- Do not use solvent paster
- Do not contact plasticizer
- Do not contact diazo copy paper immediately after copying
- Protect from wetting and scratching

FTP-020P / 030P / 040P Series

■ SPECIFICATIONS

| Printer Series Number | Paper Feed | Paper Quality | Paper Part Number | Paper Specifications | | | | | Minimum unit (rolls) | |
|--|------------|-----------------------|-------------------|------------------------|----------------------|--------------------|------------------------------------|-------------------------------|----------------------|--------|
| | | | | Paper width (mm) | Paper thickness (μm) | Length of roll (m) | Outer diameter of roll (Ø mm max.) | Inner diameter of core (Ø mm) | | |
| FTP-020 FTP-040 | Top | Standard (TF50KS-E) | FTP-020P001 | 60 | 65 | 30 | 56 | 12±0.5 | 100 | |
| | | | FTP-040P001 | 110 | 65 | 30 | 56 | 12±0.5 | 50 | |
| FTP-628WSL | Top | Mini Roll | FTP-020P0704 | 58 | 65 | 13.5 | 36 | 8 | 100 | |
| FTP-622MCL FTP-624MCL | Front | Small Roll (TF50KS-E) | FTP-020PU004 | 58 | 65 | 25 | 48 | 12±0.5 | 100 | |
| FTP-627MCL FTP-628MCL | | | All | FTP-030PU004 | 80 | 65 | 25 | 48 | 12±0.5 | 100 |
| FTP-632MCL FTP-634MCL FTP-637MCL FTP-638MCL FTP-642MCL FTP-644MCL FTP-648MCL | Front | | | Thick Paper (TF60KS-E) | FTP-040PU004 | 112 | 65 | 25 | 48 | 12±0.5 |
| | | | FTP-020PU001 | | 58 | 75 | 25 | 56 | 12±0.5 | 100 |
| | | FTP-030PU001 | 80 | | 75 | 25 | 56 | 12±0.5 | 100 | |
| | | FTP-040PU001 | 112 | | 75 | 25 | 56 | 12±0.5 | 50 | |
| FTP-622MCL FTP-624MCL | Rear | Standard (TF50KS-E) | FTP-020P0020 | 60 | 65 | 30 | 56 | 12±0.5 | 100 | |
| FTP-632MCL FTP-634MCL | Rear | | FTP-030P0020 | 85 | 65 | 30 | 56 | 12±0.5 | 100 | |
| FTP-642MCL FTP-644MCL FTP-648MCL | Rear | | FTP-040P0020 | 114 | 65 | 30 | 56 | 12±0.5 | 50 | |
| FTP-622MCL FTP-624MCL | Front | Standard (TF50KS-E) | FTP-020P0104 | 58 | 65 | 65 | 83 | 12±0.5 | 36 | |
| FTP-627MCL FTP-628MCL | | | | | | | | | | All |
| FTP-629MCL | Front | | | | | | | | | |
| FTP-632MCL FTP-634MCL | Front | | | | | | | | | |
| FTP-637MCL FTP-638MCL | | | All | | | | | | | |
| FTP-639MCL | Front | | | | | | | | | |
| FTP-642MCL FTP-644MCL | Front | | FTP-040P0104 | 112 | 65 | 65 | 83 | 12±0.5 | 18 | |
| FTP-648MCL | | | | | | | | | | Top |

■ SHELF LIFE OF THERMAL PAPER

1. SHELF LIFE OF UNPRINTED PAPER

Storage conditions:

- Store in dark place at 23°C and 50% RH without removing original packaging (not in direct sunlight)
- Do not store in area that maybe subjected to the presence of NOx, SOx, or Ozone

Under the above conditons, we guarantee the original image development capability at time of manufacture will be maintained for 5 years minimum.

2. IMAGE LIFE AFTER DEVELOPMENT

Storage conditions:

- Store in dark place at 23°C and 50% RH (not in direct sunlight)
- Must not come into contact with plastic matter (plastic file, desk mat, etc.)
- Must not come into contact with NOx, SOx, and Ozone
- Must not come into contact with oils, fats, solvents, chemicals (drugs, cosmetics)
- Must not come into contact with stationary such as adhesive tape, fluorescent pens, oil-based pens, non-starch glue, etc
- Must not come into contact with water
- Must not be stamped on either side

Under the above circumstances, we guarantee the thermal image developed at a sensitiveness of OD 1.10 will maintain its legibility for 5 years minimum.

Fujitsu Components International Headquarter Offices

Japan

Fujitsu Component Limited
Gotanda-Chuo Building
3-5, Higashigotanda 2-chome, Shinagawa-ku
Tokyo 141 8630, Japan
Tel: (81-3) 5449-7010
Fax: (81-3) 5449-2626
Email: promothq@fcl.fujitsu.com
Web: www.fcl.fujitsu.com

North and South America

Fujitsu Components America, Inc.
250 E. Caribbean Drive
Sunnyvale, CA 94089 U.S.A.
Tel: (1-408) 745-4900
Fax: (1-408) 745-4970
Email: components@us.fujitsu.com
Web: <http://us.fujitsu.com/components/>

Europe

Fujitsu Components Europe B.V.
Diamantlaan 25
2132 WV Hoofddorp
Netherlands
Tel: (31-23) 5560910
Fax: (31-23) 5560950
Email: info@fceu.fujitsu.com
Web: emea.fujitsu.com/components/

Asia Pacific

Fujitsu Components Asia Ltd.
102E Pasir Panjang Road
#01-01 Citilink Warehouse Complex
Singapore 118529
Tel: (65) 6375-8560
Fax: (65) 6273-3021
Email: fcal@fcal.fujitsu.com
Web: <http://www.fujitsu.com/sg/services/micro/components/>

©2009 Fujitsu Components America, Inc. All rights reserved. All trademarks or registered trademarks are the property of their respective owners.

Fujitsu Components America or its affiliates do not warrant that the content of datasheet is error free. In a continuing effort to improve our products Fujitsu Components America, Inc. or its affiliates reserve the right to change specifications/datasheets without prior notice.
Rev. February 26, 2009.

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкуренеспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: org@lifeelectronics.ru