

# RJ45 1000 Base-TX Jack with Magnetic Module

ARJ11E

RoHS  
Compliant



16.26 x 13.84 x 21.59mm

## FEATURES:

- Available with or without LED
- Suitable CAT 5 & 6 cable and UTP
- Comply IEEE 802.3ab
- LAN Magnetic with RJ4
- Suitable for RoHS compliant reflow

## APPLICATIONS:

- 1000 Base-TX LAN
- NIC, LoM and PC

## STANDARD SPECIFICATIONS at 25°C

Operating temperature range: 0°C to +70°C Storage temperature range: -40°C to +85°C

| Part Number          | Turns Ratio | EMI Fingers | LEDs | Insertion Loss (dB MAX) | Return Loss (dB MIN @100Ω±15Ω) |        |        |             |  |
|----------------------|-------------|-------------|------|-------------------------|--------------------------------|--------|--------|-------------|--|
|                      |             |             | L/R  | 0.3-100MHz              | 1- 30 MHz                      | 40 MHz | 50 MHz | 60 – 80 MHz |  |
| ARJ11E-M□ SA-A-B-ΔM2 | 1CT:1CT     | Yes         | G/Y  | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-M□ SB-A-B-ΔU2 | 1CT:1CT     | Yes         | G/Y  | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-M□ SC-A-B-ΔL2 | 1CT:1       | Yes         | G/Y  | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-M□ SD-A-B-ΔM2 | 1CT:1CT     | Yes         | G/Y  | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-MASA-M2       | 1CT:1CT     | Yes         | NA   | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-MASB-M2       | 1CT:1CT     | Yes         | NA   | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-MASC-L2       | 1CT:1       | Yes         | NA   | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |
| ARJ11E-MASD-M2       | 1CT:1CT     | Yes         | NA   | -1.2dB                  | -16                            | -13.5  | -11.5  | -10         |  |


| Part Number          | Crosstalk (dB MIN) |        |         | Differential to Common Mode Rejection (dB MIN) |        |         | Hipot (Vrms) |
|----------------------|--------------------|--------|---------|------------------------------------------------|--------|---------|--------------|
|                      | 30 MHz             | 60 MHz | 100 MHz | 30 MHz                                         | 60 MHz | 100 MHz |              |
| ARJ11E-M□ SA-A-B-ΔM2 | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-M□ SB-A-B-ΔU2 | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-M□ SC-A-B-ΔL2 | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-M□ SD-A-B-ΔM2 | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-MASA-M2       | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-MASB-M2       | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-MASC-L2       | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |
| ARJ11E-MASD-M2       | -40                | -36    | -30     | -35                                            | -32    | -30     | 1500         |

□ : Mechanical Option: B or C

Δ : LED Polarity Option: E, F or G

Contact Abracon for more custom configurations. See options to build a custom configuration.

## OPTIONS AND PART IDENTIFICATION



# RJ45 1000 Base-TX Jack with Magnetic Module

ARJ11E



RoHS  
Compliant





16.26 x 13.84 x 21.59mm

## MECHANICAL DIMENSIONS


MA





PC Board Layout  
Component Side Shown




MB





PC Board Layout  
Component Side Shown



MC



PC Board Layout  
Component Side Shown



# RJ45 1000 Base-TX Jack with Magnetic Module










ARJ11E

RoHS  
Compliant



16.26 x 13.84 x 21.59mm

## SCHEMATICS



# RJ45 1000 Base-TX Jack with Magnetic Module










ARJ11E

RoHS  
Compliant



16.26 x 13.84 x 21.59mm

## SCHEMATICS - continued



# RJ45 1000 Base-TX Jack with Magnetic Module







ARJ11E

RoHS  
Compliant



16.26 x 13.84 x 21.59mm

## SCHEMATICS - continued



# RJ45 1000 Base-TX Jack with Magnetic Module


ARJ11E

RoHS  
Compliant



16.26 x 13.84 x 21.59mm



## LED POLARITY




## PACKING: 60pcs/tray

Packaging material: PET

Outer carton unit 1320 pcs/ 22 Trays/box




## REFLOW PROFILE:



**ATTENTION:** Abracon Corporation's products are COTS – Commercial-Off-The-Shelf products; suitable for Commercial, Industrial and, where designated, Automotive Applications. Abracon's products are not specifically designed for Military, Aviation, Aerospace, Life-dependant Medical applications or any application requiring high reliability where component failure could result in loss of life and/or property. For applications requiring high reliability and/or presenting an extreme operating environment, written consent and authorization from Abracon Corporation is required. Please contact Abracon Corporation for more information.

ABRACON IS  
ISO 9001:2008  
CERTIFIED



**ABRACON**  
CORPORATION

Visit [www.abracon.com](http://www.abracon.com) for Terms & Conditions of Sale  
30332 Esperanza, Rancho Santa Margarita, California 92688  
tel 949-546-8000 | fax 949-546-8001 | [www.abracon.com](http://www.abracon.com)

Revised: 05.05.11

Компания «Life Electronics» занимается поставками электронных компонентов импортного и отечественного производства от производителей и со складов крупных дистрибьюторов Европы, Америки и Азии.

С конца 2013 года компания активно расширяет линейку поставок компонентов по направлению коаксиальный кабель, кварцевые генераторы и конденсаторы (керамические, пленочные, электролитические), за счёт заключения дистрибьюторских договоров

Мы предлагаем:

- Конкурентоспособные цены и скидки постоянным клиентам.
- Специальные условия для постоянных клиентов.
- Подбор аналогов.
- Поставку компонентов в любых объемах, удовлетворяющих вашим потребностям.
- Приемлемые сроки поставки, возможна ускоренная поставка.
- Доставку товара в любую точку России и стран СНГ.
- Комплексную поставку.
- Работу по проектам и поставку образцов.
- Формирование склада под заказчика.
- Сертификаты соответствия на поставляемую продукцию (по желанию клиента).
- Тестирование поставляемой продукции.
- Поставку компонентов, требующих военную и космическую приемку.
- Входной контроль качества.
- Наличие сертификата ISO.

В составе нашей компании организован Конструкторский отдел, призванный помогать разработчикам, и инженерам.

Конструкторский отдел помогает осуществить:

- Регистрацию проекта у производителя компонентов.
- Техническую поддержку проекта.
- Защиту от снятия компонента с производства.
- Оценку стоимости проекта по компонентам.
- Изготовление тестовой платы монтаж и пусконаладочные работы.



Тел: +7 (812) 336 43 04 (многоканальный)

Email: [org@lifeelectronics.ru](mailto:org@lifeelectronics.ru)

[www.lifeelectronics.ru](http://www.lifeelectronics.ru)